

ABSTRACT AND REFERENCES

ENGINEERING TECHNOLOGICAL SYSTEMS

DOI: 10.15587/1729-4061.2020.193510

IMPROVING THE ABRASIVE RESISTANCE OF A SLIDE FRAME IN A MORTAR MIXER (p. 6–14)**Stanislav Popov**National University «Yuri Kondratyuk
Poltava Polytechnic», Poltava, UkraineORCID: <http://orcid.org/0000-0003-2381-152X>**Sergiy Gnitko**National University «Yuri Kondratyuk
Poltava Polytechnic», Poltava, UkraineORCID: <http://orcid.org/0000-0003-2732-661X>**Anatoly Vasilyev**National University «Yuri Kondratyuk
Poltava Polytechnic», Poltava, UkraineORCID: <http://orcid.org/0000-0002-1767-8569>

A method has been proposed for machining the outer and inner conical surfaces of the wrist pin and insert, which represent a sliding friction pair on the mortar mixer frame. The machining implies the application on the conical surface of parts, preliminary prepared through turning, of a wear-resistant material in the form of a hard alloyed nickel-based powder. It is applied with a special burner with a hopper-dispenser filled with powder. The result of mixing a combustible gas (acetylene and oxygen) in the burner with the powder from the hopper is melting.

In the course of implementing a given technological process, by using mathematical modeling methods, we have determined the optimal mode parameters (PG10N-01 powder consumption is 33.5 g/min.; oxygen flow rate is 7.0 l/min.; acetylene pressure is 0.043 MPa) for the gas-flame surfacing, which ensured maximum effect, that is, the greatest strength of adhesion (45 MPa) for the surfaced coating. The surfaced coating quality was checked by using a pin method for determining the adhesion strength between the new coating and the base on a tensile testing machine.

A series of experimental studies into the enhancement of abrasive resistance of a sliding frame, namely a comparison of the surfaced coating with other well-known wear-resistant materials such as steel ShKh15, KhVG, were carried out at a specially designed experimental bench. Its structure is based on a vertically drilling desktop machine adjusted to the conditions of a working process that occurs inside the body of a mortar mixer. These include an abrasive medium, and the radial and axial efforts. To determine the axial load on a frame, we have proposed a structure of the hydraulic device, which includes a pressure gauge, a piston, a sleeve, and a ball. The axial load has been found for the most unfavorable conditions of mixer operation. Its value was implemented at an experimental wear bench. In addition, we have performed a series of experimental studies to determine an optimum angle of the cone at the apex of the wrist pin and insert in a conical slide frame for the minimal wear.

Using the proposed technique of a gas-flame surfacing could significantly improve the abrasive and corrosion resistance of a slide frame, thereby prolonging the lifespan of a mortar mixer in general, as well as the overhaul cycle for equipment designed to prepare soluble mixtures used for construction.

Keywords: gas-flame surfacing, abrasive wear, slide frame, hard alloyed powder, technological process.

References

1. Biletskyi, V. S. (Ed.) (2004). Mala hirnycha entsyklopediya. Donetsk: Skhidnyi vydavnychiy dim, 640.
2. Onyshchenko, O. H., Popov, S. V. (2005). Rekulovani konichni pidshypnyky kovzannia mobilnoi rozchynozmishuvalnoi ustanovky URZ-3,8. Eastern-European Journal of Enterprise Technologies, 6 (1 (18)), 45–47.
3. Onyshchenko, O. H., Vashchenko, K. M., Popov, S. V. (2007). Perspektyvy vykorystannia rozchynozmishuvalnoi ustanovky URZ-3,8 na budivelnnykh maidanchykh Ukrainy. Sovremennyye problemy stroitel'stva. Donetsk: Donetskiiy PromstroyNIIproekt, 138–144.
4. Kravchenko, S., Popov, S., Gnitko, S. (2016). The working pressure research of piston pump RN-3.8. Eastern-European Journal of Enterprise Technologies, 5 (1 (83)), 15–20. doi: <https://doi.org/10.15587/1729-4061.2016.80626>
5. Popov, S., Vasilyev, A., Lednik, R. (2015). Theoretical wear research of conical friction bearing. Technology Audit and Production Reserves, 2 (1 (22)), 60–64. doi: <https://doi.org/10.15587/2312-8372.2015.41395>
6. Kaplun, P., Gonchar, V., Bodnar, R. (2013). Enhancement of steel wear resistance in corrosive and abrasive medium. Interdisciplinary integration of science in technology, education and economy. Bydgoszcz-Poland, 320–329.
7. Sobolev, V. V., Guilemany, J. M., Miguel, J. R., Calero, J. A. (1996). Influence of in-flight dissolution process on composite powder particle (WC-Ni) behaviour during high velocity oxy-fuel spraying. Surface and Coatings Technology, 81 (2-3), 136–145. doi: [https://doi.org/10.1016/0257-8972\(95\)02481-6](https://doi.org/10.1016/0257-8972(95)02481-6)
8. Sobolev, V. V., Guilemany, J. M., Miguel, J. R., Calero, J. A. (1996). Influence of thermal processes on coating formation during high velocity oxy-fuel (HVOF) spraying of WC-Ni powder particles. Surface and Coatings Technology, 82 (1-2), 121–129. doi: [https://doi.org/10.1016/0257-8972\(95\)02657-6](https://doi.org/10.1016/0257-8972(95)02657-6)
9. Shrestha, S., Hodgkiess, T., Neville, A. (2005). Erosion-corrosion behaviour of high-velocity oxy-fuel Ni-Cr-Mo-Si-B coatings under high-velocity seawater jet impingement. Wear, 259 (1-6), 208–218. doi: <https://doi.org/10.1016/j.wear.2005.01.038>
10. Dent, A. H., Horlock, A. J., McCartney, D. G., Harris, S. J. (2001). Microstructural characterisation of a Ni-Cr-B-C based alloy coating produced by high velocity oxy-fuel thermal spraying. Surface and Coatings Technology, 139 (2-3), 244–250. doi: [https://doi.org/10.1016/S0257-8972\(01\)00996-3](https://doi.org/10.1016/S0257-8972(01)00996-3)
11. Sang, K., Li, Y. (1995). Cavitation erosion of flame spray weld coating of nickel-base alloy powder. Wear, 189 (1-2), 20–24. doi: [https://doi.org/10.1016/0043-1648\(95\)06608-x](https://doi.org/10.1016/0043-1648(95)06608-x)
12. Huang, F., Xu, H., Liu, W., Zheng, S. (2018). Microscopic characteristics and properties of titaniferous compound reinforced nickel-based wear-resisting layer via in situ precipitation of plasma spray welding. Ceramics International, 44 (6), 7088–7097. doi: <https://doi.org/10.1016/j.ceramint.2018.01.148>
13. Janka, L., Berger, L.-M., Norpoch, J., Trache, R., Thiele, S., Tomasik, C. et. al. (2018). Improving the high temperature abrasion resistance of thermally sprayed Cr₃C₂-NiCr coatings by WC addition. Surface and Coatings Technology, 337, 296–305. doi: <https://doi.org/10.1016/j.surfcoat.2018.01.035>
14. Kazasidis, M., Yin, S., Cassidy, J., Volkov-Husović, T., Vlahović, M., Martinović, S. et. al. (2020). Microstructure and cavitation erosion performance of nickel-Inconel 718 composite coatings produced with cold spray. Surface and Coatings Technology, 382, 125195. doi: <https://doi.org/10.1016/j.surfcoat.2019.125195>

DOI: 10.15587/1729-4061.2020.195355
DETERMINING THE INFLUENCE OF THE
CONDITION OF ROCK-DESTROYING TOOLS
ON THE ROCK CUTTING FORCE (p. 15–20)

Vasil Ivasiv

Ivano-Frankivsk National Technical University
of Oil and Gas, Ivano-Frankivsk, Ukraine

ORCID: <http://orcid.org/0000-0003-4837-1217>

Andriy Yurych

Ivano-Frankivsk National Technical University
of Oil and Gas, Ivano-Frankivsk, Ukraine

ORCID: <http://orcid.org/0000-0002-8772-6191>

Sergii Zabolotnyi

V. Bakul Institute for Superhard Materials of the
National Academy of Sciences of Ukraine, Kyiv, Ukraine

ORCID: <http://orcid.org/0000-0003-1287-8454>

Lidiia Yurych

Ivano-Frankivsk National Technical University
of Oil and Gas, Ivano-Frankivsk, Ukraine

ORCID: <http://orcid.org/0000-0002-2435-9785>

Vasyl Bui

Ivano-Frankivsk National Technical University
of Oil and Gas, Ivano-Frankivsk, Ukraine

ORCID: <http://orcid.org/0000-0003-3258-2167>

Orest Ivasiv

Research and production center of technical
diagnostics «Techdiagas» branch «Ukrtransgaz», Kyiv, Ukraine

ORCID: <http://orcid.org/0000-0002-3192-1879>

At present, the most common tools for drilling operations are those rock-destroying ones that are equipped with cutting elements made from polycrystalline diamonds (PDC) and diamond carbide inserts (DCI). Given this, it is a relevant task to study the influence of the degree of wear of cutting elements on the strength and energy parameters of the process of rock destruction. In order to determine this influence, we have experimentally investigated the cutting process involving a single cutter under laboratory conditions. The mean values of the cutting force components (circular (P_z) and normal (P_y)) have been established at the cutting depth 0.5; 1.0; 1.5; and 2.0 mm, at a varying degree of the cutting element wear (a flat of 0; 5.0; and 8.0 mm). We have determined the magnitude of cutting work and the specific energy of rock destruction. At a cutting depth of 0.5 mm, with an increase in the cutting element wear rate from 0 to 8 mm, the magnitude of work grows from 0.06376 to 0.121 N·m. At a cutting depth of 2.0 mm, the magnitude of work increases from 0.624 to 3.603 N·m. The energy intensity of the rock destruction process increases, with an increase in the cutting depth from 0.5 to 2.0 mm, from 3.88 kJ/m² to 11.66 kJ/m² for a sharp cutter. Based on the study results, we have built dependence charts of the average values of the cutting force components and its normal component (P_y) on cutting depth and the cutting element wear degree. The results obtained have shown a significant influence of the size of the wear flat on the increase in the process strength parameters, which is the basis for regulating a wear degree of cutting elements during drilling. We have established the tendency towards a growth in the resultant force and specific work of rock cutting by a cutting element with an increase in wear degree. This makes it possible to determine, based on the indicators of fluctuations in the instantaneous strength values during drilling of wells, or based on a change in power, the wear degree of the cutting elements, and to predict the probability of their destruction.

Keywords: destruction of rock when drilling, well drilling, PDC bits, cutting force.

References

1. Beaudoin, Y. C., Dallimore, S. R., Boswell, R. (Eds.) (2014). Frozen Heat: A UNEP Global Outlook on Methane Gas Hydrates. Vol. 2. United Nations Environment Programme, GRID-Arendal.
2. Organization of the Petroleum Exporting Countries (2017). OPEC. Annual Statistical Bulletin. Available at: https://www.opec.org/opec_web/static_files_project/media/downloads/publications/ASB2017_13062017.pdf
3. Enerhetychna stratehiya Ukrainy na period do 2035 roku Bezpeka, enerhoefektyvnist, konkurentospromozhnist. Kabinet Ministriv Ukrainy. Available at: <https://www.kmu.gov.ua/npas/250250456>
4. Ivasiv, V. M., Rachkevych, R. V., Yurych, A. R., Kozlov, A. A., Yurych, L. R. (2016). The use of elastic elements for wellbore trajectory management. *Neftyanoe hozyaystvo*, 2, 36–37.
5. Grydzhuk, J., Chudyk, I., Velychkovych, A., Andrusyak, A. (2019). Analytical estimation of inertial properties of the curved rotating section in a drill string. *Eastern-European Journal of Enterprise Technologies*, 1 (7 (97)), 6–14. doi: <https://doi.org/10.15587/1729-4061.2019.154827>
6. Rachkevich, R. V. (2014). In-Plane Bending of a Drill String During its Compression in a Horizontal Borehole. *Strength of Materials*, 46 (6), 843–847. doi: <https://doi.org/10.1007/s11223-014-9618-7>
7. Biletsky, V., Vitryk, V., Mishchuk, Y., Fyk, M., Dzhus, A., Kovalchuk, J. et. al. (2018). Examining the current of drilling mud in a power section of the screw downhole motor. *Eastern-European Journal of Enterprise Technologies*, 2 (5 (92)), 41–47. doi: <https://doi.org/10.15587/1729-4061.2018.126230>
8. Che, D., Han, P., Guo, P., Ehmann, K. (2012). Issues in Polycrystalline Diamond Compact Cutter-Rock Interaction From a Metal Machining Point of View – Part I: Temperature, Stresses, and Forces. *Journal of Manufacturing Science and Engineering*, 134 (6). doi: <https://doi.org/10.1115/1.4007468>
9. Che, D., Han, P., Guo, P., Ehmann, K. (2012). Issues in Polycrystalline Diamond Compact Cutter-Rock Interaction From a Metal Machining Point of View – Part II: Bit Performance and Rock Cutting Mechanics. *Journal of Manufacturing Science and Engineering*, 134 (6). doi: <https://doi.org/10.1115/1.4007623>
10. Zaitsev, V., Karpikov, A., Osipov, V. (2016). PDC bits application in the fields of Eastern and Western Siberia. *Proceedings of the Siberian Department of the Section of Earth Sciences, Russian Academy of Natural Sciences. Geology, Prospecting and Exploration of Ore Deposits*, 4, 62–69. doi: <https://doi.org/10.21285/0130-108x-2016-57-4-62-69>
11. Neskromnykh, V. V., Borisov, K. I., Pushmin, P. S. (2013). Analytical studies of steady-state depth of cutting and shearing under rock destruction by PDC cutters. *Proceedings of the Siberian Department of the Section of Earth Sciences, Russian Academy of Natural Sciences. Geology, Prospecting and Exploration of Ore Deposits*, 2, 78–85.
12. Zaitsev, V. I., Karpikov, A. V., Che, V. V. (2014). Application efficiency of PDC bits. *Proceedings of the Siberian Department of the Section of Earth Sciences, Russian Academy of Natural Sciences. Geology, Prospecting and Exploration of Ore Deposits*, 5 (48), 58–66.
13. Xiao, H., Liu, S., Tan, K. (2019). Experimental Investigation of Force Response, Efficiency, and Wear Behaviors of Polycrystalline Diamond Rock Cutters. *Applied Sciences*, 9 (15), 3059. doi: <https://doi.org/10.3390/app9153059>
14. Liu, J., Zheng, H., Kuang, Y., Xie, H., Qin, C. (2019). 3D Numerical Simulation of Rock Cutting of an Innovative Non-Planar Face PDC Cutter and Experimental Verification. *Applied Sciences*, 9 (20), 4372. doi: <https://doi.org/10.3390/app9204372>

15. Maistrenko, A. L., Vyrovets, L. M., Skliarov, E. D., Zabolotnyi, S. D., Svishnikov, I. A. (2005). Pat. No. 11407 UA. Device for measuring the components of a cutting force. No. u2005506696; declared: 08.07.2005; published: 15.12.2005. Bul. No. 12.
16. Zhukovskiy, O. M., Kryzhanivskiy, Ye. I., Rybchych, I. Y., Novikov, M. V., Bondarenko, M. O., Mechnyk, V. A. (2003). Pat. No. 63469 UA. Diamond-hard-alloy plate. No. u2003043732; declared: 23.04.2003; published: 16.01.2006. Bul. No. 1.

DOI: 10.15587/1729-4061.2020.195050

MODELING THE TRAJECTORY OF MOTION OF METALLIC AND ABRASIVE PARTICLES IN A WASHING GUTTER (p. 21–31)

Tetiana Nadryhailo

Dniprovsk State Technical University, Kamianske, Ukraine
ORCID: <http://orcid.org/0000-0003-1239-5946>

Viktor Vernyhora

Dniprovsk State Technical University, Kamianske, Ukraine
ORCID: <http://orcid.org/0000-0002-2536-4420>

Alexander Korobochka

Dniprovsk State Technical University, Kamianske, Ukraine
ORCID: <http://orcid.org/0000-0003-0592-108X>

Alexander Sasov

Dniprovsk State Technical University, Kamianske, Ukraine
ORCID: <http://orcid.org/0000-0002-8697-6324>

Thousands of tons of metal-containing sludge are produced every month at machine-building, especially bearing producing and metallurgy enterprises where is processed. In the production of bearings, up to 10.0 thousand tons of sludge containing up to 90 % of the metal fraction is produced annually. At present, the sludge is practically nonrecyclable and brought to landfills degrading the environment.

To increase the uniformity of metal powder at the stage of sludge washing, it is necessary to separate the solid articles by their density.

To solve this issue, a comprehensive system of environmentally friendly technology is used for reclaiming the grinding sludge where in the process of movement of the sludge particles in a flow of detergent solution, their washing and separation by density take place. The study of the trajectory of motion of solid sludge particles makes it possible to set the mode parameters of the gutter which provide effective separation of particles by density. This enables determining the height of separator installation in the solution flow and obtaining a larger percentage of homogeneous metal particles.

The main parameters of the washing gutter which can ensure effective separation of metal and abrasive particles include length and width of the gutter, level of the solution flow, flow rate of the solution, flow rate of fluid through the sidewall of the gutter, flow rate of solution through nozzles, number of nozzles and distance between them.

Based on theoretical studies and a mathematical model describing the motion of metallic and abrasive particles in a detergent solution, a program in the C++ language and in the C++ Builder 6 programming environment was developed.

The developed program makes it possible to simulate trajectories of motion of metal and abrasive particles in the detergent solution flow in the gutter. In the mode of random particle parameters, diameter in a range of 18–500 μm for metal particles and in a range of 31–200 μm for abrasive particles is selected.

Keywords: grinding sludge, metal and abrasive particles, trajectory of motion, washing gutter.

References

1. Povstyanoy, A. Yu., Rud', V. D. (2014). Ispol'zovanie othodov proizvodstva dlya izgotovleniya materialov konstruktsionnogo naznacheniya. *Ustoychivoe razvitie*, 19, 159–164.
2. Soloshych, I., Shvedchikova, I. (2016). Development of systematics ranked structure of environmental protecting equipment for cleaning of gas emissions, wastewater and solid waste. *Eastern-European Journal of Enterprise Technologies*, 6 (10 (84)), 17–23. doi: <https://doi.org/10.15587/1729-4061.2016.86462>
3. Razghonova, O., Sokolnik, V. (2014). Electric condensation and dehydration of red sludge. *Eastern-European Journal of Enterprise Technologies*, 6 (10 (72)), 4–7. doi: <https://doi.org/10.15587/1729-4061.2014.29250>
4. Vernigora, V. D., Korobochka, A. N. (2008). Izvlechenie metallicheskikh chastits iz shlamov abrazivnoy obrabotki metallov. *Zbaha-chennia korysnykh kopalyn*, 32 (73), 26–32.
5. Nakamura, K., Hayashi, S. (2006). Grinding Sludge Recycling to Reduce Environmental Load. *Tetsu-to-Hagane*, 92 (8), 535–538. doi: https://doi.org/10.2355/tetsutohagane1955.92.8_535
6. Ryabicheva, L. A., Tsyarkin, A. T., Beloshitskii, N. V. (2007). Powder produced from steel 40Kh10S2M grinding sludge. *Powder Metallurgy and Metal Ceramics*, 46 (5-6), 298–302. doi: <https://doi.org/10.1007/s11106-007-0047-z>
7. Shimizu, T., Hanada, K., Adachi, S., Katoh, M., Hatsukano, K., Matsuzaki, K. (2007). Recycling of Stainless Steel Grinding Sludge. *Materials Science Forum*, 534-536, 997–1000. doi: <https://doi.org/10.4028/www.scientific.net/msf.534-536.997>
8. Ruffino, B., Zanetti, M. C. (2008). Recycling of steel from grinding scraps: Reclamation plant design and cost analysis. *Resources, Conservation and Recycling*, 52 (11), 1315–1321. doi: <https://doi.org/10.1016/j.resconrec.2008.07.012>
9. Rud, V. D., Halchuk, T. N. (2011). Aparatna realizatsiya tekhnolohiyi utylizatsiyi vidkhodiv pidshypnykovoho vyrobnytstva. *Tekhnolohichni komplekxy*, 2 (4), 75–80.
10. Rud', V. D., Gal'chuk, T. N., Povstyanoy, A. Yu. (2005). Ispol'zovanie othodov podshypnikovogo proizvodstva v poroshkovoy metallurgii. *Poroshkovaya metallurgiya*, 1-2, 106–112.
11. Vernigoro, Y. M., Plotnikov, D. M., Frolova, N. N. (2012). Features of magnetovibrating technologies of slime separation in grinding manufacture. *Vestnik Donskogo gosudarstvennogo tekhnicheskogo universiteta*, 8 (69), 41–50.
12. Kayak, G., Fomenko, V., Andreev, V. (2017). Recycling technique for grinding sludge. *FEFU: School of Engineering Bulletin*, 1 (30), 60–67.
13. Liu, D., Chen, Q., Wang, Y. (2011). Spectral element modeling of sediment transport in shear flows. *Computer Methods in Applied Mechanics and Engineering*, 200 (17-20), 1691–1707. doi: <https://doi.org/10.1016/j.cma.2011.01.009>
14. Glowinski, R., Pan, T.-W., Hesla, T. I., Joseph, D. D. (1999). A distributed Lagrange multiplier/fictitious domain method for particulate flows. *International Journal of Multiphase Flow*, 25 (5), 755–794. doi: [https://doi.org/10.1016/s0301-9322\(98\)00048-2](https://doi.org/10.1016/s0301-9322(98)00048-2)
15. Apte, S. V., Martin, M., Patankar, N. A. (2009). A numerical method for fully resolved simulation (FRS) of rigid particle–flow interactions in complex flows. *Journal of Computational Physics*, 228 (8), 2712–2738. doi: <https://doi.org/10.1016/j.jcp.2008.11.034>
16. Bondarenko, A. A. (2013). Obosnovanie parametrov gorizontaln'nogo klassifikatora putem izucheniya vzaimodeystviya tverdogo chastitsy s potokom zhidkosti. *Zbirnyk naukovykh prats Dniprodzerzhynskoho derzhavnoho tekhnicheskoho universytetu (Tekhnichni nauky)*, 3 (28), 114–119.
17. Halchuk, T. N. (2012). Rozrobka tekhnolohiyi otrymannia metallichnogo poroshku dlia vyhotovlennia vyrobiv mashynobudivnoho vyrobnytstva. *Naukovi notatky*, 38, 25–30.

18. Furs, V. (2013). Methods of metal recycling. *Naukovi notatky*, 42, 314–318.
19. Belotserkovskii, O. M., Gushchin, V. A., Shchennikov, V. V. (1975). Use of the splitting method to solve problems of the dynamics of a viscous incompressible fluid. *USSR Computational Mathematics and Mathematical Physics*, 15 (1), 190–200. doi: [https://doi.org/10.1016/0041-5553\(75\)90146-9](https://doi.org/10.1016/0041-5553(75)90146-9)
20. Belotserkovskiy, O. M. (1984). *Chislennoe modelirovanie v mehanike sploshnyh sred*. Moscow: Nauka, 520.

DOI: 10.15587/1729-4061.2020.192680

REVEALING PATTERNS OF THE EFFECTIVE MECHANICAL CHARACTERISTICS OF CELLULAR SHEET POLYCARBONATE FOR EXPLOSION VENTING PANELS (p. 32–39)

Serhii Pozdieiev

Cherkasy Institute of Fire Safety named after Chernobyl Heroes of National University of Civil Defense of Ukraine, Cherkasy, Ukraine
ORCID: <http://orcid.org/0000-0002-9085-0513>

Myhalenko Kostiantyn

Cherkasy Institute of Fire Safety named after Chernobyl Heroes of National University of Civil Defense of Ukraine, Cherkasy, Ukraine
ORCID: <http://orcid.org/0000-0002-7125-8442>

Vitalii Nuianzin

Cherkasy Institute of Fire Safety named after Chernobyl Heroes of National University of Civil Defense of Ukraine, Cherkasy, Ukraine
ORCID: <http://orcid.org/0000-0003-4785-0814>

Oleh Zemlianskiy

Cherkasy Institute of Fire Safety named after Chernobyl Heroes of National University of Civil Defense of Ukraine, Cherkasy, Ukraine
ORCID: <http://orcid.org/0000-0002-2728-6972>

Tetiana Kostenko

Cherkasy Institute of Fire Safety named after Chernobyl Heroes of National University of Civil Defense of Ukraine, Cherkasy, Ukraine
ORCID: <http://orcid.org/0000-0001-9426-8320>

Explosive concentrations of various substances can accumulate inside industrial premises. In the presence of a sufficient amount of oxygen and an ignition source, such a situation could lead to explosion that may result in the destruction of building structures and the building in general. Strengthening the stability of supporting structures is aimed at protecting industrial premises against possible destruction by explosion indoors.

One of the effective ways to protect construction structures against the excessive pressure of explosion is to use explosion venting panels. In order to solve practical tasks on protecting industrial premises and structures against explosion, one must be able to choose both the area and parameters for explosion venting panels. In addition, in order to reduce the related loads to safe quantities, it is necessary to properly calculate the bearing structures in terms of dynamic stability while maintaining their carrying capacity. The set task to ensure protection against explosion by applying explosion venting panels with flexible elements can be solved through integrated accounting for mechanical properties of cellular polycarbonate sheets.

We have performed experimental research into performance of the inertia-free explosion venting panels with flexible enclosing elements exposed to dynamic loads under conditions of explosion. Based on the obtained results, the effective rigidity and critical displacement of cellular polycarbonate sheets of flexible elements have been determined. It has been established that for cellular polycarbonate sheets with a thickness of 4–8 mm effective rigidity

ranges within 301–215 N·m; the critical displacement of edges in this case is 2.9–9.8 mm.

A mathematical model has been proposed that takes into consideration the influence of geometric dimensions and the critical value of deflection in a polycarbonate sheet as the flexible element of fencing on the operational conditions for explosion venting panels.

Keywords: explosion venting panels, polycarbonate cellular sheet, effective mechanical characteristics, experimental-estimation method.

References

1. Travmatyzm na vyrobnytsvni v Ukraini: natsionalnyi profil protiahom 2009–2013 rokiv. Informatsiyno-analitychna profspil'kova dopovid.
2. Khokhotva, O. I. (2010). Pro stan promyslovoi bezpeky ta okhorony pratsi. *Okhorona pratsi*, 12, 7–8.
3. Migalenko, K., Nuianzin, V., Zemlianskiy, A., Dominik, A., Pozdieiev, S. (2018). Development of the technique for restricting the propagation of fire in natural peat ecosystems. *Eastern-European Journal of Enterprise Technologies*, 1 (10 (91)), 31–37. doi: <https://doi.org/10.15587/1729-4061.2018.121727>
4. Kostenko, V., Kostenko, T., Zemlianskiy, O., Maiboroda, A., Kutsenko, S. (2017). Automatization of individual anti-thermal protection of rescuers in the initial period of fire suppression. *Eastern-European Journal of Enterprise Technologies*, 5 (10 (89)), 4–11. doi: <https://doi.org/10.15587/1729-4061.2017.109484>
5. Li, J., Hao, H. (2017). Internal and external pressure prediction of vented gas explosion in large rooms by using analytical and CFD methods. *Journal of Loss Prevention in the Process Industries*, 49, 367–381. doi: <https://doi.org/10.1016/j.jlp.2017.08.002>
6. Christian, A., Chye, G. O. K. (2014). Performance of Fiber Reinforced High-strength Concrete with Steel Sandwich Composite System as Blast Mitigation Panel. *Procedia Engineering*, 95, 150–157. doi: <https://doi.org/10.1016/j.proeng.2014.12.174>
7. Draganić, H., Gazić, G., Varevac, D. (2019). Experimental investigation of design and retrofit methods for blast load mitigation – A state-of-the-art review. *Engineering Structures*, 190, 189–209. doi: <https://doi.org/10.1016/j.engstruct.2019.03.088>
8. Alberdi, R., Przywara, J., Khandelwal, K. (2013). Performance evaluation of sandwich panel systems for blast mitigation. *Engineering Structures*, 56, 2119–2130. doi: <https://doi.org/10.1016/j.engstruct.2013.08.021>
9. Niollet, J. E., Yuen, S. C. K., Nurick, G. N. (2015). A Study to Assess the Use of Cylindrical Bars as Blast Barriers. *International Journal of Protective Structures*, 6 (2), 263–286. doi: <https://doi.org/10.1260/2041-4196.6.2.263>
10. Orlov, G. G. (1987). *Legkosbrasyvaemye konstruktsii dlya vzryvo-zashchity promyshlennyh zdaniy*. Moscow: Stroyizdat, 200.
11. Pozdieiev, S., Pidgoretskiy, Y., Nekora, O., Sidnei, S., Tyshchenko, O. (2018). Research of Explode Exposure at the Relief Vent System Structures with Soft Transparent Material. *International Journal of Engineering & Technology*, 7 (4.3), 298. doi: <https://doi.org/10.14419/ijet.v7i4.3.19808>
12. Sinha, A., Wen, J. X. (2019). A simple model for calculating peak pressure in vented explosions of hydrogen and hydrocarbons. *International Journal of Hydrogen Energy*, 44 (40), 22719–22732. doi: <https://doi.org/10.1016/j.ijhydene.2019.02.213>
13. Zhang, S., Zhang, Q. (2018). Effect of vent size on vented hydrogen-air explosion. *International Journal of Hydrogen Energy*, 43 (37), 17788–17799. doi: <https://doi.org/10.1016/j.ijhydene.2018.07.194>
14. Pang, L., Hu, Q., Zhao, J., Lv, P., Sun, S., Yang, K. (2019). Numerical study of the effects of vent opening time on hydrogen explosions. *International Journal of Hydrogen Energy*, 44 (29), 15689–15701. doi: <https://doi.org/10.1016/j.ijhydene.2019.04.175>

15. Feldgun, V. R., Yankelevsky, D. Z., Karinski, Y. S. (2016). A nonlinear SDOF model for blast response simulation of elastic thin rectangular plates. *International Journal of Impact Engineering*, 88, 172–188. doi: <https://doi.org/10.1016/j.ijimpeng.2015.09.001>

DOI: 10.15587/1729-4061.2020.194584
PREDICTION OF THE SERVICE LIFE OF DEEP-SEA CONICAL ACRYLIC PORTHOLES AT DESIGNING (p. 40–46)

Yevgen Burdun

Admiral Makarov National University of Shipbuilding, Mykolayiv, Ukraine

ORCID: <http://orcid.org/0000-0002-6682-3777>

Vladimir Kochanov

Admiral Makarov National University of Shipbuilding, Mykolayiv, Ukraine

ORCID: <http://orcid.org/0000-0001-7525-0870>

Tetyana Yuresko

Admiral Makarov National University of Shipbuilding, Mykolayiv, Ukraine

ORCID: <http://orcid.org/0000-0002-4197-1677>

Conical deep-sea portholes (CDSP) from acrylic are widely used in underwater equipment. Due to the specific properties of acrylic, operating conditions and the stress-strain state of CDSP, it is difficult to evaluate service life and choose optimal geometric characteristics. The experimental studies and numerical calculations of the stress-strain state of CDSP from acrylic under various levels of hydrostatic pressure were made to develop an optimal design method of CDSP considering operating conditions. CDSP from acrylic were exposed to long-term (up to 7 days) and cyclic (up to 2000 cycles) hydrostatic pressure of 40, 60, 70 and 80 MPa.

The deformation of the CDSP was periodically determined at no less than 20 experimental points with the help of displacement sensors. Experimental dependences of the CDSP displacements were obtained under long-term and cyclic exposure to hydrostatic pressure. According to the method of stress-time analogy, a forecast of the CDSP deformability for 10 years is made.

The series of CDSP calculations with cone angles of 60–150° and relative thicknesses of 0.35–0.60 using the finite-element method was made. The calculations obtained by the finite-element method coincide with the experimental results, which demonstrated the adequacy of the adopted CDSP design scheme – continuous sliding of the translucent element with friction along the supporting surface of the porthole body. It is shown that an increase in the cone angle reduces the deflection of the CDSP, and equivalent stresses are minimal at cone angles of 75–105°. The synthesis of stress-strain state calculations by the finite-element method in aggregate with the prediction based on short-term tests allows selecting the optimal geometric characteristics of CDSP, depending on the operating conditions.

Keywords: deep-sea portholes, heat aging, acrylic, hydrostatic pressure, prediction of properties, service life.

References

- ASME PVHO-1. 2012. Safety standard for pressure vessels for human occupancy. New York (NY): American Society of Mechanical Engineers.
- Stachiw, J. D. (2003). *Handbook of Acrylics for Submersibles*. Hyperbaric Chambers and Aquaria. Best Publishing Co., 1080.
- Stechiv, Dzh., Dolan, R. (1982). Vliyanie atmosferynykh usloviy dlitel'nosti ekspluatatsii i tsiklicheskogo nagruzheniya gidrostaticheskim davleniem na rabotosposobnost' sfericheskikh korpusov iz akrilovoy plastmassy pri nagruzhenii vneshnim davleniem. *Konstruirovaniye i tehnologiya mashinostroeniya*, 104 (2), 227–244.
- Trudel, T., Stanley, K. (2019). Window Seat Weight Reduction Exploration With Nontraditional Seat Geometry. *Marine Technology Society Journal*, 53 (1), 107–116. doi: <https://doi.org/10.4031/mts.53.1.2>
- Tian, C. L., Hu, Y., Liu, D. Q., Cui, W. C. (2010). Creep analysis on deepsea structure's viewport windows. *J. Ship Mechanics*, 14 (5), 526–532.
- Pranesh, S. B. et. al. (2018). Structural analysis of spherical pressure hull viewport for manned submersibles using biological growth method. *Ships and Offshore Structures*, 13 (6), 601–616. doi: <https://doi.org/10.1080/17445302.2018.1440885>
- Wang, F., Wang, W., Zhang, Y., Du, Q., Jiang, Z., Cui, W. (2019). Effect of Temperature and Nonlinearity of PMMA Material in the Design of Observation Windows for a Full Ocean Depth Manned Submersible. *Marine Technology Society Journal*, 53 (1), 27–36. doi: <https://doi.org/10.4031/mts.53.1.4>
- Kemper, B. (2016). Use of finite element analysis in designing acrylic structures for fatigue and stress. *Proceedings of the 13th Annual Manned Underwater Vehicles Symposium (Marine Technology Society)*; New Orleans, LA. doi: <http://doi.org/10.13140/RG.2.2.26146.12482/2>
- Du, Q., Hu, Y., Cui, W. (2016). Safety assessment of the acrylic conical frustum viewport structure for a deep-sea manned submersible. *Ships and Offshore Structures*, 12 (sup1), S221–S229. doi: <https://doi.org/10.1080/17445302.2016.1261390>
- Bartenev, G. M. (1983). *Fizika i mehanika polimerov*. Moscow: Vyssh. shkola, 391.
- Shah, V.; Malkina, A. Ya. (Ed.) (2009). *Spravochnoe rukovodstvo po ispytaniyam plastmass i analizu prichin ih razrusheniya*. Sankt-Peterburg: NOT, 732.
- Urzhumtsev, Yu. S., Maksimov, R. D. (1975). *Prognostika deformativnosti polimernykh materialov*. Riga: Zinatne, 415.
- Gol'dman, A. Ya. (1988). *Prognozirovaniye deformatsionno – prochnostnykh svoystv polimernykh kompozitsionnykh materialov*. Leningrad: Himiya, 272.
- Kemper, B. (2012). *Advances in acrylics and expansion of PVHO window cyclic life*. Conference: Underwater Intervention 2012, at New Orleans, Louisiana USA.

DOI: 10.15587/1729-4061.2020.195193
IMPROVING THE RETENTION CAPACITY OF CLAMPING ELEMENTS (p. 47–51)

Emin Musa Afandiyev

Azerbaijan State University of Economics (UNEC),
 Baku, Azerbaijan

ORCID: <http://orcid.org/0000-0002-8676-7194>

Mahamadali Nuraddin Nuriyev

Azerbaijan State University of Economics (UNEC),
 Baku, Azerbaijan

ORCID: <http://orcid.org/0000-0002-6729-4627>

An analysis of the discarded drill pipes that had been used in wedge grips has revealed that the main reason for pipe rejection is the reduction of a pipe wall as a result of plastic deformations, due to damaging the pipe surface by the die teeth. The long-term exposure to loads results in the plastic deformations of cylindrical parts, which could lead to unacceptable damage and distortion of the shape. In the oil industry, when drilling and casing pipes are clamped, stresses over some areas in the capture zone exceed the fluidity limit. Multiple clamps of the pipe could reduce the wall of the pipe in the capture

area, which leads to premature failure of the pipe. Pipe crumpling occurs not immediately when the load is applied but gradually, by local plastic deformity of the pipe at various points in length and circumference, where the stresses exceed the limit of the fluidity of the pipe material. In order to prevent unacceptable deformations of pipes during hoisting operations, we have considered the possibilities to reduce loads.

In this regard, special attention has been paid to the design of clamping jaws that provide the increased retention capacity and the technology of their manufacture. The greatest retention capacity is ensured by jaws with an oblique intersecting notch. In such jaws, the teeth of the notch are arranged chequerwise. This makes it possible to exclude the formation of vertical grooves on the body of the pipe due to slippage induced by the axial load. However, the manufacture of such notches at the inner cylindrical surface of clamping jaws is associated with some difficulties. This relates to that there are no standard tools for making such notched surfaces of complex configuration. The result of our research is the designed and manufactured special tool, as well as the technology for its fabrication. That has made it easier to cut the notches on clamping jaws that ensure the reliable capture of drill pipes.

Keywords: wedge grip, drill pipes, clamp force, jaw notch, retention capacity.

References

1. Markov, O., Gerasimenko, O., Khvashchynskiy, A., Zhytnikov, R., Puzyr, R. (2019). Modeling the technological process of pipe forging without a mandrel. *Eastern-European Journal of Enterprise Technologies*, 3 (1 (99)), 42–48. doi: <https://doi.org/10.15587/1729-4061.2019.167077>
2. Raygorodskiy, R. P., Sudnitsyn, N. V. (1949). Pat. No. SU 95916 A1. Klin'evoy zahvat dlya buril'nyh i obsadnyh trub. declared: 09.06.1949; published: 01.01.1953.
3. Afandiyev, E. M., Nuriyev, M. N. (2019). Studying the quality of drill pipes clamped in a wedge clamp. *Eastern-European Journal of Enterprise Technologies*, 4 (7 (100)), 16–21. doi: <https://doi.org/10.15587/1729-4061.2019.174494>
4. Rukovodstvo po trubam neftyanogo sortamenta i ih soedineniyam, primenyayemym za rubezhom (1969). Moscow: Nedra, 296.
5. Wang, L., Guo, S., Gong, H., Shang, X. (2016). Research and development of a self-centering clamping device for deep-water multi-functional pipeline repair machinery. *Natural Gas Industry B*, 3 (1), 82–89. doi: <https://doi.org/10.1016/j.ngib.2015.12.012>
6. Djukic, L. P., Sum, W. S., Leong, K. H., Hillier, W. D., Eccleshall, T. W., Leong, A. Y. L. (2015). Development of a fibre reinforced polymer composite clamp for metallic pipeline repairs. *Materials & Design*, 70, 68–80. doi: <https://doi.org/10.1016/j.matdes.2014.12.059>
7. Yakhin, A. R., Ismakov, R. A., Garifullin, R. R., Yangirov, F. N. (2014). Surface hardening for drill pipe life improvement. *Neftegazovoe delo*, 4, 381–399.
8. Bulatov, A. I., Proselkov, Yu. M., Shamanov, S. A. (2013). Tehnika i tehnologiya bureniya neftyanyh i gazovyh skvazhin. *Vestnik nauki Sibiri*, 3 (9).
9. Markov, O., Gerasimenko, O., Aliieva, L., Shapoval, A. (2019). Development of the metal rheology model of high-temperature deformation for modeling by finite element method. *EUREKA: Physics and Engineering*, 2, 52–60. doi: <https://doi.org/10.21303/2461-4262.2019.00877>
10. Lopatuhin, I. M. (1989). Razrabotka zashimnyh ustroystv neftepromyslovogo oborudovaniya s povyshennoy uderzhivayushchey sposobnost'yu. Moscow.
11. Efendiev, E. M., Lopatuhin, I. M. (1972). Avtorskoe svidetel'stvo SSSR No. 356059. Instrument dlya narezaniya kosykh vnutrennih nasechek. *Bul. No. 32*.

DOI: 10.15587/1729-4061.2020.192590
SIMULATION MODEL OF THE MORPHOLOGICAL FIELD OF DATA FOR CONSTRUCTING A UNIVERSAL DESIGN OF TROUSERS (p. 52–61)

Alla Slavinska

Khmelnitskiy National University, Khmelnytskyi, Ukraine
ORCID: <http://orcid.org/0000-0003-0663-9422>

Oksana Syrotenko

Khmelnitskiy National University, Khmelnytskyi, Ukraine
ORCID: <http://orcid.org/0000-0002-6816-6467>

Oksana Dombrovska

Khmelnitskiy National University, Khmelnytskyi, Ukraine
ORCID: <http://orcid.org/0000-0001-7076-7627>

Victoriia Mytsa

Khmelnitskiy National University, Khmelnytskyi, Ukraine
ORCID: <http://orcid.org/0000-0002-5453-9787>

The reported research into the influence of a database on the processes of universal design formation has established a mechanism for the interactive application of clusters of size-based attributes. It has been proven that the typological series of a structural size characterizes a conditional standard body figure of the youth type. This has made it possible to determine the mobility of structural zones in accordance with the morphological features of a body structure at the stages of forming the base for a design. Our experimental study has confirmed that the boundaries of functional sections in the grouping of structural zones are governed by the variability of gains by the basic structural points. That leads to the poly-variance of the pelvic section when forming properties for the proportionality of trousers. Specifically, it has been established that due to identifying the similarity of structures based on a scaling ratio, the adequacy of a database is improved by coordinating the information base for constructing structural zones. This allows us to assert the reliability of the mechanism that forms clusters within an anthropometric database, as well as practical attractiveness of the proposed interactive design technology. It has been shown that the variance in gains ensures decomposition of the closed contour of a part at the points of change in functional sections, which is the advantage of the current research. We have shown the prospects for extending the range of morphological types based on the age-trait biodynamics of functional movements.

Thus, there are grounds to assert the possibility of targeted control over the processes that form a universal design by employing an integrated database that combines the clusters of size-based attributes, gains, as well as a structural zones nomenclature.

Keywords: cluster, size-based attributes, universal design, structural zones, gains, morphological field.

References

1. Traumann, A., Peets, T., Dabolina, I., Lapkovska, E. (2019). Analysis of 3-D body measurements to determine trousers sizes of military combat clothing. *Textile & Leather Review*, 2 (1), 6–14. doi: <https://doi.org/10.31881/tlr.2019.2>
2. Brito, P. Q., Soares, C., Almeida, S., Monte, A., Byvoet, M. (2015). Customer segmentation in a large database of an online customized fashion business. *Robotics and Computer-Integrated Manufacturing*, 36, 93–100. doi: <https://doi.org/10.1016/j.rcim.2014.12.014>
3. Sudacevski, S. (2015). Changes and modifications of the trousers patterns for non-standard figures. *Studii Artelor și Culturologie: Istorie, Teorie, Practică*, 4 (27), 81–85.
4. Hong, Y., Bruniaux, P., Zeng, X., Liu, K., Curteza, A., Chen, Y. (2018). Visual-Simulation-Based Personalized Garment Block Design

- Method for Physically Disabled People with Scoliosis (PDPS). *Autex Research Journal*, 18 (1), 35–45. doi: <https://doi.org/10.1515/aut-2017-0001>
5. Nayak, R., Padhye, R., Wang, L., Chatterjee, K., Gupta, S. (2015). The role of mass customisation in the apparel industry. *International Journal of Fashion Design, Technology and Education*, 8 (2), 162–172. doi: <https://doi.org/10.1080/17543266.2015.1045041>
 6. Hong, Y., Curteza, A., Zeng, X., Bruniaux, P., Chen, Y. (2016). Sensory evaluation based fuzzy AHP approach for material selection in customized garment design and development process. *IOP Conference Series: Materials Science and Engineering*, 133, 012058. doi: <https://doi.org/10.1088/1757-899x/133/1/012058>
 7. Tao, X., Chen, X., Zeng, X., Koehl, L. (2018). A customized garment collaborative design process by using virtual reality and sensory evaluation on garment fit. *Computers & Industrial Engineering*, 115, 683–695. doi: <https://doi.org/10.1016/j.cie.2017.10.023>
 8. Sybilska, W., Napieralska, L., Mielicka, E. (2010). Analysis of body measurements using a 3D contactless scanning method. *AUTEX Research Journal*, 10 (3), 77–79.
 9. Sayem, A. S. M., Kennon, R., Clarke, N. (2012). Resizable trouser template for virtual design and pattern flattening. *International Journal of Fashion Design, Technology and Education*, 5 (1), 55–65. doi: <https://doi.org/10.1080/17543266.2011.614963>
 10. Etikan, I. (2016). Comparison of Convenience Sampling and Purposive Sampling. *American Journal of Theoretical and Applied Statistics*, 5 (1), 1. doi: <https://doi.org/10.11648/j.ajtas.20160501.11>
 11. Mpampa, M. L., Azariadis, P. N., Sapidis, N. S. (2010). A new methodology for the development of sizing systems for the mass customization of garments. *International Journal of Clothing Science and Technology*, 22 (1), 49–68. doi: <https://doi.org/10.1108/09556221011008802>
 12. Ding, Y.-S., Hu, Z.-H., Zhang, W.-B. (2011). Multi-criteria decision making approach based on immune co-evolutionary algorithm with application to garment matching problem. *Expert Systems with Applications*, 38 (8), 10377–10383. doi: <https://doi.org/10.1016/j.eswa.2011.02.053>
 13. Domingo, J., Ibáñez, M. V., Simó, A., Dura, E., Ayala, G., Alemany, S. (2014). Modeling of female human body shapes for apparel design based on cross mean sets. *Expert Systems with Applications*, 41 (14), 6224–6234. doi: <https://doi.org/10.1016/j.eswa.2014.04.014>
 14. Olaru, S., Filipescu, E., Avădanei, M., Mocenco, A., Popescu, G., Săliștean, A. (2015). Applied 3D Virtual Try-on for Bodies with Atypical Characteristics. *Procedia Engineering*, 100, 672–681. doi: <https://doi.org/10.1016/j.proeng.2015.01.419>
 15. Chaw Hlaing, E., Krzywinski, S., Roedel, H. (2013). Garment prototyping based on scalable virtual female bodies. *International Journal of Clothing Science and Technology*, 25 (3), 184–197. doi: <https://doi.org/10.1108/09556221311300200>
 16. Slavinska, A. L. (2011). Mekhanizm vyznachennia obsiahu vybirky dlia antropolohichnykh obstezhen naseleennia. *Visnyk Khmelnytskoho natsionalnoho universytetu*, 5, 51–57.
 17. Mok, P. Y., Xu, J., Wu, Y. Y. (2016). Fashion design using evolutionary algorithms and fuzzy set theory – a case to realize skirt design customizations. *Information Systems for the Fashion and Apparel Industry*, 163–197. doi: <https://doi.org/10.1016/b978-0-08-100571-2.00009-9>
 18. McKinney, E., Gill, S., Dorie, A., Roth, S. (2016). Body-to-Pattern Relationships in Women's Trouser Drafting Methods. *Clothing and Textiles Research Journal*, 35 (1), 16–32. doi: <https://doi.org/10.1177/0887302x16664406>
 19. Yamazaki, K., Oya, R., Nagahama, K., Okada, K., Inaba, M. (2016). Bottom Dressing by a Dual-Arm Robot Using a Clothing State Estimation Based on Dynamic Shape Changes. *International Journal of Advanced Robotic Systems*, 13 (1), 5. doi: <https://doi.org/10.5772/61930>
 20. McKinney, E. C., Bye, E., LaBat, K. (2012). Building patternmaking theory: a case study of published patternmaking practices for pants. *International Journal of Fashion Design, Technology and Education*, 5 (3), 153–167. doi: <https://doi.org/10.1080/17543266.2012.666269>
 21. Gill, S., Hayes, S. (2012). Lower body functional ease requirements in the garment pattern. *International Journal of Fashion Design, Technology and Education*, 5 (1), 13–23. doi: <https://doi.org/10.1080/17543266.2011.593560>
 22. Zakharkovich, O. V., Kuleshova, S. G. (2017). Development of the method of scaling patterns and virtual garments forms. *Vlakna a Textil*, 4, 34–40.
 23. Dombrovska, O. M., Mytsa, V. V. (2017). Research of basic constructions for clothes and daily primary age group. *Herald of Khmelnytskyi national university*, 5, 54–57.
 24. Slavinskaya, A. L., Vovk, Yu. V. (2013). Formirovanie optsiy preobrazovaniya interaktivnoy konstruksii pryamoy yubki v konstruksiyu klassicheskikh bryuk. *Molodoy ucheniy*, 10 (57), 198–201.
 25. Mengna, G., Kuzmichev, V. E. (2013). Pressure and comfort perception in the system «female body – dress». *Autex Research Journal*, 13 (3), 71–78. doi: <https://doi.org/10.2478/v10304-012-0032-6>
 26. Slavinska, A., Zakharkovich, O., Kuleshova, S., Syrotenko, O. (2018). Development of a technology for interactive design of garments using add-ons of a virtual mannequin. *Eastern-European Journal of Enterprise Technologies*, 6 (1 (96)), 28–39. doi: <https://doi.org/10.15587/1729-4061.2018.148984>
 27. Shvets, H. S. (2009). Antropometrychna modyfikatsiya hrachnoi modeli poverkhni tazovoi chastyny manekena na sumizhni rozmiry i povnoty typovykh fihur. *Visnyk Khmelnytskoho natsionalnoho universytetu*, 4, 160–163.
 28. Zakharkovich, O. V., Kuleshova, S. G., Slavinska, A. L. (2015). Scale factors calculating for recreating women's garments' form. *Magazine textile and clothing*, 6, 146–151.
 29. Njagi, R. K., Zwane, P. E. (2011). Variation in measurements across different brands of same style ladies' pants in Swaziland. *International Journal of Fashion Design, Technology and Education*, 4 (1), 51–57. doi: <https://doi.org/10.1080/17543266.2010.521195>