

ABSTRACT AND REFERENCES

ECOLODY

DOI: 10.15587/1729-4061.2020.200140
USE OF UNCERTAINTY FUNCTION FOR
IDENTIFICATION OF HAZARDOUS STATES OF
ATMOSPHERIC POLLUTION VECTOR (p. 6–12)

Boris Pospelov

V. N. Karazin Kharkiv National University,
 Kharkiv, Ukraine

ORCID: <http://orcid.org/0000-0002-0957-3839>

Evgeniy Rybka

National University of Civil Defence of Ukraine,
 Kharkiv, Ukraine

ORCID: <http://orcid.org/0000-0002-5396-5151>

Ruslan Meleshchenko

National University of Civil Defence of Ukraine,
 Kharkiv, Ukraine

ORCID: <http://orcid.org/0000-0001-5411-2030>

Oleksii Krainiukov

V. N. Karazin Kharkiv National University,
 Kharkiv, Ukraine

ORCID: <http://orcid.org/0000-0002-5264-3118>

Serhii Harbuz

National University of Civil Defence of Ukraine,
 Kharkiv, Ukraine

ORCID: <http://orcid.org/0000-0001-6345-6214>

Yuliia Bezuhla

National University of Civil Defence of Ukraine,
 Kharkiv, Ukraine

ORCID: <http://orcid.org/0000-0003-4022-2807>

Ihor Morozov

National Academy of the National Guard of Ukraine,
 Kharkiv, Ukraine

ORCID: <http://orcid.org/0000-0002-9643-481X>

Anna Kuruch

National Academy of the National Guard of Ukraine,
 Kharkiv, Ukraine

ORCID: <http://orcid.org/0000-0001-8310-6836>

Olena Saliyenko

National Academy of the National Guard of Ukraine,
 Kharkiv, Ukraine

ORCID: <http://orcid.org/0000-0002-3531-9455>

Ruslan Vasylychenko

National Academy of the National Guard of Ukraine,
 Kharkiv, Ukraine

ORCID: <http://orcid.org/0000-0002-8854-1252>

The use of estimation of the values of the uncertainty function to identify hazardous states of an arbitrary atmospheric pollution vector is considered. At the same time, it is proposed to estimate the uncertainty function in a fixed-width window moving along the trajectory of the state vector. This allows not only identifying the occurrence of hazardous states of atmospheric pollution, but also determining their radial velocity relative to the monitoring post. Zero radial velocity of hazardous states of

atmospheric pollution allows identifying current states of no pollution dispersion in the atmosphere. These states turn out to be especially dangerous, since they lead to the accumulation of pollution and an increase in their concentration in the atmosphere. Verification of the possibility of using the uncertainty function to identify hazardous states of the atmospheric pollution vector was carried out using experimental data. At the same time, formaldehyde, ammonia and carbon monoxide were considered as hazardous components of the state vector of atmospheric pollution. The verification results generally indicate the possibility of using the uncertainty function to identify hazardous states of the atmospheric pollution vector. The use of uncertainty function is found to be invariant with respect to the irregularity of recording of atmospheric pollution at stationary monitoring posts. It is shown that the use of uncertainty function enables the identification of hazardous states characterized not only by exceeding the maximum permissible concentrations, but also by the zero radial velocity relative to the monitoring point. It is experimentally found that in order to identify hazardous states of atmospheric pollution, the window length should be from 4 to 8 readings

Keywords: atmospheric pollution, pollution concentration, uncertainty function, radial velocity, state vector

References

1. Kondratenko, O. M., Vambol, S. O., Stokov, O. P., Avramenko, A. M. (2015). Mathematical model of the efficiency of diesel particulate matter filter. *Naukovyi Visnyk Natsionalnoho Hirnychoho Universytetu*, 6, 55–61.
2. Vasiliev, M. I., Movchan, I. O., Koval, O. M. (2014). Diminishing of ecological risk via optimization of fire-extinguishing system projects in timber-yards. *Naukovyi Visnyk Natsionalnoho Hirnychoho Universytetu*, 5, 106–113.
3. Dubinin, D., Korytchenko, K., Lisnyak, A., Hrytsyna, I., Trigub, V. (2017). Numerical simulation of the creation of a fire fighting barrier using an explosion of a combustible charge. *Eastern-European Journal of Enterprise Technologies*, 6 (10 (90)), 11–16. doi: <https://doi.org/10.15587/1729-4061.2017.114504>
4. Semko, A., Rusanova, O., Kazak, O., Beskrovnaya, M., Vinogradov, S., Gricina, I. (2015). The use of pulsed high-speed liquid jet for putting out gas blow-out. *The International Journal of Multiphysics*, 9 (1), 9–20. doi: <https://doi.org/10.1260/1750-9548.9.1.9>
5. Kustov, M. V., Kalugin, V. D., Tutunik, V. V., Tarakhno, E. V. (2019). Physicochemical principles of the technology of modified pyrotechnic compositions to reduce the chemical pollution of the atmosphere. *Voprosy khimii i khimicheskoi tekhnologii*, 1, 92–99. doi: <https://doi.org/10.32434/0321-4095-2019-122-1-92-99>
6. Vasyukov, A., Loboichenko, V., Bushtec, S. (2016). Identification of bottled natural waters by using direct conductometry. *Ecology Environment and Conservation*, 22 (3), 1171–1176.
7. Pascual, M., Ellner, S. P. (2000). Linking ecological patterns to environmental forcing via nonlinear time series models. *Ecol-*

- ogy, 81 (10), 2767–2780. doi: [https://doi.org/10.1890/0012-9658\(2000\)081\[2767:leptef\]2.0.co;2](https://doi.org/10.1890/0012-9658(2000)081[2767:leptef]2.0.co;2)
8. Parrott, L. (2004). Analysis of simulated long-term ecosystem dynamics using visual recurrence analysis. *Ecological Complexity*, 1 (2), 111–125. doi: <https://doi.org/10.1016/j.ecocom.2004.01.002>
 9. Proulx, R. (2007). Ecological complexity for unifying ecological theory across scales: A field ecologist's perspective. *Ecological Complexity*, 4 (3), 85–92. doi: <https://doi.org/10.1016/j.ecocom.2007.03.003>
 10. Marwan, N., Kurths, J. (2002). Nonlinear analysis of bivariate data with cross recurrence plots. *Physics Letters A*, 302 (5-6), 299–307. doi: [https://doi.org/10.1016/s0375-9601\(02\)01170-2](https://doi.org/10.1016/s0375-9601(02)01170-2)
 11. Kantz, H., Schreiber, T. (2003). *Nonlinear Time Series Analysis*. Cambridge University Press. doi: <https://doi.org/10.1017/cbo9780511755798>
 12. Eckmann, J.-P., Kamphorst, S. O., Ruelle, D. (1987). Recurrence Plots of Dynamical Systems. *Europhysics Letters (EPL)*, 4 (9), 973–977. doi: <https://doi.org/10.1209/0295-5075/4/9/004>
 13. Webber, C. L., Zbilut, J. P.; Riley, M. A., Van Orden, G. (Eds.) (2004). Chapter 2. Recurrence quantification analysis of nonlinear dynamical systems. *Tutorials in Contemporary Nonlinear Methods for the Behavioral Sciences*. Available at: <https://www.nsf.gov/pubs/2005/nsf05057/nmbs/nmbs.pdf>
 14. Webber, C. L., Zbilut, J. P. (1994). Dynamical assessment of physiological systems and states using recurrence plot strategies. *Journal of Applied Physiology*, 76 (2), 965–973. doi: <https://doi.org/10.1152/jappl.1994.76.2.965>
 15. Marwan, N., Trauth, M. H., Vuille, M., Kurths, J. (2003). Comparing modern and Pleistocene ENSO-like influences in NW Argentina using nonlinear time series analysis methods. *Climate Dynamics*, 21 (3-4), 317–326. doi: <https://doi.org/10.1007/s00382-003-0335-3>
 16. Pospelov, B., Andronov, V., Rybka, E., Meleshchenko, R., Borodych, P. (2018). Studying the recurrent diagrams of carbon monoxide concentration at early ignitions in premises. *Eastern-European Journal of Enterprise Technologies*, 3 (9 (93)), 34–40. doi: <https://doi.org/10.15587/1729-4061.2018.133127>
 17. Turcotte, D. L. (1997). *Fractals and chaos in geology and geophysics*. Cambridge University Press. doi: <https://doi.org/10.1017/CBO9781139174695>
 18. Poulsen, A., Jomaas, G. (2011). Experimental Study on the Burning Behavior of Pool Fires in Rooms with Different Wall Linings. *Fire Technology*, 48 (2), 419–439. doi: <https://doi.org/10.1007/s10694-011-0230-0>
 19. Zhang, D., Xue, W. (2010). Effect of heat radiation on combustion heat release rate of larch. *Journal of West China Forestry Science*, 39, 148.
 20. Andronov, V., Pospelov, B., Rybka, E. (2017). Development of a method to improve the performance speed of maximal fire detectors. *Eastern-European Journal of Enterprise Technologies*, 2 (9 (86)), 32–37. doi: <https://doi.org/10.15587/1729-4061.2017.96694>
 21. Pospelov, B., Andronov, V., Rybka, E., Skliarov, S. (2017). Design of fire detectors capable of self-adjusting by ignition. *Eastern-European Journal of Enterprise Technologies*, 4 (9 (88)), 53–59. doi: <https://doi.org/10.15587/1729-4061.2017.108448>
 22. Pospelov, B., Andronov, V., Rybka, E., Skliarov, S. (2017). Research into dynamics of setting the threshold and a probability of ignition detection by self-adjusting fire detectors. *Eastern-European Journal of Enterprise Technologies*, 5 (9 (89)), 43–48. doi: <https://doi.org/10.15587/1729-4061.2017.110092>
 23. Pospelov, B., Andronov, V., Rybka, E., Meleshchenko, R., Gornostal, S. (2018). Analysis of correlation dimensionality of the state of a gas medium at early ignition of materials. *Eastern-European Journal of Enterprise Technologies*, 5 (10 (95)), 25–30. doi: <https://doi.org/10.15587/1729-4061.2018.142995>
 24. Pospelov, B., Rybka, E., Meleshchenko, R., Gornostal, S., Shcherbak, S. (2017). Results of experimental research into correlations between hazardous factors of ignition of materials in premises. *Eastern-European Journal of Enterprise Technologies*, 6 (10 (90)), 50–56. doi: <https://doi.org/10.15587/1729-4061.2017.117789>
 25. Bendat, J. S., Piersol, A. G. (2010). *Random data: analysis and measurement procedures*. John Wiley & Sons, 640.
 26. Shafi, I., Ahmad, J., Shah, S. I., Kashif, F. M. (2009). Techniques to Obtain Good Resolution and Concentrated Time-Frequency Distributions: A Review. *EURASIP Journal on Advances in Signal Processing*, 2009 (1). doi: <https://doi.org/10.1155/2009/673539>
 27. Pospelov, B., Rybka, E., Meleshchenko, R., Borodych, P., Gornostal, S. (2019). Development of the method for rapid detection of hazardous atmospheric pollution of cities with the help of recurrence measures. *Eastern-European Journal of Enterprise Technologies*, 1 (10 (97)), 29–35. doi: <https://doi.org/10.15587/1729-4061.2019.155027>
 28. Pospelov, B., Rybka, E., Togobytska, V., Meleshchenko, R., Danchenko, Y., Butenko, T. et al. (2019). Construction of the method for semi-adaptive threshold scaling transformation when computing recurrent plots. *Eastern-European Journal of Enterprise Technologies*, 4 (10 (100)), 22–29. doi: <https://doi.org/10.15587/1729-4061.2019.176579>
 29. Singh, P. (2016). Time-frequency analysis via the fourier representation. HAL. Available at: <https://hal.archives-ouvertes.fr/hal-01303330/document>
 30. Pospelov, B., Andronov, V., Rybka, E., Popov, V., Romin, A. (2018). Experimental study of the fluctuations of gas medium parameters as early signs of fire. *Eastern-European Journal of Enterprise Technologies*, 1 (10 (91)), 50–55. doi: <https://doi.org/10.15587/1729-4061.2018.122419>
 31. Stankovic, L., Dakovic, M., Thayaparan, T. (2014). *Time-frequency signal analysis*. Kindle edition, Amazon, 655.
 32. Avargel, Y., Cohen, I. (2010). Modeling and Identification of Nonlinear Systems in the Short-Time Fourier Transform Domain. *IEEE Transactions on Signal Processing*, 58 (1), 291–304. doi: <https://doi.org/10.1109/tsp.2009.2028978>
 33. Giv, H. H. (2013). Directional short-time Fourier transform. *Journal of Mathematical Analysis and Applications*, 399 (1), 100–107. doi: <https://doi.org/10.1016/j.jmaa.2012.09.053>
 34. Pospelov, B., Andronov, V., Rybka, E., Popov, V., Semkiv, O. (2018). Development of the method of frequency-temporal representation of fluctuations of gaseous medium parameters at fire. *Eastern-European Journal of Enterprise Technologies*, 2 (10 (92)), 44–49. doi: <https://doi.org/10.15587/1729-4061.2018.125926>

35. Akhtimankina, A. V. (2015). Lecturer Investigation of dynamics of concentration of harmful substances in atmosphere of shelekhov city. *Izvestiya Irkutskogo gosudarstvennogo universiteta. Seriya «Nauki o Zemle»*, 13, 42–57.

DOI: 10.15587/1729-4061.2020.200467

DETERMINATION OF THE LAWS OF THERMAL RESISTANCE OF WOOD IN APPLICATION OF FIRE-RETARDANT FABRIC COATINGS (p. 13-18)

Yuriy Tsapko

National University of Life and Environmental Sciences of Ukraine, Kyiv, Ukraine

ORCID: <http://orcid.org/0000-0003-0625-0783>

Oleksii Tsapko

National University of Life and Environmental Sciences of Ukraine, Kyiv, Ukraine

ORCID: <http://orcid.org/0000-0003-2298-068X>

Olga Bondarenko

Kyiv National University of Construction and Architecture, Kyiv, Ukraine

ORCID: <http://orcid.org/0000-0002-8164-6473>

The creation of environmentally safe fire-retardant materials for wooden building structures will allow influencing the processes of heat resistance and physicochemical properties of the protective coating during its service life. Therefore, there is a need to study the conditions for forming a barrier to thermal conductivity and determine a mechanism of inhibiting heat transfer to the material. In this regard, a mathematical model of the thermal conductivity process when using fire-retardant fabric as a coating is developed, the solution of which allows obtaining changes in the thermal conductivity of the material. According to experimental data, it is calculated that the thermal conductivity coefficient during fire protection in the temperature range from 0 to 110 °C increases due to water evaporation and then gradually decreases to 0.25 W/(m·°C), which corresponds to the value of coked foam. It is proved that the process of temperature inhibition consists in the formation of soot-like products that insulate the wooden structure. This made it possible to determine the conditions of fire protection of wood, formation of a barrier to thermal conductivity using fire-retardant fabric. Experimental studies confirmed that the wood sample with fire-retardant fabric withstood the temperature effect, namely, under the influence of the heat flux, the coating swelled, heat insulation continued for 900 s. Estimation of the maximum possible temperature penetration through the coating is carried out. It is found that when creating the sample surface temperature, which significantly exceeded the ignition temperature of wood, the temperature under the fabric did not reach the ignition temperature, and on the unheated surface it did not exceed 100 °C.

Thus, there are reasons to argue about the possibility of directed control of the processes of wood fire protection using fire-retardant coatings capable of forming a protective layer on the material surface, which reduces the burnout rate of wood

Keywords: protective means, fire resistance, weight loss, surface treatment, wood burnout, fire-retardant fabric

References

1. Tsapko, Y., Tsapko, A. (2017). Establishment of the mechanism and fireproof efficiency of wood treated with an impregnating solution and coatings. *Eastern-European Journal of Enterprise Technologies*, 3 (10 (87)), 50–55. doi: <https://doi.org/10.15587/1729-4061.2017.102393>
2. Tsapko, Y., Tsapko, A. (2018). Establishment of fire protective effectiveness of reed treated with an impregnating solution and coatings. *Eastern-European Journal of Enterprise Technologies*, 4 (10 (94)), 62–68. doi: <https://doi.org/10.15587/1729-4061.2018.141030>
3. Tsapko, Y., Tsapko, A., Bondarenko, O. (2019). Establishment of heatexchange process regularities at inflammation of reed samples. *Eastern-European Journal of Enterprise Technologies*, 1 (10 (97)), 36–42. doi: <https://doi.org/10.15587/1729-4061.2019.156644>
4. Tsapko, J., Tsapko, A. (2017). Simulation of the phase transformation front advancement during the swelling of fire retardant coatings. *Eastern-European Journal of Enterprise Technologies*, 2 (11 (86)), 50–55. doi: <https://doi.org/10.15587/1729-4061.2017.73542>
5. Krüger, S., Gluth, G. J. G., Watolla, M.-B., Morys, M., Häbler, D., Schartel, B. (2016). Neue Wege: Reaktive Brandschutzbeschichtungen für Extrembedingungen. *Bautechnik*, 93 (8), 531–542. doi: <https://doi.org/10.1002/bate.201600032>
6. Xiao, N., Zheng, X., Song, S., Pu, J. (2014). Effects of Complex Flame Retardant on the Thermal Decomposition of Natural Fiber. *BioResources*, 9 (3), 4924–4933. doi: <https://doi.org/10.15376/biores.9.3.4924-4933>
7. Gaff, M., Kačik, F., Gašparík, M., Todaro, L., Jones, D., Corleto, R. et. al. (2019). The effect of synthetic and natural fire-retardants on burning and chemical characteristics of thermally modified teak (*Tectona grandis* L. f.) wood. *Construction and Building Materials*, 200, 551–558. doi: <https://doi.org/10.1016/j.conbuildmat.2018.12.106>
8. Zhao, P., Guo, C., Li, L. (2018). Flame retardancy and thermal degradation properties of polypropylene/wood flour composite modified with aluminum hypophosphite/melamine cyanurate. *Journal of Thermal Analysis and Calorimetry*, 135 (6), 3085–3093. doi: <https://doi.org/10.1007/s10973-018-7544-9>
9. Cirpici, B. K., Wang, Y. C., Rogers, B. (2016). Assessment of the thermal conductivity of intumescent coatings in fire. *Fire Safety Journal*, 81, 74–84. doi: <https://doi.org/10.1016/j.fire-saf.2016.01.011>
10. Nine, M. J., Tran, D. N. H., Tung, T. T., Kabiri, S., Losic, D. (2017). Graphene-Borate as an Efficient Fire Retardant for Cellulosic Materials with Multiple and Synergetic Modes of Action. *ACS Applied Materials & Interfaces*, 9 (11), 10160–10168. doi: <https://doi.org/10.1021/acsami.7b00572>
11. Carosio, F., Alongi, J. (2016). Ultra-Fast Layer-by-Layer Approach for Depositing Flame Retardant Coatings on Flexible PU Foams within Seconds. *ACS Applied Materials & Interfaces*, 8 (10), 6315–6319. doi: <https://doi.org/10.1021/acsami.6b00598>
12. Md Nasir, K., Ramli Sulong, N. H., Johan, M. R., Afifi, A. M. (2018). An investigation into waterborne intumescent coating

with different fillers for steel application. *Pigment & Resin Technology*, 47 (2), 142–153. doi: <https://doi.org/10.1108/prt-09-2016-0089>

13. Erdoğan, Y. (2016). Production of an insulation material from carpet and boron wastes. *Bulletin Of The Mineral Research and Exploration*, 152, 197–202. doi: <https://doi.org/10.19111/bmre.74700>
14. Khalili, P., Tshai, K. Y., Hui, D., Kong, I. (2017). Synergistic of ammonium polyphosphate and alumina trihydrate as fire retardants for natural fiber reinforced epoxy composite. *Composites Part B: Engineering*, 114, 101–110. doi: <https://doi.org/10.1016/j.compositesb.2017.01.049>
15. Potter, M. C. (2019). *Engineering analysis*. Springer. doi: <https://doi.org/10.1007/978-3-319-91683-5>

DOI: 10.15587/1729-4061.2020.201696

EXTRACTION OF IRON-CONTAINING CATALYST FROM CHLORORGANIC WASTES GENERATED BY ETHYLENE CHLORINATION (p. 19–26)

Mykola Shpariy

“KARPATNAFTOCHIM” LTD., Kalush,
Ivano-Frankivsk region, Ukraine

ORCID: <http://orcid.org/0000-0002-6736-7515>

Volodymyr Starchevskyy

Lviv Polytechnic National University,
Lviv, Ukraine

ORCID: <http://orcid.org/0000-0003-1095-138X>

Zenovii Znak

Lviv Polytechnic National University,
Lviv, Ukraine

ORCID: <http://orcid.org/0000-0002-3871-4063>

Roman Mnykh

Lviv Polytechnic National University,
Lviv, Ukraine

ORCID: <http://orcid.org/0000-0003-3248-919X>

Ihor Poliuzhyn

Lviv Polytechnic National University,
Lviv, Ukraine

ORCID: <http://orcid.org/0000-0002-8142-5048>

The technologies for extracting an iron-containing catalyst from process streams of direct chlorination of ethylene, as well as methods for the disposal of organochlorine wastes from vinyl chloride production, are considered. Problems arising from thermal waste disposal necessitate studies on the extraction of iron compounds from organochlorine by-products of the ethylene chlorination process. X-ray fluorescence analysis found that the composition of the burning sludge, as the main elements, includes iron – 33.25 % and chlorine – 32.69 %. The extraction of iron compounds with aqueous and aqueous acidic media under mechanical stirring is studied. It is shown that the addition of hydrochloric acid to the solution does not contribute to an increase in the degree of extraction of iron compounds. It is found that an increase in the duration of extraction and the temperature of this process provides a degree of extraction of iron compounds of more than 80 %. The process of separation of an aqueous-organic emulsion, which is formed during

extraction, by sedimentation, filtration and centrifugation, is investigated. It is found that at a temperature of about 80 °C there is an effective and rapid separation of the aqueous and organic phases as a result of sedimentation. Based on the obtained experimental results of the extraction study, a functional scheme for the extraction of an iron-containing catalyst is proposed, as well as ways to solve technological and environmental problems that arise during the combustion of organochlorine wastes from vinyl chloride production. The scheme provides for the use of the heat of hot organochlorine wastes for the extraction of iron compounds with industrial water. In addition, the use of the heat of the gases generated during the combustion of organochlorine wastes is provided for heating air, which low-boiling components from these wastes are blown off. In the future, this air is used to burn organochlorine wastes purified from iron compounds

Keywords: organochlorine wastes, vinyl chloride, burning of organic waste, burning sludge, extraction of iron-containing catalyst, extraction

References

1. Cowfer, J. A., Wilkes, C. E., Summers, J. W., Daniels, C. A. (2005). Part 2. Vinyl Chloride Monomer. *PVC Handbook*. 1 st ed. Munich: Carl Hanser Verlag, 19–56.
2. Myszkowski, J., Milchert, E., Bartkowiak, M., Pelech, R. (2010). Utilization of waste chloroorganic compounds. *Polish Journal of Chemical Technology*, 12 (3), 36–39. doi: <http://doi.org/10.2478/v10026-010-0031-0>
3. Kurta, S., Zakrzhevsky, A., Kurta, M. (2007). Utilization of chloroorganic waste by their catalytic copolymerization. *Polimery*, 52 (1), 51–55. doi: <http://doi.org/10.14314/polimery.2007.051>
4. Kurta, S. A., Volinsky, A. A., Kurta, M. S. (2013). Environmentally-friendly organochlorine waste processing and recycling. *Journal of Cleaner Production*, 54, 150–156. doi: <http://doi.org/10.1016/j.jclepro.2013.05.010>
5. Kurta, S. A., Zakrzhevskii, A. Iu. (2006). Izuchenie sovmesnoi utilizatsii serosoderzhaschikh i khlrororganicheskikh otkhodov. *Voprosy khimii i khimicheskoi tekhnologii*, 2, 158–160.
6. Kurta, S. A., Khaber, M. V., Zakrzhevskiy, A. Yu. (2002). Doslidzhennia sposobu utylizatsii khlrorhanichnykh vidkhodiv vyrobnytstva 1,2-dykhloretanu. *Visnyk Prykarpatskoho universytetu. Seriya «Khimii»*, 3, 29–34.
7. Chaika, A. A., Gogotov, A. F., Panasenkova, E. Yu., Stankevich, V. K. (2013). Purposeful Utilization of Chloro-Organic Production Wastes. 1. Amination. *Vestnik ministry of education and science of the Russian Federation of Irkutsk State Technical University*, 4 (75), 123–126. Available at: http://journals.istu.edu/vestnik_irgtu/journals/2013/04
8. Chaika, A. A., Gogotov, A. F., Panasenkova, E. Yu., Stankevich, V. K. (2013). Purposeful Disposal of Chloroorganic Wastes of Chemical Production. 2. Condensation Reaction with Lignin. *Vestnik ministry of education and science of the Russian Federation of Irkutsk State Technical University*, 6 (77), 157–159. Available at: http://journals.istu.edu/vestnik_irgtu/journals/2013/06
9. Kiselev, V. P., Gogotov, A. F., Bugaenko, M. B., Ivanova, L. A., Dronov, V. G., Grigoreva, A. A., Kemenev, N. V. (2013). The Additive for the Bitumen on the Basis of the Modified Hydrolytic Lignin of the Organochlorine Wastes of the Chemical Industries. *Journal of Siberian Federal University. Engineering & Technol-*

- ogies, 6 (8), 885–894. Available at: <http://journal.sfu-kras.ru/article/10210>
10. Zakrzhevskiy, O. Yu., Kurta, S. A., Khaber, M. V. (2005). Doslidzhennia umov khloruvannia vidkhodiv vyrobnytstva vinilkhlorydu. *Visnyk Natsionalnoho universytetu «Lvivska Politehnika»: Khimiia, tekhnolohiia rechovyn ta yikh zastosuvannia*, 536, 129–133. Available at: <http://ena.lp.edu.ua:8080/handle/ntb/9114>
 11. Islamutdinova, A. A., Sadykov, N. B. (2006). Poluchenie chetvertichnykh ammonievnykh solei iz otkhodov khlororganicheskogo proizvodstva. *Bashkirskii khimicheskii zhurnal*, 13 (3), 54–56. Available at: <https://cyberleninka.ru/article/n/poluchenie-chetvertichnykh-ammonievnykh-soley-iz-otkhodov-hlororganicheskogo-proizvodstva/viewer>
 12. Dmitriev, V. I., Stuchkov, G. S. (1988). Ognevoe obezvrezhivanie khlororganicheskikh otkhodov. *Promyshlennaia teplotekhnika*, 10 (5), 93–97.
 13. Elektorowicz, M., Muslat, Z. (2008). Removal of heavy metals from oil ash using ion exchange textiles. *Environmental Technology*, 29 (4), 393–399. doi: <http://doi.org/10.1080/09593330801984290>
 14. Mustafina, E. A., Poletaeva, O. Iu., Movsumzade, E. M. (2014). Heavy metal content of oil and their demetallisation. *Oil & Gas Chemistry*, 4, 15–18. Available at: <http://neftegazohimiya.ru/english-version/abstracts/71-contents-of-journal-oil-gas-chemistry-4-2014-russia.html>
 15. Garrett, C. E., Prasad, K. (2004). The Art of Meeting Palladium Specifications in Active Pharmaceutical Ingredients Produced by Pd-Catalyzed Reactions. *Advanced Synthesis & Catalysis*, 346 (8), 889–900. doi: <http://doi.org/10.1002/adsc.200404071>
 16. Barbaras, D., Brozio, J., Johannsen, I., Allmendinger, T. (2009). Removal of Heavy Metals from Organic Reaction Mixtures: Preparation and Application of Functionalized Resins(1). *Organic Process Research & Development*, 13 (6), 1068–1079. doi: <http://doi.org/10.1021/op900102a>
 17. Rosso, V. W., Lust, D. A., Bernot, P. J., Grosso, J. A., Modi, S. P., Rusowicz, A. et. al. (1997). Removal of Palladium from Organic Reaction Mixtures by Trimercaptotriazine. *Organic Process Research & Development*, 1 (4), 311–314. doi: <http://doi.org/10.1021/op970107f>
 18. Mogolloñ, L., Rodríguez, R., Larrota, W., Ortiz, C., Torres, R. (1998). Biocatalytic removal of nickel and vanadium from petroporphyrins and asphaltenes. *Applied Biochemistry and Biotechnology*, 70-72(1), 765–777. doi: <http://doi.org/10.1007/bf02920187>
 19. Krebs, T., Schroën, C. G. P. H., Boom, R. M. (2013). Coalescence kinetics of oil-in-water emulsions studied with microfluidics. *Fuel*, 106, 327–334. doi: <http://doi.org/10.1016/j.fuel.2012.10.067>
 20. Li, J., Gu, Y. (2005). Coalescence of oil-in-water emulsions in fibrous and granular beds. *Separation and Purification Technology*, 42 (1), 1–13. doi: <http://doi.org/10.1016/j.seppur.2004.05.006>
 21. Frising, T., Noik, C., Dalmazzone, C., Peysson, Y., Palermo, T. (2008). Contribution of the Sedimentation and Coalescence Mechanisms to the Separation of Concentrated Water-in-Oil Emulsions. *Journal of Dispersion Science and Technology*, 29 (6), 827–834. doi: <http://doi.org/10.1080/01932690701781501>
 22. Faizov, A. A., Driakhlov, V. O., Fazullin, D. D., Iagafarova, G. G., Iagafarova, D. I. (2015). Razdelenie vodoneftiannykh emulsiy s ispolzovaniem membrannykh filtrov. *Vestnik Kazanskogo Tekhnologicheskogo Universiteta*, 18 (24), 136–138. Available at: http://www.kstu.ru/article.jsp?id=1910&id_e=23840
 23. Topilnytskyi, P., Romanchuk, V., Boichenko, S., Golych, Y. (2014). Physico-Chemical Properties and Efficiency of Demulsifiers based on Block Copolymers of Ethylene and Propylene Oxides. *Chemistry & Chemical Technology*, 8 (2), 211–218. doi: <http://doi.org/10.23939/chcht08.02.211>
 24. Hafiz, A. A., El-Din, H. M., Badawi, A. M. (2005). Chemical destabilization of oil-in-water emulsion by novel polymerized diethanolamines. *Journal of Colloid and Interface Science*, 284 (1), 167–175. doi: <http://doi.org/10.1016/j.jcis.2004.10.010>
 25. Topilnytskyi, P. I., Holych, Yu. V., Romanchuk, V. V. (2015). Znevodnennia sumishi nafti i pastkovoho produktu. *Visnyk Natsionalnoho universytetu «Lvivska Politehnika»*. *Khimiia, tekhnolohiia rechovyn ta yikh zastosuvannia*, 812, 152–157. Available at: http://nbuv.gov.ua/UJRN/VNULPX_2015_812_28
 26. Thayee Al-Janabi, O. Y., Ibrahim, M. S., Waheed, I. F., Sayda, A. W., Spearman, P. (2019). Breaking water-in-oil emulsion of Northern Iraq's crude oil using commercial polymers and surfactants. *Polymers and Polymer Composites*, 28 (3), 187–198. doi: <http://doi.org/10.1177/0967391119868118>
 27. Matos, M., Garcia, C. E., Suárez, M. A., Pazos, C., Benito, J. M. (2016). Treatment of oil-in-water emulsions by a destabilization/ultrafiltration hybrid process: Statistical analysis of operating parameters. *Journal of the Taiwan Institute of Chemical Engineers*, 59, 295–302. doi: <http://doi.org/10.1016/j.jtice.2015.08.006>
 28. Li, Q., Chen, J. Q., Wang, K. S. (2014). Investigation of Water Separation from Water-in-Oil Emulsion Using Centrifugal Field and Gravity with CFD Method. *Advanced Materials Research*, 1081, 93–97. doi: <http://doi.org/10.4028/www.scientific.net/amr.1081.93>
 29. Vilkova, N. G., Kruglyakov, P. M. (2001). Behavior of an Emulsion in a Centrifugal Field: Kinetics of an Increase in the Excess Pressure and Destruction of an Emulsion. *Colloid Journal*, 63 (6), 675–679. doi: <http://doi.org/10.1023/a:1013207516725>
 30. Kharkov, N., Ermak, O., Aver'yanova, O. (2014). Numerical Simulation of the Centrifugal Separator for Oil-Water Emulsion. *Advanced Materials Research*, 945-949, 944–950. doi: <http://doi.org/10.4028/www.scientific.net/amr.945-949.944>
 31. Topilnytskyi, P. I., Holych, Yu. V., Romanchuk, V. V. (2014). Doslidzhennia neionohennykh deemulhatoriv riznoi budovy na shtuchnykh naftovykh emulsiakh. *Visnyk Natsionalnoho universytetu «Lvivska Politehnika»*. *Khimiia, tekhnolohiia rechovyn ta yikh zastosuvannia*, 787, 169–173. Available at: http://nbuv.gov.ua/UJRN/VNULPX_2014_787_36

DOI: 10.15587/1729-4061.2020.200591

CHOOSING THE PHYTOREMEDIATION TECHNOLOGIES FOR CLEANING VARIOUS TYPES OF WASTEWATER (p. 27–37)

Olena Dmitrieva

Scientific Research Institution «Ukrainian Scientific Research Institute of Ecological Problems» (USRIEP),
Kharkiv, Ukraine

ORCID: <http://orcid.org/0000-0002-7494-0674>

Irina Khorenzhaja

The Committee of the Verkhovna Rada of Ukraine on
Environmental Policy and Utilization of Natural Resources,
Kyiv, Ukraine

ORCID: <http://orcid.org/0000-0002-2107-2893>

Valerie Vasylenko

National Academy of the National Guard of Ukraine,
Kharkiv, Ukraine

ORCID: <http://orcid.org/0000-0002-0430-0540>

Stanislav Osypenko

National Academy of the National Guard of Ukraine,
Kharkiv, Ukraine

ORCID: <http://orcid.org/0000-0003-0548-6428>

Natalia Teliura

O. M. Beketov National University of Urban Economy in Kharkiv,
Kharkiv, Ukraine

ORCID: <http://orcid.org/0000-0003-0732-7789>

Olga Lomakina

O. M. Beketov National University of Urban Economy in Kharkiv,
Kharkiv, Ukraine

ORCID: <http://orcid.org/0000-0003-3908-4638>

Liudmyla Melnik

Scientific Research Institution «Ukrainian Scientific Research
Institute of Ecological Problems» (USRIEP),
Kharkiv, Ukraine

Irina Koldoba

Scientific Research Institution «Ukrainian Scientific Research
Institute of Ecological Problems» (USRIEP),
Kharkiv, Ukraine

ORCID: <http://orcid.org/0000-0001-9334-6219>

A methodological approach has been devised for determining the priority phytoremediation technology for the treatment of wastewater from settlements, based on the hierarchy analysis method (MAI). The proposed approach makes it possible to involve experts from municipal authorities of a settlement to substantiate decisions on managing the environmental safety of surface water bodies adjacent to the selected settlements.

The criteria (groups of factors) have been proposed, which reflected the input and output parameters of a treatment system, conditions at a construction site of treatment plants, and the requirements for phytoremediation technologies. Experts in various professional aspects gave their judgments regarding the priority of advantages of the mentioned criteria. The multidisciplinary experts' judgments, which reflected the specific features of phytoremediation and the conditions for a would-be location of treatment plants, processed according to the scientifically based MAI procedure, formed the basis for decision-making on the choice of a priority phytoremediation technology under specific conditions.

The advantages of the proposed methodological approach include a possibility to link the entire array of the necessary information to a single algorithm for substantiating a solution. The information differs both in its content (environmental, biological, urban planning, social and economic) and in the form of its representation (the data on direct measurements, statistical and forecast estimates).

The proposed methodological approach has been tested based on an example of choosing the phytoremediation technologies for treatment plants at three different types of facilities

such as an industrial enterprise, a residential building, and a city hospital. The obtained results demonstrated an acceptable level of conformity, which testifies to their reliability.

The devised methodological approach is useful for making managerial decisions on the choice of technology for the phytoremediation at treatment plants in order to substantiate their improvement or to build new plants.

Keywords: environmental safety, phytoremediation and its technologies, higher aquatic plants.

References

1. Beans, C. (2017). Core Concept: Phytoremediation advances in the lab but lags in the field. *Proceedings of the National Academy of Sciences*, 114 (29), 7475–7477. doi: <https://doi.org/10.1073/pnas.1707883114>
2. Dmitrieva, O. O., Teliura, N. O., Vasilenko, V. P. (2018). Implementation environmentally safe wastewater as an element of sustainable human settlements development Ukraine. *Municipal economy of cities*, 7 (146), 174–179. doi: <https://doi.org/10.33042/2522-1809-2018-7-146-174-179>
3. Arthur, E. L., Rice, P. J., Rice, P. J., Anderson, T. A., Baladi, S. M., Henderson, K. L. D., Coats, J. R. (2005). Phytoremediation – An Overview. *Critical Reviews in Plant Sciences*, 24 (2), 109–122. doi: <https://doi.org/10.1080/07352680590952496>
4. Comín, F. A., Sorando, R., Darwiche-Criado, N., Garcia, M., Mas-ip, A. (2014). A protocol to prioritize wetland restoration and creation for water quality improvement in agricultural watersheds. *Ecological Engineering*, 66, 10–18. doi: <https://doi.org/10.1016/j.ecoleng.2013.04.059>
5. Verhoeven, J. T. A. (2014). Wetlands in Europe: Perspectives for restoration of a lost paradise. *Ecological Engineering*, 66, 6–9. doi: <https://doi.org/10.1016/j.ecoleng.2013.03.006>
6. Sumiahadi, A., Acar, R. (2018). A review of phytoremediation technology: heavy metals uptake by plants. *IOP Conference Series: Earth and Environmental Science*, 142, 012023. doi: <https://doi.org/10.1088/1755-1315/142/1/012023>
7. Ghanem, H., Chalak, L., Baydoun, S. (2019). Phytoremediation of Lebanese polluted waters: a review of current initiatives. *MATEC Web of Conferences*, 281, 03007. doi: <https://doi.org/10.1051/mateconf/201928103007>
8. Maiga, Y., von Sperling, M., Mihelcic, J. (2017). Constructed Wetlands. *Global Water Pathogen Project*. doi: <https://doi.org/10.14321/waterpathogens.66>
9. Morley, M. S., Vitorino, D., Behzadian, K., Ugarelli, R., Kapelan, Z., Coelho, S. T., Do Céu Almeida, M. (2015). Decision support system for the long-term city metabolism planning problem. *Water Supply*, 16 (2), 542–550. doi: <https://doi.org/10.2166/ws.2015.167>
10. Saaty, T. L., Ergu, D. (2015). When is a Decision-Making Method Trustworthy? Criteria for Evaluating Multi-Criteria Decision-Making Methods. *International Journal of Information Technology & Decision Making*, 14 (06), 1171–1187. doi: <https://doi.org/10.1142/s021962201550025x>
11. Saati, T. L. (1993). *Prinyatie resheniy: Metod analiza ierarhiy*. Moscow: Radio i svyaz', 278. Available at: <http://pqm-online.com/assets/files/lib/books/saati.pdf>
12. Maksimenko, O., Pancheva, H., Madzhd, S., Pysanko, Y., Briankin, O., Tykhomyrova, T., Hrebeniuk, T. (2018). Examining

the efficiency of electrochemical purification of storm wastewater at machinebuilding enterprises. *Eastern-European Journal of Enterprise Technologies*, 6 (10 (96)), 21–27. doi: <https://doi.org/10.15587/1729-4061.2018.150088>

13. Isaienko, V., Madzhd, S., Pysanko, Y., Nikolaiev, K., Bovsunovskiy, E., Cherniak, L. (2019). Development of a procedure for determining the basic parameter of aquatic ecosystems functioning – environmental capacity. *Eastern-European Journal of Enterprise Technologies*, 1 (10 (97)), 21–28. doi: <https://doi.org/10.15587/1729-4061.2019.157089>

DOI: 10.15587/1729-4061.2020.201819
ENGINEERING METHOD FOR DETERMINING RATIONAL FIRE PROTECTION PARAMETERS OF WAREHOUSES (p. 38–45)

Edward Hulida

Lviv State University of Life Safety,
Lviv, Ukraine

ORCID: <http://orcid.org/0000-0002-3881-7206>

Ivan Pasnak

Lviv State University of Life Safety,
Lviv, Ukraine

ORCID: <http://orcid.org/0000-0002-8405-4625>

Artur Renkas

Lviv State University of Life Safety,
Lviv, Ukraine

ORCID: <http://orcid.org/0000-0002-5518-3508>

Volodymyr Sharyy

Lviv State University of Life Safety,
Lviv, Ukraine

ORCID: <http://orcid.org/0000-0001-8746-2184>

A mathematical model and methodology has been developed to determine the optimal amount of means of a fire-prevention system for protecting warehouses in enclosed spaces, on the basis of which it is possible to determine measures to improve this system, taking into account the value of the probability of its failure acceptable for the warehouse. The essence of the developed methodology is to determine the required number of fire protection equipment in accordance with the standards, to determine the probability of failure of fire protection and to determine the optimal number of fire protection equipment to ensure the value of the probability of failure within acceptable limits. The optimization criteria selected direct losses from the fire and the costs of fire and rescue units to extinguish it. The function of the goal of this model is to reduce the probability of failure of the fire system of the object to a value less than or equal to the permissible. The input data when using the mathematical model is the estimated number of fire protection equipment in accordance with the norms and standards.

The developed methodology allows predicting the probability of failure of the fire system to implement the fire safety of the objects of protection and its consequences for people and material values, which is very important to ensure the possibility of quick response in case of fire. Also, the result of applying the technique is the optimal amount of firefighting equipment at the facility, providing an acceptable value for the probability of failures. This technique is applied on

the example of an existing logistic warehouse on which fire protection systems are mounted. Simulation results show that at the facility it is necessary to increase the number of fire detectors up to 70 pieces, smoke control devices – up to 3 pieces, vertical curtains – up to 4, equip aeration lamps in the amount of 4 pieces, and increase the number of evacuation exits - up to 10.

Keywords: fire protection system, fire damage, fire protection costs, probability of system failure.

References

- Hulida, E. M. (2016). Influence of fire risk on fire losses in the rooms of various facilities. *Pozhezhna bezpeka*, 28, 36–42.
- Analitychna dovidka pro pozhezhi ta yikh naslidky v Ukraini za 12 misiatsiv 2019 roku (2019). Kyiv, 56. Available at: https://undicz.dns.gov.ua/files/2020/1/27/Analitychna%20dovidka%20pro%20pojeji_12.2019.pdf
- Campbell, R. (2016). Structure fires in warehouse properties. National Fire Protection Association.
- Ahrens, M. (2009). Warehouse fires excluding cold storage. National Fire Protection Association.
- DBN V.2.5-56:2014. Systemy protypozhezhnoho zakhystu. Inzhenerne obladnannia budynkiv i sporud.
- Holshchevnikov, V. V. (2003). Problems of evaluation of people's safety in case of fire in unique buildings and installations. *Pozharovzryvobezopasnost'*, 4, 21–27.
- Khrystych, V. V., Derevianko, O. A., Bondarenko, S. M., Antoshkin, O. A. (2001). Systemy pozhezhoi ta okhoronnoi syhnalizatsiyi. Kharkiv: APBU MVS, 104.
- Voitovych, D. P. (2011). Pidvyshchennia efektyvnosti funkcionuvannia pozhezho-riatuvalnykh pidrozdiliv v protsesi likvidatsiyi pozhezhi. Lviv.
- Xiaojun, C., Lizhong, Y., Zhijia, D., Weicheng, F. (2005). A multi-layer zone model for predicting fire behavior in a fire room. *Fire Safety Journal*, 40 (3), 267–281. doi: <https://doi.org/10.1016/j.firesaf.2005.01.005>
- Pro zatverdzhennia kryteriyiv, za yakymy otsiniuietsia stupin ryzyku vid provadzhennia hospodarskoi diyalnosti ta vyznachaietsia periodychnist zdisnennia planovykh zakhodiv derzhavnogo nahliadu (kontroliu) u sferi tekhnohennoi ta pozhezhoi bezpeky vid 29.02.2012 No. 306. Verkhovna Rada Ukrainy. Available at: <https://zakon.rada.gov.ua/laws/show/306-2012-%D0%BF?lang=uk>
- Kong, D., Lu, S., Kang, Q., Lo, S., Xie, Q. (2011). Fuzzy Risk Assessment for Life Safety Under Building Fires. *Fire Technology*, 50 (4), 977–991. doi: <https://doi.org/10.1007/s10694-011-0223-z>
- Rausand, M. (2014). Reliability of Safety-Critical Systems: Theory and Applications. John Wiley & Sons. doi: <https://doi.org/10.1002/9781118776353>
- Moinuddin, K. A. M., Thomas, I. R. (2014). Reliability of sprinkler system in Australian high rise office buildings. *Fire Safety Journal*, 63, 52–68. doi: <https://doi.org/10.1016/j.firesaf.2013.11.009>
- Paś, J. (2015). Selected Methods For Increases Reliability The Of Electronic Systems Security. *Journal of KONBiN*, 35 (1), 147–156. doi: <https://doi.org/10.1515/jok-2015-0048>
- Klimczak, T., Paś, J. (2019). Reliability and Operating Analysis of Transmission of Alarm Signals of Distributed Fire Signaling

- System. Journal of KONBiN, 49 (1), 165–174. doi: <https://doi.org/10.2478/jok-2019-0009>
16. Akhmedova, A., Shevtsova, T., Kotlyarov, R., Krol, A. (2019). Estimation of Reliability of Fire Alarm System. *Food Processing: Techniques and Technology*, 48 (4), 79–86. doi: <https://doi.org/10.21603/2074-9414-2018-4-79-86>
 17. Alvarez, A., Meacham, B. J., Dembsey, N. A., Thomas, J. R. (2013). A Framework for Risk-Informed Performance-Based Fire Protection Design for the Built Environment. *Fire Technology*, 50 (2), 161–181. doi: <https://doi.org/10.1007/s10694-013-0366-1>
 18. DBN V.1.1-7:2016. Pozhezha bezpeka ob'ektiv budivnytstva. Zahalni vymohy.
 19. Hulida, E., Pashak, I., Koval, O., Tryhuba, A. (2019). Determination of the Critical Time of Fire in the Building and Ensure Successful Evacuation of People. *Periodica Polytechnica Civil Engineering*, 63 (1), 308–316. doi: <https://doi.org/10.3311/ppci.12760>

DOI: 10.15587/1729-4061.2020.201748

THERMOTECNICAL PROPERTIES OF THE FIRE-EXTINGUISHING POWDER FOR EXTINGUISHING MATERIALS BASED ON MAGNESIUM ALLOY CHIPS (p. 46–53)

Bogdan Gusar

Lviv State University of Life Safety,
Lviv, Ukraine

ORCID: <http://orcid.org/0000-0001-5866-0392>

Vasyl Kovalyshyn

Lviv State University of Life Safety,
Lviv, Ukraine

ORCID: <http://orcid.org/0000-0002-5463-0230>

Serhii Pozdieiev

Cherkasy Institute of Fire Safety named after Chernobyl Heroes of National University of Civil Defense of Ukraine,
Cherkasy, Ukraine

ORCID: <http://orcid.org/0000-0002-9085-0513>

Volodymyr Kovalyshyn

Main Control Service Emergencies Ukraine in Lviv,
Lviv, Ukraine

ORCID: <http://orcid.org/0000-0003-3739-8668>

Oleh Zemlianskyi

Cherkasy Institute of Fire Safety named after Chernobyl Heroes of National University of Civil Defense of Ukraine,
Cherkasy, Ukraine

ORCID: <http://orcid.org/0000-0002-2728-6972>

Kostiantyn Myhalenko

Cherkasy Institute of Fire Safety named after Chernobyl Heroes of National University of Civil Defense of Ukraine,
Cherkasy, Ukraine

ORCID: <http://orcid.org/0000-0002-7125-8442>

The article addresses the relevant issue of determining the thermotechnical characteristics of the fire-extinguishing powder for thermal insulation of the fire center of materials based on magnesium alloy chips to prevent fire development and propagation and its effective extinguishing. To solve this problem, laboratory and field experimental studies of the heat-insulating ability of the fire-extinguishing powder of combined

effect were conducted. As a result, we obtained the data on the temperature in the center of the fire of materials based on magnesium alloy chips and outside during their suppressing by the fire-extinguishing powder with a combined effect. In this case, the temperature of the non-heated side of the fire-extinguishing powder layer does not exceed 170 °C at the average temperature of the fire center of 740 °C, which indicates high insulation capacity of the powder and, consequently, its high fire-fighting efficiency in extinguishing the fires of materials based on magnesium alloy chips. The obtained temperature data were used to determine the thermophysical parameters of the layer of the fire-fighting powder using the created mathematical model of the heat transfer process in the powder layer at the heat insulation of the fire center. To create a mathematical model of the heat transfer process, the main provisions during consecutive consideration of several experimental situations were stated. The first experimental situation meets the conditions of the stationary thermal process, and other experimental situations meet the conditions of the non-stationary thermal process. These experimental situations were created with the help of changing the thickness of the fire-fighting powder layer at different parameters of its feeding to the fire center. The mathematical model of the process is based on the use of the differential equation of heat transfer at its approximation by the method of finite differences. At the same time, it is believed that the heat transfer conditions at the boundary between the non-heated side of the insulating layer of the fire-extinguishing powder and the environment in each experimental situation are the same.

Using the created model, the coefficient of heat transfer between the non-heated side of the insulating layer of the fire-extinguishing powder and the environment was determined. It amounted to 395.7 W(m²·°C). The dependence of the effective thermal conductivity coefficient on the thickness of the insulating layer was explored. It was shown that this dependence can be approximated by linear dependence $\lambda(\delta) = -0.016 + 93.907 \cdot \delta$ (δ is the thickness of the layer of the fire-extinguishing powder in meters).

After conducting the necessary calculations, we obtained the value of the required thickness of the layer of fire-extinguishing powder $\delta = 45.2$ mm.

Keywords: fire-extinguishing powder, metal combustion, magnesium alloys, insulating layer, intensity of extinguishing.

References

1. Kovalyshyn, V., Marych, V., Novitskyi, Y., Gusar, B., Chernetskiy, V., Mirus, O.-Z. (2018). Improvement of a discharge nozzle damping attachment to suppress fires of class D. *Eastern-European Journal of Enterprise Technologies*, 5 (5 (95)), 68–76. doi: <https://doi.org/10.15587/1729-4061.2018.144874>
2. Antonov, A., Stylyk, I. (2013). Test methods for dry chemical powders for the determination of their fire extinguishing capability for D - class of fire. *Naukovyi visnyk UkrNDIPB*, 2 (28), 242–248. Available at: http://nbuv.gov.ua/UJRN/Nvundipb_2013_2_40
3. Huo, Y., Zhang, Z.-G., Zou, G.-W. (2020). Experimental study on the thermal flow characteristics of a columnar sodium fire affected by a small amount of fire extinguishing powder in a cylindrical confined space. *Applied Thermal Engineering*, 170, 114983. doi: <https://doi.org/10.1016/j.applthermaleng.2020.114983>

4. Dufaud, O., Bideau, D., Le Guyadec, F., Corriou, J.-P., Perrin, L., Caleyron, A. (2014). Selfignition of layers of metal powder mixtures. *Powder Technology*, 254, 160–169. doi: <https://doi.org/10.1016/j.powtec.2013.11.053>
5. Afzalabadi, A., Poorfar, A. K., Bidabadi, M., Moghadasi, H., Hochgreb, S., Rahbari, A., Dubois, C. (2017). Study on hybrid combustion of aero-suspensions of boron-aluminum powders in a quiescent reaction medium. *Journal of Loss Prevention in the Process Industries*, 49, 645–651. doi: <https://doi.org/10.1016/j.jlp.2017.08.012>
6. Sharma, T. P., Varshney, B. S., Kumar, S. (1993). Studies on the burning behaviour of metal powder fires and their extinguishment: Part II – Magnesium powder heaps on insulated and conducting material beds. *Fire Safety Journal*, 21 (2), 153–176. doi: [https://doi.org/10.1016/0379-7112\(93\)90040-w](https://doi.org/10.1016/0379-7112(93)90040-w)
7. Nam, K.-H., Lee, J.-S. (2018). Study on the effective response method to reduce combustible metal fire. *Journal of the Korea Academia-Industrial cooperation Society*, 19 (12), 600–606. doi: <https://doi.org/10.5762/KAIS.2018.19.12.600>
8. Taveau, J., Vingerhoets, J., Snoeys, J., Going, J., Farrell, T. (2015). Suppression of metal dust deflagrations. *Journal of Loss Prevention in the Process Industries*, 36, 244–251. doi: <https://doi.org/10.1016/j.jlp.2015.02.011>
9. Jiang, H., Bi, M., Li, B., Zhang, D., Gao, W. (2019). Inhibition evaluation of ABC powder in aluminum dust explosion. *Journal of Hazardous Materials*, 361, 273–282. doi: <https://doi.org/10.1016/j.jhazmat.2018.07.045>
10. Hagge, H., Simpson, T., Chattaway, A. (2018). Vermiculite based fire suppression agent. No. 15/935,620. declared: 26.03.2018; published: 26.08.2019. Available at: <https://patents.google.com/patent/US20190290950A1/en>
11. Zemlianskiy, O., Maladyka, I., Miroschnik, O., Shkarabura, I., Kaplenko, G. (2017). Forecasting the emergency explosive environment with the use of fuzzy data. *Eastern-European Journal of Enterprise Technologies*, 6 (4 (90)), 19–27. doi: <https://doi.org/10.15587/1729-4061.2017.116839>
12. Pozdieiev, S., Myhalenko, K., Nuianzin, V., Zemlianskiy, O., Kostenko, T. (2020). Revealing patterns of the effective mechanical characteristics of cellular sheet polycarbonate for explosion venting panels. *Eastern-European Journal of Enterprise Technologies*, 1 (1 (103)), 32–39. doi: <https://doi.org/10.15587/1729-4061.2020.192680>
13. Ognetchitel' poroshkoviy spetsial'niy OPS-5 Diapazon+. Available at: <https://www.magazin01.ru/catalog/ognetchiteli/Specialnye-ognetchiteli-klass-D/Ognetchitel-poroshkovyy-specialnyy-OPS-5-z-D-U2/>
14. Class D Stored Pressure Dry Powder Extinguisher. Available at: <https://www.amerex-fire.com/products/class-d-stored-pressure-dry-powder-extinguisher/>
15. Ansul Met-L-X Class D Extinguisher Powder, 50 lb pail. Available at: <https://www.ansul.com/en/us/DocMedia/F-76230.pdf>
16. Kovalyshyn, V., Marych, V., Gusar, B., Navalianyi, V., Fedyuk, Y. (2019). Justification of dry chemical powders testing procedure. *Fire Safety*, 33, 53–59. doi: <https://doi.org/10.32447/20786662.33.2018.07>
17. Husar, B., Kovalyshyn, V., Marych, V., Lozynskyi, R., Pastukhov, P. (2020). Combined extinguishing of class D, class A and class B fires. *Fire Safety*, 35, 30–34. doi: <https://doi.org/10.32447/20786662.35.2019.05>
18. Isachenko, V. P. et. al. (1981). *Teploperedacha*. Moscow: «Energoizdat», 415.
19. Matsevityi, Yu. M. (2002). *Obratnye zadachi teploprovodnosti*. Vol. 1: Metodologiya. Kyiv: Naukova dumka, 408.
20. Beshelev, S. D., Gurvich, F. G. (1980). *Matematiko-statisticheskie metody ekspertnyh otsenok*. Moscow: Statistika, 263.
21. Drayzdeyl, D.; Koshmarov, Yu. A., Makarov, V. E. (Eds.) (1990). *Vvedenie v dinamiku pozharov*. Moscow: Stroyizdat, 424.