

ABSTRACT AND REFERENCES
ENERGY-SAVING TECHNOLOGIES AND EQUIPMENT

RESEARCH ON MANOEUVRING CAPABILITIES OF A NUCLEAR POWER PLANT WHEN SWITCHING IN-USE CONTROL PROGRAMMES (p. 4-13)

Ievgeniia Kokol

The study is devoted to the development of object-oriented analysis for an automated control system to enhance the capabilities of manoeuvring a nuclear power unit with the WWER-1000 by switching the power control programmes of the NPP during its operation. The research was conducted to check whether the reactor unit was stable or not at the in-operation transition mode. According to the simulation results, control programmes during the operation of the nuclear power plant can be switched. The reactor unit remains in a stable state, which is evidenced by the values of the axial offset as a quantitative measure of the reactor stability. By using the suggestion and manoeuvring not only the capacity of the nuclear power plant but also the control programmes, it is possible to bring the consumption schedule of electric power to conformity with the schedule of electric power generation without affecting the safety of the nuclear power plant in operation.

Keywords: nuclear power plant, control programme, power, reactor stability.

References

1. Ivanov, V. A., Ozhiganov, Yu. V. (1986). Avtomatizatsiya energeticheskikh ustanovok TES i AES. Leningrad: SZPI, 64.
2. Tsiselskaya, T. A., Pelyih, S. N., Nazarenko, A. A. (2011). Analiz ustoychivosti aktivnoy zonyi yadernogo reaktora VVER-1000 pri razlichnyih programmah regulirovaniya reaktornoy ustanovki. Pratsi Odeskogo polItehnichnogo universitetu, 2 (36), 109–114.
3. Pelyih, S. N., Maksimov, M. V. Tsiselskaya, T. A., Baskakov, V. E. (2011). Sposob stabilizatsii aksialnogo raspredeleniya neytronnogo polya pri manevrirovaniyu moschnostyu VVER-1000. Yadernaya i radiatsionnaya bezopasnost, 1 (49), 27–32.
4. Kokol, E. (2015). Structural optimization of static power control programs for nuclear power plants with VVER-1000. Pratsi Odeskogo polItehnichnogo universitetu, 3(47), 41–46.
5. Shleer, S., Mellor, S. (1993). Ob'ektno-orientirovannyiy analiz: modelirovanie mira v sostoyaniyah. Kyiv, 240.
6. Tsiselskaya, T. A., Pelyih, S. N., Nazarenko, A. A. (2011). Analiz ustoychivosti aktivnoy zonyi yadernogo reaktora VVER-1000 pri razlichnyih programmah regulirovaniya reaktornoy usta-novki. Pratsi Odeskogo polItehnichnogo universitetu, 2 (36), 109–114.
7. Babich, S., Davydov, V. (2015). Objective function for municipal heat supply systems structural optimuzation. Pratsi Odeskogo polItehnichnogo universitetu, 3 (47), 134–140.
8. Pelykh, S. N., Gontar, R. L., Tsiselskaya, T. A. (2011). Estimation of local linear heat rate jump values in the variable loading mode. Nuclear physics and atomic energy, 12 (3), 242–245.
9. SangInova, O. V., Medvedev, R. B., Merduh, S. L. (2015). Development of the diagnostics algorithms of the water chemistry conditions at the nuclear power plant second circuit. Technology audit and production reserves, 3 (21), 37–41. doi: 10.15587/2312-8372.2015.37632
10. Maksimov, M. V., Tsiselskaya, T. A., Kokol, E. A. (2015). Sposob upravleniya reaktornoy ustanovkoj s VVER-1000 v manevrennom rezhime. Problemyi upravleniya i avtomatiki, 3, 59–75.
11. Khater, H., Abu-El-Maty, T., El-Morshdy, E.-D. (2006). Thermal-hydraulic modeling of reactivity accidents in MTR reactors. Nuclear Technology and Radiation Protection, 21 (2), 21–32. doi: 10.2298/ntrp0602021k
12. Porras, W.-R., Gualberto, J., Boza, V. (2012). Study of the effect of the Static Var Compensator on the Load Flow problem. Energy engineering. XXXIII (1), 1–8.
13. D'Auria, F., Cherubini, M., Galassi, M., Muellner, N. (2005). Analysis of measured and calculated counterpart test data in PWR and VVER 1000 simulators. Nuclear Technology and Radiation Protection, 20 (1), 3–15. doi: 10.2298/ntrp0501003d
14. Reventós, F., Batet, L., Llopis, C., Pretel, C., Sol, I. (2008). Thermal-Hydraulic Analysis Tasks for ANAV NPPs in Support of Plant Operation and Control. Science and Technology of Nuclear Installations, 2008, 1–13. doi: 10.1155/2008/153858

DEVELOPING OF METHODS CALCULATION OF COMUTATION OVERVOLTAGE IN SEMICONDUCTOR APPARATUS IN AC CIRCUITS (p. 14-22)

Anatoly Soskov,
Natalia Sabalaeva, Marina Glebova, Yana Forkun

The study focuses on switching overvoltage applied to semiconductor switches of semiconductor AC devices at the moment of switching electric circuits owing to the energy that has accumulated in the inductive elements of the mains and a disconnectable load.

Since the cost of power semiconductor devices is determined both by the current with which they are compatible and the class of the device that determines the amount of blocked voltage, it is important to use special measures that would reduce the voltage and make it closer to that of the network. Usually, the voltage is reduced with the help of protective RC-circuits and nonlinear surge suppressors (varistors).

The aim of the research was to refine the methods of calculating the switching overvoltage and parameters of protection circuits in semiconductor devices with account for the diversity of semiconductor switches and their dynamic characteristics since the current methods of calculation do not fully account for them and, therefore, are not fully precise.

The newly developed methods of calculating the switching surge consider dependence of the reverse recovery of power semiconductor devices on the rate of current decline in their circuit as well as high resistance of modern semiconductor devices to the effect of ultra-high voltage slew rates. The methodology also takes into account the conditions of the load switching with the help of these devices.

The developed methodology of selecting parameters for the RC-protective circuit accounts for the nature of any switching transients and significantly extends the range of protective circuit parameters.

The proposed surge suppressor for semiconductor AC switching devices is additionally supplied with a varistor that is connected in parallel to the RC-circuit, which allows a significant reduction in the capacitance of the circuit condenser and the leakage current and approximately 30 % reduction in the rate of switching surges. This would greatly reduce the class of power semiconductor devices.

Keywords: semiconductor device, switching overvoltage, protection RC-circuit, varistor/variable transistor, calculation methods.

References

1. Soskov, A. G., Soskova, I. A. (2005). Poluprovodnikovye apparaty: kommutatsiya, upravlenie, zaschita. Kyiv: Karavella, 344.

2. Murai, K., Tanaka, T., Babasaki, T., Nozaki, Y. (2011). Development of PDC and PDU with semiconductor breakers. 2011 IEEE 33rd International Telecommunications Energy Conference (INTELEC), 1–8. doi: 10.1109/intlec.2011.6099748
3. Tanaka, Y., Takatsuka, A., Yatsuo, T., Sato, Y., Ohashi, H. (2013). Development of semiconductor switches (SiC-BGSIT) applied for DC circuit breakers. 2013 2nd International Conference on Electric Power Equipment - Switching Technology (ICEPE-ST), 1–4. doi: 10.1109/icepe-st.2013.6804323
4. Soskov, A. G., Glebova, M. L., Sabalaeva, N. O., Forkun, Ya. B. (2014). Calculation of the thermal mode in semiconductor devices in conditions of their operation in semiconductor apparatuses. Eastern-European Journal of Enterprise Technologies, 5/8 (71), 58–66. doi: 10.15587/1729-4061.2014.27983
5. Soskov, A. G., Sabalaeva, N. O. (2012). Gibrnidni kontaktori nizkoyi naprugi z pokraschenimi tehniko-ekonomichnimi harakteristikami. Kharkivska natsional'na akademiya miskogo gospodarstva, 268.
6. Shukla, A., Demetriades, G. D. (2015). A Survey on Hybrid Circuit-Breaker Topologies. IEEE Trans. Power Delivery, 30 (2), 627–641. doi: 10.1109/tpwrd.2014.2331696
7. Khalifa, M., Rahman, A., Enamul-Haque, S. (1979). Solid-state a.c. circuit breaker. Proceedings of the Institution of Electrical Engineers, 126 (1), 75–76. doi: 10.1049/piee.1979.0013
8. Soskov, A. G. (2011). Usovershenstvovannye silovye kommutatsionnye poluprovodnikovyye apparaty nizkogo napryazheniya. Khar'kovskaya natsional'naya akademiya gorodskogo hozyaistva, 156.
9. Abe, S., Fukushima, K., Sihun, Y., Ogawa, M., Nomura, K., Shoyama, M., Ninomiya, T., Matsumoto, A., Fukui, A., Yamasaki, M. (2010). Malfunction mechanism of semiconductor circuit breaker in HVDC power supply system. 2010 IEEE Energy Conversion Congress and Exposition, 3733–3738. doi: 10.1109/ecce.2010.5617785
10. Magnusson, J., Bissal, A., Engdahl, G., Saers, R., Zhang, Z., Liljestrand, L. (2013). On the use of metal oxide varistors as a snubber circuit in solid-state breakers. IEEE PES ISGT Europe 2013, 1–4. doi: 10.1109/isgteurope.2013.6695454
11. Kerboua, H., Sebille, D., Miserey, F. (1993). 1200 V snubberless symmetrical GTO for AC switches. Power Electronics and Applications, 1993. Fifth European Conference on IET Conference Publications, 2, 272–277.
12. Magnusson, J., Saers, R., Liljestrand, L., Engdahl, G. (2014). Separation of the Energy Absorption and Overvoltage Protection in Solid-State Breakers by the Use of Parallel Varistors. IEEE Transactions on Power Electronics, 29 (6), 2715–2722. doi: 10.1109/tpel.2013.2272857
13. Bessonov, L. A. (2002). Teoreticheskie osnovy elekrotehniki. Elektricheskie tsepi. Moscow: Gardariki, 640.

RESEARCH OF DYNAMIC PROCESSES IN THE CONTROL SYSTEM OF THE HYDRAULIC DRIVE OF BELT CONVEYORS WITH VARIABLE CARGO FLOWS (p. 22-29)

**Leonid Polishchuk,
Yevhen Kharchenko, Oleh Piontkevych, Oleh Koval**

The dynamic processes in the hydraulic drive control system of the conveyor with parallel hydraulic motors were studied using a mathematical model, constructed on the basis of physical phenomena occurring during the variable load acting on the hydraulic system.

The obtained results allow justifying the settings of the conveyor hydraulic drive control system, which provide continuous operation of the hydraulic drive system under short-term or long-term overloads and switching on and off the additional hydraulic motor in the given regimes depending on the moment of useful resistance on the drive conveyor drum.

The analysis of theoretical graphs showed that the shut-off-and-regulating element of the control unit provides the desired mode of the system with a delay in the friction clutch engagement after switching on the additional hydraulic motor for its acceleration in the idle mode, thereby the executive body effectively overcomes the short-term and long-term overloads of the drive system.

The influence of the specific volume of the additional hydraulic motor, relationships of the sealing areas of the shut-off element, plunger mass and damping coefficient of the control system, as well as the mode of the load changes on the control system transients was determined. The values of the specific volume of the additional hydraulic motor, relationships between the sealing areas of the shut-off element affect the stability of the sensor transients. To avoid a vacuum cavity in the additional hydraulic motor during the friction clutch disengagement, it is needed to install a check valve between the pressure and discharge lines. The mass change or damping of the plunger by connecting the parallel check valve and throttle provide vibration damping during the clutch disengagement. To prevent the adjustment overpressure in the sensor, it is needed to install the safety-relief valve in the hydraulic system, which limits the pressure in the pressure line. The efficiency of using a direct-acting valve with parametric control as a sensor in the control device, which allows regulating the closing pressure by the selection of the valve geometric characteristics independently of the mode of the load changes was proved.

The research results can be used for hydraulic drives of the machines of various technological purposes that operate under variable loads.

Keywords: hydraulic drive, control system, conveyor, variable cargo flows, dynamic processes, mathematical modelling.

References

1. Dmitriev, V., Spivakovskij, A. (1977). Theoretical fundamentals of calculation of belt conveyors. Moscow: Nauka Publ., 154.
2. Shakhmeister, L., Dmytryev, V. (1978). Theory and calculation of belt conveyors. Moscow: Mashynstroenye Publ., 392.
3. Polishchuk, L., Iskovych-Lototskyi, R., Kotsiubivskyi, R. (2002). The usage of hydraulic drive in bead packing machines. Vibrations in technic and technologies, 5 (26), 106–108.
4. Forental, V. I., Forental, M. V., Nazarov, F. M. (2015). Investigation of Dynamic Characteristics of the Hydraulic Drive with Proportional Control. Procedia Engineering, 129, 695–701. doi: 10.1016/j.proeng.2015.12.093
5. Noskiewic, P. (2013). Control of the hydraulic drive using embedded control system. Proceedings of the 14th International Carpathian Control Conference (ICCC), 255–261. doi: 10.1109/carpathericc.2013.6560549
6. Kotlobay, A., Kotlobay, A., Tamelo, V. (2015). Hydraulic aggregates of systems of drives of moving equipment of road-building machines. Nayka i tehnika, 15 (1), 69–77.
7. Li, R., Luo, J., Sun, C., Liu, S. (2012). Analysis of Electro-hydraulic Proportional Speed Control System on Conveyer. Procedia Engineering, 31, 1185–1193. doi: 10.1016/j.proeng.2012.01.1161
8. Guan, C., Pan, S. (2008). Adaptive sliding mode control of electro-hydraulic system with nonlinear unknown parameters. Control Engineering Practice, 16 (11), 1275–1284. doi: 10.1016/j.conengprac.2008.02.002
9. Engineering Essentials: Hydraulic Motor Circuits (2012). Hydraulics & Pneumatics. Available at: <http://hydraulicspneumatics.com/200/TechZone/HydraulicPumpsM/Article/False/6472/Tech-Zone-HydraulicPumpsM>
10. Ho, T. H., Ahn, K. K. (2012). Speed Control of a Hydraulic Pressure Coupling Drive Using an Adaptive Fuzzy Sliding-Mode Control.

- IEEE/ASME Transactions on Mechatronics, 17 (5), 976–986.
doi: 10.1109/tmech.2011.2153866
11. Xu, B., Ding, R., Zhang, J., Cheng, M., Sun, T. (2015). Pump/valves coordinate control of the independent metering system for mobile machinery. Automation in Construction, 57, 98–111. doi: 10.1016/j.autcon.2015.04.012
 12. Shi, H., Yang, H., Gong, G., Liu, H., Hou, D. (2014). Energy saving of cutterhead hydraulic drive system of shield tunneling machine. Automation in Construction, 37, 11–21. doi: 10.1016/j.autcon.2013.09.002
 13. Polishchuk, L., Adler, O., Saleh, M., (2010). Parameter chosen of built-in hydraulic drive with control device. Mashinoznavstvo, 6, 36–40.
 14. Polishchuk, L., Koval, O. (2015). Mathematical modeling of dynamic processes of control device of hydraulic drive of belt conveyor with variable load. Tehnomus. New Technologies and Products in Machine Manufacturing Technologies, 1, 141–147.
 15. Polishchuk, L., Adler, O. (2010). Bulit-in hydraulic drives of conveyor with flexible traction body. Vinnitsya, 184.
 16. Iskovych-Lototskyi, R., Obertiukh, R., Arkhypchuk, M. (2008). Pressure pulses Generators for control of hydraulic drives of vibration and vibration-hit technological machines. Vinnitsya, 171.
 17. Polishchuk, L., Obertuh, R., Kharchenko, Ye., Adler, O., Kyslytsya, D. (2011). Controlled hydraulic motor-drum. Patent UA, no. 68816. The applicant and patentee Vinnytsia National Technical University. № u201111872; stated 10.10.2011; published 10.04.2012, № 7.
 2. Haakh, D.-I. F. (2003). Vortex chamber diodes as throttle devices in pipe systems. Computation of transient flow. Journal of Hydraulic Research, 41 (1), 53–59. doi: 10.1080/00221680309499928
 3. Overko, V. M., Ovsyannikov, V. P., Papayany, O. F. (2006). Zashchita ot hidravlicheskih udarov vodootlivnykh ustyanovok s pohruzhnymi nasosami. Razrabotka rudnykh mestorozhdenii nauch Tekhn Sb Krivorozhskii tekhn-nicheskii universitet, 90, 158–162.
 4. Hymadyev, A. H., Utkin, A. V. (2015). Issledovaniye kharakterystyk vikhrevoho hidravlycheskogo drosselya dlya system podhotovky prob teplonosityelya. Vestnik Samarskogo gosudarstvennogo aerokosmicheskogo universiteta, 4, 110–117.
 5. Lv, Q. Design, Sun, X., Chtistensen, R., Blue, T., Yoder, G., Wilson, D. (2015). Testing and Modeling of the Direct Reactor Auxiliary Cooling System for AHTRs. Office of the Assistant Secretary for Nuclear Energy. Oak Ridge, US, 169. doi: 10.2172/1183704 Available at: <https://neup.inl.gov/SiteAssets/Final%20%20Reports/FY%202010-10-951%20NEUP%20Final%20Report.pdf>
 6. Mathai, J. P. (1992). A study of vortex diodes at low Reynolds number. Electronic Theses and Dissertations, 88. Available at: <http://scholar.uwindsor.ca/cgi/viewcontent.cgi?article=1825&context=etd>
 7. Baker, P. J. (1967). A comparison of fluid diodes, In Proceedings of the 2-nd Cranfield Fluidics Conference, 2, 88–126
 8. Lebedev, I. V., Treskunov, S. L., Yakovenko, V. S. (1973). Elementyi struynoy avtomatiki, 359.
 9. Burnett, R., Caso, D., Tang, J. (2010). Fluidic Diode Development and Optimization Department of Nuclear Engineering University of California, 36.
 10. Yoder, J., Graydon, L., Elkassabgi, Y., De Leon, G. (2011). Vortex Diode Analysis and Testing for Fluoride Salt-Cooled High-Temperature Reactors ORNL, 28.
 11. Kulkarni, A. A., Ranade, V. V., Rajeev, R., Koganti, S. B. (2009). Pressure drop across vortex diodes: Experiments and design guidelines. Chemical Engineering Science, 64 (6), 1285–1292. doi: 10.1016/j.ces.2008.10.060
 12. Kononenko, A. P., Overko, V. M., Overko, M. V., Goncharov, V. M. (2012). Ukraine patent No UA 75770. Kyiv, Ukrainian intellectual property institute, 4.
 13. Molchanov, A. M. (2013). Matematicheskoe modelirovanie zadach gazodinamiki i teplomassoobmena. MAI, 206.
 14. Pravila izmereniya rashoda gazov i zhidkostey standartnymi suzhayuschimi ustroystvami (1982). Moscow: Izd-vo standartov, 320.
 15. Timoshenko, G. M., Zima, P. F. (1991). Teoriya inzhenernogo eksperimenta. UMK, 124.
 16. Kononenko, A. P., Ovsyannikov, V. P., Overko, M. V. (2015). Vyibor osnovnyih parametrov vihrevogo dioda dlya predotvrascheniya hidravlicheskih udarov v vertikalnyih truboprovodah. Vestnik Nationalnogo tehnicheskogo universiteta KhPI. Seriya Matematicheskoe modelirovanie v tehnike i tehnologiyah, 6 (1115), 40–49.

EXPERIMENTAL RESEARCH OF THE OPERATION EFFICIENCY OF THE VORTEX DIODE FOR PROTECTION AGAINST WATER HAMMER (p. 29-36)

Mykhailo Overko

If the main cause of water hammer in a long discharge line is the sudden shutdown of the pump, it is enough to increase the reverse resistance of the discharge line for the protection against high pressure using large-size inkjet diodes, which have no moving parts and therefore are reliable, which is important for safety valves. Vortex diodes, the most important parameter of which is diodicity – the ratio of the reverse hydraulic resistance to forward best meet the requirements for reducing the water hammer magnitude. The description of the design of a new vortex diode with a conical inlet, the bench, the methodology of the experiments and the results obtained is given. A characteristic feature of the proposed design of the vortex diode is a conical inlet to the vortex chamber and the end arrangement of the offset on the outer surface. The flow characteristics of the diode in the reverse and forward fluid flow are built. The dependence of the diodicity on the flow rate is determined. It is shown, in particular, that this dependence is a third-order algebraic equation. The maximum diodicity is 12 at a water velocity of 3.8 m/s. The vortex diode time constant, which amounts to 1.35 s at the fluid velocity of 3.54 m/s, which confirms the adequacy of the numerical method for calculating the dynamic characteristics of vortex diodes is determined. The data are obtained in the simulation of the vortex diode operation by the numerical method.

Keywords: water hammer, protection, diodicity, vortex diode, hydraulic resistance, experimental characteristics.

References

1. Seerer, G. (1970). Das Wasserschloss des Kaunertalkraftwerk der TIWAG: ein neuer Typ eines rückstromgedrosselten Kammerwaserschlosses Schweizerische Bauzeitung, Sonderdruck, 88, 1–8.

AUTOMATED COMPARISON SYSTEM OF THE TECHNICAL AND ECONOMIC EFFICIENCY OF ELECTRIC DRIVES OF CRANE MECHANISMS (p. 37-49)

Victor Busher, Svetlana Savich,
Svyatoslav Savich, Vadym Medvediev

Various types of the AC electric drive: traditional one with resistor control, with thyristor voltage converter and with frequency converter, the latter with power recovery are considered. The review of static and dynamic characteristics of each of the electric drives is presented, based on which recommendations are made concerning the application of a particular asynchronous electric drive of the proposed options in specific cases. Energy performance, loss in the motor circuits are calculated for specific crane hoist mechanisms.

The CAD-system for technical and economic comparison of the crane drives taking into account the main operation features: loads, moments of inertia with/without load, the relative operating time with reduced speed is developed. Due to the unification of approaches to the analysis of the operating conditions of the hoist and swing mechanisms, the program calculates the power consumption in static and dynamic modes. Known capital and depreciation costs and total annual power losses obtained in the CAD-system allow making decisions about the choice or necessity of reconstruction of the electric drive.

Keywords: electric drive, CAD-system for technical and economic comparison, resistor control, voltage converter, frequency converter, resistor braking.

References

1. Javied, T., Rackow, T., Stankalla, R., Sterk, C., Franke, J. (2016). A Study on Electric Energy Consumption of Manufacturing Companies in the German Industry with the Focus on Electric Drives. *Procedia CIRP*, 41, 318–322. doi: 10.1016/j.procir.2015.10.006
2. Raubar, E., Vrancic, D. (2012). Anti-Sway System for Ship-to-Shore Cranes. *Journal of Mechanical Engineering*, 58 (5), 338–344. doi: 10.5545/sv-jme.2010.127
3. Miller, P., Olateju, B., Kumar, A. (2012). A techno-economic analysis of cost savings for retrofitting industrial aerial coolers with variable frequency drives. *Energy Conversion and Management*, 54 (1), 81–89. doi: 10.1016/j.enconman.2011.09.018
4. Usynin, Y. S., Valov, A. V., Kozina, T. A. (2011). Asynchronous electric drive with pulse-vector control. *Russian Electrical Engineering*, 82 (3), 134–137. doi: 10.3103/s1068371211030102
5. Emelyanov, A. P., Kozyaruk, A. E. (2011). Algorithms for management, modeling, and analysis of highly dynamical asynchronous electric drives. *Russian Electrical Engineering*, 82 (2), 61–68. doi: 10.3103/s1068371211020052
6. Tunyasirut, S., Kinnares, V. (2013). Speed and Power Control of a Slip Energy Recovery Drive Using Voltage-source PWM Converter with Current Controlled Technique. *Energy Procedia*, 34, 326–340. doi: 10.1016/j.egypro.2013.06.761
7. Nicolae, P.-M., Stanescu, D.-G., Sirbu, I.-G. (2008). About the experimental results of an electric driving system based on asynchronous motor and PWM converter. 2008 13th International Power Electronics and Motion Control Conference. doi: 10.1109/epemc.2008.4635428
8. Nicolae, P.-M., Stanescu, D.-G., Sirbu, I.-G. (2008). About the experimental results of an electric driving system based on asynchronous motor and PWM converter. 2008 13th International Power Electronics and Motion Control Conference, 259–274. doi: 10.1109/epemc.2008.4635428
9. Blanusa, B. (2010). New Trends in Efficiency Optimization of Induction Motor Drives. *New Trends in Technologies: Devices, Computer, Communication and Industrial Systems*. doi: 10.5772/10427
10. Grygorov, O. V., Svyrgun, V. P., Stryzhak, V. V., Zajcev, Ju. I. (2010). Energoberezhennja shljahom zastosuvannja racional'nogo keruvannja asynchronnyh elektropryvodiv VPM. *Sbornyk nachnih trudov «Vestnyk NTU «HPY»: Tehnologii» v mashynobuduvanni*, 49, 61–64.
11. Grygorov, O. V., Zaytsev, Y. I., Svirgun, V. P., Stryzhak, V. V. (2010). Realization of energy-saving control modes on cranes of great load-carrying capacity. *Annals of the University of Petrosani: Mechanical Engineering*, 12, 111–118.
12. Zalizec'kyj, A. M., Piznjur, O. V. (2012). Doslidzhennja chastotnogo elektropryvoda v statichnyh rezhymah roboty. *Visnyk Hmel'nyc'kogo nacional'nogo universytetu*, 3, 69–74.
13. Firago, B. I., Vasil'ev, D. S. (2011). Primenenie ustrojstv plavnogo puska i tormozhenija asynchronnyh elektricheskikh dvigatelej s k.z. rotorom v elektroprivodah kranovyh mehanizmov peredvizhenija. *Elektrotehnicheskie i kompjuternye sistemy*, 4 (80), 30–38.
14. Radimov, S. N., Anichenko, K. A. (2006). Potencial jenergosberezhennja elektroprivodov portovyh gruzopod'emyh mashin. *Elektromashinobuduvannja ta elektrobladnannja*, 66, 322–323.
15. Moshhinskij, Ju. A., Aung, Vin Tut (2007). Obobshhennaja matematicheskaja model' chastotno-reguliruemogo asinhronnogo dvigatelya s uchetom poter' v stali. *Elektrotehnika*, 11, 61–66.
16. Braslavskij, I. Ja., Ishmatov, Z. Sh. (2003). Realizacija energooshadnyh tehnologij na osnovi regul'ovanyh asynchronnyh elektroprivodov. *Elektroinform*, 3, 11–15.
17. Grygorov, O. V., Stryzhak, V. V. (2012). Analiz pusko-gal'mivnyh procesiv kranovyh mehanizmov z chastotno-regul'ovanim pryvodom. *Vestnyk HNADU*, 57, 249–256.
18. Savych, S. P. (2012). Porivannja ekonomichnoi' efektyvnosti al'ternatyvnyh elektropryvodiv u nestacionarnyh rezhymah. *Elektrotehnichni ta kompjuterni sistemy*, 07 (83), 50–55.
19. Gerasymiak, R., Busher, V., Savich, S., Shvets, L. (2012). Computer-aided Design System for Technical and Economical Comparison of Crane Electrical Drives. *Computational Problems of Electrical Engineering*, 2, 21–25.
20. Braslavskij, I. Ja., Ishmatov, Z. Sh., Poljakov, V. N. (2004). Jenergosberegushhij asynchronnyj elektroprivod. Moscow: ASA-DEMA, 202.
21. Gerasymjak, R. P., Savych, S. P., Shvec, L. A. (2011). Ekonomichna efektyvnist' vykorystannja peretvorjuvachiv chastyoty dlja kranovyh mehanizmov pidgomu. *Elektrotehnichni ta kompjuterni sistemy*, 03 (79), 392–393.
22. SINAMICS G110, SINAMICS G120. Standartnye preobrazovateli. SINAMICS G 110 D, SINAMICS G 120 D. Decentralizovannye preobrazovateli. Katalog D 11.1.2009.
23. Altivar 71. Preobrazovateli chastyoty (2009). Schneider Electric, 332.

EVALUATION OF THERMODYNAMIC PERFECTION OF THE HEATING CASCADE MACHINE CYCLES (p. 50-55)

Larisa Morozyuk

One of the promising trends in the refrigerating engineering is building machines for industrial processes with the simultaneous use of two thermal effects (heat and cold). The fundamental possibility to build machines, operating on a complex reverse thermodynamic cycle with the production of low-grade cold and high-grade heat is considered. Such machines are called heating cascade machines. The synthesis of cyclic machine solutions for various pairs of materials, based on thermodynamic analysis by the “method of cycles” is carried out. The analysis of the supercritical cycle of the upper cascade with R744 by the entropy-cycle method is performed. It is shown that the compound Carnot-Lorenz cycle (“triangular”) should be chosen as the cycle model. The problem of determining the degree of thermodynamic perfection of the cascade cycle, which takes into account the simultaneous production of two thermal effects – cold and heat is solved. An example of the calculation of the machine characteristics under variable input parameters: temperature in the condenser-evaporator and the pressure in the gas cooler is given. The comparison with the characteristics of the cascade machine, operating in the same mode, but with one thermal effect – the production of cold, which showed the benefits of heating cycles is performed. It is proved that, given the simultaneous high temperatures of the heat produced and low temperature of the cold produced in the cascade heating machine, energy performance is quite high. General recommendations – in terms of energy saving, heating cascade units and machines, operating with R744 as a working substance of the upper cascade and the cycle in the supercritical region with the simultaneous heat and cold production should be designed.

Keywords: heating cascade machine, R744, supercritical cycle, degree of thermodynamic perfection.

References

1. Lorentzen, G. (1994). The use of natural refrigerants. IIR conference on new application of natural working fluids in refrigeration and air-conditioning. Germany.
2. Bingming, W., Huagen, W., Jianfeng, L., Ziwen, X. (2009). Experimental investigation on the performance of NH₃/CO₂ cascade refrigeration system with twin-screw compressor. International Journal of Refrigeration, 32 (6), 1358–1365. doi: 10.1016/j.ijrefrig.2009.03.008
3. Dopazo, J. A., Fernández-Seara, J. (2011). Experimental evaluation of a cascade refrigeration system prototype with CO₂ and NH₃ for freezing process applications. International Journal of Refrigeration, 34 (1), 257–267. doi: 10.1016/j.ijrefrig.2010.07.010
4. Bhattacharyya, S., Mukhopadhyay, S., Kumar, A., Khurana, R. K., Sarkar, J. (2005). Optimization of a CO₂–C₃H₈ cascade system for refrigeration and heating. International Journal of Refrigeration, 28 (8), 1284–1292. doi: 10.1016/j.ijrefrig.2005.08.010
5. Di Nicola, G., Giuliani, G., Polonara, F., Stryjek, R. (2005). Blends of carbon dioxide and HFCs as working fluids for the low-temperature circuit in cascade refrigerating systems. International Journal of Refrigeration, 28 (2), 130–140. doi: 10.1016/j.ijrefrig.2004.06.014
6. Yamaguchi, H., Niu, X.-D., Sekimoto, K., Neksā, P. (2011). Investigation of dry ice blockage in an ultra-low temperature cascade refrigeration system using CO₂ as a working fluid. International Journal of Refrigeration, 34 (2), 466–475. doi: 10.1016/j.ijrefrig.2010.11.001
7. Martyinovskiy, V. S. (1972). Analiz deystvitelnyih termodinamicheskikh tsiklov. Moscow: Energiya, 216.
8. Kompressoryi dlya CO₂. Danfoss. Available at: <http://s-parts.com.ua/documentation-20/danfoss/co2.html> (Last accessed: 29.05.2012).
9. Novyyi spiralnyi kompressor dlya CO₂. Emerson Climate Technologies. Available at: http://www.emersonclimate.com/europe/Documents/RU_Documents/2011_0526_PREL_CO2scroll_RU.pdf (Last accessed: 26.10.2011).
10. Nikulshin, R. K. (2012). Entropiynyiy metod modelirovaniya i analiza dvuhstupenchatyih tsiklov holodilnih mashin i teplovih nasosov. Sbornik nauchnyih trudov 8-oy Mezhdunarodnoy nauchno-tehnicheskoy konferentsii «Ustoychivoe razvitiye i iskusstvennyiy holod», 1, 8–16.
11. Morozyuk, L. I. (2016). Termodinamicheskiy analiz kaskadnyih holodilnyih mashin s R744 v verhnem. Holodilnaya tekhnika i tehnologiya, 52 (1), 12–17.
12. Morosuk, T., Nikulshin, R., Morosuk, L. (2006). Entropy-cycle method for analysis of refrigeration machine and heat pump cycles. Thermal Science, 10 (1), 111–124. doi: 10.2298/tsci0601111m
13. Rozhentsev, A., Naer, V. A., Wang, C.-C. (2005). The analysis of triangular cycles of cooling and heating. Applied Thermal Engineering, 25 (1), 21–30. doi: 10.1016/j.applthermaleng.2004.05.009
14. Khaliq, A. (2009). Exergy analysis of gas turbine trigeneration system for combined production of power heat and refrigeration. International Journal of Refrigeration, 32 (3), 534–545. doi: 10.1016/j.ijrefrig.2008.06.007

A STUDY OF THE RATES OF PORE NUCLEATION AND PORE GROWTH IN ALUMINA-BASED THERMAL INSULATION MATERIALS (p. 56-62)

Andriy Cheylitko

The study considers the Gibbs energy change at the time of pore nucleation. An equation is suggested for describing the critical radius of a pore nucleus. Since it is directly proportional to the sur-

face tension, pores are formed in places with density irregularities or fluctuations. An analysis has revealed conditions for a pore to exist, the minimum work for a pore to nucleate, the time necessary for a pore to appear, and the likelihood of a pore nucleation. The undertaken laboratory tests concern the pore formation rate and the pore growth rate in aluminous materials. The study has determined the general dependencies of wetness changes in the material under its heat treatment and the dynamics of porosity changes in an intumescent material. It allows distinguishing between three stages of change in the number of pores in an intumescent alumina-based material: a stage of a declining number of generated pores, a stage of equal reduction of the number of pores, and a stage of pores overgrowth.

The obtained results are applicable to such thermal insulation materials as expanded clay and refractory materials as well as other aluminous materials that are produced by swelling.

The conducted experiments have identified the main patterns of changes in the number of pores and the total porosity in aluminous materials when they are heat-treated. It has consequently helped develop a system of equations that describe changes in the porosity of an alumina-based material. The devised equations suggest that the number of pores is directly proportional to the heat treatment temperature as well as to the difference between the surrounding pressure and the critical pressure of a pore. Besides, this system of equations can help predict the number of pores in an intumescent material, which facilitates control over thermophysical properties of the material.

The research findings are very important for developing new high-intensity technologies in various industries, in particular for improving the existing production technology of thermal insulation materials based on alumina. Besides, the obtained results can help create new insulating materials.

Keywords: pores, porous system, pore nucleation rate, Gibbs energy, alumina, expanded clay, refractories.

References

1. Cheylitko, A. A. (2013). Study of vesiculation in intumescent material. Technology Audit and Production Reserves, 5/4 (13), 38–40. Available at: <http://journals.uran.ua/tarp/article/view/18251/16063>
2. Pavlenko, A. M., Koshlak, H. V., Cheylitko, A. A., Nosov, M. A. (2015). Gas parameters agent-blown agent inside a closed spherical pores in a state of equilibrium. Vestnik NTU "KPI", Series: New solutions in modern technologies, 62 (1171), 28–35.
3. Cheylitko, A. A. (2015). Osobennosti vliyanija poristosti na teploprovodnost glinozemestiyih materialov perevoda. Dnepropetrovsk: Serednyak T. K., 76.
4. Shpak, A., Cheremskoi, P., Kunitskii, Yu., Sobol', O. (2005). Klasternye i nanostrukturnye materialy. Vol. 3. Poristost' kak osoboe sostoianie samoorganizovannoi struktury v tverdotel'nyh materialah. Kyiv: VD «Akademperiodika», 516.
5. Freire-Gormaly, M. (2013). The Pore Structure of Indiana Lime-stone and Pink Dolomite for the Modeling of Carbon Dioxide in Geologic Carbonate Rock Formations. Department of Mechanical and Industrial Engineering. University of Toronto, 85. Available at: https://tspace.library.utoronto.ca/bitstream/1807/42840/1/Freire-Gormaly_Marina_201311_MASc_thesis.pdf
6. Eom, J.-H., Kim, Y.-W., Raju, S. (2013). Processing and properties of macroporous silicon carbide ceramics: A review. Journal of Asian Ceramic Societies, 1 (3), 220–242. doi: 10.1016/j.jascer.2013.07.003
7. Pavlenko, A. M., Koshlak, H. V. (2015). Design of processes of thermal bloating of silicates, 1, 118–122.
8. Bajare, D., Kazjonovs, J., Korjakins, A. (2013). Lightweight Concrete with Aggregates Made by Using Industrial Waste. Journal of

- Sustainable Architecture and Civil Engineering, 4 (5). doi: 10.5755/j01.sace.4.5.4188
9. Bodnarova, L., Hela, R., Hubertova, M., Novakova, I. (2014). Behaviour of Lightweight Expanded Clay Aggregate Concrete Exposed to High Temperatures: International Journal of Civil, Environmental, Structural, Construction and Architectural Engineering, 8 (12), 1205–1208.
10. Dincov, D. D., Parrott, K. A., Pericleous, K. A. (2004). Heat and mass transfer in two-phase porous materials under intensive microwave heating. Journal of Food Engineering, 65 (3), 403–412. doi: 10.1016/j.jfoodeng.2004.02.011 Available at: <http://www.researchgate.net/publication/222658046>
11. Lopez-Pamies, O., Castaneda, P. P., Idiart, M. I. (2012). Effects of internal pore pressure on closed-cell elastomeric foams. International Journal of Solids and Structures, 49 (19-20), 2793–2798. doi: 10.1016/j.ijsolstr.2012.02.024 Available at: http://www.researchgate.net/publication/256733990_Effects_of_internal_pore_pressure_on_closed-cell_elastomeric_foams
12. Vesenjak, M., Öchsner, A., Ren, Z. (2005). Influence of pore gas in closed-cell cellular structures under dynamic loading. German LS-DYNA Forum. Available at: <https://www.dynamore.de/de/download/papers/forum04/new-methods/influence-of-pore-gas-in-closed-cell-cellular>
13. Komissarchuk, O., Xu, Z., Hao, H. (2014). Pore structure and mechanical properties of directionally solidified porous aluminum alloys: China Foundry, 11 (1), 1–7. Available at: <https://doaj.org/article/002c72e2e01345db8bf4fef190113057>