

### STUDYING THE PECULIARITIES OF BALANCING OF FLEXIBLE DOUBLE-SUPPORT ROTORS BY TWO PASSIVE AUTOMATIC BALANCERS PLACED NEAR SUPPORTS (p. 4-9)

Valery Goncharov, Gennadiy Filimonikhin, Kostyantyn Dumenko, Mihail Lychuk

A discrete N-mass model of a flexible double-support rotor with two passive automatic balancers of pendulum, ball or roller type was constructed. Automatic balancers are placed near supports. The system of differential equations, which describes the motion of a rotor machine, is obtained.

The primary (sustained) motions of a system as the motions, in which automatic balancers eliminated displacements of a rotor in supports, were found. It is shown that on the primary motions, the total imbalances of a rotor and AB, reduced to two correction planes (supports), equal zero.

It was proposed to examine the stability (of the family) of sustained motions by generalized coordinates, which set the displacement of a rotor in the supports and by dynamic variables that equal total imbalances of a rotor and AB in two correction planes. We obtained differential equations, which describe the change in these variables that describe the process of self-balancing.

By the analysis of differential equations of the motion of a system it was established that:

- on the primary motions, AB eliminate rotor deflections and vibrations in elastic viscous supports, but do not remove shaft deflections in non-supporting points;
- on the primary motions elastic viscous supports are conditionally converted into hinge supports;
- shaft deflections in non-supporting points and the primary motions change with the change in angular speed of rotation of the rotor;
- primary motions exist at a certain distance of the speed of rotation of the rotor from the critical speeds of flexible rotor rotation with the hinge supports instead of elastic viscous supports;
- at the speeds of rotation of a rotor shaft close to any of these speeds, the conditions of existence of the primary motions are disrupted because shaft deflections theoretically grow to infinity and the balancing capacity of AB is not sufficient for the compensation for the imbalances of the rotor;
- in practice these deflections are limited and, therefore, proper selection of the balancing capacity of AB can ensure existence of primary motions at all speeds of rotation of rotor.

**Keywords:** flexible rotor, automatic balancer, self-balancing, primary motion, critical speed, resonance speed.

#### References

1. Simonovsky, V. I. (2006). *Dinamika rotorov tsentrobezhnykh mashin* [The dynamics of the rotors of centrifugal machines]. Sumy: Publ. house Sumy State University, 126.
2. Yamamoto, T., Ishida, Y. (2012). *Linear and Nonlinear Rotordynamics: A Modern Treatment with Applications*. Wiley-VCH, 474. doi: 10.1002/9783527651894
3. Thearle, E. L. (1950). Automatic dynamic balancers Part 2 – Ring, pendulum and ball balancers. *Machine Design*, 22 (10), 103–106.
4. Detinko, F. M. (1956). Ob ustoychivosti raboty avtobalansira dlya dinamicheskoy balansirovki [On the stability of work auto-balancer for dynamic balancing]. *Proceedings of the Academy of Sciences of the USSR. Meh. and machine building*, 4, 38–45.
5. Ehyaei, J., Moghaddam, M. M. (2009). Dynamic response and stability analysis of an unbalanced flexible rotating shaft equipped with n automatic ball-balancers. *Journal of Sound and Vibration*, 321 (3-5), 554–571. doi: 10.1016/j.jsv.2008.10.019
6. Hsieh, H.-Y., Lu, C.-J. (2015). Application of automatic balancers on a flexible-shaft rotor system. *The 22-nd International Congress on Sound and Vibration, ICSV22*. Florence, Italy.
7. DeSmidt, H. A. (2009). Imbalance Vibration Suppression of a Supercritical Shaft via an Automatic Balancing Device. *Journal of Vibration and Acoustics*, 131 (4), 041001. doi: 10.1115/1.3025834
8. Majewski, T., Szwedowicz, D., Melo, M. A. M. (2015). Self-balancing system of the disk on an elastic shaft. *Journal of Sound and Vibration*, 359, 2–20. doi: 10.1016/j.jsv.2015.06.035
9. Filimonikhin, G. B., Gadiaka, V. G., Panenko, V. G., Goncharov, V. V. (2015). Patent of Ukraine No. 107719 (of 20 years), IPC G01M 1/32. Sposib balansuvannya hnuchkoho dvooporno-ho rotora pasyvnymy avtobalansyramy [Method for balancing flexible double-seat rotor with passive auto balancers]. No. a201301213, declared: 11.08.2014; published: 10.02.2015, *Bul. № 3*, 8.
10. Sperling, L., Ryzhik, B., Duckstein, H. (2001). Two-plain automatic balancing. *Machine Dynamics Problems*, 25 (3/4), 139–152.
11. Hadyaka, V. G., Leykikh, D. V., Simonovsky, V. I. (2010). Matematicheskaya model rotora turbokompresora dlya issledovaniya nesinkhronnykh sostavlyayushchikh vibratsii [A mathematical model of rotor of the turbocharger for research asynchronous components vibration]. *Compressor and power engineering*, 2 (20), 48–50.
12. Gorbenko, A. N. (2003). On the Stability of Self-Balancing of a Rotor with the Help of Balls. *Strength of Materials*, 35 (3), 305–312. doi: 10.1023/a:1024621023821
13. Filimonikhin, G. B., Goncharov, V. V. (2011). Diskretna model gnuchkogo rotora z pasyvnymy avtobalansyramy [Discrete model of flexible rotor with of passive auto-balancer]. *Avtomatyzatsiya vyrobnychikh protsesiv u mashynobuduvanni ta pruladobuduvanni*, 45, 488–495.
14. Filimonikhin, G. B., Goncharov, V. V. (2015). Vid i struktura differentsialnykh uravneniy dvizheniya i protsessa uravnoveshivaniya rotornoy mashiny s avtobalansirami [Form and structure of differential equations of motion and process of auto-balancing in the rotor machine with auto-balancers]. *Bulletin of the Tomsk Polytechnic University. Geo Assets Engineering*, 326 (12), 20–30. Available at: [http://www.lib.tpu.ru/fulltext/v/Bulletin\\_TPU/2015/v326/i12/02.pdf](http://www.lib.tpu.ru/fulltext/v/Bulletin_TPU/2015/v326/i12/02.pdf)
15. Filimonikhin, G. B., Nevdakha, Yu. A. (2002). Balancing a Rotor with Two Coupled Perfectly Rigid Bodies. *International Applied Mechanics*, 38 (3), 377–386. doi: 10.1023/a:1016050732065

## ANALYTICAL STUDY OF THE BENDING OF ISOTROPIC PLATES, INHOMOGENEOUS IN THICKNESS (p. 10-16)

**Volodymyr Plevako, Volodymyr Potapov, Viktor Kucenko, Ighor Lebedinec, Iryna Pedorych**

A three-dimensional problem of bending the plate, in which the parameters of elasticity of the material vary by thickness and are arbitrary integrable functions, was examined. And the plate itself is exposed to the action of mass forces while the action of surface loads is studied as a separate case.

An analytical solution to the boundary problem by the operator methods was obtained in a case when the boundary conditions are satisfied exactly on the flat surfaces of the plates and on the lateral surface – in the Saint Venant approximation.

It was theoretically proved that the exact, in the sense of Saint Venant, analytical solutions may be obtained if the plate is exposed to the action of the mass and surface forces, distributed on the plate and on its surface by the two-dimensional polyharmonic law. In this case, the thinner the plate, the more exact the solution will be, since the corresponding solutions represent the series that contain a finite number of members.

It was demonstrated that the obtained formulas for the calculation of bending the thin plates in the case of homogeneous material transfer to the classic formulas of the theory of bending thin plates.

The obtained solutions allow using them as the approximate, “technical” theory for engineering calculations of the stressed and deformed state of non-homogeneous plates.

**Keywords:** theory of elasticity, isotropic bodies, non-homogeneous materials, bending of plates, stress and deformations.

### References

- Zenkour, A. M., Mashat, D. S. (2008). Exact solutions for variable-thickness inhomogeneous elastic plates under various boundary conditions. *Meccanica*, 44 (4), 433–447. doi: 10.1007/s11012-008-9181-z
- Li, X., Ding, H., Chen, W. (2006). Pure bending of simply supported circular plate of transversely isotropic functionally graded material. *Journal of Zhejiang University SCIENCE A*, 7 (8), 1324–1328. doi: 10.1631/jzus.2006.a1324
- Zhang, Z. M., Wang, W., Wong, P. L. (2013). An explicit solution for the elastic quarter-space problem in matrix formulation. *International Journal of Solids and Structures*, 50 (6), 976–980. doi: 10.1016/j.ijsolstr.2012.12.001
- Gao, Y., Zhao, B.-S. (2008). A refined theory of elastic thick plates for extensional deformation. *Archive of Applied Mechanics*, 79 (1), 5–18. doi: 10.1007/s00419-008-0210-0
- Salehipour, H., Nahvi, H., Shahidi, A. R. (2015). Closed-form elasticity solution for three-dimensional deformation of functionally graded micro/nano plates on elastic foundation. *Latin American Journal of Solids and Structures*, 12 (4), 747–762. doi: 10.1590/1679-78251398
- Zenkour, A. M., Allam, M. N. M., Radwan, A. F., El-Mekawy, H. F. (2015). Thermo-Mechanical Bending Response of Exponentially Graded Thick Plates Resting on Elastic Foundations. *International Journal of Applied Mechanics*, 07 (04), 1550062. doi: 10.1142/s1758825115500623
- Chondhury, P. (1957). Stresses in an elastic layer with varying modulus of elasticity. *Bulletin of the Calcutta Mathematical Society*, 49 (2), 99–104.
- Kogan, B. N. (1957). Stresses and strains in the coating with a continuously varying modulus. *Tr. Khark. avtomob.-dor. yn-ta.V* 19, 53–66.
- Gibson, R. E., Brown, P. T., Andrews, K. R. F. (1971). Some results concerning displacements in a non-homogeneous elastic layer. *Zeitschrift Fur Angewandte Mathematik Und Physik ZAMP*, 22 (5), 855–864. doi: 10.1007/bf01591813
- Bufler, H. (1963). Elastische Schicht und elastischer Halbraum bei mit der Tiefe stetig abnehmendem Elastizitätsmodul. *Ingenieur-Archiv*, 32 (6), 430–436. doi: 10.1007/bf00531790
- Awojobi, A. O., Gibson, R. E. (1973). Plane strain and axially symmetric problems of a linearly nonhomogeneous elastic half-space. *The Quarterly Journal of Mechanics and Applied Mathematics*, 26 (3), 285–302. doi: 10.1093/qjmam/26.3.285
- Awojobi, A. O. (1976). On the hyperbolic variation of elastic modulus in a non-homogeneous stratum. *International Journal of Solids and Structures*, 12 (11), 739–748. doi: 10.1016/0020-7683(76)90039-1
- Puro, A. E. (1975). On the solution of equations of the theory of an inhomogeneous medium elastic. *Journal of applied mechanics*, 11 (3), 50–55.
- Plevako, V. P. (1997). Common solutions in problems of the theory of elasticity of inhomogeneous media. *Kharkiv: Osnova*, 159.
- Plevako V. P. (1978). Plane problems bending inhomogeneous bodies with the polynomial loadings. *Journal of applied mechanics*, 14 (3), 59–65.
- Ustynov, Y. A. (1975). Homogeneous solutions and the problems of transition from three-dimensional to two-dimensional problems for the boards of elektrouprugih materials with variable thickness properties. *Tbylysy: Yzdvo «Metsnyereba»*.
- Korn, H., Korn, T. (1973). *Mathematical Handbook for Scientists and Engineers*. Moscow: Nauka, 832.

## ANALYSIS OF ORIGIN OF SHEAR BANDS IN A REINFORCING ELASTIC-PLASTIC BODY (p. 17-22)

**Yurii Chernyakov, Artur Shevchenko**

The area of the line of localization of plastic deformation in the section of reinforcement is presented in the form of a band of finite length for the case of plane strain. The banks of the band can slide freely, but in this case they must stay in contact. The theory of microdeformation, which leads to the singular surface of fluidity is used for describing mechanical behavior, which is very important in the problems of localization.

We built a closed analytical solution of the problem of building the fields of rates of displacements and changes in stresses in the vicinity of apex of the assigned line of discontinuity of the speeds of displacements. It was established that three different forms of the solution, depending on the results of the solution to the problem of localization, are possible. The point of localization is defined as the point of intersection of the curve defining the dependency of parameters of material on the parameters of load according to the theory of microdeformations, with the curve that defines the boundary between elliptic and hyperbolic regime of the solutions. The field of rates of change in stresses has a root peculiarity.

The criterion for ductile fracture (advance of line of discontinuity) was formulated based on the approaches, accepted in the Novozhilov criterion of brittle fracture. In this case it was taken into account that with the ductile fracture we deal

with the occurrence of a localized flow, in which the development of line of discontinuity will be determined by average rates of change in stresses in the vicinity of a singular point. The orientation of the line of discontinuity of the rates of displacements and the fields of rates of change in stresses and displacements were defined. The dependence of the length of the line of localization on subcritical stresses is obtained from the limitation of the angle of fracture of the trajectory of load. It was established that the line of localization in the initial state can have dimension comparable with size of the grain. It was shown that localization in the form of the slip line of finite length precedes the localization at the point.

**Keywords:** theory of plasticity, micromechanics, shear bands, theory of microdeformations, bifurcation, polycrystal, critical load.

### References

- Kadashevich, Yu. I., Chernyakov, Yu. A. (1992). Theory of plasticity, taking into account micro stresses. *Advances in Mechanics*, 15 (3-4), 3–39.
- Hill, R. (1962). Acceleration waves in solids. *Journal of the Mechanics and Physics of Solids*, 10 (1), 1–16. doi: 10.1016/0022-5096(62)90024-8
- Rice, J. R. (1976). The localization of plastic deformation. *Theoretical and Applied Mechanics*, 1, 207–220.
- Hill, R., Hutchinson, J. W. (1975). Bifurcation phenomena in the plane tension test. *Journal of the Mechanics and Physics of Solids*, 23 (4-5), 239–264. doi: 10.1016/0022-5096(75)90027-7
- Needleman, A., Rice, J. R. (1978). Limits to Ductility Set by Plastic Flow Localization. *Mechanics of Sheet Metal Forming*, 237–267. doi: 10.1007/978-1-4613-2880-3\_10
- Anand, L., Spitzig, W. A. (1980). Initiation of localized shear bands in plane strain. *Journal of the Mechanics and Physics of Solids*, 28 (2), 113–128. doi: 10.1016/0022-5096(80)90017-4
- Chernyavskii, Y. E., Chernyakov, Y. A. (1984). Localization of plastic strains in an incompressible strain-hardening medium. *Soviet Applied Mechanics*, 20 (12), 1161–1164. doi: 10.1007/bf00888970
- Hill, R. (1967). The essential structure of constitutive laws for metal composites and polycrystals. *Journal of the Mechanics and Physics of Solids*, 15 (2), 79–95. doi: 10.1016/0022-5096(67)90018-x
- Hutchinson, J. W. (1970). Elastic-plastic behaviour of polycrystalline metals and composites. *Proc. R. Soc. London*, 319, 247–272.
- Needleman, A., Tvergaard, V. (1992). Analyses of Plastic Flow Localization in Metals. *Applied Mechanics Reviews*, 45 (3S), S3. doi: 10.1115/1.3121390
- Bigoni, D., Capuani, D. (2002). Green's function for incremental nonlinear elasticity: shear bands and boundary integral formulation. *Journal of the Mechanics and Physics of Solids*, 50 (3), 471–500. doi: 10.1016/s0022-5096(01)00090-4
- Radi, E., Bigoni, D., Capuani, D. (2002). Effects of pre-stress on crack-tip fields in elastic, incompressible solids. *International Journal of Solids and Structures*, 39 (15), 3971–3996. doi: 10.1016/s0020-7683(02)00252-4
- Bigoni, D., Dal Corso, F. (2008). The unrestrainable growth of a shear band in a prestressed material. *Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences*, 464 (2097), 2365–2390. doi: 10.1098/rspa.2008.0029
- Novozhilov, V. V. (1969). O neobkhdimom i dostatochnom kriterii khрупkoy prochnosti. *Prikladnaya matematika i mekhanika*, 33 (2), 212–222.
- Novozhilov, V. V. (1969). K osnovam ravnovesnykh uprugikh treshchin v uprugikh telakh. *PMM*, 33 (5), 797–812.
- Bordignon, N., Piccolroaz, A., Corso, F. D., Bigoni, D. (2015). Strain localization and shear band propagation in ductile materials. *Frontiers in Materials*.
- Argani, L., Bigoni, D., Mishuris, G. (2013). Dislocations and inclusions in prestressed metals. *Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences*, 469 (2154), 20120752–20120752. doi: 10.1098/rspa.2012.0752
- Jia, N., Eisenlohr, P., Roters, F., Raabe, D., Zhao, X. (2012). Orientation dependence of shear banding in face-centered-cubic single crystals. *Acta Materialia*, 60 (8), 3415–3434. doi: 10.1016/j.actamat.2012.03.005
- Arriaga, M., McAuliffe, C., Waisman, H. (2015). Onset of shear band localization by a local generalized eigenvalue analysis. *Computer Methods in Applied Mechanics and Engineering*, 289, 179–208. doi: 10.1016/j.cma.2015.02.010
- Tvergaard, V. (2014). Bifurcation into a localized mode from non-uniform periodic deformations around a periodic pattern of voids. *Journal of the Mechanics and Physics of Solids*, 69, 112–122. doi: 10.1016/j.jmps.2014.05.002
- Chernyakov, Y. A., Polishchuk, A. S., Shneider, V. P. (2011). On extension of the phenomenological approach in the theory of plasticity. *Journal of Engineering Mathematics*, 78 (1), 55–66. doi: 10.1007/s10665-011-9470-8

---

### MODELLING A THROTTLING DEVICE DURING SEPARATION OF MOISTURE FROM GAS FLOW (p. 23-29)

Georgiy Kulinchenko, Petro Leontiev

The need to design a model of a throttling device, which is used in the process of low temperature separation (LTS) of moisture from the gas flow, is predetermined by the necessity to coordinate the modes of functioning of the throttle with the modes of the heat exchanger and the separator that are included in the installation of separation. Proceeding from the task of efficient management of the process of the LTS of moisture from the gas flow, we analyzed a channel of control of the flow of gas under throttling. The peculiarity of managing the process of separation of moisture is in the contradiction between the productivity of the gas flow and the conditions of moisture removal. In order to study the influence of parameters of a throttle on the formation of the modes of passing flow, a distribution of the field of the flow velocities is obtained in the software environment of ANSYS Workbench. Visualization of the flow stream allows analyzing the level of turbulence of the flow under throttling and forecasting the trajectory of moisture droplets formed at throttling. By comparing the data obtained from the experimental installation with the data of numerical calculations, carried out in accordance with well-known mathematical models of the flow under throttling, we conducted the assessment of the adequacy of the description of the object of control. It is shown that the assumption of incompressibility of natural gas when evaluating the rate leads to significant errors. As a result of the identification of the parameters of a throttling device, its simulation was implemented in the



environment of MatLab Simulink. Block construction of the model allows performing simulation under conditions of arbitrary nature of the change in the parameters of the process over time. The assessment of the adequacy of simulating a throttle device allows using the studied model for constructing a model of an installation of moisture separation from gas flow.

**Keywords:** subcritical flow mode, supercritical flow mode, throttle valve, pipeline hydraulic resistance, dew point temperature.

### References

1. Sefko, S., Edin, B. (2015). Analysis of Droplet Deposition in a Vertical Air-water Dispersed Flow. *Procedia Engineering*, 100, 105–114. doi: 10.1016/j.proeng.2015.01.348
2. Willis, A., Peixinho, J., Kerswell, R., Mullin, T. (2008). Experimental and theoretical progress in pipe flow transition. *Philosophical Transactions of the Royal Society A: Mathematical, Physical and Engineering Sciences*, 366 (1876), 2671–2684. doi: 10.1098/rsta.2008.0063
3. Roy, P. S., Amin, M. R. (2012). Aspen-HYSYS Simulation of Natural Gas Processing Plant. *Journal of Chemical Engineering*, 26 (1). doi: 10.3329/jce.v26i1.10186
4. Dolganov, I. M., Pisarev, M. O., Ivashkina, E. N., Dolganova I. O. (2015). Modeling of liquid separators work in gas and gas condensate preparation unit in low-temperature separation technology. *Petroleum & Coal*, 57 (4), 328–335.
5. Yaoxi, D., Jiayi, Y. (2015). Simulation of downhole throttling process. *IJSET – International Journal of Innovative Science, Engineering & Technology*, 2 (9), 376–379.
6. Horbiychuk, M. I., Kulyryn, N. L. (2006). Matematychna model procesu nyzkotemperaturnoy separaciy gazu. *Naukoviy visnyk Nacionalnogo Tehnichnogo Universytetu Nafty I Gazu*, 1 (13), 88–92.
7. Wendeker, M., Grabowski, L., Pietrykowski, K., Magryta, P. (2011). Flow simulation through wankel engine throttle using computational fluid dynamics. *Journal of KONES Powertrain and Transport*, 18 (1), 677–682.
8. Joseph, A., Ajiienka, J. A. (2014). A practical approach to the evaluation of subcritical multiphase flow through down-hole safety valves (storm chokes). *Journal of Petroleum and Gas Engineering*, 5 (5), 57–69. doi: 10.8997/jpge2014.0203
9. Efremova, K. D. (2013). Sravnitel'nay ocenka effektivnosti droselnogo regulirovaniy pnevmoprivodov. *Inzhenernyy zhurnal: nauka i innovacii*, 4, 1–12.
10. Stenmark, E. (2013). On Multiphase Flow Models in ANSYS CFD Software. Department of Applied Mechanics Division of Fluid Dynamics. Chalmers university of technology. Goteborg, Sweden, 75.
11. Sodiki, J. I., Adigio, E. M. (2014). A Review On The Development And Application Of Methods For Estimating Head Loss Components In Water Distribution Pipework. *American Journal of Engineering Research (AJER)*, 3 (9), 91–96.
12. Kulichenko, G. V., Pavlov, A. V., Leontiev, P. V. (2015). Formuvanniy pidhodu do syntezu reguliytora procesu nyzkotemperaturnoy separaciy pryrodnogo gazu. *Visnyk Vinnyckogo politehnicnogo*, 6, 9–17.
13. Lawrence, M. G. (2005). The Relationship between Relative Humidity and the Dewpoint Temperature in Moist Air: A Simple Conversion and Applications. *Bulletin of the American Meteorological Society*, 86 (2), 225–233. doi: 10.1175/bams-86-2-225

## DEVELOPMENT OF GAS DYNAMIC LINEAR SYSTEMS FOR SETTING LOW PRESSURES (p. 30-36)

Ihor Dilay, Zenoviy Teplukh, Roman Brylyns'kyy, Ivan-Roman Kubara

The results of research into the schemes of serial connection of capillaries – pressure dividers, both two- and multi-capillary, were presented, with a linear dependency of change in inter-throttle pressures on supply pressure. Based on the analysis of the results, the schemes for multi-range pressure setting devices are built – a cascade connection of dividers and with binary ramification of pressure dividers.

For each of these schemes, the corresponding setting of dimensions of passable capillary channels can set such pressure drops in capillaries, at which the division pressure coefficients will vary by several orders of magnitude and remain constant. The designed schemes provide one direction and proportionality of all inter-throttle pressures (drops) of a scheme when changing the input supply pressure, but the scheme with binary branches of dividers enables setting the drops of pressures at the level of pascal particles.

The built four-decade device for setting the drops of pressures was explored by the obtained mathematical models under the action of impact factors (change in supply pressures of the setting device, temperature of throttled gas) on the coefficients of division. It was found that the influence of pressure changes in the designed scheme is practically absent while the temperature change of the gas flow by  $\pm 5$  K does not exceed 0,2 %.

Application of the tools of pressure reproduction, based on the designed schemes, opens up the prospect of building high precision devices for one-stage preparation of complex gas mixtures with micro-concentrations of components, the devices for setting low and micro-rates of gases, as well as for testing the tools for measuring pressures.

**Keywords:** pressure reproduction, capillary, combiner and divider of flows, linear divider of pressures.

### References

1. The 8th international Gas Analysis Symposium & Exhibition WTC Rotterdam, the Netherlands (2015). GAS 2015. Available at <http://www.gas2015.org/publicaties/4349>
2. Demichelis, A., Sassi, G., Sassi, M. P. (2012). Metrological performances of mass flow controllers for dynamic gas dilution. 20th IMEKO World Congress 2012. Busan, Republic of Korea, 1, 1014–1017
3. Hachevich, E. A. (2000). Kontrol' kachestva prirodnykh gazov xromatograficheskim metodom. Sankt-Peterburg: B.i., 218.
4. Nelson, G. O. (1992). Gas mixtures: preparation and control. Lewis Publishers, 294.
5. Dilay, I., Teplyukh, Z. (2014). Development of throttle selector of significantly different pressures for gas-dynamic tools. *Eastern-European Journal of Enterprise Technologies*, 6/7 (72), 28–33. doi: 10.15587/1729-4061.2014.31390
6. Teplukh, Z. N., Dilay, I. V. (2012). Zadatchik rashoda gazanositel'ya v hromatografe. *Datchiki i sistemy*, 2, 41–44.
7. Kucheruk, V. Ju., Dudatijev, I. A. (2011). Systema avtomatichnogo keruvannja koteljnoju ustanovkoju z kontrol'em skladu dymovykh ghaziv na osnovi optyko-absorbciynogo infrachervonogo metodu. *Naukovi praci VNTU*, 3, 1–7. Available at: [http://www.nbu.gov.ua/e-journals/VNTU/2011\\_3/2011-3.htm](http://www.nbu.gov.ua/e-journals/VNTU/2011_3/2011-3.htm)

8. Ivasenko, V. M., Prymysjkyj, V. P. (2014). Metody i pry-lady kontrolju vykydiv avtozapravnykh stancij. *Visnyk NTU «KhPI»*, 60 (1102), 174–180.
9. Bondarenko, V. L., Losyakov, N. P., Simonenko, Yu. M., D'yachenko, O. V., D'yachenko, T. V. (2012). Metody prigo-tovleniya smesej na osnove inertnyx gazov. *Vestnik MGTU im. N.E. Bauman. Ser. "Mashinostroenie"*, 8, 41–53.
10. Dantas, H. V., Barbosa, M. F., Moreira, P. N. T., Gal-vaio, R. K. H., Araujo, M. C. U. (2015). An automatic system for accurate preparation of gas mixtures. *Microchemical Journal*, 119, 123–127. doi: 10.1016/j.microc.2014.11.011
11. Vitenberg, A. G., Dobryakov, Y. G., Gromysh, E. M. (2010). Preparation of stable gas mixtures with microconcentrations of volatile substances in vapor-phase sources at elevated pres-sures. *Journal of Analytical Chemistry*, 65 (12), 1284–1290. doi: 10.1134/s1061934810120142
12. Brewer, P. J., Minarro, M. D., di Meane, E. A., Brown, R. J. C. (2014). A high accuracy dilution system for generating low concentration reference standards of reactive gases. *Measurement*, 47, 607–612. doi: 10.1016/j.measurement.2013.09.045
13. Helwig, N., Schuler, M., Bur, C., Schutze, A., Sauerwald, T. (2014). Gas mixing apparatus for automated gas sensor char-acterization. *Measurement Science and Technology*, 25 (5), 055903. doi: 10.1088/0957-0233/25/5/055903
14. Moshkovska, L., Prymyskyi, V., Nikolaiev, I. (2010). Metrolo-hichne zabezpechennia hazoanalitichnykh vymiriuvan. *Standartyzatsiia, sertyfikatsiia, yakist*, 2, 34–38.
15. Vins, V., Hosek, J., Hykl, J., Hruby, J. (2015). An apparatus with a horizontal capillary tube intended for measurement of the surface tension of supercooled liquids. *EPJ Web of Conferences*, 92, 02108. doi: 10.1051/epjconf/20159202108
16. Dilay, I., Teplukh, Z., Vashkurak, Y. (2014). Basic throttling schemes of gas mixture synthesis systems. *Eastern-Euro-pean Journal of Enterprise Technologies*, 4/8 (70), 39–45. doi: 10.15587/1729-4061.2014.26257
17. Stablyzator absolyutnogo davleniya SAD-307. Available at: [http://www.oavt.ru/uploads/catalog/62\\_file.pdf](http://www.oavt.ru/uploads/catalog/62_file.pdf)
18. Prohorov, V. A. (1984). *Osnovy avtomatizacii analiticheskogo kontrolja himicheskikh proizvodstv*. Moscow: Himija, 320.

---

**FORMATION OF A RATIONAL CHANGE IN CONTROLLING CONTINUOUSLY VARIABLE TRANSMISSION AT THE STAGES OF A TRACTOR'S ACCELERATION AND BRAKING (p. 37-44)**

**Vadim Samorodov, Andrey Kozhushko, Eugene Pelipenko**

We formalized the criteria for evaluation of indicators of a wheeled tractor with continuously variable hydrovolumetric-mechanical transmission from the point of view of loading a hydraulic branch of hydrovolumetric transmission in direct and reverse power flows. The given description of the criteria is used for the formation of change in parameters of adjustment of hydraulic machines (hydraulic pump and hydraulic engine) in the process of acceleration and braking of a wheeled tractor.

We formed a rational change in parameters of adjustment of a hydraulic machine at the stages of acceleration and braking for a wheeled tractor with continuously variable hydrovolumetric-mechanical transmission that is made by the scheme of the differential at the output. In the study of the obtained dependency of parameters of adjustment of hydraulic machines, we determined the change of such indicators as the time of acceleration and braking; braking distance of a wheeled tractor; coefficient of performance of hydrovolumetric drive and hydrovolumetric-

mechanical transmissions; the difference of working pressure in hydrovolumetric drive. It was found that when applying the rational change in the parameters of adjustment of hydraulic machines instead of the linear one at the stages of acceleration and braking, the zone of the highest value of the coefficient of performance of hydrovolumetric-mechanical transmission narrows, which, in turn, points to the loading of the hydraulic branch of a hydrovolumetric transmission.

**Keywords:** hydrovolumetric-mechanical transmission, rational change in parameters, hydraulic branch of transmis-sion, coefficient of performance, evaluation criteria.

**References**

1. Sheltsin, N., Frumkin, L., Ivanov, I. (2011). Sovremenie bestupenchatie transmisii selkohozyaistvenih traktorov. *Traktori i selhozmashini*, 11, 18–26.
2. Beunk, H., Wilmer, H. (2002). *So Arbeiten «Auto Powr» und «Eccom»*. Profi, 5.
3. Renius, K. T., Resch, R. (2005). *Continuously Variable Tractor Transmissions*. ASAE – The Society for Engineering in Agricultural, Food, and Biological, Systems. Louisville, Kentucky, 35.
4. Rydberg, K. (2010). *Hydro-mechanical Transmissions*. *Fluid and Mechatronic Systems*, 2, 51–60.
5. Samorodov, V. B., Bondarenko, A. I., Kozhushko, A. P., Pelipenko, E. S., Mittsel, M. O. (2014). Perspektivni transmisii kolisnykh traktoriv. *Visnyk Natsionalnoho tekhnichnoho universytetu «KhPI»*, 10 (1053), 3–10.
6. Samorodov, V., Pelipenko, E. (2016). Analysis of the devel-opment modern transmission wheeled tractors. *International Collection of scientific proceedings*, 6 (13), 49–57.
7. Popa, Gh., Dumitru, I. (2005). Theoretical studies regarding the tractive efforts for vehicles using the hydrostatic transmis-sions. *Scientific Bulletin Series C: Fascicle Mechanics, Tribology, Machine Manufacturing Technology*.
8. Huhtala, K. (2010). Chengyan sun hydrostatic-mechanical power split CVT. *Mechanical and Materials engineering on 8th of September 2010*, 67.
9. Pusha, A., Deldar, M., Izadian, A. (2013). Efficiency analy-sis of hydraulic wind power transfer system. *IEEE Inter-national Conference on Electro-Information Technology, EIT 2013*, 1–7. doi: 10.1109/eit.2013.6632717
10. Ijas, M., Makinen, E. (2008). Improvement of total efficiency of hydrostatic transmission by using optimized control. *Proceedings of the JFPS International Symposium on Fluid Power, 2008 (7-2)*, 271–276. doi: 10.5739/isfp.2008.271
11. Coombs, D. (2012). Hydraulic efficiency of a hydrostatic transmission with variable displacement pump and motor. *Mechanical and aerospace engineering*, 82.
12. Dasgupta, K., Kumar, N., Kumar, R. (2013). Steady state performance analysis of hydrostatic transmission system us-ing two motor simulation drive. *Journal of The Institution of Engineers (India): Series C*, 94 (4), 357–363. doi: 10.1007/s40032-013-0084-y
13. Samorodov, V. B. (2001). Vyivod obshego zakona upravleniya gidroob'emno-mekhanicheskikh transmissiy transportnykh mashin v protsesse pryamolineynogo razgona i sposob ego tehniceskoy realizatsii. *Integrirovannyye tehnologii i energosberezhenie*, 4, 112–120.
14. Kozhushko, A. P. (2014). Vyznachennia optimalnoho zakonu zminy parametriv rehuliuвання hidromashyn hidroob'emnoi peredachi v protsesi rozghonu kolisnykh traktoriv z hidroob'emno-mekhanichnoi transmissiieiu. *Visnyk Sums-koho natsionalnoho ahrarynoho universytetu*, 11 (26), 108–114.

15. Bondarenko, A. I. (2015). Optymyzatsiya upravleniya besstupenchatoi hidroob'iemno-mekhanichnoiu transmissi-ieiu kolesnykh traktorov pri ekstremom tormozheny. *Science in the modern information society*, 1, 135–141.
16. Bondarenko, A. I. (2015). Osoblyvosti systemy keruvannia protsesom halmuvannia samokhidnykh mashyn z hidroob'iemno-mekhanichnymy transmissiiami. *Prylodobuvannia: stani perspektyvy*, 27–28.
17. Kozhushko, A. P. (2015). Osoblyvosti roboty kolisnykh traktoriv z hidroob'iemno-mekhanichnymy transmissiiami. *Silskohospodarski mashyny*, 31, 70–82.
18. Rebrov, A. Yu., Korobka, T. A., Lahman, S. V. (2012). Matematicheskaya model dizelnogo dvigatelya v bezrazmernih velichinah s uchetom ego zagruzki i podachi topliva. *VIsnik Natsionalnogo tehnichnogo unIversitetu «KhPI»*, 19, 31–36.
19. Anosov, V. I., Samorodov, V. B., Rebrov, A. Yu., Pelipenko, E. S. (2014). Nauchnoe obosnovanie rezhimov ekspress-proverki tormoznoy sistemyi kolesnykh traktorov AO "HTZ". *VIsnik Natsionalnogo tehnichnogo unIversitetu «KhPI»*, 8, 3–13.
20. Metlyuk, N. F., Avtushko, V. P. (1980). *Dinamika pnevmaticheskikh i gidravlicheskh privodov avtomobilya*. Moscow: Mashinostroenie, 231.
21. Pettersson, K. (2013). Design Automation of Complex Hydromechanical Transmissions. Division of Fluid and Mechatronic Systems Department of Management and Engineering Linköping University. Linköping, Sweden, 85.

---

#### REDUNDANT INFORMATION PROCESSING TECHNIQUES COMPARISON FOR DIFFERENTIAL VIBRATORY GYROSCOPE (p. 45-52)

Valerii Chikovani, Olha Sushchenko, Hanna Tsiruk

Advantages of differential Coriolis vibratory gyroscope of the new type with two measuring channels of angle rate with opposite signs that provides redundant measuring information about angle rate are analyzed. Comparative analysis of four different techniques of redundant signals processing including technology of "virtual" gyro signals processing in application to the differential vibratory gyroscope is carried out.

Importance of creation of redundant information processing techniques is caused by distinction of the differential vibratory gyroscope from other micro-electro-mechanical gyros, for example, tuning fork gyro, in that it has two output signals, which come from the single resonator and correspond to angle rates with opposite signs.

As a result redundant output information processing techniques were obtained. This information comes from the differential vibratory gyroscope output and is formed by subtracting of two measuring channel signals. The algorithm of "virtual" gyro redundant output information processing was modified. The algorithm differs from known ones by calculation of inter-channel correlation matrix in on-line manner. This leads to decrease of angle rate measuring random error and to decrease overshoot in conditions of abrupt change of angle rate.

The obtained results are important and useful for application of differential vibratory gyroscopes in stabilization systems and angular motion control. This is caused by high requirements to accuracy and ability to function in hash environment.

**Keywords:** differential vibratory gyro, "virtual" gyro technology, bias, correlation matrix.

#### References

1. Chikovani, V. V. (2014). Trends of Ukrainian All Digital Coriolis Vibratory Gyroscopes Development. Institute of

- Electrical & Electronics Engineers (IEEE). Kyiv, 25–28. doi: 10.1109/msnmc.2014.6979720
2. Wang, W., Lv, X., Sun, F. (2013). Design of a novel MEMS gyroscope array. *Sensors*, 13 (2), 1651–1663. doi: 10.3390/s130201651
3. Xue, L., Wang, L., Xiong, T., Jiang, C., Yuan, W. (2014). Analysis of Dynamic Performance of a Kalman Filter for Combining Multiple MEMS Gyroscopes. *Micromachines*, 5 (4), 1034–1050. doi: 10.3390/mi5041034
4. Ting, T. O., Man, K. L., Lei, C.-U., Lu, C. (2014). State-of-Charge for Battery Management System via Kalman Filter. *Engineering Letters*, 22 (2), 75–82.
5. Chaudhuri, S. S., Konar, A. (2007). Vision Based Target-Tracking Realized with Mobile Robots using Extended Kalman Filter. *Engineering Letters*, 14 (1), 176–184.
6. Jiang, C., Xue, L., Chang, H., Yuan, G., Yuan, W. (2012). Signal Processing of MEMS Gyroscope Arrays to Improve Accuracy Using a 1st Order Markov for Rate Signal Modeling. *Sensors*, 12 (12), 1720–1737. doi: 10.3390/s120201720
7. Liu, J., Shen, Q., Qin, W. (2015). Signal Processing Technique for Combining Numerous MEMS Gyroscopes Based on Dynamic Conditional Correlation. *Micromachines*, 6 (6), 684–689. doi: 10.3390/mi6060684
8. Ji, X. (2015). Research on Signal Processing of MEMS Gyro Array. *Mathematical Problems in Engineering*, 2015, 1–6. doi: 10.1155/2015/120954
9. Bayard, D. S., Ploen, S. R. (2015). Patent No. US 10/383,475. High Accuracy Inertial Sensors from Inexpensive Components. No. 6882964 B2, declared: 06.03.2003; published: 19.04.2015.
10. Chikovani, V. V., Umakhanov, T. O., Marusyk, P. I. (2008). The Compensated Differential CVG. In *Proceedings of Symposium Gyro Technology*. University of Karlsruhe, Germany, 3.1–3.8.
11. Chikovani, V. V. (2013). Patent No. 95709. MPK. G01C 19/02. Metod vimiryuvannya kutovoi shvidkosti Koriolosovim vibratsiynim giroskopom. No. a201001344, declared: 25.08.2011; published: 26.06.2013, Buyl. № 16.
12. Chikovani, V. V., Tsiruk, H. V. (2015). Differential Mode of Operation For Multimode Vibratory Gyroscope. Institute of Electrical & Electronics Engineers (IEEE). Kyiv, 87–90. doi: 10.1109/apuavd.2015.7346568
13. Trusov, A. A., Rozelle, D. M., Atikyan, G., Zotov, S. A., Simon, B. R., Shkel, A. M., Meyer, A. D. (2014). Non-Axisymmetric Coriolis Vibratory Gyroscope With Whole Angle, Force Rebalance, and Self-Calibration. *Solid-State Sensors, Actuators and Microsystems. Workshop Hilton Head Island, South Carolina*, 419–422.
14. Gregory, J., Cho, J., Najafi, K. (2012). Characterization and Control of a High-Q MEMS Inertial Sensor Using Low-Cost Hardware. Institute of Electrical & Electronics Engineers (IEEE). Myrtle Beach, S.C., 239–247. doi: 10.1109/plans.2012.6236886
15. Chikovani, V. V., Suschenko, O. A. (2014). Differential mode of operation for ring-like resonator CVG. Institute of Electrical & Electronics Engineers (IEEE). Kyiv, 451–455. doi: 10.1109/elnano.2014.6873426
16. Lynch, D. D. (1998). Coriolis Vibratory Gyros. In *Proceedings of Symposium Gyro Technology*. University of Karlsruhe, Germany, 1.1–1.14.
17. Lynch, D. D. (1995). Vibratory gyro analysis by the method of averaging. *Gyroscopic Technology and Navigation*. Scientific Council of the Russian Academy of Sciences on the Traffic Control and Navigation Problems. Sankt-Peterburg, 26–34.