DEVELOPMENT OF A METHOD FOR APPROXIMATE SOLUTION OF NONLINEAR ORDINARY DIFFERENTIAL EQUATIONS USING PENDULUM MOTION AS AN EXAMPLE (p. 4-11)

Olexander Brunetkin
Odessa National Polytechnic University, Odessa, Ukraine
ORCID: http://orcid.org/0000-0002-6701-8737

Maksym Maksymov
Odessa National Polytechnic University, Odessa, Ukraine
ORCID: http://orcid.org/0000-0002-7536-2570

Oksana Maksymova
Odessa National Academy of Food Technologies, Odessa, Ukraine
ORCID: http://orcid.org/0000-0003-3986-0991

Anton Zosymchuk
Odessa National Polytechnic University, Odessa, Ukraine
ORCID: http://orcid.org/0000-0002-3604-3948

A method of deletion of dimensions for a mathematical model which gives the number of variables less than that prescribed by the π-theorem was proposed. In a number of cases, it is possible to exclude from consideration all similarity criteria or, in other words, achieve self-similarity in them. In the framework of deletion of dimensions, this is expressed in a transition from criteria to similarity numbers. Thus, information is reduced without its loss.

The limit reduction of the number of variables in the mathematical model makes it possible to use analytical approximation dependences as approximate solutions. Such dependences are obtained from the initial solutions by using the coefficients of stretch, which corresponds to the group methods for solving equations. It was proposed to use solutions of the linearized forms of the original nonlinear equations as initial solutions. Such approach makes it possible to take into account physical character of the change in the studied quantities in the approximation dependences when solution of nonlinear equations cannot be realized using standard functions.

Efficiency of the method was illustrated by the example of study of the pendulum motion, which is a counterpart of inertial link of the second order in the theory of automatic control. Solutions were obtained for the cases of presence and absence of environmental resistance. The last variant is interesting by the feasibility of comparing the proposed and available analytical solutions in terms of elliptic integrals.

Keywords: deletion of dimensions of a mathematical model, group methods of solution, second order inertial link.

References

1. Brunetkin, A. I., Maksymov, M. V. (2015). Method for determining the composition of combustion gases when burned. Scientific Journal Natsionalnho Mining University, 5, 83–90.
2. Maksymov, M. V., Brunetkin, A. I., Bondarenko, A. V. (2013). Model and method for determining conditional formula hydrocarbon fuel combustion. Eastern-European Journal of Enterprise Technologies, 6 (8 (66)), 20–27. Available at: http://journals.uran.ua/eejet/article/view/18702/17074
3. Atherton, M. A., Bates, R. A., Wynn, H. P. (2014). Dimensional Analysis Using Toric Ideals: Primitive Invariants. PLoS ONE, 9 (12), e112827. doi: 10.1371/journal.pone.0112827
4. Sonin, A. A. (2004). A generalization of the -theorem and dimensional analysis. Proceedings of the National Academy of Sciences, 101 (23), 8525–8526. doi: 10.1073/pnas.0402931101
5. Klayn, S. Dzh.; Alad'ev, I. T., Voskresenskiy, K. D. (Eds.) (1968). Podobie: priblizhennye metody [Similarity: approximate methods]. Moscow: Mir, 302.
6. Oliveri, F. (2010). Lie Symmetries of Differential Equations: Classical Results and Recent Contributions. Symmetry, 2 (2), 658–706. doi: 10.3390/sym2020658
7. Chhay, M., Hamdouni, A. (2010). Lie Symmetry Preservation by Finite Difference Schemes for the Burgers Equation. Symmetry, 2 (2), 868–883. doi: 10.3390/sym2020868
8. Gazizov, R. K., Ibragimov, N. H., Lukashchuk, V. O. (2010). Integration of ordinary differential equation with a small parameter via approximate symmetries: Reduction of approximate symmetry algebra to a canonical form. Lobachevskii Journal of Mathematics, 31 (2), 141–151. doi: 10.1134/s1995080210020058
9. Starrett, J. (2007). Solving Differential Equations by Symmetry Groups. Mathematical Association of America, 114 (9), 778–792.
10. Lehenky, V. I. (2008). On the bundle of algebraic equations. Symmetries of differential equations, 121–131.
11. Brennan, S., Alleyne, A. (2005). Dimensionless robust control with application to vehicles. IEEE Transactions on Control Systems Technology, 13 (4), 624–630. doi: 10.1109/tcst.2004.841669
12. Lyogenky, V. I., Yakovenko, G. N. (2009). Dimensionless variables: group-theoretical approach. Symmetries of differential equations, 132–134.
13. Seshadri, R., Na, T. Y. (1985). Group Invariance in Engineering Boundary Value Problems. Springer-Verlag, New York Inc., 224. doi: 10.1007/978-1-4612-5102-6
14. Gukhman, A. A. (1973). Introduction to the theory of similarity. Moscow: Higher School, 296.
15. Patankar, S. (1984). Numerical heat transfer and fluid flow. Moscow: Energoatomizdat, 124.
16. Brunetkin, A. I. (2014). Integrated approach to solving the fluid dynamics and heat transfer problems. Odeskyi Politechnichnyi Universytet. Pratsi, 2, 108–115. doi: 10.15276/opu.2.44.2014.21

DEVELOPMENT OF MAXIMUM CLIQUE DEFINITION METHOD IN A NONORIENTED GRAPH (p. 12-17)

Sergey Listrovoy
Ukrainian State University of Railway Transport, Kharkiv, Ukraine
ORCID: http://orcid.org/0000-0002-3313-4035

Volodymyr Butenko
Ukrainian State University of Railway Transport, Kharkiv, Ukraine
ORCID: http://orcid.org/0000-0001-9958-3960

Volodymyr Bryksin
Ukrainian State University of
Railway Transport, Kharkiv, Ukraine
ORCID: http://orcid.org/0000-0002-8036-8811

Oleksandra Golovko
Ukrainian State University of
Railway Transport, Kharkiv, Ukraine
ORCID: http://orcid.org/0000-0002-9880-428X

The paper recommends the MCP solution method with small time complexity $O(2n^3\log_2 n)$, that allows from one viewpoint solving such problems as definition of the maximum independent sets and minimum vertex covers in graphs, as well as isomorphism of graphs and isomorphic embedding, as far as all those problems may be converted within polynomial time into MCP. This set of problems is formal models of a wide range of management problems in rail transport information systems, and the solution thereof requires the algorithms for their realization with small time complexity. Therefore, the time complexity decrease is an actual task. In the paper, admissibility of decreasing the time complexity of the suggested procedure A for solving MCP is based on using the subsidiary procedure B for defining the estimates of the largest graph clique values, and on its basis the method of the problem solution is described in the paper as procedure A. Procedure A allows forming the cliques on the base of each vertex of graph i. As the process of clique formation on the base of each vertex may be independent, then procedure A may be effectively vectorized. It makes possible in case of using processing cells for solving the MCP to decrease the time complexity of its operation to $O(2n^2\log_2 n)$, and the mentioned complex of the problems will be solved in a real-time scale.

Keywords: cliques in non-oriented arbitrary graph, parallel computing methods.

References

1. Butenko, V. M. (2008). Yakist informatsiyno-vymiriuvalnykh system na zaliznychnomu transporti Ukrainy. Zb. naukov. prats. UkrDAZT, 99, 151–155.

2. Boynik, A. B., Zagariy, G. I., Koshevoy, S. V. et. al. (2008). Diagnostirovanie ustroystv zheleznodorozhnoy avtomatiki i agregatov podvizhnyh edinic. Kharkiv: ChP Izdatel'stvo "Novoe slovo", 304.

3. Listrovyi, S. V., Panchenko, S. V., Moiseienko, V. I., Butenko, V. M. (2017). Matematychne modeliuvannia v rozpodilenykh informatsiino-keruiuchykh systemakh zaliznychnoho transportu. Kharkiv: FOP Brovin O. V., 220.

4. Listrovoy, S. V., Minuhin, S. V., Listrovaya, E. S. (2015). Monitoring distributed computing systems on the basis of the determined shortest paths and shortest hamiltonian cycles in a graph. Eastern-European Journal of Enterprise Technologies, 6 (4 (78)), 32–45. doi: 10.15587/1729-4061.2015.56247

5. San Segundo, P., Lopez, A., Pardalos, P. M. (2016). A new exact maximum clique algorithm for large and massive sparse graphs. Computers & Operations Research, 66, 81–94. doi: 10.1016/j.cor.2015.07.013

6. El Mouelhi, A., Jégou, P., Terrioux, C., Zanuttini, B. (2013). Some New Tractable Classes of CSPs and Their Relations with Backtracking Algorithms. Lecture Notes in Computer Science, 61–76. doi: 10.1007/978-3-642-38171-3_5

7. Zhang, S., Wang, J., Wu, Q., Zhan, J. (2014). A fast genetic algorithm for solving the maximum clique problem. 2014 10th International Conference on Natural Computation (ICNC). doi: 10.1109/icnc.2014.6975933

8. San Segundo, P., Matia, F., Rodriguez-Losada, D., Hernando, M. (2011). An improved bit parallel exact maximum clique algorithm. Optimization Letters, 7 (3), 467–479. doi: 10.1007/s11590-011-0431-y

9. Bykova, V. (2012). The Clique Minimal Separator Decomposition of a Hypergraph. J. of Siberian Federal University. Mathematics Physics, 5 (1), 36–45.

10. Bykova, V., Illarionov, R. (2014). On CLIQUE Problem for Sparse Graphs of Large Dimension. Information Technologies and Mathematical Modelling, 69–75. doi: 10.1007/978-3-319-13671-4_9

11. Minukhin, S. (2012). Efficient method for single machine total tardiness problem. 2012 IV International Conference "Problems of Cybernetics and Informatics" (PCI). doi: 10.1109/icpci.2012.6486283

12. Buchanan, A., Walteros, J. L., Butenko, S., Pardalos, P. M. (2014). Solving maximum clique in sparse graphs: An O(nm+n2d/4) algorithm for d-degenerate graphs. Optimization Letters, 8 (5), 1611–1617. doi: 10.1007/s11590-013-0698-2

13. Veremyev, A., Prokopyev, O. A., Butenko, S., Pasiliao, E. L. (2015). Exact MIP-based approaches for finding maximum quasi-cliques and dense subgraphs. Computational Optimization and Applications, 64 (1), 177–214. doi: 10.1007/s10589-015-9804-y

14. Listrovoy, S. V., Tretiak, V. F., Listrovaya, A. S. (1999). Parallel algorithms of calculation process optimization for the Boolean programming problems. Engineering Simulation, 16, 569–579.

INFORMATIONEXTREME MACHINE LEARNING OF THE CONTROL SYSTEM OVER THE POWER UNIT OF A THERMAL POWER MAIN LINE (p. 17-24)

Anatoliy Dovbysh
Sumy State University, Sumy, Ukraine
ORCID: http://orcid.org/0000-0003-1829-3318

Dmytro Velykodnyi
Sumy State University, Sumy, Ukraine
ORCID: http://orcid.org/0000-0003-0044-5619

Igor Shelehov
Sumy State University, Sumy, Ukraine
ORCID: http://orcid.org/0000-0003-4304-7768

Myroslav Bibyk
Sumy State University, Sumy, Ukraine
ORCID: http://orcid.org/0000-0003-0431-7200

The study considers a method of deep machine learning of a decision-making support system of control of a power unit of a thermal power plant. We developed a method within the framework of information-extreme intelligent technology, it is based on maximization of informational capacity of a control system in the process of machine learning. We developed categorical models of information-extreme machine learning with optimization of control tolerances to recognition attributes and levels of selection of coordinates of averaged binary vector-realizations of recognition classes. We considered a modified Kullback information criterion as a criterion for optimization of learning parameters. We implemented algorithms of machine learning with polymodal and unimodal decisive rules. We formed a learning matrix based on archival data of the operation of Shostka thermal and power plant. The results of physical modeling showed that the use of

polymodal decisive rules does not provide a high functional efficiency of machine learning. We ordered the alphabet of recognition classes to the magnitude of deviation of a functional state of the technological process from the standard regime for the application of unimodal decisive rules. At the same time, we constructed unimodal decisive rules according to geometric parameters of hyper-spherical containers of recognition classes x by the enclosed structure. We proved experimentally that the use of the unimodal classifier gives possibility to construct decisive rules, which error-free by a learning matrix. The obtained results give possibility to provide high functional efficiency of machine learning of control systems of technological processes whose classes of recognition intersect substantially in a space of attributes.

Keywords: information-extreme intelligent technology, machine learning, decision making support system, information criterion, power unit, thermal power plant.

References

1. Eremin, E., Temchenko, D. (2009). Adaptive and robust control of objects of thermal power engineering. Blagoveshchensk: Amur state university, 228.
2. Dorf, R. C., Bishop, R. H. (2011). Modern Control Systems. Prentice Hall, 1082.
3. Han, J., Kamber, M., Pei, J. (2012). Data mining: concepts and techniques. Elsevier, 744.
4. Subbotin, S., Oleinik, An., Hoffman, E., Zaitsev, S., Oleinik, Al.; Subbotin, S. (Ed.) (2012). Intelligent Information Technologies for the Designing of Automated Systems for Diagnosing and Recognizing Images. Kharkiv: SMIT Company, 318.
5. Campbell, C., Ying, Y. (2011). Learning with Support Vector Machines. Morgan and Claypool, 95.
6. Mikulandrić, R., Lončar, D., Cvetinović, D., Spiridon, G. (2013). Improvement of existing coal fired thermal power plants performance by control systems modifications. Energy, 57, 55–65. doi: 10.1016/j.energy.2013.02.033
7. Kumar, S., Cherukuri, R. (2007). A Survey on Artificial Intelligence Techniques in Power Station. International Journal of Innovative Research in Science, Engineering and Technology, 6 (1), 852–861.
8. Mayadevi, N., Vinodchandra, S. S., Ushakumari, S. (2014). A Review on Expert System Applications in Power Plants. International Journal of Electrical and Computer Engineering (IJECE), 4 (1), 116–126. doi: 10.11591/ijece.v4i1.5025
9. Ongsakul, W., Dieu, V. N. (2013). Artificial Intelligence in Power System Optimization. CRC Press, 520.
10. De Oliveira, M. V., De Almeida, J. C. S. (2013). Application of artificial intelligence techniques in modeling and control of a nuclear power plant pressurizer system. Progress in Nuclear Energy, 63, 71–85. doi: 10.1016/j.pnucene.2012.11.005
11. Sai, T. K., Reddy, K. A. (2015). Fuzzy Applications in a Power Station. International Journal on Soft Computing, 6 (2), 01–16. doi: 10.5121/ijsc.2015.6201
12. Dovbysh, A. S. (2009). Foundation of intelligent systems designing. Sumy: Publisher SSU, 171.
13. Dovbysh, A., Bibyk, M., Rudyi, A. (2015). Optimization of the parameters of teaching the control system of the power unit of the heat power plant. Compressor and Power Engineering, 3 (41), 37–40.
14. Kutsenko, O., Kascheev, B., Mironenko, M. (2017). Geoinformation system of personnel identification at re-construction of the area. Bulletin of the NTU "KhPI". Series: System Analysis, Management and Information Technology, 28 (1250), 34–40.

Nadiia Bouraou
National Technical University of Ukraine "Igor Sikorsky Kyiv Polytechnic Institute", Kyiv, Ukraine
ORCID: http://orcid.org/0000-0001-6848-816X

Diana Pivtorak
National Technical University of Ukraine "Igor Sikorsky Kyiv Polytechnic Institute", Kyiv, Ukraine
ORCID: http://orcid.org/0000-0003-3708-5610

Sergey Rupich
National Technical University of Ukraine "Igor Sikorsky Kyiv Polytechnic Institute", Kyiv, Ukraine
ORCID: http://orcid.org/0000-0001-8237-7001

The paper deals with the efficiency study of the classifier developed based on the probabilistic neural network for multiclass diagnostics of a complex spatial object in the presence of multi-site damage. For recognition, the multidimensional diagnostic feature vector is used, the values of the features may have a deviation of ±5 % for the defect-free condition of an object, and exceed the permissible deviation in case of occurrence and development of damage. For the vector containing 5 diagnostic features, 6 classes of technical condition of an object are substantiated. Formation of sets of training and test input vectors, used for the classifier training and testing is performed. In order to evaluate the multi-class recognition efficiency, the coefficient, which is a percentage of the probability of correct classification of test vectors, is used. The analysis of the dependence of the efficiency coefficient on the characteristics of the classifier and the set of training vectors is carried out. It is found that error-free multi-class recognition of the object condition over the entire set of input vectors with different values of deviation of feature elements is provided in the range of values of the classifier parameter spread of [0,02; 0.07]. It is revealed that the greater the diagnostic feature deviation in test vectors, the greater the influence of the dimension of the set of training vectors on the multi-class recognition efficiency. The minimum size of the set of training vectors (68 vectors) and the limit value of diagnostic feature deviation in test vectors (17 %), which provide error-free multi-class recognition by the developed classifier are determined.

Keywords: multi-class recognition, neural network classifier, diagnostic feature vector, probability of correct classification.

References

1. Shanyavskiy, A. A. (2003). Bezopasnoe ustalostnoe razrushenie elementov aviakonstrukciy. Ufa, 802.
2. Goranson, U. G. (2007). Damage tolerance. Facts and fiction. Keynote Presentation in Int. Conf. on Damage Tolerance of Aircraft Structure. Delft Technical University, 58. Available at: http://dtas2007.fyper.com/userfiles/file/Paper%2011_Goranson.pdf
3. Ignatovich, S. R., Humaryan, L. A. (2013). Ocenka dostovernosti kontrolya treshchin v aviacionnyh konstrukciyah. Visnyk Ternopilskoho natsionalnoho tekhnichnoho universytetu, 72 (4), 117–124.
4. Nagarajaiah, S., Erazo, K. (2016). Structural monitoring and identification of civil infrastructure in the United States. Struc-

tural Monitoring and Maintenance, 3 (1), 51–69. doi: 10.12989/ smm.2016.3.1.051

5. Bouraou, N. I., Cybul'nik, S. A., Shevchuk, D. V. (2015). Investigation of the model of the vibration measuring channel of the complex monitoring system of steel tanks. Eastern-European Journal of Enterprise Technologies, 5 (9 (77)), 45–52. doi: 10.15587/1729-4061.2015.50980

6. Ali, Y. H., Abd Rahman, R., Raja Hamzah, R. I. (2014). Acoustic Emission Signal Analysis and Artificial Intelligence Techniques in Machine Condition Monitoring and Fault Diagnosis: A Review. Jurnal Teknologi, 69 (2). doi: 10.11113/jt.v69.3121

7. Bielza, C., Li, G., Larrañaga, P. (2011). Multi-dimensional classification with Bayesian networks. International Journal of Approximate Reasoning, 52 (6), 705–727. doi: 10.1016/ j.ijar.2011.01.007

8. Bouraou, N. I., Zazhytskyi, O. V. (2014). Rozpiznavannia tekhnichnoho stanu ob'yektiv na osnovi shtuchnykh neironnykh merezh. Kyiv: NAU, 120.

9. Hoła, J., Bień, J., Sadowski, Ł., Schabowicz, K. (2015). Non-destructive and semi-destructive diagnostics of concrete structures in assessment of their durability. Bulletin of the Polish Academy of Sciences Technical Sciences, 63 (1). doi: 10.1515/ bpasts-2015-0010

10. Balageas, D., Fritzen, C.-P., Gemes, A. (2006). Structural Health Monitoring. John Wiley & Sons, 495. doi: 10.1002/ 9780470612071

11. Dworakowski, Z., Ambrozinski, L., Packo, P., Dragan, K., Stepinski, T., Uhl, T. (2013). Application of Artificial Neural Networks for Damage Indices Classification with the Use of Lamb Waves for the Aerospace Structures. Key Engineering Materials, 588, 12–21. doi: 10.4028/www.scientific.net/kem.588.12

12. Shen, T., Wan, F., Song, B., Wu, Y. (2011). Damage location and identification of the wing structure with Probabilistic Neural Networks. 2011 Prognostics and System Health Managment Confernece. doi: 10.1109/phm.2011.5939524

13. Palomino, L. V., Steffen, V., Finzi Neto, R. M. (2014). Probabilistic Neural Network and Fuzzy Cluster Analysis Methods Applied to Impedance-Based SHM for Damage Classification. Shock and Vibration, 2014, 1–12. doi: 10.1155/2014/401942

14. Bouraou, N. I., Protasov, A. H., Myronenko, P. S., Rupich, S. S. (2015). Syntez neironnoi merezhi dlia bahatoklasovoi diahnostyky elementiv konstruktsiy v ekspluatatsiy. Metody ta prylady kontroliu yakosti, 2 (35), 83–93.

IMPROVING EFFICIENCY OF PROVIDING DATA GROUP ANONYMITY BY AUTOMATING DATA MODIFICATION QUALITY EVALUATION (p. 31-39)

Oleg Chertov
National Technical University of Ukraine
"Igor Sikorsky Kyiv Polytechnic Institute", Kyiv, Ukraine
ORCID: http://orcid.org/0000-0003-0087-1028

Dan Tavrov
National Technical University of Ukraine
"Igor Sikorsky Kyiv Polytechnic Institute", Kyiv, Ukraine
ORCID: http://orcid.org/0000-0002-3689-2931

In the work, a modification of the method for solving the task of providing data group anonymity is proposed, which implies automated solution selection without expert participation. Modification lies in identifying solutions to the task, in which outliers are detected automatically and don't match the outliers in the initial distribution of the information about the group of respondents. Thus, automating the solution selection improves data group anonymization efficiency by reducing the time necessary for their analysis for masking sensitive features of the distribution.

Testing the developed modification is done by solving the task of masking regional distribution of military personnel in the state of New York. As a result of solving the corresponding group anonymization task, 1,000 solutions were obtained. It is established that only 24 out of 1,000 solutions, or 2.4 % of the total number, are feasible, i. e. the ones in which all the outliers are masked. Automated selection of such a small number of solutions is significantly faster than the manual approach, which speaks in favor of the proposed modification for improving data group anonymization efficiency.

Keywords: memetic algorithm, group anonymity, microfile, outlier, modified Thompson tau technique.

References

1. Rafalski, E. M. (Ed.) Health Insurance Portability and Accountability Act of 1996 (HIPAA). Encyclopedia of Health Services Research. doi: 10.4135/9781412971942.n180

2. Patient Safety and Quality Improvement Act of 2005 (PSQIA) (2001). Federal Register, No. 73 (266).

3. Regulation (EU) 2016/679 of the European Parliament and of the Council of 27 April 2016: May 4, 2016 (2016). Official Journal of the European Union, L 119, 1–88.

4. Pfitzmann, A., Hansen, M. (2010). A Terminology for Talking About Privacy by Data Minimization: Anonymity, Unlinkability, Undetectability, Unobservability, Pseudonymity, and Identity Management. Version v0.34. Privacy and data security. Available at: http://dud.inf.tu-dresden.de/Anon_Terminology. shtml

5. Hawkins, D. (1980). Identification of Outliers. Springer, 198. doi: 10.1007/978-94-015-3994-4

6. Chertov, O., Tavrov, D. (2010). Group Anonymity. Information Processing and Management of Uncertainty in Knowledge-Based Systems. Applications, 592–601. doi: 10.1007/978-3-642-14058-7_61

7. Chertov, O., Tavrov, D. (2014). Microfiles as a Potential Source of Confidential Information Leakage. Studies in Computational Intelligence, 87–114. doi: 10.1007/978-3-319-08624-8_4

8. Sweeney, L. (2002). k-Anonymity: A Model for Protecting Privacy. International Journal of Uncertainty, Fuzziness and Knowledge-Based Systems, 10 (05), 557–570. doi: 10.1142/ s0218488502001648

9. Angiuli, O., Waldo, J. (2016). Statistical Tradeoffs between Generalization and Suppression in the De-identification of Large-Scale Data Sets. 2016 IEEE 40th Annual Computer Software and Applications Conference (COMPSAC). doi: 10.1109/ compsac.2016.198

10. Templ, M., Meindl, B., Kowarik, A. (2015). Statistical Disclosure Control for Micro-Data Using the R Package sdcMicro. Journal of Statistical Software, 67 (4). doi: 10.18637/jss.v067.i04

11. Machanavajjhala, A., Kifer, D., Gehrke, J., Venkitasubramaniam, M. (2007). L-Diversity: Privacy Beyond k-Anonymity. ACM Transactions on Knowledge Discovery from Data, 1 (1). doi: 10.1145/1217299.1217302

12. Domingo-Ferrer, J., Soria-Comas, J. (2015). From t-closeness to differential privacy and vice versa in data anonymization. Knowledge-Based Systems, 74, 151–158. doi: 10.1016/ j.knosys.2014.11.011

13. Salazar-González, J.-J. (2008). Statistical confidentiality: Optimization techniques to protect tables. Computers & Operations Research, 35 (5), 1638–1651. doi: 10.1016/j.cor.2006.09.007

14. Parmar, A. A., Rao, U. P., Patel, D. R. (2011). Blocking Based Approach for Classification Rule Hiding to Preserve the Privacy in Database. 2011 International Symposium on Computer Science and Society. doi: 10.1109/isccs.2011.103

15. Singh, A., Bansal, D., Sofat, S. (2014). Privacy Preserving Techniques in Social Networks Data Publishing – A Review. International Journal of Computer Applications, 87 (15), 9–14. doi: 10.5120/15282-3880

16. Chertov, O., Tavrov, D. (2016). Two-Phase Memetic Modifying Transformation for Solving the Task of Providing Group Anonymity. Studies in Fuzziness and Soft Computing, 239–253. doi: 10.1007/978-3-319-32229-2_17

17. Kleinberg, J., Tardos, E. (2005). Algorithm Design. Pearson, 864.

18. Tavrov, D. (2015). Memetic approach to anonymizing groups that can be approximated by a fuzzy inference system. 2015 Annual Conference of the North American Fuzzy Information Processing Society (NAFIPS) Held Jointly with 2015 5th World Conference on Soft Computing (WConSC). doi: 10.1109/nafips-wconsc.2015.7284189

19. Chertov, O., Tavrov, D. (2014). Memetic Algorithm for Solving the Task of Providing Group Anonymity. Studies in Fuzziness and Soft Computing, 281–292. doi: 10.1007/978-3-319-03674-8_27

20. Neri, F., Cotta, C. (2012). A Primer on Memetic Algorithms. Studies in Computational Intelligence, 43–52. doi: 10.1007/978-3-642-23247-3_4

21. Eiben, A. E., Smith, J. E. (2015). Introduction to Evolutionary Computing. Berlin, Heidelberg: Springer-Verlag, 287. doi: 10.1007/978-3-662-44874-8

22. Zhang, Y., Liu, J., Zhou, M., Jiang, Z. (2016). A multi-objective memetic algorithm based on decomposition for big optimization problems. Memetic Computing, 8 (1), 45–61. doi: 10.1007/s12293-015-0175-9

23. Turky, A., Sabar, N. R., Song, A. (2016). A multi-population memetic algorithm for dynamic shortest path routing in mobile ad-hoc networks. 2016 IEEE Congress on Evolutionary Computation (CEC). doi: 10.1109/cec.2016.7744313

24. Wang, Y., Chen, J., Sun, H., Yin, M. (2017). A Memetic Algorithm for Minimum Independent Dominating Set Problem. Neural Computing and Applications. doi: 10.1007/s00521-016-2813-7

25. Jain, P., Srivastava, K., Saran, G. (2016). Minimizing cyclic cutwidth of graphs using a memetic algorithm. Journal of Heuristics, 22 (6), 815–848. doi: 10.1007/s10732-016-9319-4

26. Aggarwal, C. C. (2013). Outlier Analysis. New York: Springer-Verlag, 461. doi: 10.1007/978-1-4614-6396-2

27. Ruggles, S., Genadek, K., Goeken, R., Grover, J., Sobek, M. (2015). Integrated Public Use Microdata Series: Version 6.0. Minneapolis: University of Minnesota. Available at: https://usa.ipums.org/usa/

28. Base Structure Report Fiscal Year 2014 Baseline – A Summary of the Real Property Inventory. Available at: https://www.acq.osd.mil/eie/Downloads/BSI/Base%20Structure%20Report%20FY14.pdf

29. Syswerda, G. (1991). Schedule Optimization Using Genetic Algorithms. Handbook of Genetic Algorithms. New York: Van Nostrand Reinhold, 332–349.

30. Brindle, A. (1981). Genetic Algorithms for Function Optimization. Edmonton: University of Alberta, Department of Computer Science, 93.

DEVELOPMENT OF THE METHOD FOR CREATING EXPLICIT INTEGRAL DYNAMIC MODELS OF MEASURING TRANSDUCERS (p. 40-48)

Alexander Sytnik
Cherkasy State Technological University, Cherkasy, Ukraine
ORCID: http://orcid.org/0000-0002-4720-0267

Sergey Protasov
Cherkasy State Technological University, Cherkasy, Ukraine
ORCID: http://orcid.org/0000-0003-3592-0627

Konstantin Klyuchka
Cherkasy State Technological University, Cherkasy, Ukraine
ORCID: http://orcid.org/0000-0003-1154-4938

Increasing requirements to measuring transducers lead to the need to improve and propose alternatives of their mathematical description. The application in this case of differential equations of various types testifies to great computational complexity of the given problem statement. In this regard, constructively relevant are the methods for creating integral dynamic models of measuring transducers that enable expansion of the tools for computer simulation.

The method considered in present paper implies determining a pulse transient characteristic and leads to the formation of the operators (cores) of measuring transducers in the form of integral mathematical dependences, that is, explicit integral dynamic models.

The method of obtaining an analytic expression of the pulse transition function of measuring transducers with lumped parameters is represented as a solution to the homogeneous differential equation that corresponds to the specified non-homogeneous differential equation. This technique is easily illustrated on the examples of measuring transducers of the first and second order.

The principle of determining a pulse transient characteristic for measuring transducers with distributed parameters by the assigned equations in partial derivatives is the same as for the case with lumped parameters.

Keywords: integral dynamic model, pulse transition function, measuring transducer, differential equation.

References

1. Capenko, M. P. (1982). Izmeritel'nye informacionnye sistemy: Struktury i algoritmy, sistemotekhnicheskoe proektirovanie. Moscow: Energoatomizdat, 440.

2. Granovskiy, V. A. (1984). Dinamicheskie izmereniya: Osnovy metrologicheskogo obespecheniya. Leningrad: Energoatomizdat, 224.

3. Rudenko, V. S., Sen'ko, V. I., Chizhenko, I. M. (1978). Preobrazovatel'naya tekhnika. Kyiv: Vyshcha shkola, 424.

4. Lega, Yu. G., Sytnik, A. A., Yuzvenko, V. F., Podgorniy, O. V. (2004). Modelirovanie processov v tekhnicheskih sistemah. Cherkasy: CHGTU, 183.

5. Close, C. M., Frederick, D. K., Newell, J. C. (2001). Modeling and Analysis of Dynamic Systems. Wiley, 592.

6. Hayrer, E., Nersett, S., Vanner, G. (1990). Reshenie obyknovennyh differencial'nyh uravneniy. Nezhestkie zadachi. Moscow: Mir, 512.

7. Stoian, V. A. (2003). Modeliuvannia ta identyfikatsiya dynamiky system iz rozpodilenymy parametramy. Kyiv: VPTs «Kyivskyi universytet», 201.

8. Sytnik, A. A. (2005). Matematicheskoe opisanie mnogoparametricheskih izmeritel'nyh preobrazovateley posredstvom

integral'nyh modeley. Modeliuvannia ta informatsiini tekhnolohyi, 34, 75–80.

9. Verlan', A. F., Sizikov, V. S. (1986). Integral'nye uravneniya: metody, algoritmy, programmy. Kyiv: Naukova dumka, 544.

10. Babak, V. P., Eremenko, V. S.; Babaka, V. P. (Ed.) (2014). Teoreticheskie osnovy informacionno-izmeritel'nyh sistem. Kyiv: TOV «Sofiya-A», 832.

11. Sytnik, A. A. (2003). Approksimaciya mnogoparametricheskih pervichnyh izmeritel'nyh preobrazovateley na osnove metoda naimen'shih kvadratov. Visnyk Cherkaskoho derzhavnoho tekhnolohichnoho universytetu, 4, 86–89.

12. Sviatnyi, V. A., Moldovanova, O. V., Chut, A. M. (2008). Stan ta perspektyvy rozrobok paralelnykh modeliuiuchykh seredovyshch dlia skladnykh dynamichnykh system z rozpodilenymy ta zoseredzhenymy parametramy. Vol. 1. Sbornik trudov konferencii „Modelirovanie-2008 (Simulation-2008)". Kyiv, 25–37.

13. Hulkó, G., Belavý, C., Ondrejkovič, K., Bartalský, L., Bartko, M. (2017). Control of technological and production processes as distributed parameter systems based on advanced numerical modeling. Control Engineering Practice, 66, 23–38. doi: 10.1016/j.conengprac.2017.05.010

14. Murtaza, S. S., Khreich, W., Hamou-Lhadj, A., Bener, A. B. (2016). Mining trends and patterns of software vulnerabilities. Journal of Systems and Software, 117, 218–228. doi: 10.1016/j.jss.2016.02.048

15. Sytnik, A. A., Kozak, A. V. (2006). Algoritm formirovaniya differencial'nogo uravneniya izmeritel'nogo preobrazovatelya. Visnyk Cherkaskoho derzhavnoho tekhnolohichnoho universytetu, 3, 84–87.

16. Lal, H. P., Godbole, S. M., Dubey, J. K., Sarkar, S., Gupta, S. (2016). Reduced Order Models in Analysis of Stochastically Parametered Linear Dynamical Systems. Procedia Engineering, 144, 1325–1331. doi: 10.1016/j.proeng.2016.05.161

17. Protasov, S. Yu. (2010). Dinamicheskie harakteristiki lineynyh ob'ektov s peremennymi parametrami. Modeliuvannia ta informatsiyni tekhnolohyi, 56, 64–71.

18. Faraji, M., Voit, E. O. (2017). Nonparametric dynamic modeling. Mathematical Biosciences, 287, 130–146. doi: 10.1016/j.mbs.2016.08.004

19. Ikonnikov, O. A. (2013). Issledovanie neparametricheskih modeley dinamicheskih system. Vestnik Sibirskogo gosudarstvennogo aehrokosmicheskogo universiteta im. akademika M. F. Reshetneva, 47 (1), 36–40.

20. Sytnik, A. A., Klyuchka, K. N., Protasov, S. Yu. (2013). Primenenie integral'nyh dinamicheskih modeley pri reshenii zadachi identifikacii parametrov ehlektricheskih cepey. Izvestiya Tomskogo politekhnicheskogo universiteta, 322 (4), 103–106.

21. Annunziato, M., Brunner, H., Messina, E. (2012). Asymptotic stability of solutions to Volterra-renewal integral equations with space maps. Journal of Mathematical Analysis and Applications, 395 (2), 766–775. doi: 10.1016/j.jmaa.2012.05.080

DEVELOPMENT OF THE MODEL OF MINIMAX ADAPTIVE MANAGEMENT OF INNOVATIVE PROCESSES AT AN ENTERPRISE WITH CONSIDERATION OF RISKS (p. 49-56)

Vitalina Babenko
V. N. Karazin Kharkiv National University, Kharkiv, Ukraine
ORCID: http://orcid.org/0000-0002-4816-4579

Yuri Romanenkov
N. E. Zhukovsky National Aerospace University "Kharkiv Aviation Institute", Kharkiv, Ukraine
ORCID: http://orcid.org/0000-0002-3526-7237

Larysa Yakymova
Yuriy Fedkovych Chernivtsi National University, Chernivtsi, Ukraine
ORCID: http://orcid.org/0000-0003-1515-6975

Oleksandr Nakisko
Kharkiv Petro Vasylenko National Technical University of Agriculture, Kharkiv, Ukraine
ORCID: http://orcid.org/0000-0003-3789-2455

The authors consider a discrete dynamic system, containing an object – the innovative process (IP). Its dynamics is described by the vector linear discrete recurrent ratio and is influenced by controlled parameters (controls) and an uncontrolled parameter (the vector of risk or obstacle). In this case, risks in the system of IP management at an enterprise will imply the factors that influence negatively or disastrously the results processes, considered in it.

To solve the set problem, a general model of IP management for organization of minimax adaptive management in the selected class of permissible strategies of adaptive management was formalized. It was proposed to use a deterministic approach for modeling and solution of the original problem in the form of dynamic problem of minimax IP management (optimization of the guaranteed result) at a given moment of time, with consideration of risks. To solve the problem of minimax IP management in the face of risks, the authors propose the method that is reduced to implementation of solutions of a finite number of problems of linear and convex mathematical programming, as well as a discrete optimization problem. Solution of the set problem of minimax IP management allows obtaining the optimal guaranteed (minimax) outcome.

For effective implementation of the resulting mathematical apparatus in practice of work of enterprises, the detailed model of multicriteria optimization of IP management at an enterprise in the face of risks was developed, which describes dynamics of the studied process to the full. Generated optimization criteria and the system of phase constraints of the model take into consideration possibilities of production capacities, as well as meet the requirements for IP.

The proposed method makes it possible to develop effective numerical procedures that enable us to implement computer modeling of dynamics of the considered problem, to formulate adaptive minimax IP management at an enterprise and to obtain the optimum guaranteed results.

The presented results could be used for economic-mathematical modeling and solution of other problems of optimization of processes of data forecasting and management under conditions of information deficit and existence of risks. In addition, the developed tools of modeling can be the basis for development of appropriate software and hardware complexes for supporting effective managerial decision making in practice.

Keywords: innovative process, modeling, risks, optimization, minimax adaptive management, guaranteed outcome.

References

1. Vasylieva, N. K., Vinichenko, I. I., Katan, L. I. (2015). Economic and mathematical evaluation of Ukrainian agrarian market by branches. Economic Annals-XXI, 9-10, 41–44.

2. Vasylieva, N. (2016). Cluster models of households' agrarian production development. Economic Annals-XXI, 158 (3-4 (2)), 13–16. doi: 10.21003/ea.v158-03

3. Babenko, V. A. (2013). Formirovanie ekonomiko-matematicheskoy modeli dinamiki processa upravleniya innovacionnymi tekhnologiyami na predpriyatiyah APK. Aktualni problemy ekonomiky, 1 (139), 182–186.

4. Dilenko, V. A. (2013). Ekonomiko-matematicheskoe modelirovanie innovacionnyh processov. Odessa: Feniks, 348.

5. Rafalski, R. (2012). A new concept of evaluation of the production assets. Foundations of Management, 4 (1), 75–104. doi: 10.2478/fman-2013-0005

6. Kaplan, S. (Ed.) (2012). The Business Model Innovation Factory: How to Stay Relevant When The World is Changin. Wiley. doi: 10.1002/9781119205234

7. Rosegger G. (2010). The Economics of Production and Innovation. An Industrial Perspective. Pergamon Press, 236.

8. Sosna, M., Trevinyo-Rodríguez, R. N., Velamuri, S. R. (2010). Business Model Innovation through Trial-and-Error Learning. Long Range Planning, 43 (2-3), 383–407. doi: 10.1016/j.lrp.2010.02.003

9. Teece, D. J. (2010). Business Models, Business Strategy and Innovation. Long Range Planning, 43 (2-3), 172–194. doi: 10.1016/j.lrp.2009.07.003

10. Shorikov, A. F. (2005). Algoritm resheniya zadachi optimal'nogo terminal'nogo upravleniya v lineynyh diskretnyh dinamicheskih sistemah. Informacionnye tekhnologii v ekonomike: teoriya, modeli i metody. Ekaterinburg: Izd-vo Ural. gos. ekon. un-ta, 119–138.

11. Shorikov, A. F., Babenko, V. A. (2014). Optimizaciya garantirovannogo rezul'tata v dinamicheskoy modeli upravleniya innovacionnym processom na predpriyatii. Ekonomika regiona, 1, 196–202.

12. Babenko, V. O. (2014). Upravlinnia innovatsiynymy protsesamy pererobnykh pidpryiemstv APK (matematychne modeliuvannia ta informatsiyni tekhnolohyi). Kharkiv: KhNAU, Kh. – Machulyn, 380 .

13. Babenko, V. O. (2017). Modeling of factors influencing innovation activities of agricultural enterprises of Ukraine. Scientific Bulletin of Polissia, 2 (1 (9)), 115–121. doi: 10.25140/2410-9576-2017-2-1(9)-115-121

14. Lotov, A. V. (1984). Vvedenie v ekonomiko-matematicheskoe modelirovanie. Moscow: Nauka, Glavnaya redakciya fiziko-matematicheskoy literatury, 332.

15. Propoy, A. I. (1973). Elementy teorii optimal'nyh diskretnyh processov. Moscow: Nauka, Glavnaya redakciya fiziko-matematicheskoy literatury, 368.

16. Ter-Krikorov, A. M. (1977). Optimal'noe upravlenie i matematicheskaya ekonomika. Moscow: Nauka, 216.

17. Babenko, V. A. (2013). Formirovanie detalizirovannoy ekonomiko-matematicheskoy modeli dinamiki upravleniya innovacionnymi processami predpriyatiy APK pri nalichii riskov. Izvestiya Ural. gos. ekon. un-ta, 6, 31–38.

18. Johnson, M. W. (2010). Seizing the white space. Business Model Innovation for growth and renewal. Harvard Business Press, 240.

19. Babenko, V., Pasmor, M., Pankova, J., Sidorov, M. (2017). The place and perspectives of Ukraine in international integration space. Problems and Perspectives in Management, 15 (1), 80–92. doi: 10.21511/ppm.15(1).2017.08

20. Pushkar, O., Garkin, V. (2012). Model and quality criteria of the structural subsystems of information systems. Scientific enquiry in the contemporary world: theoretical basics and innovative approach. L&L Publishing Tittusville, FL, USA Copyright, 6, 66–71.

21. Hryhoruk, P. M., Paraska, S. H. (2014). Analiz ekonomiko-matematychnykh modelei innovatsiynoi diyalnosti pidpryiemstva. Naukovyi visnyk Khersonskoho derzhavnoho universytetu, 7, 162–165.

22. Hrytsiuk, P. M. (2014). Modeliuvannia vplyvu infliatsyi na ekonomichne zrostannia Ukrainy. Naukovi zapysky Natsionalnoho universytetu "Ostrozka akademiya". Seriya: Ekonomika, 27, 144–149.

23. Cherniak, O. I., Zakharchenko, P. V. (2013). Suchasni kontseptsyi prohnozuvannia rozvytku skladnykh sotsialno-ekonomichnykh system. Berdiansk: Vydavets Tkachuk O. V., 556.

A NEW METHOD FOR SOLVING THE PROBLEM ON THE ORGANIZATION OF WAGON FLOWS UNDER CONDITION OF ENERGY EFFICIENCY OF TRANSPORTATION (p. 57-62)

Oleksandr Papakhov
Dnipropetrovsk National University of Railway Transport named after academician V. Lazaryan, Dnipro, Ukraine
ORCID: http://orcid.org/0000-0003-2357-8158

Natalya Logvinova
Dnipropetrovsk National University of Railway Transport named after academician V. Lazaryan, Dnipro, Ukraine
ORCID: http://orcid.org/0000-0002-9350-881X

Olesya Kharchenko
Dnipropetrovsk National University of Railway Transport named after academician V. Lazaryan, Dnipro, Ukraine
ORCID: http://orcid.org/0000-0003-2068-0640

Andriy Milyanych
Lviv Branch of Dnipropetrovsk National University of Railway Transport named after academician V. Lazaryan, Lviv, Ukraine
ORCID: http://orcid.org/0000-0003-3583-792X

Victor Sichenko
Dnipropetrovsk National University of Railway Transport named after academician V. Lazaryan, Dnipro, Ukraine
ORCID: http://orcid.org/0000-0002-9533-2897

The paper considers solving a problem of rational organization of wagon flows in a polygon of selected technological railroad stations using a technique for solving a knapsack problem employing set functions. Based on the results of present work, the authors developed a method for solving a knapsack-type problem that makes it possible to adapt the algorithm of solving a vector optimization problem to the rational system of organizing wagon flows in trains without using differentiation operations and to solve a basic optimization problem employing the Lagrange multipliers. The applicability of the Lagrange method was proved for the problems on a conditional extremum in terms of set functions. Its special feature is the rejection of Boolean variables. We confirmed correctness of the mathematical notation of solution to a knapsack-type problem and proved adequacy of the proposed algorithm, as well as adapted it for adjusting a plan of freight trains formation in order to improve energy efficiency of transportation. By reducing the complexity of the problem, it has become possible to reduce computer processor time needed for calculation, and employ this algorithm when designing an automated work place (AWP) for an engineer responsible for planning the formation of trains. It should be specially noted that a reduction of the time needed to solve a problem makes it possible to timely adjust the plan of freight trains formation, to eliminate a lot of irrational variants when handling wagons at technical stations.

The proposed algorithm helps identify variants to direct train flows to the most promising destinations at minimal energy cost for transportation. Limitations of the proposed approach include a closed cycle of routes of the loaded wagons

and part of these routes traveled unloaded until the next loading. In some cases, there is a need to change a weight of the train composition, associated with fractures of weight, and, therefore, a change in the balance between wagon flows and train flows.

References

1. Mazurenko, O. O., Kudryashov, A. V. (2014). Efficiency of formation of two-group trains in operative conditions of organization of carriages. Collection of scientific works of the State Research and Production Enterprise «Transport systems and technologies of transportation», 7, 50–55.

2. González, E. M., Sánchez, G. G., Romero, J. M. M. (2014). Analysis and Viability of Railway Exportation to Europe from the South of Spain. Procedia – Social and Behavioral Sciences, 160, 264–273. doi: 10.1016/j.sbspro.2014.12.138

3. Baushev, A. N., Osminin, A. T., Osminin, L. A. (2013). Mathematical model of multiphase railroad cargo transportation. Mathematical modeling, 25 (10), 108–122.

4. Papakhov, A. Yu. (2016). Use of the set-function method for the rational organization of car-stream flows. Transport systems and transport technologies, 12, 69–74.

5. Reznikov, A. E., Fedorin, A. N. (2009). Mathematical Models and Algorithms for Solving the Problems of Optimal Loading of Vehicles. In Sat. tr. 11th International Scientific and Industrial Forum "Great Rivers". ICEF. Problems and prospects of development of educational, scientific and innovative transport complexes. Nizhniy Novgorod.

6. Myamlin, S. V., Zhyzhko, K. V. (2014). Upgrading of economic simulation methods for increasing efficiency of investments. Science and Transport Progress. Bulletin of Dnipropetrovsk National University of Railway Transport, 6 (54), 34–41. doi: 10.15802/stp2014/32656

7. Klamroth, K., Wiecek, M. M. (2015). Dynamic Programming Approaches to the Multiple Criteria Knapsack Problem. Clemson University Clemson, SC USA, 30.

8. Bazgan, C., Hugot, H., Vanderpooten, D. (2007). An Efficient Implementation for the 0-1 Multi-objective Knapsack Problem. Vol. 4525. Lecture Notes in Computer Science. Springer, 406–419. doi: 10.1007/978-3-540-72845-0_31

9. Beausoleil, R. P., Baldoquin, G., Montejo, R. A. (2007). Multistart and path relinking methods to deal with multiobjective knapsack problems. Annals of Operations Research, 157 (1), 105–133. doi: 10.1007/s10479-007-0199-8

10. Lin, B. (2017). Integrating car path optimization with train formation plan: a non-linear binary programming model and simulated annealing based heuristics. arXiv. Available at: https://arxiv.org/ftp/arxiv/papers/1707/1707.08326.pdf

11. Bosov, A. A. (2007). Functions of sets and their application. Dneprodzerzhinsk: Izd. House "Andrew", 182.

12. Lazorev, A. A., Gafarov, E. R. (2011). Theory of schedules. Tasks and algorithms. Moscow: Publishing House of Moscow State University. M. V. Lomonosov, 222.