

ABSTRACT AND REFERENCES

APPLIED MECHANICS

DOI: 10.15587/1729-4061.2017.114359

**EXAMINING ELASTIC INTERACTION
BETWEEN A CRACK AND THE LINE OF
JUNCTION OF DISSIMILAR SEMI-INFINITE PLATES
(p. 4-10)**

Volodymyr ZelenyakLviv Polytechnic National University, Lviv, Ukraine
ORCID: <http://orcid.org/0000-0002-6653-4326>**Lubov Kolyasa**Lviv Polytechnic National University, Lviv, Ukraine
ORCID: <http://orcid.org/0000-0002-9690-8042>**Oksana Oryshchyn**Lviv Polytechnic National University, Lviv, Ukraine
ORCID: <http://orcid.org/0000-0002-8965-1891>**Svitlana Vozna**Lviv Polytechnic National University, Lviv, Ukraine
ORCID: <http://orcid.org/0000-0002-5354-2124>**Olha Tokar**Lviv Polytechnic National University, Lviv, Ukraine
ORCID: <http://orcid.org/0000-0001-9428-2472>

We examined a two-dimensional mathematical model for the problem of elasticity theory on welded dissimilar elastic half-planes containing rectilinear cracks under the action of mechanical efforts on the shores of a crack. As a consequence, the intensity of stresses in the vicinity of tops of the cracks increases, which significantly affects strength of the body. This may lead to the growth of a crack and to the local destruction of a structure. Such a model represents to some extent a mechanism of destruction of the elements of engineering structures with cracks when the water, contained in them, freezes to ice. It creates normal pressure on the shores of the cracks. Based on the application of the apparatus of singular integral equations (SIE), the problem is reduced to the system of SIE of the first kind on the contours of cracks. We obtained numerical solutions to the corresponding integral equation in particular cases of two welded dissimilar half-planes with one randomly-oriented crack, as well as a two-link irregular crack, which crosses the line of junction when the crack's shores are exposed to uniformly distributed normal pressure. By employing these solutions, we determined stress intensity coefficients (SIC) at the tops of the crack, which are subsequently used to determine critical values of the normal pressure on the shores of the crack.

We built graphic dependences of SIC, which characterize distribution of the intensity of stresses at the tops of a crack, on the angle of crack inclination and elastic characteristics of half-planes. This makes it possible to analyze the intensity of stresses in the vicinity of a crack's tops depending on the geometrical and mechanical factors, as well as to determine the limit of permissible values of normal pressure on the shores of the crack at which the growth of the crack starts, as well as the local destruction of the body.

It is shown that the proper selection of elastic characteristics of the components of welded dissimilar half-planes can help achieve an improvement in the strength of the body in terms of the mechanics of destruction by reducing SIC at the crack's tops.

Keywords: stress intensity coefficient, singular integral equation, normally distributed pressure, welded dissimilar plates.

References

- Zeleniak, V., Martyniak, R., Slobodian, B. (2008). Napruzhenia v spaianykh riznorodnykh pivplohchynakh z vkluchenniam i trishchynoiu za diy roztiahu. *Visnyk Natsionalnoho universytetu «Lvivska politehnika»*, 625, 54–58.
- Savruk, M. P., Zelenyak, V. M. (1988). Plane problem of thermal conductivity and thermal elasticity for two joined dissimilar half-planes with curved inclusions and cracks. *Soviet Materials Science*, 24 (2), 124–129. doi: 10.1007/bf00736348
- Zeleniak, V., Slobodian, B. (2010). Modeliuvannya termopruzhnogo dvovymirnoho stanu dvokh spaianykh riznorodnykh pivplohchyn z vkluchenniamy i trishchynamy. *Fyzyko-matematychnye modeliuvannia ta informatsiyni tekhnolohiy*, 12, 94–101.
- Shatskyi, I. P., Daliak, T. M. (2015). Vzaiemodiya trishchyny z kolinearnoiu shchylinoiu za zghynu plastyny. *Visnyk Zaporizkoho natsionalnoho universytetu. Fyzyko-matematychni nauky*, 1, 211–218.
- Tagliavia, G., Porfiri, M., Gupta, N. (2011). Elastic interaction of interfacial spherical-cap cracks in hollow particle filled composites. *International Journal of Solids and Structures*, 48 (7-8), 1141–1153. doi: 10.1016/j.ijsolstr.2010.12.017
- Chu, S. N. G. (1982). Elastic interaction between a screw dislocation and surface crack. *Journal of Applied Physics*, 53 (12), 8678–8685. doi: 10.1063/1.330465
- Ming-huan, Z., Ren-ji, T. (1995). Interaction between crack and elastic inclusion. *Applied Mathematics and Mechanics*, 16 (4), 307–318. doi: 10.1007/bf02456943
- Mykhas'kiv, V. V., Khay, O. M. (2009). Interaction between rigid-disc inclusion and penny-shaped crack under elastic time-harmonic wave incidence. *International Journal of Solids and Structures*, 46 (3-4), 602–616. doi: 10.1016/j.ijsolstr.2008.09.005
- Kryvyi, O. F. (2012). Interface circular inclusion under mixed conditions of interaction with a piecewise homogeneous transversally isotropic space. *Journal of Mathematical Sciences*, 184 (1), 101–119. doi: 10.1007/s10958-012-0856-6
- Elfakhkhre, N. R. F., Nik long, N. M. A., Eshkuvatov, Z. K. (2017). Stress intensity factor for multiple cracks in half plane elasticity. *AIP Conference Proceedings*, 020010-1–020010-8. doi: 10.1063/1.4972154
- Savruk, M. P. (1981). *Dvumernye zadachi uprugosti dlya tel s treshchinami*. Kyiv: Naukova dumka, 324.
- Panasuk, V. V., Savruk, M. P., Datsyshin, A. P. (1976). *Raspredele-nie napryazheniy okolo treshchin v plastinah i obolochkah*. Kyiv: Naukova dumka, 444.

DOI: 10.15587/1729-4061.2017.116692

**INTRODUCTION OF THE METHOD OF
FINITE-DISCRETE ELEMENTS INTO THE
ABAQUS/EXPLICIT SOFTWARE COMPLEX
FOR MODELING DEFORMATION AND FRACTURE
OF ROCKS (p. 11-18)**

Anatoliy ProtoseniaSaint-Petersburg Mining University, Saint-Petersburg, Russia
ORCID: <http://orcid.org/0000-0001-7829-6743>**Maxim Karasev**Saint-Petersburg Mining University, Saint-Petersburg, Russia
ORCID: <http://orcid.org/0000-0001-8939-0807>

Valery Ochkurov

Saint-Petersburg Mining University, Saint-Petersburg, Russia
ORCID: <http://orcid.org/0000-0002-3160-3811>

The paper has considered development of a model within the framework of the method of finite-discrete elements for describing processes of rock deformation and fracture. Analysis of the methods of mathematical modeling of geomechanical processes which makes it possible to take into account the medium damage or fracture was presented. A physical model of rock fracture was proposed. It considers the fracture process as formation of microcracks of separation and shear or their combination. Examples of numerical modeling of loading a rock sample by the scheme of uniaxial compression and splitting by compression along generatrices and in conditions of volume compression were considered. Formulation and results of simulation of development of a stress-strain state in the vicinity of the rock outcrop within the framework of the method of finite-discrete elements were presented.

Within the framework of the study, an algorithm of implementing the method of finite-discrete elements in the Abaqus/Explicit software complex for strength calculations including all main stages of forming the numerical model from generation of an elemental grid to specification of boundary conditions has been worked out. A software solution for generation of the elemental grid was developed and capabilities of the Abaqus/Explicit software complex were expanded. This solution allows one to generate elemental grids for bodies of arbitrary shapes taking into account presence of surfaces of weakening within the body, both in flat and spatial formulations. The capabilities of the Abaqus/Explicit software complex were expanded in the field of modeling rock strength under the conditions of volumetric compression. According to the results of the performed studies, it was established that modeling of fracture formation (formation of shear and separation cracks) at the microlevel has allowed us to reliably represent processes of rock deformation and fracture. The possibility of using the method of finite-discrete elements for prediction of development of geomechanical processes in the vicinity of underground structures was presented.

The presented study results allow us to extend the scope of the method of finite-discrete elements to solve the problems of geomechanics and form the basis for application of this method in solving engineering problems.

Keywords: underground construction, rock, mechanics of fracture, method of finite-discrete elements.

References

- Olovyanniy, A. G. (2010). Matematicheskoe modelirovanie processov deformirovaniya i razrusheniya v treshchinovatykh massivakh skal'nykh porod. *Zapiski Gornogo institute*, 185, 95–98.
- Olovyanniy, A. G. (2011). Matematicheskoe modelirovanie formirovaniya zon razrusheniya porod v bokah gornyh vyrabotok. *Marksheyderskiy vestnik*, 1, 50–53.
- Zienkiewicz, O. C., Pande, G. N. (1977). Time-dependent multilaminar model of rocks – a numerical study of deformation and failure of rock masses. *International Journal for Numerical and Analytical Methods in Geomechanics*, 1 (3), 219–247. doi: 10.1002/nag.1610010302
- Bazant, Z. P., Zi, G. (2002). Microplane constitutive model for porous isotropic rocks. *International Journal for Numerical and Analytical Methods in Geomechanics*, 27 (1), 25–47. doi: 10.1002/nag.261
- Wittke, W., Wittke, M., Kiehl, J. R. (2012). Interaction of a Masonry Dam and the Rock Foundation. *Geotechnical and Geological Engineering*, 30 (3), 581–601. doi: 10.1007/s10706-012-9493-6
- Lee, Y.-K., Pietruszczak, S. (2008). Application of critical plane approach to the prediction of strength anisotropy in transversely isotropic rock masses. *International Journal of Rock Mechanics and Mining Sciences*, 45 (4), 513–523. doi: 10.1016/j.ijrmms.2007.07.017
- Munjiza, A., Andrews, K. R. F., White, J. K. (1999). Combined single and smeared crack model in combined finite-discrete element analysis. *International Journal for Numerical Methods in Engineering*, 44 (1), 41–57. doi: 10.1002/(sici)1097-0207(19990110)44:1<41::aid-nme487>3.0.co;2-a
- Mahabadi, O. K., Grasselli, G., Munjiza, A. (2009). Numerical modelling of a Brazilian disc test of layered rocks using the combined finite-discrete element method. *Proceedings of the 3rd CanadaUS (CANUS) Rock Mechanics Symposium (RockEng09)*, 412–423.
- Mahabadi, O. K., Randall, N. X., Zong, Z., Grasselli, G. (2012). A novel approach for micro-scale characterization and modeling of geomaterials incorporating actual material heterogeneity. *Geophysical Research Letters*, 39 (1). doi: 10.1029/2011gl050411
- Lisjak, A., Grasselli, G., Vietor, T. (2014). Continuum-discontinuum analysis of failure mechanisms around unsupported circular excavations in anisotropic clay shales. *International Journal of Rock Mechanics and Mining Sciences*, 65, 96–115. doi: 10.1016/j.ijrmms.2013.10.006
- Lisjak, A., Tatone, B. S. A., Grasselli, G., Vietor, T. (2012). Numerical Modelling of the Anisotropic Mechanical Behaviour of Opalinus Clay at the Laboratory-Scale Using FEM/DEM. *Rock Mechanics and Rock Engineering*, 47 (1), 187–206. doi: 10.1007/s00603-012-0354-7
- Gordeev, V. A., Il'yasov, B. T. (2015). Primenenie metoda konechno-diskretnykh ehlementov dlya prognozirovaniya deformatsiy gornyh vyrabotok. *Innovatsionnye geotekhnologii v gornom dele*. Ekaterinburg, 98–101.
- Il'yasov, B. T. (2016). Modelirovanie dlitel'nogo razrusheniya massivov gornyh porod metodom konechno-diskretnykh ehlementov. *Marksheyderskiy vestnik*, 1, 48–52.
- Stavrogin, A. N., Tarasov, B. G. (2001). *Ehksperimental'naya fizika i mekhanika gornyh porod*. Sankt-Peterburg: Nauka, 343.
- Stavrogin, A. N., Protosenya, A. G. (1985). *Prochnost' gornyh porod i ustoychivost' vyrabotok na bol'shih glubinah*. Moscow: Nedra, 271.
- Stavrogin, A. N., Protosenya, A. G. (1979). *Plastichnost' gornyh porod*. Moscow: Nedra, 301.
- Karasev, M. A. (2016). Investigating Mechanical Properties of Argillaceous Grounds in Order to Improve Safety of Development of Megapolis Underground Space. *International Journal of Applied Engineering Research*, 11, 8849–8956.

DOI: 10.15587/1729-4061.2017.116194

RESEARCH ON THE SAFETY FACTOR AGAINST DERAILMENT OF RAILWAY VEHICLELESS (p. 19-25)

Svitlana Sapronova

State University of Infrastructure and Technology, Kyiv, Ukraine
ORCID: <http://orcid.org/0000-0002-1482-1665>

Viktor Tkachenko

State University of Infrastructure and Technology, Kyiv, Ukraine
ORCID: <http://orcid.org/0000-0002-5513-2436>

Oleksij Fomin

State University of Infrastructure and Technology, Kyiv, Ukraine
ORCID: <http://orcid.org/0000-0003-2387-9946>

Viktoria Gatchenko

State University of Infrastructure and Technology, Kyiv, Ukraine
ORCID: <http://orcid.org/0000-0002-1956-7555>

Sergiy Maliuk

State University of Infrastructure and Technology, Kyiv, Ukraine
ORCID: <http://orcid.org/0000-0003-1777-2384>

The study highlights the necessity to specify the safety factor against derailing of the wheels of a railway rolling stock. The modeling of the wheels' derailment was carried out on the basis of considering the complete pattern of frictional interaction with the rails of the approaching and running-off wheels of a wheel pair.

The simulation included the following previously overlooked factors: the dependence of the vertical component of the frictional force in the flange contact of the approaching wheel on the angle of the wheel running onto the rail; the influence of the frictional force in the flange contact of the approaching wheel on the increase in the horizontal lateral load on the flange; and the influence of the frictional force in the contact of the running-off wheel on the increase in the lateral load on the flange of the approaching wheel.

The study has specified the safety factor – the Nadal criterion – against the derailment of the wheels of a railway stock. Unlike in the traditional approach, the safety factor of the wheel steadiness against derailment is assessed taking the frame force, rather than the lateral load on the flange, as the main factor of safety. This approach to determining the stability criterion gives more reliable results, since the frame force is more accessible for experimental and theoretical analysis.

The proposed safety factor against the derailment of a railway stock, for different values of the flange inclination angle and the friction coefficient, is 10–50 % lower than the classical Nadal stability criterion. This makes the proposed criterion more reliable in assessing the safety of a railway rolling stock derailment.

Keywords: railway stock, derailment, safety criterion/factor, approach angle, flange contact.

References

- Ling, L., Dhanasekar, M., Thambiratnam, D. P., Sun, Y. Q. (2016). Lateral impact derailment mechanisms, simulation and analysis. *International Journal of Impact Engineering*, 94, 36–49. doi: 10.1016/j.ijimpeng.2016.04.001
- Leishman, E. M., Hendry, M. T., Martin, C. D. (2017). Canadian main track derailment trends, 2001 to 2014. *Canadian Journal of Civil Engineering*, 44 (11), 927–934. doi: 10.1139/cjce-2017-0076
- Railway safety statistics. Eurostat Statistics Explained. Available at: http://ec.europa.eu/eurostat/statistics-explained/index.php/Railway_safety_statistics
- Liu, X. (2015). Statistical Temporal Analysis of Freight Train Derailment Rates in the United States. *Transportation Research Record: Journal of the Transportation Research Board*, 2476, 119–125. doi: 10.3141/2476-16
- Liu, X. (2017). Statistical Causal Analysis of Freight-Train Derailments in the United States. *Journal of Transportation Engineering, Part A: Systems*, 143 (2), 04016007. doi: 10.1061/jtepbs.0000014
- Nadal, M. J. (1986). Theorie de la Stabilité des locomotives, Part II: mouvement de lacet. *Annales des Mines*, 232–255.
- Ishida, H., Matsuo, M. (1999). Safety Criteria for Evaluation of Railway Vehicle Derailment. *Quarterly Report of RTRI*, 40 (1), 18–25. doi: 10.2219/rtriqr.40.18
- Ishida, H., Miyamoto, T., Maebashi, E., Doi, H., Iida, K., Furukawa, A. (2006). Safety Assessment for Flange Climb Derailment of Trains Running at Low Speeds on Sharp Curves. *Quarterly Report of RTRI*, 47 (2), 65–71. doi: 10.2219/rtriqr.47.65
- Tkachenko, V. P., Saponova, S. Yu. (2015). Otsinka stiykosti zaliznychnykh ekipazhiv vid skhodu z reiook. *Visnyk Shhidnoukrainskoho natsionalnoho universytetu imeni Volodymyra Dalia*, 1, 266–271.
- Shabana, A. A. (2012). Nadal's Formula and High Speed Rail Derailments. *Journal of Computational and Nonlinear Dynamics*, 7 (4), 041003. doi: 10.1115/1.4006730
- Dukkipati, R. (2000). *Vehicle Dynamics*. Narosa Publishing House, 600.
- Santamaria, J., Vadillo, E. G., Gomez, J. (2009). Influence of creep forces on the risk of derailment of railway vehicles. *Vehicle System Dynamics*, 47 (9), 721–752. doi: 10.1080/00423110802368817
- Marquis, B., Greif, R. (2011). Application of Nadal Limit for the Prediction of Wheel Climb Derailment. 2011 Joint Rail Conference. doi: 10.1115/jrc2011-56064
- Ohno, K. (2002). Research and development for eliminating wheel-climb derailment accidents. *JR East Technical Review*, 2, 46–50.
- Bibel, G. (2012). *Train Wreck – the Forensics of Rail Disasters*. Baltimore: Hopkins University Press, 368.
- Takai, H., Uchida, M., Muramatsu, H., Ishida, H. (2002). Derailment Safety Evaluation by Analytic Equations. *Quarterly Report of RTRI*, 43 (3), 119–124. doi: 10.2219/rtriqr.43.119
- Sokol, E. (2010). Vkatyvanie grebnya kolesa na ostriye ostryaka strelochnogo perevoda. *Zaliznychnyi transport Ukrainy*, 5, 26–30.
- Kardas-Cinal, E. (2009). Comparative study of running safety and ride comfort of railway vehicle. *Prace naukowe politechniki warszawskiej*, 75–84.
- Iijima, H., Yoshida, H., Suzuki, K., Yasuda, Y. (2014). A Study on the Prevention of Wheel-Climb Derailment at Low Speed Ranges. *Quarterly Report of Railway Technical Research Institute*, 30, 21–24.
- Zeng, J., Wei, L., Wu, P. (2016). Safety evaluation for railway vehicles using an improved indirect measurement method of wheel-rail forces. *Journal of Modern Transportation*, 24 (2), 114–123. doi: 10.1007/s40534-016-0107-5
- Myamlin, S., Lingaitis, L. P., Dailydka, S., Vaičiūnas, G., Bogdevičius, M., Bureika, G. (2015). Determination of the dynamic characteristics of freight wagons with various bogie. *Transport*, 30 (1), 88–92. doi: 10.3846/16484142.2015.1020565
- Miyamoto, M. (1996). Mechanism of derailment phenomena of railway vehicles. *Railway Technical Research Institute, Quarterly Reports*, 37 (3), 147–155.
- Molatefi, H., Mazraeh, A. (2016). On the investigation of wheel flange climb derailment mechanism and methods to control it. *Journal of theoretical and applied mechanics*, 54 (2), 541–550. doi: 10.15632/jtam-pl.54.2.541
- Kardas-Cinal, E. (2015). Selected problems in railway vehicle dynamics related to running safety. *Archives of Transport*, 31 (3), 37–45. doi: 10.5604/08669546.1146984
- A technical guide on derailments. Government of India ministry of railways (1998). Centre for Advanced Maintenance Technology, 133.
- Burgelman, N., Li, Z., Dollevoet, R. (2016). Effect of the Longitudinal Contact Location on Vehicle Dynamics Simulation. *Mathematical Problems in Engineering*, 2016, 1–6. doi: 10.1155/2016/1901089
- Costea, D.-M., Gaman, M.-N., Dumitru, G. (2013). Considerations on Tribological Phenomenons at the Wheel-Rail Contact Level, Specific to the Br 189 Class Locomotives. *Annals of the Faculty of Engineering Hunedoara*, 11 (4), 181–188.
- Pombo, J. C., Ambrósio, J. A. C. (2007). Application of a wheel-rail contact model to railway dynamics in small radius curved tracks. *Multibody System Dynamics*, 19 (1-2), 91–114. doi: 10.1007/s11044-007-9094-y
- Golubenko, A., Saponova, S., Tkachenko, V. (2007). Kinematics of point-to-point contact of wheels with a rails. *Transport Problems*, 2 (3), 57–61.
- Saponova, S., Tkachenko, V., Kramar, N., Voron'ko, A. (2008). Regularities of shaping of a wheel profile as a result of deterioration of the rolling surface in exploitation. *Transport Problems*, 3 (4), 47–54.
- Fomin, O., Kulbovsky, I., Sorochinska, E., Saponova, S., Bambura, O. (2017). Experimental confirmation of the theory of implementation of the coupled design of center girder of the hopper wagons for iron ore pellets. *Eastern-European Journal of Enterprise Technologies*, 5 (1 (89)), 11–18. doi: 10.15587/1729-4061.2017.109588

32. Tkachenko, V., Sapronova, S., Kulbovskiy, I., Fomin, O. (2017). Research into resistance to the motion of railroad undercarriages related to directing the wheelsets by a rail track. *Eastern-European Journal of Enterprise Technologies*, 5 (7 (89)), 65–72. doi: 10.15587/1729-4061.2017.109791
33. Taturevich, A. A. (2003). Teoreticheskie issledovaniya ustoychivosti podvizhnogo sostava protiv skhoda ot vkatyvaniya grebnya koleasa na rel's. *Visnyk DNUZT*, 2, 133–137.
34. Martland, C., Zhu, Y., Lahrech, Y., Sussman, J. (2001). Risk and Train Control: A Framework for Analysis. *Transportation Research Record: Journal of the Transportation Research Board*, 1742, 25–33. doi: 10.3141/1742-04

DOI: 10.15587/1729-4061.2017.116855

SEARCH FOR THE CONDITIONS FOR THE OCCURRENCE OF AUTO-BALANCING IN THE FRAMEWORK OF A PLANAR MODEL OF THE ROTOR MOUNTED ON ANISOTROPIC VISCOUS-ELASTIC SUPPORTS (p. 26-33)

Irina Filimonikhina

Central Ukrainian National
Technical University, Kropivnitskiy, Ukraine
ORCID: <http://orcid.org/0000-0002-1384-6027>

Vasiliy Gutsul

Central Ukrainian National
Technical University, Kropivnitskiy, Ukraine
ORCID: <http://orcid.org/0000-0003-4155-5355>

Kostyantyn Dumenko

Central Ukrainian National
Technical University, Kropivnitskiy, Ukraine
ORCID: <http://orcid.org/0000-0002-9718-6408>

Yuriy Nevdakha

Central Ukrainian National
Technical University, Kropivnitskiy, Ukraine
ORCID: <http://orcid.org/0000-0003-4355-4065>

Within the framework of the planar model of the rotor mounted on anisotropic elastic-viscous supports and balanced by a passive auto-balancer, conditions for the occurrence of auto-balancing were analytically determined.

An empirical criterion for stability of the main motion was applied. It was found that depending on the forces of viscous resistance in supports, the rotor has one or three critical speeds. These speeds are between two natural frequencies of rotor oscillation in absence of resistance forces in supports. Auto-balancing, respectively, occurs when the single critical speed is exceeded or between the first and the second and above the third critical speeds.

At low forces of viscous resistance, the rotor has three critical speeds. The first and the third critical speeds coincide with two natural frequencies of rotor oscillation in absence of resistance forces in supports. The second critical speed is between the first two. An additional (second) critical speed appears when the auto-balancer is mounted on the rotor. In the transition of this speed the behavior of the auto-balancer changes: the auto-balancer reduces the rotor imbalance at slightly lower rotor speeds and increases it at somewhat higher speeds.

At finite forces of viscous resistance in supports, depending on the magnitude of these forces, the rotor has one or three critical speeds.

At large forces of viscous resistance in supports, the rotor has one critical speed. Depending on the relationship between the coefficients of the forces of viscous resistance, this speed is closer to the smallest or the largest natural frequency of the rotor oscillation.

The results obtained were confirmed by computational experiments. It was established that the criterion correctly describes

the qualitative behavior of the rotor – auto-balancer system: it determines the number of critical speeds and the region of the auto-balancing onset. Accuracy of determining critical speeds (the boundaries of the regions of auto-balancing onset) increases with:

- reduction of the auto-balancer mass with respect to the rotor mass;
- an increase in forces of viscous resistance to the motion of correction weights.

Keywords: rotor mounted on anisotropic supports, passive auto-balancer, auto-balancing, criterion of auto-balancing onset, critical rotor speeds.

References

1. Thearle, E. L. (1950). Automatic dynamic balancers Part 2 – Ring, pendulum and ball balancers. *Machine Design*, 22 (10), 103–106.
2. Filimonikhin, G. B. (2004). Zrivnovazhennia i vibrozakhyst rotoriv avtobalansyramy z tverdymy koryhuvalnymy vantazhamy [Balancing and protection from vibrations of rotors by autobalancers with rigid corrective weights]. Kirovohrad: KNTU, 352.
3. Detinko, F. M. (1956). Ob ustoychivosti raboty avtobalansira dlya dinamicheskoy balansirovki [On the stability of work auto-balancer for dynamic balancing]. *Proceedings of the Academy of Sciences of the USSR. Meh. and machine building*, 4, 38–45.
4. Filimonikhin, G. B. (1996). K ustoychivosti osnovnogo dvizheniya dvukhmayatnikovogo avtobalansira [On the stability of the main motion of an automatic two-pendulum balance]. *Dokl. NAN Ukrainy. Ser. A*, 8, 74–78.
5. Gorbenko, A. N. (2003). On the Stability of Self-Balancing of a Rotor with the Help of Balls. *Strength of Materials*, 35 (3), 305–312. doi: 10.1023/a:1024621023821
6. Blekhman, I. I. (1981). *Sinkhronizatsiya v prirode i tekhnike* [Synchronisation in Nature and Technical Engineering]. Moscow: Nauka, 352.
7. Nesterenko, V. (1985). *Avtomaticheskaya balansirovka rotorov priborov i mashin so mnogimi stepenyami svobody* [Automatic rotor balancing devices and machines with many degrees of freedom]. Tomsk: Izd-vo Tomsk. un-ta, 84.
8. Dubovik, V. A., Ziyakaev, G. R. (2010). Osnovnoe dvizhenie dvukhmayatnikovogo avtobalansira na gibkom valu s uprugimi oporami [Main movement of two pendulum device at flexible shaft with elastic supports]. *Bulletin of the Tomsk Polytechnic University: Mathematics and Mechanics. Physics*, 317 (2), 37–39. Available at: http://www.lib.tpu.ru/fulltext/v/Bulletin_TPU/2010/v317/i2/08.pdf
9. Goncharov, V., Filimonikhin, G. (2015). Vid i struktura differentsialnykh uravneniy dvizheniya i protsesa uravnovesivaniya rotornoy mashiny s avtobalansirami [Form and structure of differential equations of motion and process of auto-balancing in the rotor machine with auto-balancers]. *Bulletin of the Tomsk Polytechnic University*, 326 (12), 20–30. Available at: http://www.lib.tpu.ru/fulltext/v/Bulletin_TPU/2015/v326/i12/02.pdf
10. Kovalenko, O. V. (2010). Analitichni umovy zrivnovazhennya kul'ovym (rolykovym) avtobalansyrom dyska ruchnoyi shlifuval'noyi mashyny na kulisi [Analytical conditions for balancing of a disk of a hand grinder on a slide by a ball-type (roller-type) auto-balancer]. *Scientific Bulletin of National Mining University*, 6, 63–69.
11. Filimonikhina, I. I., Filimonikhin, G. B. (2007). Conditions for balancing a rotating body in an isolated system with automatic balancers. *International Applied Mechanics*, 43 (11), 1276–1282. doi: 10.1007/s10778-007-0132-5
12. Filimonikhin, G., Filimonikhina, I., Dumenko, K., Lichuk, M. (2016). Empirical criterion for the occurrence of auto-balancing and its application for axisymmetric rotor with a fixed point and isotropic elastic support. *Eastern-European Journal of Enterprise Technologies*, 5 (7 (83)), 11–18. doi: 10.15587/1729-4061.2016.79970

13. Nayfeh, A. H. (1993). *Introduction to Perturbation Techniques*. New York, United States: John Wiley and Sons Ltd., 533.

DOI: 10.15587/1729-4061.2017.115040

EVALUATION OF METAL PLASTICITY AND RESEARCH ON THE MECHANICS OF PRESSURE TREATMENT PROCESSES UNDER COMPLEX LOADING (p. 34-41)

Roman Sivak

Vinnitsia National Technical University, Vinnitsia, Ukraine

A calculating apparatus has been developed to help evaluate the stress-strain state in the plastic forming processes accompanied by a complex loading in which the Bauschinger effect can be manifested. The developed methods are based on the phenomenological approach in which a material map is devised in the form of flow curves, Bauschinger curves, a function ϕ characterizing the hereditary influence of the loading history, plasticity diagrams, and limiting strain surfaces. To evaluate the plasticity resource used, taking into account the non-monotonicity of loading, the relations for determining the main components of the guiding strain-rate tensor were obtained, which made it possible to simplify the calculation of the components of the damage tensor. With the help of the developed calculating apparatus, the applied plasticity resource was evaluated in the process of radial extrusion with the contour sag, which allowed setting the limiting parameters of the shaping. Also, as a result of the research, an increase in the plasticity of the metal was established by selecting rational loading paths in the space of the dimensionless coordinates η , μ_{σ} , and ϵ_{ii} . For example, in the process of radial extrusion with the contour sag due to a change in the nature of the deformation, it was possible to obtain a flange diameter of 44 mm, with the initial diameter of the cylindrical workpiece being 20 mm. The results obtained are important because in most cases the processes of metal pressure treatment are accompanied by non-monotonic deformation.

Keywords: plasticity of a metal, complex loading, stress tensor, stress deviator, Bauschinger effect, loading history.

References

- Zhbankov, I. G., Perig, A. V., Aliieva, L. I. (2015). New schemes of forging plates, shafts, and discs. *The International Journal of Advanced Manufacturing Technology*, 82 (1-4), 287–301. doi: 10.1007/s00170-015-7377-7
- Aliiev, I., Aliieva, L., Grudkina, N., Zhbankov, I. (2011). Prediction of the variation of the form in the processes of extrusion. *Scientific and technical journal Metallurgical and Mining Industry*, 3 (7), 17–22.
- Aliieva, L., Zhbankov, Y. (2015). Radial-direct extrusion with a movable mandrel. *Metallurgical and Mining Industry*, 11, 175–183.
- Zhbankov, I. G., Perig, A. V., Aliieva, L. I. (2016). Calculation of recovery plasticity in multistage hot forging under isothermal conditions. *SpringerPlus*, 5 (1). doi: 10.1186/s40064-016-3570-x
- Dunand, M., Mohr, D. (2011). On the predictive capabilities of the shear modified Gurson and the modified Mohr–Coulomb fracture models over a wide range of stress triaxialities and Lode angles. *Journal of the Mechanics and Physics of Solids*, 59 (7), 1374–1394. doi: 10.1016/j.jmps.2011.04.006
- Driemeier, L., Brünig, M., Micheli, G., Alves, M. (2010). Experiments on stress-triaxiality dependence of material behavior of aluminum alloys. *Mechanics of Materials*, 42 (2), 207–217. doi: 10.1016/j.mechmat.2009.11.012
- Brünig, M., Gerke, S., Schmidt, M. (2016). Biaxial experiments and phenomenological modeling of stress-state-dependent ductile damage and fracture. *International Journal of Fracture*, 200 (1-2), 63–76. doi: 10.1007/s10704-016-0080-3
- Assempour, A., Hashemi, R., Abrinia, K., Ganjiani, M., Masoumi, E. (2009). A methodology for prediction of forming limit stress diagrams considering the strain path effect. *Computational Materials Science*, 45 (2), 195–204. doi: 10.1016/j.commatsci.2008.09.025
- Le Maoût, N., Thuillier, S., Manach, P. Y. (2009). Aluminum alloy damage evolution for different strain paths – Application to hemming process. *Engineering Fracture Mechanics*, 76 (9), 1202–1214. doi: 10.1016/j.engfracmech.2009.01.018
- Hora, P., Tong, L. (2009). Prediction of failure under complex 3D-stress conditions. *Proceedings of Forming Technology Forum 2009*, 133–138.
- Saanouni, K., Devalan, P. (Eds.) (2012). *Damage Mechanics in Metal Forming*. John Wiley & Sons, 523. doi: 10.1002/9781118562192
- Ogorodnikov, V. A., Kiselyov, V. B., Sivak, I. O. (2005). *Energiya. Deformatsii. Razrushenie (zadachi avtotekhnicheskoy ekspertizy)*. Vinnitsia: UNIVERSUM-Vinnitsia, 204.
- Backhaus, G. (1971). Zur analytischen Darstellung des Materialverhaltens im plastischen Bereich. *ZAMM – Zeitschrift Für Angewandte Mathematik Und Mechanik*, 51 (6), 471–477. doi: 10.1002/zamm.19710510608
- Ohorodnikov, V. A., Sivak, I. O., Sivak, R. I. (1999). Modeliuvannya protsesiv nemonotonnoi plastychnoi deformatsii. *Knyha za materialamy piatoi mizhnarodnoi naukovo-tekhnichnoi konferentsii “Kontrol i upravlinnia v skladnykh systemakh” (KUSS-99)*, 1, 195–197.
- Hvan, D. V., Rozenberg, O. A., Tsekhanov, Yu. A. (1990). Issledovanie deformatsionnoy anizotropii metallov pri nemonotonnom plasticheskom deformirovanii v usloviyah lineynogo napryazhyonnogo sostoyaniya. *Problemy prochnosti*, 12, 53–56.
- Hvan, D. V., Tomilov, F. H., Korol'kov, V. I. (1996). *Eksperimental'naya mekhanika konechnykh deformatsiy*. Voronezh: Izd-vo «ELIST», 248.
- Zav'yalov, Yu. S., Kvasov, B. I., Miroschnichenko, V. L. (1980). *Metody splayn-funktsiy*. Moscow: Nauka, 352.
- Ogorodnikov, V. A. (1989). *Deformiruemost' i razrushenie metallov pri plasticheskom deformirovanii*. Kyiv: UMK VO, 150.
- Kolmogorov, V. L. (1970). *Napryazheniya, deformatsii, razrushenie*. Moscow Metallurgiya, 230.
- Bogatov, A. A., Mizhiritskiy, O. I., Smirnov, S. V. (1984). *Resurs plastichnosti metallov pri obrabotke davleniem*. Moscow: Metallurgiya, 144.
- Del', G. D. (1982). *Plastichnost' deformirovannogo metalla. Fizika i tekhnika vysokikh davleniy*, 11, 28–32.
- Ogorodnikov, V., Del, G., Spiridonov, L. (1974). Plasticity of Metal Subjected to Complex Loading. *Izv. Vyssh. Uchebn. Zaved. Mashinost., 12, 22–26.*
- Aliieva, L. I., Dereven'ko, I. A., Sivak, R. I. (2013). Resurs plastichnosti v protsessah kombinirovannogo vydavlivaniya. *Obrabotka materialov davleniem*, 1 (34), 11–17.

DOI: 10.15587/1729-4061.2017.114269

GEOMETRICAL MODELING OF THE INERTIAL UNFOLDING OF A MULTI-LINK PENDULUM IN WEIGHTLESSNESS (p. 42-50)

Leonid Kutsenko

National University of Civil Protection of Ukraine, Kharkiv, Ukraine
ORCID: <http://orcid.org/0000-0003-1554-8848>

Olga Shoman

National Technical University “Kharkiv Polytechnic Institute”, Ukraine
ORCID: <http://orcid.org/0000-0002-3660-0441>

Oleg Semkiv

National University of Civil Protection of Ukraine, Kharkiv, Ukraine
ORCID: <http://orcid.org/0000-0002-9347-0997>

Leonid Zapolsky

The State Emergency Service of Ukraine, Kyiv, Ukraine
ORCID: <http://orcid.org/0000-0003-4357-2933>

Irina Adashevskay

National Technical University
 “Kharkiv Polytechnic Institute”, Kharkiv, Ukraine
ORCID: <http://orcid.org/0000-0001-5447-5114>

Volodymyr Danylenko

Kharkiv National University of
 Automobile and Highways, Kharkiv, Ukraine
ORCID: <http://orcid.org/0000-0003-4952-7498>

Victoria Semenova-Kulich

Ukrainian State University of Railway Transport, Kharkiv, Ukraine
ORCID: <http://orcid.org/0000-0001-7500-336X>

Dmitriy Borodin

Ukrainian State University of Railway Transport, Kharkiv, Ukraine
ORCID: <http://orcid.org/0000-0002-2105-023X>

Jaroslav Legeta

Uzhhorod National University, Uzhhorod, Ukraine
ORCID: <http://orcid.org/0000-0002-2579-3671>

We investigated a geometrical model of unfolding a rod frame of an orbital object as a process of oscillations of a multi-link pendulum under conditions of weightlessness and within an abstract plane. The initiation of oscillations is assumed to be driven by the pulse action on one of the nodal elements of the pendulum, implemented using a pulsed rocket engine. The transported (starting) position of a multilink pendulum shall be accepted in the “folded” form. A notation of the inertial frame unfolding is performed employing the Lagrange equation of the second kind, in which potential energy was not taken into consideration because of weightlessness.

It was established in the course of research:

- to unfold the structure, there is no need to synchronize the means of control over the magnitudes of angles in separate nodes;
- transverse oscillations of nodes (tremor) before the moment of full unfolding of a multi-link pendulum can be used as signal for the actuation of locks in order to fix the position of its adjacent links;
- based on a circuit for unfolding a single multi-link structure, it is possible to form multi-beam circuits with a shared non-movable attachment node (a triad as an example).

Reliability of the obtained approximate solution was tested using the created animated film about the unfolding process of the structure. An example of a four-link pendulum was studied in detail. The results might prove useful when designing the unfolding of large-size structures under conditions of weightlessness, for example, frames for solar mirrors.

Keywords: multi-link pendulum, large-scale structure, deployment in cosmos, mirror in space, Lagrangian equation of the second kind.

References

1. Lovegrove, K., Stein, W. (2012). Concentrating Solar Power Technology. Principles, Developments and Applications. Cambridge: Woodhead Publishing Limited, 708. doi: 10.1533/9780857096173
2. Krafft, A. E. (1979). The future of the space industry. Moscow: Mechanical Engineering, 200.
3. Barathwaj, G., Srinag, K. (2011). Wireless power transmission of space based solar power. Vol. 6. 2nd International Conference on Environmental Science and Technology, IPCBEE. IACSIT Press, Singapore, v2-227–v2-231.
4. Szuminski, W. (2014). Dynamics of multiple pendula without gravity. Chaotic Modeling and Simulation, 1, 57–67. Available at: http://www.cmsim.eu/papers_pdf/january_2014_papers/7_CMSIM_Journal_2014_Szuminski_1_57-67.pdf

5. Krylov, A. V., Churilin, S. A. (2011). Modeling of the disclosure of solar batteries of various configurations. Bulletin of the Moscow State Technical University. N. E. Bauman. Ser.: “Mechanical Engineering”, 1, 106–111.
6. Yudinsev, V. V. (2012). Modeling of the processes of disclosure of multi-element structures of space vehicles. Polelet, 5, 28–33.
7. Borzykh, S. V., Bakulin, D. V., Shchiblev, Yu. N. (1999). Modeling of the process of opening large-sized solar batteries. Aviakosmicheskaya tekhnika i tekhnologiya, 1, 35–41.
8. Bakulin, D. V., Borzykh, S. V., Ososov, N. S., Shchiblev, Yu. N. (2004). Modeling of the process of solar battery disclosure. Matem. Modeling, 16 (6), 88–92.
9. Bushuyev, A. Yu., Farafonov, B. A. (2014). Mathematical modeling of the process of opening a large solar battery. Mathematical model and numerical methods, 2, 101–114.
10. Anokhin, N. V. (2013). Reduction of a pendulum pendulum to a position of equilibrium by means of a single control torque. Izv. RAS. Theory and control systems, 5, 44–53.
11. Anan'evskiy, I. M., Anokhin, N. V. (2014). Control of the spatial motion of a multi-link inverted pendulum with the help of a moment applied to the first link. Mathematics and Mechanics, 78 (6), 755–765.
12. Schesnyak, S., Romanov, A. et. al. (2009). Designing and calculation of large-sized unfolding structures with the help of software complexes MSC.Software. CADmaster, 2-3, 28–36.
13. Boykov, V. G. (2009). The program complex of the automated dynamic analysis of multi-component mechanical systems EULER. CAD and graphics, 9, 17–20.
14. Zimin, V., Krylov, A., Meshkovskii, V., Sdobnikov, A., Fayzullin, F., Churilin, S. (2014). Features of the Calculation Deployment Large Transformable Structures of Different Configurations. Science and Education of the Bauman MSTU, 10, 179–191. doi: 10.7463/1014.0728802
15. Simulation of the process of solar battery openings of Yamal-200 communications satellite. Available at: <http://www.euler.ru/distr/praxis/space/yamal200.pdf>
16. Gmiterko, A., Grossman, M. (2010). N-link Inverted Pendulum Modeling. Recent Advances in Mechatronics, 151–156. doi: 10.1007/978-3-642-05022-0_26
17. Martinez-Alfaro, H. Obtaining the dynamic equations, their simulation, and animation for N pendulums using Maple. Available at: <http://www2.esm.vt.edu/~anayfeh/conf10/Abstracts/martinez-alfaro.pdf>
18. Kutsenko, L. N., Adashevskaya, I. Yu. (2008). Geometric modeling of the oscillation of multilink pendulums. Kharkiv: “NTMT”, 176.
19. Kutsenko, L. M. Iliustratsiy do heometrychnoho modeliuвання inertsynoho rozkryttia bahatolankovoho maiatnyka u nevahomosti. Available at: <http://repositsc.nuczu.edu.ua/handle/123456789/4868>

DOI: 10.15587/1729-4061.2017.110683

DETERMINING PERFORMANCE EFFICIENCY OF THE DIFFERENTIAL IN A DEVICE FOR SPEED CHANGE THROUGH EPICYCLE (p. 51-57)

Volodymyr Malashchenko

Lviv Polytechnic National University, Lviv, Ukraine
ORCID: <http://orcid.org/0000-0001-7889-7303>

Oleh Strilets

National University of Water and
 Environmental Engineering, Rivne, Ukraine
ORCID: <http://orcid.org/0000-0003-3834-7176>

Volodymyr Strilets

National University of
 Water and Environmental Engineering, Rivne, Ukraine
ORCID: <http://orcid.org/0000-0003-2098-2315>

We determined coefficient of performance efficiency for the multi-stage toothed differentials in a device for speed change when the drive link is a sun cogwheel of the first stage, the driven link is a carrier, or vice versa, with the epicycles of separate stages as control links.

Analytical dependences for determining performance efficiency of the multistage toothed differentials were derived using a method of potential power, which is the product of circular force on teeth and circular velocity of the point of initial circle of the satellite relative to the carrier, or the product of torque of a given force by angular velocity. Given the complexity of the task, we performed here a theoretical-computer study into performance efficiency of multistage toothed differentials in the devices for speed change with hydraulic systems using two- and three-stage transmissions as examples. By using a given procedure, it is possible to determine performance efficiency of the four- and multistage transmissions.

We constructed graphical dependences for performance efficiency of two- and three-stage transmissions. These charts enable visual tracking of change in the value of performance efficiency depending on angular velocity of the epicycle, transfer ratio, and the number of stages.

It was established that for the two- and three-stage toothed differentials the condition of automatic braking is not applicable because performance efficiency is far greater than zero. In all cases, an increase in the number of stages in toothed differential results in the decrease of performance efficiency, which confirms general patterns.

The results obtained might have practical application at the stage of development and design of new devices for speed control, they make it possible to estimate operation of multi-stage toothed differentials in terms of energy consumption and automatic braking, thereby creating a basis for further research.

Keywords: performance efficiency, toothed differential, change in speed, satellite, epicycle.

References

- Sklyarov, V. N., Volkov, V. P., Sklyarov, N. V., Rudenko, I. D., Sergienko, N. E. (2013). *Avtomobil. Osobennosti konstruksii*. Kharkiv, 520.
- Khmara, L. A., Kravets, S. V., Skobliuk, M. P. et. al.; Khmara, L. A., Kravets, S. V. (Eds.) (2014). *Mashyny dlia zemlianykh robot. Dni-propetrovsk; Rivne; Kharkiv: KhNADU*, 546.
- Bochkov, V. M., Silin, R. I., Havrylchenko, O. V.; Silin, R. I. (Ed.) (2009). *Metalorizalni verstaty*. Lviv: Vydavnytstvo Lvivskoi politekhniki, 268.
- D'yakov, I. F., Kuznetsov, V. A., Tarhanov, V. I. (2003). *Stupenchatye i planetarnye korobki peredach mekhanicheskikh transmissiy*. Ul'yanovsk: UIGTU, 120.
- Sharipov, V. M., Krumbol'dt, L. N., Marinkin, A. P. (2000). *Planetarnye korobki peredach kolesnyh i gusenichnyh mashin*. Moscow: MGTU "MAMI", 142.
- Narbut, A. N. (2013). *Gidrodinamicheskie peredachi*. Moscow: KNORUS, 176.
- Haritonov, S. A. (2003). *Avtomaticheskije korobki peredach*. Moscow: Astrel' AST, 280.
- Kudenko, M. M., Strilets, V. M. (2001). Pat. No. 44135 UA. *Vantazhouporny zupynnyk [Load-support stop gear]*. MPK V66D5/32. No. 2001053400; declared: 21.05.2001; published: 15.03.2005, Bul. No. 3.
- Kudenko, N. M., Strelets, V. N. (2001). Pat. No. 2211796 RU. *Ostanovka dlya gruzha, peremeshchaemogo mekhanizmom pod'ema [Stop gear for a load moved by a lifting mechanism]*. MPK V66D5/00. No. 2001107699/28; declared: 21.03.2001; published: 10.09.2003, Bul. No. 25.
- Kinytskyi, Ya. T. (2002). *Teoriya mekhanizmiv i mashyn*. Kyiv: Naukova Dumka, 660.
- Uicker, J. J., Pennock, G. R., Shigley, J. E. (2003). *Theory of Machines and Mechanisms*. Oxford University Press, New York, USA.
- Hohn, B.-R., Stahl, K., Gwinner, P. (2013). *Light-Weight Design for Planetary Gear Transmissions*. *Geartechnology*, 96–103.
- Malashchenko, V. O., Strilets, O. R., Strilets, V. M. (2015). *Klasyfikatsiya sposobiv i prystroiv keruvannia protsesom zminy shvydkosti v tekhnitsi. Pidiomno-transportna tekhnika*, 1, 70–78.
- Pawar, P. V. (2015). *Design of two stage planetary gear train for high reduction ratio*. *International Journal of Research in Engineering and Technology*, 04 (06), 150–157. doi: 10.15623/ijret.2015.0406025
- Bahk, C.-J., Parker, R. G. (2013). *Analytical investigation of tooth profile modification effects on planetary gear dynamics*. *Mechanism and Machine Theory*, 70, 298–319. doi: 10.1016/j.mechmachtheory.2013.07.018
- Huang, Q., Wang, Y., Huo, Z., Xie, Y. (2013). *Nonlinear Dynamic Analysis and Optimization of Closed-Form Planetary Gear System*. *Mathematical Problems in Engineering*, 2013, 1–12. doi: 10.1155/2013/149046
- Pleguezuelos, M., Pedrero, J. I., Sánchez, M. B. (2013). *Analytical Expressions of the Efficiency of Standard and High Contact Ratio Involute Spur Gears*. *Mathematical Problems in Engineering*, 2013, 1–14. doi: 10.1155/2013/142849
- Chen, C. (2013). *Power flow and efficiency analysis of epicyclic gear transmission with split power*. *Mechanism and Machine Theory*, 59, 96–106. doi: 10.1016/j.mechmachtheory.2012.09.004
- Chen, C., Chen, J. (2015). *Efficiency analysis of two degrees of freedom epicyclic gear transmission and experimental validation*. *Mechanism and Machine Theory*, 87, 115–130. doi: 10.1016/j.mechmachtheory.2014.12.017
- Laus, L. P., Simas, H., Martins, D. (2012). *Efficiency of gear trains determined using graph and screw theories*. *Mechanism and Machine Theory*, 52, 296–325. doi: 10.1016/j.mechmachtheory.2012.01.011
- Strilets, O. R. (2015). *Keruvannia zminamy shvydkosti za dopomohoiu dyferentsialnoi peredachi cherez epitsykl*. *Visnyk Ternopil'skoho natsionalnoho tekhnichnoho universytetu*, 4, 131–137.
- Malashchenko, V., Strilets, O., Strilets, V. (2017). *Justification of efficiency of epicyclic gear train in device for speed changes management*. *Ukrainian Journal of Mechanical Engineering and Materials Science*, 3 (1), 72–76.
- Strilets, O. R. (2007). Pat. No. 25335 UA. *Zubchastyi dyferentsial z prystroiem dlia keruvannia zminamy shvydkosti*. MPK (2006) F16N1/28. No. u200504847; declared: 19.02.2007; published: 10.08.2007, Bul. No. 12.
- Strilets, O. R. (2007). Pat. No. 28489 UA. *Planetarna korobka peredach*. MPK (2006) V60K17/06. No. u200709132; declared: 09.08.2007; published: 10.12.2007, Bul. No. 20.

DOI: 10.15587/1729-4061.2017.117683

SEARCH FOR TWO-FREQUENCY MOTION MODES OF SINGLE-MASS VIBRATORY MACHINE WITH VIBRATION EXCITER IN THE FORM OF PASSIVE AUTO-BALANCER (p. 58-66)

Volodymyr Yatsun

Central Ukrainian National
Technical University, Kropivnitskiy, Ukraine
ORCID: <http://orcid.org/0000-0003-4973-3080>

Gennadiy Filimonikhin

Central Ukrainian National
Technical University, Kropivnitskiy, Ukraine
ORCID: <http://orcid.org/0000-0002-2819-0569>

Kostyantyn Dumenko

Central Ukrainian National
Technical University, Kropivnitskiy, Ukraine
ORCID: <http://orcid.org/0000-0002-9718-6408>

Andrey Nevdakha
Central Ukrainian National
Technical University, Kropivnitskiy, Ukraine
ORCID: <http://orcid.org/0000-0002-0849-9331>

Dynamics of a single-mass vibratory machine with rectilinear translational motion of the platform and a vibration exciter in the form of a ball, a roller, or a pendulum auto-balancer was analytically explored.

The steady-state motion modes, close to dual-frequency modes were found. At these motions, loads in the auto-balancer create constant imbalance, cannot catch up with the rotor and get stuck at a certain frequency. In this way, loads operate as the first vibration exciter, exciting vibrations at frequency of the loads getting stuck. The second vibration exciter is formed by unbalanced mass on the auto-balancer body. The mass rotates at rotor speed and excites more rapid vibrations with this frequency. It was found that despite a strong asymmetry of supports, the auto-balancer excites almost perfect dual-frequency vibrations. Deviations from the dual-frequency law are proportional to the ratio of loads' mass to the mass of the entire machine and do not exceed 2 %.

It was established that at small forces of external and internal resistance, when the loads' mass is much smaller than the platform's mass, etc., there are three characteristic rotor speeds. These speeds are larger than the resonance velocity of platform oscillations. At the same time:

- at the rotor speeds smaller than the first characteristic speed, there is only frequency when the loads get stuck, in this case it is smaller than the resonance velocity of platform oscillations;

- at the above-resonance rotor speeds, located between the first and the second characteristic speeds, there are three frequencies when the loads get stuck, among which only one is below-resonance;

- at the above-resonance rotor speeds, located between the second and the third characteristic speeds, there are three frequencies of the loads getting stuck, in this case, they are all above-resonance;

- at the above-resonance rotor speeds, exceeding the third characteristic speed, there is only one frequency when the loads get stuck, in addition, it is above-resonant and close to the rotor speed.

Only at the rotor speeds smaller than the second characteristic speed, there always exists one, and only one, below-resonance frequency of the loads getting stuck.

Keywords: inertial vibration exciter, dual-frequency vibration, resonance vibratory machine, auto-balancer, single-mass vibratory machine, Sommerfeld effect.

References

1. Bukin, S. L., Maslov, S. G., Ljutyj, A. P., Reznichenko, G. L. (2009). Intensification of technological processes through the implementation of vibrators biharmonic modes. *Enrichment of minerals*, 36 (77) – 37 (78), 81–89.
2. Kryukov, B. I. (1967). *Dinamika vibratsionnykh mashin rezonansnogo tipa* [Dynamics of vibratory machines of resonance type]. Kyiv: Naukova dumka, 210.
3. Lanets, O. S. (2008). *Vysokoeffektyvni mizhrezonansni vibratsiyni mashyny z elektromagnitnym pryvodom (teoretychni osnovy ta praktyka stvorennia)* [High-Efficiency Inter-Resonances Vibratory Machines with an Electromagnetic Vibration Exciter (Theoretical Bases and Practice of Creation)]. Lviv: Publishing house of Lviv Polytechnic National University, 324.
4. Filimonikhin, G. B., Yatsun, V. V. (2015). Method of excitation of dual frequency vibrations by passive autobalancers. *Eastern-European Journal of Enterprise Technologies*, 4 (7 (76)), 9–14. doi: 10.15587/1729-4061.2015.47116
5. Artyunin, A. I. (1993). Research of motion of the rotor with autobalance. *Proceedings of the higher educational institutions. Mechanical Engineering*, 1, 15–19.
6. Filimonihin, G. B. (2004) *Zrivnovazhennia i vibrozahyst rotoriv avtobalansyramy z tverdymy koryguval'nymy vantazhamy* [Balancing and protection from vibrations of rotors by autobalancers with rigid corrective weights]. Kirovograd: KNTU, 352.
7. Sommerfeld, A. (1904). Beitrage zum dynamischen Ausbay der Festigkeislehre. *Zeitschrift des Vereins Deutscher Ingenieure*, 48 (18), 631–636.
8. Filimonikhin, G. B., Yatsun, V. V. (2016). Investigation of the process of excitation of dual-frequency vibrations by ball auto-balancer of GIL 42 screen. *Eastern-European Journal of Enterprise Technologies*, 1 (7 (79)), 17–23. doi: 10.15587/1729-4061.2016.59881
9. Yatsun, V., Filimonikhin, G., Dumenko, K., Nevdakha, A. (2017). Experimental research of rectilinear translational vibrations of a screen box excited by a ball balancer. *Eastern-European Journal of Enterprise Technologies*, 3 (1 (87)), 23–29. doi: 10.15587/1729-4061.2017.101798
10. Yatsun, V., Filimonikhin, G., Dumenko, K., Nevdakha, A. (2017). Equations of motion of vibration machines with a translational motion of platforms and a vibration exciter in the form of a passive auto-balancer. *Eastern-European Journal of Enterprise Technologies*, 5 (1 (89)), 19–25. doi: 10.15587/1729-4061.2017.111216
11. Blekhman, I. I. (1981). *Sinkhronizatsiya v prirode i tekhnike* [Synchronisation in Nature and Technical Engineering]. Moscow: Nauka, 352.
12. Lanets, O. V., Shpak, Ya. V., Lozynskiy, V. I., Leonovych, P. Yu. (2013). Realizatsiya efektu Zommerfel'da u vibratsionomu maydanchyku z inertsionym pryvodom [Realization of the Sommerfeld effect in a vibration platform with an inertia drive]. *Avtomatyzatsiya vyrobnychikh protsesiv u mashynobuduvanni ta prykladobuduvanni*, 47, 12–28. Available at: http://nbuv.gov.ua/UJRN/Avtomatyzac_2013_47_4
13. Kuzo, I. V., Lanets, O. V., Hurskyi, V. M. (2013). Syntez nyz'kochastotnykh rezonansnykh vibratsiynykh mashyn z aero-inertsionym zburennyam [Synthesis of low-frequency resonance-vibratory machines with an aeroinertia drive]. *Naukovyi visnyk Natsional'noho hirnychoho universytetu*, 2, 60–67. Available at: http://nbuv.gov.ua/UJRN/Nvngu_2013_2_11
14. Yaroshevich, N. P., Zabrodets, I. P., Yaroshevich, T. S. (2016). Dynamics of Starting of Vibrating Machines with Unbalanced Vibroexciters on Solid Body with Flat Vibrations. *Applied Mechanics and Materials*, 849, 36–45. doi: 10.4028/www.scientific.net/amm.849.36
15. Ryzhik, B., Sperling, L., Duckstein, H. (2004). Non-synchronous Motions Near Critical Speeds in a Single-plane Autobalancing Device. *Technische Mechanik*, 24, 25–36.
16. Lu, C.-J., Tien, M.-H. (2012). Pure-rotary periodic motions of a planar two-ball auto-balancer system. *Mechanical Systems and Signal Processing*, 32, 251–268. doi: 10.1016/j.ymssp.2012.06.001
17. Artyunin, A. I., Alhunsae, G. G., Serebrennikov, K. V. (2005). Primenenie metoda razdeleniya dvizheniy dlya issledovaniya dinamiki rotornoy sistemy s gibkim rotorom i mayatnikovyim avtobalansirov [The application of the method of separation of movements to study the dynamics of a rotor system with a flexible rotor and a pendulum autobalance]. *Izvestiya vysshikh uchebnykh zavedeniy. Mashinostroenie*, 9, 8–14.
18. Artyunin, A. I., Eliseyev, S. V. (2013). Effect of “Crawling” and Peculiarities of Motion of a Rotor with Pendular Self-Balancers. *Applied Mechanics and Materials*, 373-375, 38–42. doi: 10.4028/www.scientific.net/amm.373-375.38
19. Nayfeh, A. H. (1993). *Introduction to Perturbation Techniques*. New York, United States: John Wiley and Sons Ltd., 533.

DOI: 10.15587/1729-4061.2017.117664

COMPUTER VARIANT DYNAMIC FORMING OF TECHNICAL OBJECTS ON THE EXAMPLE OF THE AIRCRAFT WING (p. 67-73)

Volodymyr Vanin

National Technical University of Ukraine
«Igor Sikorsky Kyiv Polytechnic Institute», Kyiv, Ukraine
ORCID: <http://orcid.org/0000-0001-7008-7269>

Gennadii Virchenko

National Technical University of Ukraine
«Igor Sikorsky Kyiv Polytechnic Institute», Kyiv, Ukraine
ORCID: <http://orcid.org/0000-0001-9586-4538>

Serhii Virchenko

National Technical University of Ukraine
«Igor Sikorsky Kyiv Polytechnic Institute», Kyiv, Ukraine
ORCID: <http://orcid.org/0000-0002-9320-4664>

Andrii Nezenko

National Technical University of Ukraine
«Igor Sikorsky Kyiv Polytechnic Institute», Kyiv, Ukraine
ORCID: <http://orcid.org/0000-0002-2403-477X>

This article describes a mathematical apparatus of dynamic formation of technical objects on the basis of a study that has devised it with the aim to improve and develop computerized structural and parametric geometric models by appropriate integration with their available mathematical support. The practical value of the obtained results consists in creating a methodology for computer variant dynamic shaping, which helps flexibly combine the designing and manufacturing of technical objects, as is illustrated by the example of the wing of an aircraft. The proposed techniques provide an automated design of the wing surface and a computer simulation of such technological operations for manufacturing a centreplane longeron as cutting, pressure treatment, assembly, etc. The created structural and parametric geometric models contribute to the multicriteria optimization of technical objects throughout the lifecycle. The described approach can also be used for the computer variant dynamic formation of such structural units of the airframe as ribs, panels, sections, bends, and the like. Through further studying, the research materials can be

distributed to diverse products of mechanical engineering and other industries.

Keywords: computer variant dynamic formation, aircraft wing, structural and parametric geometric modeling.

References

1. Ketul, B. B., Dipal, M. P., Nirmith, K. S. (2014). Parametric modelling of Oldham coupling. *International Journal of Innovative Research in Science, Engineering and Technology*, 3 (2), 9120–9125.
2. Popescu, D. I., Chioltean, L. (2013). Design Configuration under Parametric Control. *Scientific Bulletin of the Politehnica University of Timisoara, Transactions on Hydrotechnics*, 58 (72), 67–70.
3. Pomazan, V. (2013). Assembly Top Down Design in Parametric CAD. *Scientific Bulletin of the Politehnica University of Timisoara, Transactions on Hydrotechnics*, 58 (72), 153–156.
4. Sun, W., Ma, H., Li, C., Wen, B. (2009). Study on Parametric Modeling Based on Visual Optimization Design of Mechanical Product. 2009 Second International Conference on Intelligent Computation Technology and Automation. doi: 10.1109/icit.2009.304
5. Gavrilă, C. C. (2016). 3D modeling, fem analysis and detail design for a testing device with spherical joint. *Annals of the oradea university. Fascicle of Management and Technological Engineering*, Volume XXV (XV), 2016/1 (1). doi: 10.15660/auofmte.2016-1.3201
6. Vanin, V. V., Virchenko, H. A. (2009). Vyznachennia ta osnovni polozhennia strukturno-parametrychnoho heometrychnoho modeliuвання. *Heometrychne ta kompiuterne modeliuвання*, 23, 42–48.
7. Vanin, V. V., Virchenko, H. A. (2014). Strukturno-parametrychni heometrychni modeli yak zasib intehratsiy avtomatyzovanoho proektuvannia suchasnoho litaka. *Visnyk Khersonskoho nats. tekhn. un-tu.*, 3, 571–574.
8. Taras, I. P., Virchenko, V. G. (2013). Computer combinatorial-variation geometric modeling of engineering objects. *Scientific Bulletin of the Politehnica University of Timisoara, Transactions on Hydrotechnics*, 58 (72), 173–176.
9. Vanin, V. V., Virchenko, H. I., Virchenko, S. H. (2014). Variantne modeliuвання heometrychnykh ob'ektiv metodom poliparmetryzatsiy. *Problemy informatsiynykh tekhnolohiy*, 2, 76–79.
10. Shambina, S. L., Virchenko, V. G. (2013). Modul'noe variantnoe geometricheskoe modelirovanie slozhnyh tekhnicheskikh ob'ektov. *Vestnik Rossiyskogo universiteta druzhby narodov*, 2, 5–8.