

## ABSTRACT AND REFERENCES

## TECHNOLOGY ORGANIC AND INORGANIC SUBSTANCES

DOI: 10.15587/1729-4061.2018.150690

**TECHNOLOGICAL FEATURES IN OBTAINING HIGHLY EFFECTIVE HYDROGEL DRESSINGS FOR MEDICAL PURPOSES (p. 6-13)****Oleksandr Grytsenko**Lviv Polytechnic National University, Lviv, Ukraine  
ORCID: <http://orcid.org/0000-0001-8578-4657>**Anna Pokhmurska**Lviv Polytechnic National University, Lviv, Ukraine  
ORCID: <http://orcid.org/0000-0003-3722-0616>**Sofia Suberliak**Lviv Polytechnic National University, Lviv, Ukraine  
ORCID: <http://orcid.org/0000-0003-4280-910X>**Mykola Kushnirchuk**Danylo Halytsky Lviv National Medical University, Lviv, Ukraine  
ORCID: <http://orcid.org/0000-0002-0589-4045>**Marta Panas**Danylo Halytsky Lviv National Medical University, Lviv, Ukraine  
ORCID: <http://orcid.org/0000-0002-3302-6974>**Volodymyr Moravskiy**Lviv Polytechnic National University, Lviv, Ukraine  
ORCID: <http://orcid.org/0000-0001-8524-6269>**Roman Kovalchuk**Hetman Petro Sahaidachnyi National Army Academy, Lviv, Ukraine  
ORCID: <http://orcid.org/0000-0001-8337-8591>

The new technology of formation of hydrogel dressings for medical purposes, containing particles of silver was developed. To obtain metal-containing composite hydrogels, we proposed a high-tech single-stage method, which involves polymerization of polymer-monomer compositions based on polyvinyl-pyrrolidone and 2-hydroxyethylmethacrylate with simultaneous chemical reduction of silver ions from its nitrate by ethanol. It was found by the thermometric research that the temperature conditions needed for chemical reduction of silver ions are achieved due to the heat, which is released at the exothermic polymerization reaction. The temporal and temperature parameters of polymerization depending on the composition of the original polymer-monomer composition, the content of solvent and of the initiator, and silver nitrate concentration were determined. They include the initial temperature of polymerization, maximum exothermic temperature, the time of reaching the maximum exothermic temperature, and duration of effect gel. The use of combined initiating system of iron (II) sulfate + benzoyl peroxide makes it possible to implement the process of obtaining hydrogels, containing silver particles, at room temperature, in the open air. The synthesis is technologically simple and is executed without complicated apparatus design. The authors proposed a new technology of formation of hydrogel films with the use of the centrifugal method. Polymerization with silver deposition occurs in the centrifugal form simultaneously with film formation, which allows obtaining the materials with predictable properties that have a uniform distribution of the filler with equal thickness and high quality surfaces in the polymer matrix. The film products obtained as a result of the developed technology can swell in water and other polar solvents, are characterized by durability, elasticity, bactericidal and antifungal properties. The results of the clinical

studies showed sufficient clinical effectiveness of using the developed hydrogel dressings for medical purposes based on hydrogels, containing silver particles. Such materials in combination with the integrated therapy help to increase the speed and intensity of treatment of trophic venous ulcers of lower limbs.

**Keywords:** hydrogel medical dressings, silver-containing hydrogels, centrifugal formation, metal-polymeric composites, trophic ulcers.

**References**

- Schexnaider, P., Schmidt, G. (2008). Nanocomposite polymer hydrogels. *Colloid and Polymer Science*, 287 (1), 1–11. doi: <https://doi.org/10.1007/s00396-008-1949-0>
- Nicolais, L., Carotenuto, G. (Eds.) (2004). *Metal-Polymer Nanocomposites*. John Wiley & Sons. doi: <https://doi.org/10.1002/0471695432>
- Grytsenko, O., Spišák, E., Dulebová, L., Moravskii, V., Suberlyak, O. (2015). Sorption Capable Film Coatings with Variable Conductivity. *Materials Science Forum*, 818, 97–100. doi: <https://doi.org/10.4028/www.scientific.net/msf.818.97>
- Vashchuk, V. V., Kyryk, T. P., Kushnirchuk, M. I., Baidala, R. P., Ivanyshyn, A. Z., Hrytsenko, O. M. (2018). Nova metodyka mist-sevoi terapiyi trofichnykh vyrazok nyzhnikh kintsivok. *Kharkivska khirurgichna shkola*, 1, 51–53.
- Norman, G., Dumville, J. C., Westby, M. J., Stubbs, N., Soares, M. O. (2017). Dressings and topical agents for treating venous leg ulcers. *Cochrane Database of Systematic Reviews*. doi: <https://doi.org/10.1002/14651858.cd012583>
- O'Meara, S., Richardson, R., Lipsky, B. A. (2014). Topical and Systemic Antimicrobial Therapy for Venous Leg Ulcers. *JAMA*, 311 (24), 2534. doi: <https://doi.org/10.1001/jama.2014.4574>
- Raffetto, J. D., Eberhardt, R. T., Dean, S. M., Ligi, D., Mannello, F. (2016). Pharmacologic treatment to improve venous leg ulcer healing. *Journal of Vascular Surgery: Venous and Lymphatic Disorders*, 4 (3), 371–374. doi: <https://doi.org/10.1016/j.jvsv.2015.10.002>
- Savchyn, V. S., Lukavetskyi, O. V., Huda, N. V., Stoianovskiy, I. V., Chemerys, O. M., Tuziuk, N. V. (2015). Pat. No. 111557 UA. Method for treating wounds using lyophilized xenodermografts containing silver as antibacterial component. No. a201504337; declared: 05.05.2015; published: 10.05.2016, Bul. No. 9.
- Vlasenko, I. O., Ivanov, E. A., Davtian, L. L., Popovych, V. P. (2014). Study of assortment of medicinal agents for local treatment of trophic ulcers. *Zbirnyk naukovykh prats spivrobitnykiv NMAPO im. P. L. Shupyka*, 23 (4), 437–446.
- Suberlyak, O., Grytsenko, O., Hishchak, Kh., Hnatchuk, N. (2013). Researching influence the nature of metal on mechanism of synthesis polyvinilpyrrolidone metal copolymers. *Chemistry & Chemical technology*, 7 (3), 289–294.
- Kacarevic-Popovic, Z., Dragasevic, M., Krkljes, A., Popovic, S., Jovanovic, Z., Tomic, S., Miskovic-Stankovic, V. (2010). On the Use of Radiation Technology for Nanoscale Engineering of Silver/Hydrogel Based Nanocomposites for Potential Biomedical Application. *The Open Conference Proceedings Journal*, 1 (1), 200–206. doi: <https://doi.org/10.2174/22102892010010100200>
- Palza, H. (2015). Antimicrobial Polymers with Metal Nanoparticles. *International Journal of Molecular Sciences*, 16 (1), 2099–2116. doi: <https://doi.org/10.3390/ijms16012099>
- Hres, O. V., Lebediev, Ye. V., Matiushov, V. F. (2008). Silver-containing polymer nanocomposites. *Polimernyi zhurnal*, 30 (3), 186–191.
- Shmakov, S. N. (2008). Synthesis and properties of silver nanoparticles stabilized by polymers. *Abstr. III Int. Workshop «Specialty*

- polymers for environmentprotection, bio-, nanotechnology and medicine». *Almaty*, 14.
15. Tarnavchik, I., Voronov, A., Kohut, A., Nosova, N., Varvarenko, S., Samaryk, V., Voronov, S. (2009). Reactive Hydrogel Networks for the Fabrication of Metal-Polymer Nanocomposites. *Macromolecular Rapid Communications*, 30 (18), 1564–1569. doi: <https://doi.org/10.1002/marc.200900285>
  16. Yanez, F., Concheiro, A., Alvarezlorenzo, C. (2008). Macromolecule release and smoothness of semi-interpenetrating PVP–pHEMA networks for comfortable soft contact lenses. *European Journal of Pharmaceutics and Biopharmaceutics*, 69 (3), 1094–1103. doi: <https://doi.org/10.1016/j.ejpb.2008.01.023>
  17. Samaryk, V., Varvarenko, S., Tarnavchik, I., Nosova, N., Puzko, N., Voronov, S. (2008). Formation of Polymer Nanolayers with Special Properties at Polymer Surfaces. *Macromolecular Symposia*, 267 (1), 113–117. doi: <https://doi.org/10.1002/masy.200850721>
  18. Don, T.-M., Hsu, Y.-C., Tai, H.-Y., Fu, E., Cheng, L.-P. (2012). Preparation of bi-continuous macroporous polyamide copolymer membranes for cell culture. *Journal of Membrane Science*, 415–416, 784–792. doi: <https://doi.org/10.1016/j.memsci.2012.05.070>
  19. Melnyk, Yu. Ya., Yatsulchak, H. V., Hil, N. V., Suberliak, O. V. (2013). Tonkoplivkovi polimerni kompozyty membrannoho typu z pidvyshchenymy fizyko-mekhanichnymy vlastyvostiamy. *Visnyk Natsionalnoho universytetu «Lvivska politehnika»*. *Khimiya, tekhnolohiya rechovyn ta yikh zastosuvannia*, 761, 433–436.
  20. Suberliak, O. V. (1982). Termometrycheskye yssledovaniya blochnoi trekhmernoii polymeryzatsyy kompozytsyi na osnove 2-OEMA. *Visnyk Natsionalnoho universytetu «Lvivska politehnika»*. *Khimiya, tekhnolohiya rechovyn ta yikh zastosuvannia*, 163, 41.
  21. Gricenko, O. M., Suberlyak, O. V., Moravs'kiy, V. S., Gayduk, A. V. (2016). Investigation of nickel chemical precipitation kinetics. *Eastern-European Journal of Enterprise Technologies*, 1 (6 (79)), 26–31. doi: <https://doi.org/10.15587/1729-4061.2016.59506>
  22. Suberlyak, O., Grytsenko, O., Kochubei, V. (2015). The Role of FeSO<sub>4</sub> in the Obtaining of Polyvinylpyrrolidone Copolymers. *Chemistry & Chemical Technology*, 9 (4), 429–434. doi: <https://doi.org/10.23939/chcht09.04.429>
  23. Suberlyak, O., Skorokhoda, V., Grytsenko, O. (2004). Complex PVP–Men+ – active catalyst of vinyl monomers polymerization. *Materialy polimerowe i ich przetworstwo*, 1, 140–145.
  24. Grytsenko, O. (2014). The features of film composite hydrogel materials obtaining technology by centrifugal molding. Vol. II. Technological and design aspects of extrusion and injection moulding of thermoplastic polymer composites and nanocomposites. *Kosice*.

DOI: 10.15587/1729-4061.2018.150771

**OBTAINING, STUDYING THE PROPERTIES, AND APPLICATION OF ZIRCONIUM(IV) OXYMETHANESULFONATE (p. 1-19)**

**Victor Vereschak**

Ukrainian State University of Chemical Technology, Dnipro, Ukraine  
ORCID: <https://orcid.org/0000-0003-0914-6527>

The author has investigated the process to obtain zirconium (IV) oxymethanesulfonate via the interaction between methane sulfonic acid (CH<sub>3</sub>SO<sub>3</sub>H) (MSA) and zirconium (IV) oxocarbonate (ZrOCO<sub>3</sub>nH<sub>2</sub>O), and explored its basic physical-chemical and technological properties. The research was undertaken to address the lack of data on the chemistry of such a class of organic compounds as zirconium (IV), as well as to examine their possible application in modern materials science.

The methods of element, X-ray phase, thermal, and infrared analyses have confirmed that the product of interaction between zirconium (IV) oxocarbonate (ZrOCO<sub>3</sub>nH<sub>2</sub>O) and methane sulfonic

acid is zirconium (IV) oxymethanesulfonate with the composition ZrO(CH<sub>3</sub>SO<sub>3</sub>)<sub>2</sub>·4H<sub>2</sub>O.

It has been established that the synthesized zirconium (IV) oxymethanesulfonate is a white crystalline powder, which dissolves well in water while is weakly soluble in ethanol and isopropyl alcohol. It absorbs moisture in the open air. It thermally decomposes in the temperature range of 390–410 °C, forming a low-temperature cubic zirconium dioxide modification that, at temperatures above 750 °C, consistently passes into the monoclinic structure of zirconium dioxide. At the zirconium (IV) oxymethanesulfonate thermolysis there form the nanodispersed powders of zirconium dioxide whose size of primary particles is 20–50 nm, which, under the action of dispersion forces, agglomerate into aggregates of 200–400 nm. The specific surface of powders, determined based on a BET procedure, is 32 m<sup>2</sup>/g. It has been shown that the aqueous-alcohol solutions of ZrO(CH<sub>3</sub>SO<sub>3</sub>)<sub>2</sub>·4H<sub>2</sub>O actively interact with solid surfaces thereby forming hyperfine near-the-surface polymerized films, from which, when treated thermally, the surface coatings are formed from zirconium dioxide. Thus, new data have been acquired on the chemistry of complex compounds of zirconium(IV). This paper shows promising application of zirconium (IV) oxymethanesulfonate for the needs of modern materials science.

**Keywords:** methane sulfonic acid, methane sulfonate, zirconium (IV) oxymethanesulfonate, complex compound, nanocrystalline powders, zirconium oxide, surface films.

**References**

1. Wincewicz, K., Cooper, J. (2005). Taxonomies of SOFC material and manufacturing alternatives. *Journal of Power Sources*, 140 (2), 280–296. doi: <https://doi.org/10.1016/j.jpowsour.2004.08.032>
2. Vasylyev, O. D., Brodnikovskiy, Y. M., Brychevskiy, M. M. et al. (2018). From Powder to Power: Ukrainian Way. *SF Journal of Material and Chemical Engineering*, 1. Available at: <https://scienceforcasoa.com/Articles/SJMCE-V1-E1-1001.pdf>
3. Puzyrev, I. S., Alyabyshev, A. V., Lipilin, A. S., Ivanov, V. V., Yatluk, Yu. G. (2009). Sintez polioliatov cirkonila s ih posleduyushchim prevrashcheniem v nanorazmernyy dioksid cirkoniya. *Izvestiya AN. Ser.: Khimiya*, 6, 1078–1085.
4. Collins, D. E., Bowman, K. J. (1998). Influence of atmosphere on crystallization of zirconia from a zirconium alkoxide. *Journal of Materials Research*, 13 (05), 1230–1237. doi: <https://doi.org/10.1557/jmr.1998.0175>
5. Yoldas, B. E. (1977). Preparation of glasses and ceramics from metal-organic compounds. *Journal of Materials Science*, 12 (6), 1203–1208. doi: <https://doi.org/10.1007/bf02426858>
6. Gernon, M. D., Wu, M., Buszta, T., Janney, P. (1999). Environmental benefits of methanesulfonic acid. *Green Chemistry*, 1 (3), 127–140. doi: <https://doi.org/10.1039/a900157c>
7. Tuszynskiy, V. Dzh. (1990). Svoystva metansul'fokisloty i ee primeneniye v elektrohimicheskikh sistemah. *Elektrohimiya*, 26 (2), 249–251.
8. Kapoor, R., Wadhawan, P., Kapoor, P. (1987). Preparation, properties, and characterization of methanesulfonate complexes of arsenic(III), antimony (III), and bismuth(III). *Canadian Journal of Chemistry*, 65 (6), 1195–1199. doi: <https://doi.org/10.1139/v87-200>
9. Wang, R., Li, R., Jiang, H., Gong, H., Bi, Y. (2017). Crystal structure, thermal decomposition mechanism and catalytic performance of hexaquaaluminum methanesulfonate. *Journal of Coordination Chemistry*, 70 (8), 1327–1338. doi: <https://doi.org/10.1080/00958972.2017.1287907>
10. Trella, T., Frank, W. (2012). Hexaquaaluminium(III) tris(methanesulfonate). *Acta Crystallographica Section E Structure Reports Online*, 68 (8), m1136–m1137. doi: <https://doi.org/10.1107/s1600536812033235>

11. Preda, A. M., Kitschke, P., Rüffer, T., Lang, H., Mehring, M. (2016). Synthesis and Characterization of the Germanium Sulfonate  $\text{Ge}(\text{CH}_3\text{SO}_3)_2$ - a 3D Coordination Network Solid. *Zeitschrift Für Anorganische Und Allgemeine Chemie*, 642 (6), 467–471. doi: <https://doi.org/10.1002/zaac.201600023>
12. Vereshchak, V. G. (2015). Metansulfonaty perspektyvni organichni precursorsy dlia otrymannia nanodispersnykh oksydykh poroshkovykh materialiv. *Zbirnyk materialiv VII Mizhnarodnoyi naukovo-praktychnoyi konferentsiyi "Suchasni problemy technologii neorganichnykh rechovyv ta resursozberezhennia"*. Dnipropetrovsk, 52.
13. Vereshchak, V. H., Sorochkina, K. O., Vlieiev, D. V. (2018). Metansulfonaty yak perspektyvni orhanichni spoluky dlia oderzhannia funktsionalnykh oksydykh nanomaterialiv. *XX Ukrainska konf. z neorh. khimiyi*. Dnipro, 183.
14. Givan, A., Loewenschuss, A., Nielsen, C. J. (2005). Infrared spectrum and ab initio calculations of matrix isolated methanesulfonic acid species and its 1:1 water complex. *Journal of Molecular Structure*, 748 (1-3), 77–90. doi: <https://doi.org/10.1016/j.molstruc.2005.03.015>

DOI: 10.15587/1729-4061.2018.150764

#### ANALYSIS OF PROPERTIES OF EPOXY COMPOSITIONS THAT OPERATE IN CONTACT WITH WATER AND OIL PRODUCTS (p. 20-26)

Anatoliy Gara

Odessa State Academy of Building and Architecture, Odessa, Ukraine

ORCID: <http://orcid.org/0000-0002-0766-1157>

Alexander Gara

Odessa State Academy of Building and Architecture, Odessa, Ukraine

ORCID: <http://orcid.org/0000-0002-2413-1860>

Svetlana Sukhanova

Odessa State Academy of Building and Architecture, Odessa, Ukraine

ORCID: <http://orcid.org/0000-0003-3142-8790>

We modified epoxy resin-based polymer solutions to increase durability in aggressive environments and to reduce costs. We achieved the objective via filling them with the multifractional mineral frame and modification with zeolite and furfural. We varied a content of furfural, a total content of the mineral frame and a proportion of individual components in the frame. The investigated compositions should work under conditions of influence of mixtures of water with oil products and other agents (in elements of structures for the transport service). We determined properties of compositions after exposure separately in air, in water and in two types of oil.

We applied an iterative procedure of random scanning of fields of material properties in five coordinates of varying factors in search for optimal compositions. We studied property fields using experimental statistical models obtained in field experiments. ES models serve to implement calculation experiments using the Monte Carlo method.

We confirmed the possibility for determining the optimal (by the set of criteria) multicomponent polymer compositions for different operating conditions using an iterative procedure of random scanning of property fields.

We obtained compositions for repair and protection of structures, which are in contact with water: paste (reduced viscosity composition without sand) and solution (with reduced epoxy resin consumption). We used compositions that ensure the preservation of the required properties of a protective solution after prolonged exposure to mixtures of water with oil products in the complete overhaul of railway crossing flooring.

**Keywords:** epoxy-rubber resin, zeolite, furfural, experimental statistical model, Monte-Carlo method, compromise optimization.

#### References

1. Venkateela, G., Klein, M., Najm, H., Balaguru, P. N. (2017). Evaluation of the Compatibility of Repair Materials for Concrete Structures. *International Journal of Concrete Structures and Materials*, 11 (3), 435–445. doi: <https://doi.org/10.1007/s40069-017-0208-5>
2. Kormann, A. C. M., Portella, K. F., Pereira, P. N., Santos, R. P. (2003). Study of the performance of four repairing material systems for hydraulic structures of concrete dams. *Cerâmica*, 49 (309), 48–54. doi: <https://doi.org/10.1590/s0366-69132003000100011>
3. Huang, H., Hao, J., Zhao, B., Zhao, X., Li, M., Liu, J., Shao, W. (2017). Application of Epoxy Mortar in Anti-erosive Protection of the Spillway on the Xin'anjiang Hydropower Station Plant. *Energy Procedia*, 105, 1199–1204. doi: <https://doi.org/10.1016/j.egypro.2017.03.412>
4. Stehlik, M., Novak, J. (2011). Verification of the effect of concrete surface protection on the permeability of acid gases using accelerated carbonation depth test in an atmosphere of 98 %  $\text{CO}_2$ . *Ceramics – Silikáty*, 55 (1), 79–84. doi: <https://doi.org/10.1155/2018/8386426>
5. Nguyen, T. H., Nguyen, T. A. (2018). Protection of Steel Rebar in Salt-Contaminated Cement Mortar Using Epoxy Nanocomposite Coatings. *International Journal of Electrochemistry*, 2018, 1–10. doi: <https://doi.org/10.1155/2018/8386426>
6. Pereira, A. A. C., d' Almeida, J. R. M. (2016). Effect of the hardener to epoxy monomer ratio on the water absorption behavior of the DGEBA/TETA epoxy system. *Polimeros*, 26 (1), 30–37. doi: <https://doi.org/10.1590/0104-1428.2106>
7. Ozeren Ozgul, E., Ozkul, M. H. (2018). Effects of epoxy, hardener, and diluent types on the workability of epoxy mixtures. *Construction and Building Materials*, 158, 369–377. doi: <https://doi.org/10.1016/j.conbuildmat.2017.10.008>
8. Debska, B., Lichołai, L. (2016). Resin Composites with High Chemical Resistance for Application in Civil Engineering. *Periodica Polytechnica Civil Engineering*, 60 (2), 281–287. doi: <https://doi.org/10.3311/ppci.7744>
9. Dębska, B., Wójcik, K. (2018). Evaluation of the influence of aggregate type on selected properties of epoxy mortars. *E3S Web of Conferences*, 49, 00018. doi: <https://doi.org/10.1051/e3sconf/20184900018>
10. Yemam, D., Kim, B.-J., Moon, J.-Y., Yi, C. (2017). Mechanical Properties of Epoxy Resin Mortar with Sand Washing Waste as Filler. *Materials*, 10 (3), 246. doi: <https://doi.org/10.3390/ma10030246>
11. Railkin, A. I., Otvalko, Z. A., Korotkov, S. I., Fomin, S. E., Kuleva, N. V. (2017). Concept of environmentally friendly protection against sea fouling and its development using epoxy-rubber coats. *Marine Biological Journal*, 2 (3), 40–52. doi: <https://doi.org/10.21072/mbj.2017.02.3.04>
12. Valášek, P. (2014). Long-Term Degradation of Composites Exposed to Liquid Environments in Agriculture. *Scientia Agriculturae Bohemica*, 45 (3), 187–192. doi: <https://doi.org/10.2478/sab-2014-0107>
13. Gara, An. A. (2014). Analiz vliyaniya mnogofrakcionnogo karkasa na mekhanicheskie svoystva polimernykh kompozitsiy. *Visnyk Odeskoi derzhavnoi akademiyi budivnytstva ta arkhitektury*, 55, 54–61.
14. Gara, An. A. (2016). The operating properties of the rubber epoxy compositions after the influence of the adsorption-active environment. *Visnyk Odeskoi derzhavnoi akademiyi budivnytstva ta arkhitektury*, 62, 28–32.
15. Debska, B., Lichołai, L. (2018). Long-Term Chemical Resistance of Ecological Epoxy Polymer Composites. *Journal of Ecological Engineering*, 19 (2), 204–212. doi: <https://doi.org/10.12911/22998993/82802>
16. Voznesenskiy, V. A., Lyashenko, T. V., Dovgan', A. D. (2004). Kompromissnaya minimizatsiya polimeroemkosti i maksimizatsiya vodo- i neflestoykosti zashchitnogo kompozita. *Resursoekonomni materyaly, konstruktzii, budivli ta sporudy*, 11, 11–16.

17. Czarnecki, L. (2004). Repair systems; searching towards compatibility measure. Bonded Concrete Overlays. Proc. Int. RILEM Workshop, 14–20.
18. Voznesenskiy, V. A., Lyashenko, T. V. (2017). Metodologiya recepturno-tehnologicheskikh poley v komp'yuternom stroitel'nom materialovedenii. Odessa, 168.
19. Paturuev, V. V. (1987). Polimerbetony. Moscow, 286.
20. Lyashenko, T. V., Voznesenskiy, V. A., Gavriiliuk, V. P. (2009). Multicriterial optimisation of autoclaved aerated concrete properties and expenditure of energy resources. Brittle Matrix Composites 9, 219–226. doi: <https://doi.org/10.1533/9781845697754.219>
21. Voznesenskiy, V. A., Lyashenko, T. V., Dovgan', A. D. (2007). Kompromissnaya mnogofaktornaya optimizatsiya garantirovannogo kachestva shlakoshchelochnykh vyazhushchih (maksimizatsiya prochnosti i morozostoykosti, minimizatsiya raskhoda resursa). Sovremennoe promyshlennoe i grazhdanskoe stroitel'stvo, 3 (1), 5–15.
22. Frey, K. (Ed.) (1985). Mineralogicheskaya enciklopediya. Leningrad, 317–322.

DOI: 10.15587/1729-4061.2018.147585

**THE EFFECT OF ADDITIVE ON COMBUSTION CHARACTERISTICS AND CYCLE TO CYCLE VARIATIONS ON SI ENGINE FUELED BY GASOLINE AND BIOETHANOL (p. 27-36)**

**Setia Abikusna**

Universitas Indonesia, Jawa Barat, Indonesia

**Bambang Sugiarto**

Universitas Indonesia, Jawa Barat, Indonesia

**Ratna Monasari**

Universitas Indonesia, Jawa Barat, Indonesia

**Iqbal Yamin**

Universitas Indonesia, Jawa Barat, Indonesia

Currently, the main energy source is heavily dependent on fossil energy. The current transportation technology also uses fossil-derived energy sources to make vehicle engines are ignited. Also, the electricity that is currently enjoyed by billions of people resulted enormously from the use of fossil energy. Limitations of existing fossil energy sources and the issue of global warming have led many to expand on renewable energy and energy conservation to maintain energy availability. One of an alternative energy source that is currently being developed is the use of bioethanol as a mixture or replacement of fossil fuel. The use of bioethanol (C<sub>2</sub>H<sub>5</sub>OH) as a substitute for a mixture of fossil fuels affects the efficiency of the engine produced by fuel. This study examines the effect of a mixture of bioethanol gasoline (RON 80) on a single-cylinder spark ignition (SI) 125 cc engine that is carried out with variations in fuel mixtures (E0, E5, E10, and E15) with the addition of 0.5 vol % oxygenated cyclohexanol and this experimental test is carried out as much as 800 cycles for each fuel mixture, with throttle opening, maintained 100 %, and variations in engine speed at 4,000 rpm up to 8,500 rpm with engine speed increases every 500 rpm. Engine performance is measured by connecting a machine with a dynamometer, and the variation of cylinder pressure combustion is measured by a pressure transducer. The test results are expected to prove that the mixture of fuel with oxygenated cyclohexanol can reduce COV<sub>IMEP</sub> in the cycle to cycle variations (E10++ which is 4.24 %), so that torque fluctuations do not occur which results in reliable engine performance or vehicle driveability increase, besides that the performance of both power and torque becomes better.

**Keywords:** bioethanol, oxygenated, cylinder pressure, coefficient of variation, cycle to cycle variations, power, torque.

**References**

1. Data Handbook of Energy & Economic Statistic of Indonesia (2014). Ministry of Energy and Mineral Resources.
2. Zhuang, Y., Hong, G. (2014). Effects of direct injection timing of ethanol fuel on engine knock and lean burn in a port injection gasoline engine. Fuel, 135, 27–37. doi: <https://doi.org/10.1016/j.fuel.2014.06.028>
3. Yao, Y.-C., Tsai, J.-H., Wang, I.-T. (2013). Emissions of gaseous pollutant from motorcycle powered by ethanol–gasoline blend. Applied Energy, 102, 93–100. doi: <https://doi.org/10.1016/j.apenergy.2012.07.041>
4. Turkcan, A., Ozsezen, A. N., Canakci, M. (2014). Experimental investigation of the effects of different injection parameters on a direct injection HCCI engine fueled with alcohol–gasoline fuel blends. Fuel Processing Technology, 126, 487–496. doi: <https://doi.org/10.1016/j.fuproc.2014.05.023>
5. Zhuang, Y., Hong, G. (2013). Primary investigation to leveraging effect of using ethanol fuel on reducing gasoline fuel consumption. Fuel, 105, 425–431. doi: <https://doi.org/10.1016/j.fuel.2012.09.013>
6. Feng, R., Fu, J., Yang, J., Wang, Y., Li, Y., Deng, B. et. al. (2015). Combustion and emissions study on motorcycle engine fueled with butanol-gasoline blend. Renewable Energy, 81, 113–122. doi: <https://doi.org/10.1016/j.renene.2015.03.025>
7. Schifter, I., Diaz, L., Gómez, J. P Gonzalez, U. (2013). Combustion characterization in a single cylinder engine with mid-level hydrated ethanol–gasoline blended fuels. Fuel, 103, 292–298. doi: <https://doi.org/10.1016/j.fuel.2012.06.002>
8. Wang, X., Chen, Z., Ni, J., Liu, S., Zhou, H. (2015). The effects of hydrous ethanol gasoline on combustion and emission characteristics of a port injection gasoline engine. Case Studies in Thermal Engineering, 6, 147–154. doi: <https://doi.org/10.1016/j.csite.2015.09.007>
9. Sen, A. K., Medina, A., Curto-Risso, P. L., Calvo Hernández, A. (2014). Effect of ethanol addition on cyclic variability in a simulated spark ignition gasoline engine. Meccanica, 49 (10), 2285–2297. doi: <https://doi.org/10.1007/s11012-014-9974-1>
10. Kaleli, A., Ceviz, M. A., Erenturk, K. (2015). Controlling spark timing for consecutive cycles to reduce the cyclic variations of SI engines. Applied Thermal Engineering, 87, 624–632. doi: <https://doi.org/10.1016/j.applthermaleng.2015.05.042>
11. Heywood, J. (1988). Internal Combustion Engine Fundamentals. McGraw-Hill, 960.
12. Reyes, M., Melgar, A., Pérez, A., Giménez, B. (2013). Study of the cycle-to-cycle variations of an internal combustion engine fuelled with natural gas/hydrogen blends from the diagnosis of combustion pressure. International Journal of Hydrogen Energy, 38 (35), 15477–15487. doi: <https://doi.org/10.1016/j.ijhydene.2013.09.071>
13. Phuangwongtrakul, S., Wechsattol, W., Sethaput, T., Suktang, K., Wongwiset, S. (2016). Experimental study on sparking ignition engine performance for optimal mixing ratio of ethanol–gasoline blended fuels. Applied Thermal Engineering, 100, 869–879. doi: <https://doi.org/10.1016/j.applthermaleng.2016.02.084>
14. Abikusna, S., Sugiarto, B., Suntoro, D., Azami (2017). Low grade bioethanol for fuel mixing on gasoline engine using distillation process. AIP Conference Proceedings. doi: <https://doi.org/10.1063/1.4979235>
15. Abikusna, S., Sugiarto, B., Monasari, R., Aditya, R., Hendrawan, D. (2018). Performance analysis (WHP and torque) on SI engine fueled with low-grade bioethanol and oxygenated fuel additive. IOP Conference Series: Earth and Environmental Science, 105, 012057. doi: <https://doi.org/10.1088/1755-1315/105/1/012057>
16. Anand, T. N. C., Madan Mohan, A., Ravikrishna, R. V. (2012). Spray characterization of gasoline-ethanol blends from a multi-hole port fuel injector. Fuel, 102, 613–623. doi: <https://doi.org/10.1016/j.fuel.2012.06.107>

17. Catapano, F., Sementa, P., Vaglieco, B. M. (2016). Air-fuel mixing and combustion behavior of gasoline-ethanol blends in a GDI wall-guided turbocharged multi-cylinder optical engine. *Renewable Energy*, 96, 319–332. doi: <https://doi.org/10.1016/j.renene.2016.04.087>
18. Costa, R. C., Sodr , J. R. (2011). Compression ratio effects on an ethanol/gasoline fuelled engine performance. *Applied Thermal Engineering*, 31 (2-3), 278–283. doi: <https://doi.org/10.1016/j.applthermaleng.2010.09.007>
19. Huang, Y., Hong, G., Huang, R. (2015). Investigation to charge cooling effect and combustion characteristics of ethanol direct injection in a gasoline port injection engine. *Applied Energy*, 160, 244–254. doi: <https://doi.org/10.1016/j.apenergy.2015.09.059>
20. Kim, N., Cho, S., Min, K. (2015). A study on the combustion and emission characteristics of an SI engine under full load conditions with ethanol port injection and gasoline direct injection. *Fuel*, 158, 725–732. doi: <https://doi.org/10.1016/j.fuel.2015.06.025>
21. Li, L., Ge, Y., Wang, M., Peng, Z., Song, Y., Zhang, L., Yuan, W. (2015). Exhaust and evaporative emissions from motorcycles fueled with ethanol gasoline blends. *Science of The Total Environment*, 502, 627–631. doi: <https://doi.org/10.1016/j.scitotenv.2014.09.068>
22. Li, Y., Meng, L., Nithyanandan, K., Lee, T. H., Lin, Y., Lee, C. F., Liao, S. (2016). Combustion, performance and emissions characteristics of a spark-ignition engine fueled with isopropanol-n-butanol-ethanol and gasoline blends. *Fuel*, 184, 864–872. doi: <https://doi.org/10.1016/j.fuel.2016.07.063>
23. Liu, H., Wang, Z., Long, Y., Wang, J. (2015). Dual-Fuel Spark Ignition (DFSI) combustion fuelled with different alcohols and gasoline for fuel efficiency. *Fuel*, 157, 255–260. doi: <https://doi.org/10.1016/j.fuel.2015.04.042>
24. Liu, H., Wang, Z., Long, Y., Xiang, S., Wang, J., Fatouraie, M. (2015). Comparative study on alcohol–gasoline and gasoline–alcohol Dual-Fuel Spark Ignition (DFSI) combustion for engine particle number (PN) reduction. *Fuel*, 159, 250–258. doi: <https://doi.org/10.1016/j.fuel.2015.06.059>
25. Masum, B. M., Masjuki, H. H., Kalam, M. A., Palash, S. M., Habibullah, M. (2015). Effect of alcohol–gasoline blends optimization on fuel properties, performance and emissions of a SI engine. *Journal of Cleaner Production*, 86, 230–237. doi: <https://doi.org/10.1016/j.jclepro.2014.08.032>
26. Melo, T. C. C. de, Machado, G. B., Belchior, C. R. P., Colaço, M. J., Barros, J. E. M., de Oliveira, E. J., de Oliveira, D. G. (2012). Hydrous ethanol–gasoline blends – Combustion and emission investigations on a Flex-Fuel engine. *Fuel*, 97, 796–804. doi: <https://doi.org/10.1016/j.fuel.2012.03.018>
27. Najafi, G., Ghobadian, B., Yusaf, T., Safieddin Ardebili, S. M., Mamat, R. (2015). Optimization of performance and exhaust emission parameters of a SI (spark ignition) engine with gasoline–ethanol blended fuels using response surface methodology. *Energy*, 90, 1815–1829. doi: <https://doi.org/10.1016/j.energy.2015.07.004>
28. Reyes, M., Tinaut, F. V., Melgar, A., P rez, A. (2016). Characterization of the combustion process and cycle-to-cycle variations in a spark ignition engine fuelled with natural gas/hydrogen mixtures. *International Journal of Hydrogen Energy*, 41 (3), 2064–2074. doi: <https://doi.org/10.1016/j.ijhydene.2015.10.082>
29. Sileghem, L., Wallner, T., Verhelst, S. (2015). A quasi-dimensional model for SI engines fueled with gasoline–alcohol blends: Knock modeling. *Fuel*, 140, 217–226. doi: <https://doi.org/10.1016/j.fuel.2014.09.091>
30. Suarez-Bertoa, R., Zardini, A. A., Keuken, H., Astorga, C. (2015). Impact of ethanol containing gasoline blends on emissions from a flex-fuel vehicle tested over the Worldwide Harmonized Light duty Test Cycle (WLTC). *Fuel*, 143, 173–182. doi: <https://doi.org/10.1016/j.fuel.2014.10.076>
31. Wang, Z., Liu, H., Long, Y., Wang, J., He, X. (2015). Comparative study on alcohols–gasoline and gasoline–alcohols dual-fuel spark ignition (DFSI) combustion for high load extension and high fuel efficiency. *Energy*, 82, 395–405. doi: <https://doi.org/10.1016/j.energy.2015.01.049>

DOI: 10.15587/1729-4061.2018.148372

**RESEARCH OF THE IMPACT OF THE METHOD OF HEATING OF HEAT UNITS ON THE QUALITATIVE CHARACTERISTICS OF TREATED MATERIALS (p. 37-43)**

**Valeriy Nikolsky**

Ukrainian State University of Chemical Technology, Dnipro, Ukraine  
ORCID: <http://orcid.org/0000-0001-6069-169X>

**Olga Oliynyk**

Ukrainian State University of Chemical Technology, Dnipro, Ukraine  
ORCID: <http://orcid.org/0000-0003-2666-3825>

**Andrii Pugach**

Dnipro State Agrarian and Economic University, Dnipro, Ukraine  
ORCID: <http://orcid.org/0000-0002-5586-424X>

**Oleksandr Aliksandrov**

Ukrainian State University of Chemical Technology, Dnipro, Ukraine  
ORCID: <http://orcid.org/0000-0002-0442-0008>

**Olena Gnatko**

Ukrainian State University of Chemical Technology, Dnipro, Ukraine  
ORCID: <http://orcid.org/0000-0003-4376-3860>

**Yevhenii Chernetskyi**

Limited Liability Partnership “Scientific Production Enterprise Ecosynthesis”, Zhytomyr, Ukraine  
ORCID: <http://orcid.org/0000-0002-4197-7171>

An analytical method for calculating the chemical potentials of the components of the gas-solid system based on thermodynamic calculations of carbon potentials of the C–O–H–N gas mixture (combustion products of the methane-air mixture) and the solid phase (alloyed steel) is developed. Dependences describing the influence of the main parameters of heating the medium composition, flow rate, as well as their interaction, on metal losses associated with decarburization are obtained.

Thermodynamic calculations of carbon potentials of alloyed steel and natural gas combustion products of different composition ( $\alpha=0.2\div 1.2$ ), metal and combustion products temperatures of 1,100–1,500 K are performed.

Based on the analysis of the structure of the thermal and diffusion boundary layers, it is proved that the decrease in the temperature of the layer of combustion product flowing around the solid product and surface flow rate reduces the diffusion flow of carbon in the boundary layer. This effect reduces the decarburization of steel.

It is found that when heating the heat unit according to the principle of indirect radiant heating (IRH) during the operation of the flat-flame burner, the main gas volume, localized at the metal surface, has a temperature significantly lower than the layer adjacent to the lining. This reduces the metal loss with decarburization compared with furnaces of the traditional heating system.

Combustion of gas in flat-flame burners with an intense circulation of combustion products in the working space of the heat unit ensures that the heated products have a uniform composition of combustion products corresponding to a practically equilibrium one. This allows recommending flat-flame burners for widespread use in modern heat-power units in the industry.

**Keywords:** heat-treatment furnace, boundary layer, decarburization, flat-flame burner, temperature control.

**References**

1. Kuznetsov, V. A., Trubaev, P. A. (2018). Resources and Problems of the Mathematical Simulating Thermo-Technological Processes.

- Journal of Physics: Conference Series, 1066, 012024. doi: <https://doi.org/10.1088/1742-6596/1066/1/012024>
- Nikolsky, V., Oliynyk, O., Shvachka, A., Nachovnyy, I. (2017). Thermal treatment of concentrated liquid toxic waste and automatic control of process efficiency. *Eastern-European Journal of Enterprise Technologies*, 5 (10 (89)), 26–31. doi: <https://doi.org/10.15587/1729-4061.2017.111846>
  - Lim, K., Lee, S., Lee, C. (2007). An experimental study on the thermal performance of ground heat exchanger. *Experimental Thermal and Fluid Science*, 31 (8), 985–990. doi: <https://doi.org/10.1016/j.expthermflusc.2006.10.011>
  - Eynard, J., Grieu, S., Polit, M. (2011). Modular approach for modeling a multi-energy district boiler. *Applied Mathematical Modelling*, 35 (8), 3926–3957. doi: <https://doi.org/10.1016/j.apm.2011.02.006>
  - Reddy, A., Kreider, J. F., Curtiss, P. S., Rabl, A. (2016). Heating and Cooling of Buildings: Principles and Practice of Energy Efficient Design. CRC Press, 900. doi: <https://doi.org/10.1201/9781315374567>
  - Edmonds, D. V., He, K., Rizzo, F. C., De Cooman, B. C., Matlock, D. K., Speer, J. G. (2006). Quenching and partitioning martensite – A novel steel heat treatment. *Materials Science and Engineering: A*, 438–440, 25–34. doi: <https://doi.org/10.1016/j.msea.2006.02.133>
  - Wu, Y.-L., Jiang, Z.-Y., Zhang, X.-X., Xue, Q.-G., Yu, A.-B., Shen, Y.-S. (2017). Modeling of Thermochemical Behavior in an Industrial-Scale Rotary Hearth Furnace for Metallurgical Dust Recycling. *Metallurgical and Materials Transactions B*, 48 (5), 2403–2418. doi: <https://doi.org/10.1007/s11663-017-1034-5>
  - Grishunin, V. A., Gromov, V. E., Ivanov, Yu. F., Teresov, A. D., Kononov, S. V. (2013). Evolyuciya fazovogo sostava i defektnoy substrukturny rel'sovoy stali, podvergnutoy obrabotke vysokointensivnym elektronnym puchkom. Poverhnost'. Rentgenovskie, sinhronnye i neytronnye issledovaniya, 10, 82–88. doi: <https://doi.org/10.7868/s0207352813090096>
  - Gao, Y., Li, X., Yang, Q., Yao, M. (2007). Influence of surface integrity on fatigue strength of 40CrNi2Si2MoVA steel. *Materials Letters*, 61 (2), 466–469. doi: <https://doi.org/10.1016/j.matlet.2006.04.089>
  - Raether, F., Klimera, A., Baber, J. (2008). In situ measurement and simulation of temperature and stress gradients during sintering of large ceramic components. *Ceramics International*, 34 (2), 385–389. doi: <https://doi.org/10.1016/j.ceramint.2006.10.025>
  - Nikolsky, V., Oliynyk, O., Yaris, V., Reshetnyak, I. (2017). Application of electromagnetic fields for intensification of heat and mass exchange in combined gas-liquid processes. *Eastern-European Journal of Enterprise Technologies*, 3 (8 (87)), 33–39. doi: <https://doi.org/10.15587/1729-4061.2017.103868>
  - Pavlov, D. Yu., Sirotkin, O. S., Trubacheva, A. M., Sirotkin, R. O. (2012). Himicheskaya priroda gomoyadernyh (prostyh) neorganicheskikh veshchestv, ih oksilitel'no-vosstanovitel'nye svoystva i vliyanie na energiyu Gibbsa obrazovaniya oksidov. *Vestnik Kazanskogo tekhnologicheskogo universiteta*, 15 (9), 35–38.
  - Nikolsky, V. Ye., Lobodenko, A. V., Reshetnyak, I. L. (2016). Thermodynamic analysis of thermal and diffusion boundary layers influence upon the thermo-technological processes parameters in gas – solid systems. *Industrial Technology and Engineering*, 2 (19), 43–52.
  - Mogutnov, B. M., Tomilin, I. A., Shvarcman, L. A. (1972). *Termodinamika zhelezouglerodistykh splavov*. Moscow: Metallurgiya, 328.
  - Bogushevskiy, V. S., Mel'nik, S. G., Zhuk, S. V. (2014). Obezuglerozhivanie stali kak osnovnoy parametru optimal'nogo upravleniya kislородno-konvertirnyy processom. *Metall i lit'e Ukrainy*, 2, 14–16.
  - Makarov, M. A., Aleksandrov, A. A., Dashevskiy, V. Ya. (2006). Issledovanie processa glubokogo obezuglerozhivaniya stali. *Metally*, 3, 3–7.
  - Mitchell, R. E., Ma, L., Kim, B. (2007). On the burning behavior of pulverized coal chars. *Combustion and Flame*, 151 (3), 426–436. doi: <https://doi.org/10.1016/j.combustflame.2007.07.014>
  - Gorsky, V. V., Zabarko, D. A., Olenicheva, A. A. (2012). Investigation of the mass loss of a carbon material within the framework of a complete thermochemical model of its destruction in the case of equilibrium chemical reactions in the boundary layer. *High Temperature*, 50 (2), 286–291. doi: <https://doi.org/10.1134/s0018151x12020083>
  - Nikol'skiy, V. E., Soroka, B. S. (1982). *Uluchshenie kachestva nagreva stali v termicheskikh toplivnykh pechah kosvennogo radiatsionnogo nagreva*. Kyiv: Znanie, 23.
  - Nikolsky, V., Oliynyk, O., Ved, V., Pugach, A., Turluev, R., Aliksandrov, O., Kosarev, V. (2018). Research into the impact of structural features of combustion chamber in energy-technological units on their operational efficiency. *Eastern-European Journal of Enterprise Technologies*, 5 (8 (95)), 58–64. doi: <https://doi.org/10.15587/1729-4061.2018.143316>
  - Soroka, B. S. (1992). *Intensifikaciya teplovykh processov v toplivnykh pechah*. Kyiv: Naukova dumka, 412.

---

DOI: 10.15587/1729-4061.2018.150606

**DEVELOPMENT OF A SOL-GEL TECHNIQUE FOR OBTAINING SINTERING ACTIVATORS FOR ENGOBE COATINGS (p. 43-51)**

**Olena Khomenko**

Ukrainian State University of Chemical Engineering, Dnipro, Ukraine

ORCID: <http://orcid.org/0000-0002-3753-3033>

**Eugene Alekseev**

Ukrainian State University of Chemical Engineering, Dnipro, Ukraine

We have developed a technology for manufacturing the glass ligaments-activators to intensify the sintering of ceramic materials, specifically engobe coatings. The comparative analysis has been performed into the glass ligaments obtained through a conventional glass melting and by applying the sol-gel synthesis. Large efficiency of the latter has been established related to the reduced energy costs required to thermally treat a composition (rather than melting glass at 1,300–1,400 °C, gel is to be thermally treated to 600 °C) as well as to the improved homogeneity of the glass ligament (chemical formulation of the composition is averaged at a molecular level).

Different sol-gel techniques for obtaining glass ligaments-activators have also been examined: a powder sol-gel technique without calcination; a sol-gel technique for the preparation of solutions of salts; a powder sol-gel technique with the composition melting. The specified techniques differ in the sequence and method for mixing the source components, while their dispersion in a gel-forming agent the ethyl silicate ETS-40 is mandatory. The chosen basic components of the activator were soluble salts  $\text{Al}(\text{NO}_3)_3 \cdot 9\text{H}_2\text{O}$ ,  $\text{Ca}(\text{NO}_3)_2$  and  $\text{NaNO}_3$ . We have investigated pattern in change of the phase composition of glass ligaments at their heating to 600 °C. It has been established that all obtained compositions approach the amorphous state at temperatures of ~600 °C. Further heating of the examined glass ligaments to 1,000 °C leads to their intensive melting. In this case, for the first two techniques, the viscosity and surface tension of melts are less compared to the melt of conventional glass, and, therefore, the wetting capacity of glass ligaments-activators is higher.

When introducing these sintering activators to the compositions of ceramic coatings, it was established that the most effective is the activator that was obtained by a technique for the preparation of salt solutions. It is the one that provides, after annealing at 1,170 °C, for the densest structure of the sintered coating with reduced water absorption (not exceeding 0.05 %) and high whiteness of the surface (87–88 %). The activators that we developed could become an alternative to conventional glass-ligaments whose melting requires considerable energy costs.

**Keywords:** sol-gel technique, sintering activator, engobe, annealing, water absorption

### References

- Kuang, X., Carotenuto, G., Nicolais, L. (1997). Advanced Performance Materials, 4 (3), 257–274. doi: <https://doi.org/10.1023/a:1008621020555>
- Lu, J., Li, Y., Zou, C., Liu, Z., Wang, C. (2018). WITHDRAWN: Effect of sintering additives on the densification, crystallization and flexural strength of sintered glass-ceramics from waste granite powder. Materials Chemistry and Physics. doi: <https://doi.org/10.1016/j.matchemphys.2018.02.010>
- Gur'eva, V. A. (2011). Aktivaciya processa spekaniya alyumomagnezial'nyh keramicheskikh mass. Vestnik OGU, 5 (124), 171–174.
- Semchenko, G. D. (1997). Zol'-gel' process v keramicheskoy tekhnologii. Kharkiv, 298.
- Shabanova, N. A. (2012). Zol'-gel' tekhnologii. Nanodispersnyy kremnezem. Moscow, 328.
- Obata, A., Kasuga, T. (2009). SiO<sub>2</sub>-CaO-P<sub>2</sub>O<sub>5</sub> sol-gel-derived glass coating on porous β-tricalcium phosphate ceramics. Journal of the Ceramic Society of Japan, 117(1370), 1120–1125. doi: <https://doi.org/10.2109/jcersj2.117.1120>
- Sakka, S. (1987). Sol-Gel Glasses and their Future Applications. Transactions of the Indian Ceramic Society, 46 (1), 1–11. doi: <https://doi.org/10.1080/0371750x.1987.10822820>
- Zheng, M., Yu, R., Chen, J., Zhao, J., Liu, G., Xing, X., Meng, J. (2008). Synthesis and Characterization of (Zn,Cd)TiO<sub>3</sub> by a Modified Sol-Gel Method. Journal of the American Ceramic Society, 91 (2), 544–547. doi: <https://doi.org/10.1111/j.1551-2916.2007.02131.x>
- Andrianov, N. T., Abdel-gavad, S. R., Zenkova, N. V. (2006). Sintez i spekanie kordieritovyh zol'-gel' poroshkov na osnove razlichnyh soley magniya. Steklo i keramika, 12, 19–22.
- Atkinson, A., Doorbar, J., Segal, D. L., White, P. J. (1998). Sol-Gel Ceramic Pigments. Key Engineering Materials, 150, 15–20. doi: <https://doi.org/10.4028/www.scientific.net/kem.150.15>
- Innocenzi, P., Zub, Y. L., Kessler, V. G. (Eds.) (2008). Sol-Gel Methods for Materials Processing. Dordrecht. doi: <https://doi.org/10.1007/978-1-4020-8514-7>
- Vinogradov, A. V., Vinogradov, V. V. (2014). Low-temperature sol-gel synthesis of crystalline materials. RSC Adv., 4 (86), 45903–45919. doi: <https://doi.org/10.1039/c4ra04454a>
- Bobkova, N. M. (2007). Fizicheskaya himiya tugoplavkikh nemetalicheskikh i silikatnyh materialov. Minsk, 301.
- Guzman, I. Ya. (Ed.) (2005). Praktikum po tekhnologii keramiki. Moscow, 334.
- Guzman, I. Ya. (Ed.) (2011). Himicheskaya tekhnologiya keramiki. Moscow, 496.
- Rabinovich, V. A., Nikol'skiy, B. N. (Eds.) (1963). Spravochnik himika. Vol. 2. Osnovnye svoystva neorganicheskikh i organicheskikh soedineniy. Ch. 1. Leningrad-Moscow, 540.
- Panasyuk, G. P., Ambarcumyan, G. V. (1988). Formirovanie struktury amorfnoho kremnezema, poluchennogo gidrolizom tetraetoksisilana s posleduyushchey termooobrabotkoy. Izvestiya AN SSSR. Neorganicheskie, materialy, 24 (5).
- Poddenezhnyi, E. N., Boyko, A. A. (2003). Klassifikaciya sposobov polucheniya ul'tradispersnyh oksidnyh poroshkov (obzor). Vestnik Gomel'skogo gosudarstvennogo tekhnicheskogo universiteta im. P. O. Suhogo, 1, 21–28.
- Aliksieiev, Ye. V., Kolieda, V. V., Mykhailiuta, O. S. et. al. (2009). Sklozviazky, oderzhani zol'-hel metodom – efektyvni aktyvatory spikannia keramichnykh materialiv. Vestnik NTU “KhPI”. Ser.: Himiya, himicheskaya tekhnologiya i ekologiya, 45, 21–26.
- Mykhailiuta, O. S., Aliksieiev, Ye. V., Kolieda, V. V., Andrianova, S. Yu., Zaichuk, O. V. (2008). Pat. No. 89587 UA. Anhob.

No. a200810548; declared: 20.08.2008; published: 10.02.2010, Bul. No. 3.

DOI: 10.15587/1729-4061.2018.150675

### AN IMPROVEMENT OF CRITERIA FOR ASSESSING THE QUALITY OF CLAY RAW MATERIAL FOR ARCHITECTURAL AND CONSTRUCTION CERAMICS (p. 51-57)

**Liudmyla Shchukina**

National Technical University “Kharkiv Polytechnic Institute”,  
Kharkiv, Ukraine

ORCID: <http://orcid.org/0000-0002-5817-4279>

**Yaroslav Galushka**

National Technical University “Kharkiv Polytechnic Institute”,  
Kharkiv, Ukraine

ORCID: <http://orcid.org/0000-0003-1696-6769>

**Kateryna Bohdanova**

National Technical University “Kharkiv Polytechnic Institute”,  
Kharkiv, Ukraine

ORCID: <http://orcid.org/0000-0001-9035-2007>

The study analyzes the existing methods for assessing the suitability of clay raw materials for the production of architectural and construction ceramics and substantiates the need for their improvement in the direction of developing an indicator based on an analysis of the mineral composition of clays. Using the compositions of the kaolinite – montmorillonite – hydromica – quartz system, which simulate the composition of polymineral clays, the effect of clay-forming minerals and quartz impurities on the properties of the clinker ceramic materials has been established. It has been determined that the montmorillonite component of the compositions has a positive effect on the water absorption of materials, and kaolinite produces a favourable effect on the mechanical strength and frost resistance. The increase in the content of quartz in the composition of compositions from 30 % to 50 % leads to an increase in water absorption of materials, reducing their strength and frost resistance to a level unacceptable for ceramic clinker. It has been established that to obtain clinker ceramics, the quartz content in the compositions cannot exceed 40 %.

A diagram of the mineral composition was developed, clearly illustrating the ratios of the main rock-forming minerals in clays with a quartz content of 30 % and 40 %, acceptable for the production of modern clinker products. The diagram shows areas of the mineral composition of clays suitable for the production of facing, paving and road clinker of the M200–300 grades and road clinker of the M400 grade at a firing temperature of 1,100 °C. The diagram of the mineral composition complements the existing indicators of the suitability of clay raw materials for the production of architectural and construction ceramics and can serve as an additional criterion for assessing their technological quality. The diagram can be used to analyze the suitability of clays for the production of ceramic clinker, provided that only the mineral composition of clays is determined without establishing their chemical and particle size distribution.

**Keywords:** architectural and construction ceramics, clinker materials, mineral clay, criteria of technological quality, industrial application/use.

### References

- Hurskyi, D. S. et. al. (2006). Metalichni ta nemetalichni korysni kopalyny Ukrainy. Vol. 2. Nemetalichni korysni kopalyny. Kyiv-Lviv, 552.
- Winkler, H. (1954). Bedeutung der Korngrößenverteilung und des Mineralbestandes von Tonen für die Herstellung grobkeramischer Erzeugnisse. Berichte der DKG, 31, 337–343.

- Wimmer-Frey, I. (2007). Ziegelrohstoffe auf Kartenblatt Ried. ATA Geologische Bundesanstalt 2007 – Oberösterreich, 221–224. Available at: [https://www.zobodat.at/pdf/Arbeitstagungen-geologisch-en-Bundesanstalt\\_2007\\_0221-0224.pdf](https://www.zobodat.at/pdf/Arbeitstagungen-geologisch-en-Bundesanstalt_2007_0221-0224.pdf)
- García León, R. A., Bolívar León, R. (2017). Hydrometric Characterization of the Clays Used in the Manufacture of Ceramic Products in Ocaña, Norte de Santander. INGE CUC, 13 (1), 53–60. doi: <https://doi.org/10.17981/ingecuc.13.1.2017.05>
- Ribeiro, M. M., Lima, E. S., Figueiredo, A. B.-H. da S., Amaral, L. F., Monteiro, S. N., Vieira, C. M. F. (2018). Improved clay ceramics incorporated with steelmaking sinter particulates. Journal of Materials Research and Technology, 7 (4), 612–616. doi: <https://doi.org/10.1016/j.jmrt.2018.08.011>
- Berkman, A. S., Mel'nikova, I. G. (1962). Struktura i morozostoykost' stenovykh materialov. Leningrad, 168.
- Schmidt, H. (1973). Rohstoffkenndaten der verschiedenen Erzeugnisarten der Ziegelindustrie. Ziegelindustrie, 26, 212–216.
- Vogt, St. (2015). Methods of evaluation for raw material suitability and body optimization (Part 1). Brick and Tile Industry International, 5. Available at: [http://www.zi-online.info/en/artikel/zi\\_Methods\\_of\\_evaluation\\_for\\_raw\\_material\\_suitability\\_and\\_body\\_optimization\\_2376845.html](http://www.zi-online.info/en/artikel/zi_Methods_of_evaluation_for_raw_material_suitability_and_body_optimization_2376845.html)
- Avgustinik, A. I. (1975). Keramika. Leningrad, 592.
- Lisachuk, G. V., Shchukina, L. P., Tsova, V. V., Belostotskaya, L. A., Trusova, Y. D. (2013). Assessment of clayey raw material suitability for wall and façade ceramic production. Glass and Ceramics, 70 (3-4), 89–92. doi: <https://doi.org/10.1007/s10717-013-9515-8>
- Chumachenko, N., Turnikov, V., Kuzmin, V. (2018). Using the calculation method for low-melting clay assessment. MATEC Web of Conferences, 196, 04014. doi: <https://doi.org/10.1051/mateconf/201819604014>
- Ryshchenko, M. I., Shchukina, L. P., Fedorenko, E. Y., Firsov, K. N. (2008). Possibility of obtaining ceramogranite using quartz-feldspar raw material from Ukraine. Glass and Ceramics, 65 (1-2), 23–26. doi: <https://doi.org/10.1007/s10717-008-9011-8>
- Holeus, V. I., Karasyk, O. V. (2016). Matematychni modeliuvannia ta optymizatsiya ob'ektiv khimichnoi tekhnolohiyi. Dnipropetrovsk, 160.

DOI 10.15587/1729-4061.2018.150659

### STUDYING THE PHYSICO-CHEMICAL REGULARITIES IN THE COLOR- AND PHASE FORMATION PROCESSES OF CLINKER CERAMIC MATERIALS (p. 58-65)

**Olena Fedorenko**

National Technical University "Kharkiv Polytechnic Institute",  
Kharkiv, Ukraine

ORCID: <http://orcid.org/0000-0003-0831-3485>

**Larysa Prysiazhna**

National Technical University "Kharkiv Polytechnic Institute",  
Kharkiv, Ukraine

ORCID: <https://orcid.org/0000-0002-3637-6136>

**Serhii Petrov**

National Technical University "Kharkiv Polytechnic Institute",  
Kharkiv, Ukraine

ORCID: <http://orcid.org/0000-0001-6500-5310>

**Maryna Chyrkina**

National University of Civil Defence of Ukraine, Kharkiv, Ukraine

ORCID: <http://orcid.org/0000-0002-2060-9142>

**Oksana Borysenko**

Simon Kuznets Kharkiv National University of Economics,  
Kharkiv, Ukraine

ORCID: <http://orcid.org/0000-0002-2746-6797>

The paper reports results of a comprehensive study, aimed at developing formulation-technological parameters for obtaining volumetrically dyed clinker ceramic materials with a wide range of colors. A possibility has been proven to obtain a ceramic clinker when using the polymineral clay raw materials at a temperature of 1,100 °C. The expediency has been shown to replace expensive ceramic pigments in the composition of masses with anthropogenic materials containing the oxides of metals with variable valency: wastes from alkaline earth syenite extraction, pegmatite enrichment, and production of ferrotitanium alloys. This shows possibilities for reducing the production cost of clinker ceramic articles. The influence of the formulation of raw materials compositions on the processes of color- and phase-formation of ceramic clinker has been investigated, depending on the character of furnace atmosphere. It was established that the brown coloration of clinker ceramics under conditions of oxidative annealing is predetermined by the presence of phases of hematite  $\alpha$ -Fe<sub>2</sub>O<sub>3</sub> and Mn<sub>2</sub>O<sub>3</sub>. At annealing in a reducing medium, products acquire color in the range from dark brown to black at the expense of formation of magnetite Fe<sub>3</sub>O<sub>4</sub> and gausmanite Mn<sub>3</sub>O<sub>4</sub>. The products' terracotta color is due to the presence of phases of hematite and hedenbergite CaFeSi<sub>2</sub>O<sub>6</sub>. The condition for obtaining clinker ceramics of yellow color is to limit the formulation's content of Fe<sub>2</sub>O<sub>3</sub> to 3 % by weight, as well as the presence of the SiO<sub>2</sub> rutile phase.

The paper illustrates the effect of the overall content of oxides of metals with a variable valence S(Fe<sub>2</sub>O<sub>3</sub>+FeO+MnO+Mn<sub>3</sub>O<sub>4</sub>) on the coloration characteristics of clinker ceramics. The ratios have been derived between the phase-forming oxides Fe<sub>2</sub>O<sub>3</sub>/(Al<sub>2</sub>O<sub>3</sub>+CaO), (Fe<sub>2</sub>O<sub>3</sub>+Mn<sub>2</sub>O<sub>3</sub>)/(FeO+Mn<sub>3</sub>O<sub>4</sub>) and TiO<sub>2</sub>/(Al<sub>2</sub>O<sub>3</sub>+CaO), as well as the limits in their variation, providing for the formation of color-carrying phases responsible for obtaining products of the desired color under conditions of oxidative and reductive annealing.

**Keywords:** clinker ceramic materials, polymineral clays, anthropogenic materials, sintering intensifiers, color-carrying phases.

### References

- Fernandez, J. (2012). Material Architecture. Emergent Materials for Innovative Buildings and Ecological Construction. Elsevier, 344. doi: <https://doi.org/10.4324/9780080940441>
- Koss, L. S., Fedorenko, E. Yu., Lesnyh, N. F., Ryschenko, M. I., Ryschenko, O. D. (2018). Modern diagnostic methods and technological principles of fabrication of bioresistant ceramic materials. Voprosy khimii i khimicheskoi tekhnologii, 1, 78–86. Available at: <http://udhtu.edu.ua/public/userfiles/file/VHHT/2018/1/Koss.pdf>
- Afsari, K., Swarts, M. E., Gentry, T. R. (2014). Integrated generative technique for interactive design of brickworks. Journal of Information Technology in Construction, 19, 225–247.
- Fedorenko, O. Yu., Bilostotska, L. O., Bohdanova, K. B., Polukhina, K. S., Pavlova, L. V. (2018). Surface coloring with solutions of salts of densely baked ceramic materials. Voprosy Khimii i Khimicheskoi Tekhnologii, 6, 139–147. doi: <https://doi.org/10.32434/0321-4095-2018-121-6-139-147>
- Pishch, I. V., Maslennikova, G. N., Gvozdeva, N. A., Klimosh, Y. A., Baranovskaya, E. I. (2007). Methods of dyeing ceramic brick. Glass and Ceramics, 64 (7-8), 270–273. doi: <https://doi.org/10.1007/s10717-007-0067-7>
- Mustafin, N. R., Aschmarin, G. D. (2006). Die Klinkerkeramik auf Grund des Kieselerderohstoffes und der technogenischen Abfallstoffe. Keramische Zeitschrift, 4, 80–81.
- Pishch, I. V., Biryuk, V. A., Klimosh, Yu. A., Popov, R. Yu., Mikulich, T. N. (2017). Poluchenie klinkernogo kirpicha na osnove mineral'nogo syr'ya respublik Belarus'. Proceedings of the National Academy of Sciences of Belarus. Chemical series, 4, 90–98.



8. Khomenko, E. S., Purdik, A. V. (2017). Particulars of Microstructure Formation in Clinker Ceramic. *Glass and Ceramics*, 74 (1-2), 48–51. doi: <https://doi.org/10.1007/s10717-017-9926-z>
9. Yatsenko, N. D., Yatsenko, E. A., Zakarlyuka, S. G. (2017). Phase Composition and Properties of Building Ceramic as a Function of the Contents of Calcium Carbonates and Iron Oxides. *Glass and Ceramics*, 73 (9-10), 319–322. doi: <https://doi.org/10.1007/s10717-017-9881-8>
10. Valanciene, V., Siauciunas, R., Baltusnikaite, J. (2010). The influence of mineralogical composition on the colour of clay body. *Journal of the European Ceramic Society*, 30 (7), 1609–1617. doi: <https://doi.org/10.1016/j.jeurceramsoc.2010.01.017>
11. Valanciene, V., Siauciunas, R., Baltusnikaite, J. (2010). The influence of mineralogical composition on the colour of clay body. *Journal of the European Ceramic Society*, 30 (7), 1609–1617. doi: <https://doi.org/10.1016/j.conbuildmat.2004.04.035>
12. De Bonis, A., Cultrone, G., Grifa, C., Langella, A., Leone, A. P., Mercurio, M., Morra, V. (2017). Different shades of red: The complexity of mineralogical and physico-chemical factors influencing the colour of ceramics. *Ceramics International*, 43 (11), 8065–8074. doi: <https://doi.org/10.1016/j.ceramint.2017.03.127>
13. Maritan, L., Nodari, L., Mazzoli, C., Milano, A., Russo, U. (2006). Influence of firing conditions on ceramic products: Experimental study on clay rich in organic matter. *Applied Clay Science*, 31 (1-2), 1–15. doi: <https://doi.org/10.1016/j.clay.2005.08.007>
14. Pontikes, Y., Rathossi, C., Nikolopoulos, P., Angelopoulos, G. N., Jayaseelan, D. D., Lee, W. E. (2009). Effect of firing temperature and atmosphere on sintering of ceramics made from Bayer process bauxite residue. *Ceramics International*, 35 (1), 401–407. doi: <https://doi.org/10.1016/j.ceramint.2007.11.013>
15. Rathossi, C., Pontikes, Y. (2010). Effect of firing temperature and atmosphere on ceramics made of NW Peloponnese clay sediments: Part II. Chemistry of pyrometamorphic minerals and comparison with ancient ceramics. *Journal of the European Ceramic Society*, 30 (9), 1853–1866. doi: <https://doi.org/10.1016/j.jeurceramsoc.2010.02.003>
16. Yustova, E. N. (2000). *Cvetovye izmereniya (Kolorimetriya)*. Sankt-Petrburg: Izd-vo SPb. un-ta, 397.