

Power Engineering

Veremeyenko I.S., Gladyshev S.V., Andryuschenko S. A. and Agibalov E. S. Measurement of a torque at the Kaplan turbine model runner blade using wireless telemetry 3

An advanced variant of an experimental method of investigating the blades torque using models of the Kaplan turbine runner was suggested. The investigation is based on using modern miniature electronics devices and wireless technologies. The experience of implementing the method suggested on the hydrodynamic test bench at IPMash NAS of Ukraine and the results of measuring the torque for a six-blade model of the PL40 runner are given. The torque was measured using a strain gauge transducers and an runner model developed by LLC Kharkovturboengineering specialists. Experiments on the hydrodynamic test bench yielded the values of blade torques for the entire hill diagram range. The torque for acceleration conditions, as well as the torque vs. centrifugal force values was measured.

Keywords: runner model, Kaplan turbine, blade, torque, strain gauge transducer, experiment.

References

1. Malyshev V. M. Model Investigations of a Hydro Turbine. – L. Mashynostroenie Publishers.- 1971. – 286 p.
2. Orgo V. M. Hydro Turbines – L. LSU Publishers, 1975. – 320 p.
3. Kovalev N. N. Hydro Turbine Design // L. Mashynostroenie Publishers. 1974. – 280 p.

Heat Transfer in Engineering Constructions

Chirkin N. B., Kuznetsov M. A., Sherstov E. V. and Stennikov V. N. Potential possibility and technical rationality of heat-pumping technologies application at the combined production of electric and thermal energy 11

Principal possibility of heat-pumping technologies application for heat recovery of the traditionally lost low-grade heat on the thermal electric stations with the purpose of efficiency increase of the primary fuel use is considered. On the example of municipal heat-electric generating plant work during a year analysis waste heat potential suitable for the use in heat-pumps as low-grade heat is appraised. Characteristics of heat-pumps that are present in the world market and suitable for thermal power-stations waste heat utilization are considered. The credible consumers of producible heat-pumping installations heat on thermal power-stations and the simplest basic schemes are analyzed. The brought results show technical feasibility and perspective of heat-pumping direction of the thermal electric stations low-grade heat utilization and necessity of further researches realization for the ground of his technical and economic expediency.

Keywords: heat-pump, heat-pump installation, thermal power-station, heat-electric generating plant, power efficiency, increase, waste heat, utilization.

References

1. Dolinskij A. A. (2013). Teplonasosnye technologii v Ukraine. Sostojanie i perspektivy razvitiya. Thesisy doklada konferentzii: Teplovye nasosy v stranah SNG. Alushta, 14-16 maja 2013, 1, CD-R.
2. Matzevity Yu. M., Chirkin N. B., Klepanda A. S. (2014). Ob ispolzovanii teplovyyh nasosov v mire i chto tormozit ich shirokomasshtabnoe vnedrenie v Ukraine. Energozberegenie. Energetika. Energoaudit, 2, 2 – 17.
3. Proc. 10th IEA Heat Pump Conference 2011, 16–19 May 2011. Tokyo, 2011. – 935 p.
4. Molodkina M. A. (2012). Povyshenie techniko-ekonomiceskikh pokazatelej parogazovyh teplovyyh elektrostantsij putem utilizatzii nizkopotentzialnoj teploty s ispolzovaniem teplovyyh nasosov. Avtoref. dis. ... kand. techn. nauk. Spb., 16.
5. Stepanenko V. A., Afanasiev A. S. (2013). Teplovye nasosy v sistemah teplosnabgenija i konditsionirovaniya gorodov i zdaniij Ukrayny v 21 veke. Thesisy doklada konferentzii: Teplovye nasosy v stranah SNG. Alushta, 14-16 maja 2013, 1, CD-R.
6. Pritzenko V. P., Puatovalov S. B., Savitzkij A. I., Leguenko S. K. (2010). Atomno- teplonasosnaja teplofifikatsija (ATT) kak novoe napravlenie v razvitiu energetiki. Energozberegenie i vodopodgotovka, 1, 25 – 29.
7. Devjanin D. N., Pischikov S. I., Sokolov Yu. N. (2000). Razrabotka I ispytanije na TEC-28 OAO «Mosenergo» laboratornogo stenda po aprobatzii shem ispolzovaniya teplonasosnyh

- ustanovok v energetike. Novosti teplosnabgenija, 1, 31 – 34.
8. Nikiforovich E. I., Litvinjuk Yu. M. (2008). Perspektivnye vykorystannja teplovyh nasosiv dlja utylizatzii nyzkopotentzijnogo tepla na prykladi TEC-5 m. Kieva. Nova tema, 4, 13 – 16.
 9. Basok B. I., Nedbailo A. N., Shvez M. Yu. (2013). Proekt ispolzovaniya moshnyh teplovyh nasosov na ob'ektaх bolshoj energetiki. Thesisy doklada konferenzii: Teplovye nasosy v stranah SNG. Alushta, 14-16 maja 2013, 1, CD-R.

Dynamics and Strength of Machines

- Raibov A. V., Katasonov A. Ye., Trubayev A. I., Vodka O. O. and Ulanov Yu. N.** Computational and experimental investigations of the dynamic characteristics of the blades of the model kaplan turbine 21

This work deals with the computational and experimental investigation of the dynamic characteristics of the model Kaplan turbine blades. Experimentally and numerically eigenfrequency spectrum of the blade in the air and in the water has been determined. Also, the parameters of the damping of the blades and its frequency response have been obtained.

References

1. Strelnikova H. A., Medvedovskaya T. F., Rzhevskaya I. E., Ganchin E. V. Research of Dynamic Characteristics for Hydro-Turbine Structure Elements Including Material and Operation Defects, Vestnik SevNTU, 2012, № 110, Pp. 37-42
2. Ganchin E. V., Rzhevskaya I. E., Strelnikova H. A. Analysis of dynamic characteristics of water wheel blades of Kaplan hydraulic turbines at interaction with a fluid, Bulletin of V. Karazin Kharkiv National University, 2008, № 847, Pp. 79-86
3. Ganchin E. V., Rzhevskaya I. E., Strelnikova H. A. Strength, dynamics and life time of the impeller vane, Aviatsionno-kosmicheskaya technika i technologiya, 2009, №9 (66). Pp. 91-94
4. Breslavskiy I. D., Strelnikova H. A., Avramov K. V. Free vibrations of a shallow shell in a fluid with geometrically nonlinear deformation, Problemy prochnosti, N1, Pp. 40-50.
5. Breslavskiy I. D., Avramov K. V. Vibrations of geometrically nonlinear shallow shells of variable thickness, clamped along part of the circuit, Dynamicheskie sistemy, 2009, №27. – PP. 17-29
6. Zenkevich O. K. Finite element method in engineering, Moscow, Mir, 1975, 420 p.
7. Model studies of the of hydraulic turbines, Leningrad, Mashinostroenie, 1971, 288 p
8. Yavits S. N. Investigation of the frequency characteristics of the blades of the impeller of the water turbines, Energomashinostroenie, 1970, N8, Pp. 25-28

- Bogomolov V. and Sklepus S.** Calculation of the stress-strain state, creep and creep-damage of multilayer plates on the elastic foundation..... 27

The paper considers the problem of calculating the stress-strain state, creep and creep-damage of multilayer orthotropic plates on elastic foundation. Plate may be loaded by the transverse load, normal and tangential contour loads and the temperature field. A variational formulation of the problem is made in the terms of refined theory of plates and shells. Cauchy problem in time for the main unknown functions of initial-boundary value problem is formulated. To solve the nonlinear initial-boundary creep and creep-damage problem is proposed to use a combination of R-functions, Ritz and Runge-Kutta-Merson methods. R-functions method allows to accurately account for the geometry of the domain and the boundary conditions of the most general form. The solution of the boundary value problem is represented as a formula - structure of the solution that exactly satisfies all (general structure of the solution) or part (partial structure of the solution) boundary conditions. Structure of solution is invariant with respect to the shape of the domain. An example of calculating of stress-strain state of two-layer plate on elastic foundation has been shown. The developed method can be used to investigate the stress-strain state and the long-term strength of road surface.

References

1. Privarnikov A. K. Solution of boundary value problems of elasticity theory for multilayer bases.– Dnepropetrovsk: Izdatelsvo Dnepropetr. universiteta, 1976.– 60 p.
2. Piskunov V. G., Verigenko V. E., Prisiagniuk V. K., Sipetov V. S., Karpilovskij V. S. Calcula-

- tion of inhomogeneous shallow shells and plates using the finite element method. – Kiew: Visha shkola, 1987. – 200 p.
3. Rudenskij A. V. Road asphalt-concrete coating. – M.: Transport, 1992.– 253 p.
 4. Zolotariov V. A. The durability of road asphalt-concrete.– Kharkov: Visha shkola, 1977.– 116 p.
 5. Boguslavskij A. M. Fundamentals of asphalt rheology. – M.: Vishaja. shkola, 1972.– 199 p.
 6. Rasskazov A. O., Sokolovskaja I.I., Shulga N.A. Theory and calculation of laminated orthotropic plates and shells.– Kiew: Visha shkola, 1986.– 191 p.
 7. Zolochevsky A. A., Sklepus A. N., Sklepus S. N. Nonlinear mechanics of deformable solids. – Kharkov: «Biznes Investor Grupp», 2011.– 720 p.
 8. Rabotnov Y. N. Creep problems in structural members– M.: Hayka, 1966.–752 p.
 9. Vlasov V. Z., Leontiev N. N. Beams, plates and shells on elastic foundation.– M.: Fizmatgiz, 1960. – 491 p.
 10. Rvachev V. L. Theory of R-functions and some applications – Kiew: Nauk. dumka, 1982. – 552 p.

Avramov K. V., Morachkovski O. K., Tonkonogenko A. M., Kozarin V. Yu., Kochurov R. Ye. Semi-analytical finite element method for deflected mode of ribbed cylindrical shells

33

Semi analytical finite element method is suggested to calculate cylindrical shells supported by longitudinal stiffness. The displacements, which are expanded into the Fourier series by circumference coordinate, are the main unknowns of the suggested approach. One dimensional finite elements are used to calculate amplitudes of the harmonics. Clamped cylindrical shells with three and twenty longitudinal stiffness are analyzed numerically. The properties of the shell deflected mode are analyzed numerically using the suggested approach.

Keywords: finite elements method, stiffness shells, stiffness matrix.

References

1. Mossakovski V.I., Makarenko P.I., Nikitin M. Strength of rockets. Moskow: Vishaja Skola, 1990.
2. Amiro J. Ya., Zarutski V.A. Theory of ribbed shell. Kiev: Naukova Dumka, 1980.
3. Rikards R.B. Finite elements method in shell theory. Riga: Zinate, 1988.

Boyarshinov A. Yu. Improving geometry and reliability multisupporting long tail compounds steam turbine blades

42

Selection of the most optimal design of low-pressure cylinder's steam pipe for high power steam turbines is not possible without usage of scientific achievements of the last decade. Different software systems can be used to optimize blades' geometry of low-pressure cylinder's steam pipe. Three dimensional models of steam flows are used for improvement of evaluation methods for biphasic medium flow in conditions of liquid medium formation and its interaction with blades.

Modern evaluational methods allow to increase reliability of blades by means of erosional wear-out minimization. Improved design of blade tails developed to optimally decrease strains is also important for reliability. Complex approach to design of low-pressure cylinder's steam pipe is useful for newly developed high power turbines as well as for upgrade of existing ones. This approach allows to design high quality blade tails which correspond to actual industry requirements to effectiveness and reliability.

Selection of the most optimal design of low-pressure cylinder's steam pipe for high power steam turbines is not possible without usage of scientific achievements of the last decade. Different software systems can be used to optimize blades' geometry of low-pressure cylinder's steam pipe. Three dimensional models of steam flows are used for improvement of evaluation methods for biphasic medium flow in conditions of liquid medium formation and its interaction with blades. Modern evaluational methods allow to increase reliability of blades by means of erosional wear-out minimization. Improved design of blade tails developed to optimally decrease strains is also important for reliability.

Complex approach to design of low-pressure cylinder's steam pipe is useful for newly developed high power turbines as well as for upgrade of existing ones. This approach allows to design high

quality blade tails which correspond to actual industry requirements to effectiveness and reliability.

Keywords: the last stage of the turbine blade, stress-strain state, bearing surface of the tooth, stress concentration factor, photoelasticity method, finite element technique, blade profile

References

1. Leykin A.C. Ob obshey neravnomernosti raspredeleniya napryajeniy v zamkakh lopatok turbomashin v sviazi s vliuaniem profilya lopatki / A.C. Leykin // Izv. AN CCCR. Mekhanika i mashinostroenie. – 1960. – №4. – C. 149 – 153.
2. Leykin A.C. Naprujennost i vinoslivost detalei slojnoi konfiguracii / A.C. Leykin . – M: Mashinostroenie, 1968. – 372 c.
3. Leykin A.C. Konstruktivnye metody povushenija prochnosti elochnyx zamkov turbomashin pri peremennix nagruzkax / A.C. Leykin // Vestn. mashinostroeniya. – 1964. – №3. – C. 15 – 18.
4. Leykin A.C. Issledovanie raspredeleniya napryajeniij v elochnyx zamkakh lopatok turbin pri rastyajenii i izgibe. Voprosy prochnosti materialov i konstrukcij / A.C. Leykin – M.: Izl.-vo. AN CCCR. – 1950. – C. 334 – 360.
5. Podgornuy A.N. Napryajeniya i dephormacii v detaluax parovux turbin / A.N. Podgornuy, V.P. Suxinin. - Kiev.: Nauk. dumka, 1978. – 276 c.
6. Suxinin V.P. Eksperimentalnoe issledovanie obiemnogo naprujennogo sostouaniya elementov lopatok / V.P. Suxinin., I.B. Volkovich // Dinamika i prochnost mashin.– 1977. – Vup. 25. – C. 81 – 86.
7. Suxinin V.P. Vliuanie formy kontaktnej poverhnosti na raspredelenie napryajeniij v xvostovyx soedineniyax rabochix lopatok parovux turbin / V.P. Suxinin., T. N.Fyrsova // Probl. mashinostroeniya. – 2008. - T.11. - №4. – C. 19 – 25.
8. Prochnost elementov parovux turbin / L.A. Shubenko-Shubin, D.M. Gerner , V.P. Suxinin. i dr. – M.: Mashgiz, 1962. – 568 c.
9. Prochnost parovux turbin / Pod red. L.A. Shubenko-Shubina. – M.: 'Mashinostroenie, 1973. – 456 c.
10. Suxinin V.P. Vliyanie formy kontaktnej poverxnosti na raspredelenie napryajeniij v xvostovyx soedineniyax rabochix lopatok parovux turbin / V.P. Suxinin., T. N.Fyrsova // Probl. mashinostroeniya.–2008. – T.11. – №4. – C. 19 — 25.
11. Pat. 54905 Ukraina, МПК F01D 5/28. Kontaktnyj vuzol ualynkovogo xvostovogo zyednannia rabochey lopatki z diskom rotora / O.L. Shubenko, V.P. Suxinin., T. N.Fyrsova, O.UO.Boyarshinov. – № u201007002; Zauavl. 07/06/2010; Opubl. 25.11.2010, Bul.№22.

Applied Mathematics

Yaskov G. N. Packing non-equal hyperspheres into a hypersphere of minimal radius 48

The problem of packing different hyperspheres into a hypersphere of minimal radius is considered. All hypersphere radii are supposed to be variable. Solving the problem is reduced to solving a sequence of mathematical programming problems. A special way of construction of starting points is suggested. A smooth transition from one local minimum point to another providing a decrease of the objective value is realized using the jump algorithm is fulfilled. Then, solution results are improved due to reduction of the solution space dimension by step-by-step fixing radii of hyperspheres and rearrangements of hypersphere pairs. Non-linear mathematical programming problems are solved with the IPOPT (Interior Point Optimizer) solver and the concept of active inequalities. A number of numerical results are given.

Key words: hypersphere, packing, mathematical modeling, jump algorithm

References

1. Skoge, M., Donev, A., Stillinger, F.H., Torquato, S. Packing hyperspheres in high-dimensional Euclidean spaces, Physical Review, E **74**, 041127, 2006.
2. Agapie, S.C., Whitlock, P.A. Random packing of hyperspheres and Marsaglia's parking lot test, Monte Carlo Methods and Applications, **16**(3-4), 197–209, 2010.
3. Conway, J. H., Sloane, N.J.A. Sphere Packings, Lattices, and Groups, New York: Springer-Verlag, 2010, 703 p.
4. Torquato, S. Exactly solvable disordered sphere-packing model in arbitrary-dimensional Euclid-

- ean spaces, Physical Review, **E 73**, 031106, 2006.
5. *Jodrey, W.S., Tory, E.M.* Computer simulation of close random packing of equal spheres, Physical Review, **A32**, 2347-2351, 1985.
 6. *Fraser, D.P.* Setting up Random Configurations, Information Quarterly for Computer Simulation of Condensed Phases, **19**, 53–59, 1985.
 7. *Morse, P., Clusel, M., Corwin, E.* Polydisperse sphere packing in high dimensions, a search for an upper critical dimension, Proc. APS March Meeting 2012, February 27–March 2, 2012, Boston, Massachusetts, **57**(1), 2012.
 8. *Stoyan, Yu., Yaskov, G.* Packing congruent hyperspheres into a hypersphere, Journal of Global Optimization, **52**(4), 855–868, 2012.
 9. *Stoyan, Yu., Yaskov, G.* Packing unequal circles into a strip of minimal length with a jump algorithm, Optimization Letters, 1-22, 2013 (DOI: 10.1007/s11590-013-0646-1).
 10. *Stoyan, Yu. G., Yaskov, G.* A mathematical model and a solution method for the problem of placing various-sized circles into a strip, European Journal of Operational Research, **156**, 590–600, 2004.
 11. *Wächter, A., Biegler, L. T.* On the implementation of a primal-dual interior point filter line search algorithm for large-scale nonlinear programming, Mathematical Programming, **106**(1), 25–57, 2006.
 12. *Zoutendijk, G.* Methods of feasible directions. A study in linear and non-linear programming, Amsterdam, London, New York, Princeton: Elsevier Publishing Company, 1960, 126 p.

Non-traditional Power Engineering

- Tymchik A. V. and Safonov N. A.** Heating the particles of coal dust plasma microwave discharge 54

The article presents the physical and mathematical model of heating coal dust particles microwave discharge plasma at atmospheric pressure in a stream of carbon aerosol. Calculation of the temperature of the coal particles, depending on the time when it moves together with the gas medium is reduced to the solution of the Cauchy problem for an ordinary differential equation modeling the process of heating a coal particle. To calculate the temperature distribution in the microwave discharge plasma used transient heat conduction equation with internal heat sources. It was believed that the source is only Joule heating; convection and thermal conductivity are considered drains energy in the equation is also not taken into account in the amount of energy release due to viscous friction forces, as well as due to compression and expansion volume. The results of numerical studies of the air temperature and the coal particles in the discharge volume in relation to the experimental plasma-coal burner.

References

1. Kanilo P. M, Kostuk V. E., Tymchik A. V. i dr. (2004). SVCh-plasmennaya technologiya szhiganiya nizkosortnyh ugley. Probl. Mashinostroenia, **7**(2), 72-77.
2. Karpenko E. I., Messerle V. E. (1997). Vvedenie v plazmenno-energeticheskie technologii ispolsovaniya tverdyh topliv. Novosibirsk, Nauka, 119.
3. Kukota Yu. P., Bondzik D. L., Dunaevckaya N. I. i dr. (2004). Plasmennyi podzhig vysokosolnyh antrazitov pri ih fakelnom szhiganii. Prom. Teploenergetika, **6**, 146-151.
4. Vavril D. M., Tymchik A. V., Ivanovskiy A. I. i dr. (2006). O mehanizme vzaimodeystviya SVCh-razryada s pyleugolnym potokom. Probl. Mashinostroeniya, **5**(1), 85-90.
5. Tymchik A. V. (2009). Vosplamenenie ugolnoj pyli plasmoj SVCh-razryada. Probl. Mashinostroenia, **7**(3), 72-77.
7. Dresvin S. V., Bobrov A. A., Lelevkin V. M. i dr. (1992) VCh- i SVCh-plasmotrony (Nizkotemperaturnaya plasma; T. 6). Novosibirsk, Nauka, 319.
6. Tymchik A. V. (2011) Usloviya vosplameneniya ugolnoj pyli plasmoj SVCh-razryada. Probl. mashinostroenia, **7**(2), 69-71.
8. Dresvin S. V. Osnovy teorii i rascheta VCh-plasmotronov. (1991). Leningrad, Energoatomizdat, 312.
9. Tymchik A. V., Safonov N. A. (2012). SVCh-razryad v potoke ugolnogo aerozolya. Probl. mashinostroeniya, **15**(1), 60-65.
10. Raiser Yu. P. (1987). Fizika gazovogo razryada. Mosrow, Nauka, 592.
11. Pomerantsev V. V., Arefyev K. V., Achmetov D.B. i dr. (1986). Osnovy prakticheskoy

- teorii gorenja: Uchebn. Posobie. Leningrad, Energoatomizdat, 310.
12. Bachvalov N. S., Zhidkov N. P., Kobelkov G. V. (1987). Chislennye metody. Moskow, Nauka, 600 s.
 13. Vlasov V. I., Zalogin G. N., Kusov A. L. (2007). Sublimaciya chertsits ugleroda v plasmennom potoke, generiruemym v vysokochastotnom indukcionnom plasmotrone. Zhurn. techn. Fiziki, 77(1), 1-7.

Materials Science in Mechanical Engineering

- Matsevity V., Vakulenko K., and Kazak I.** On differences in mechanisms of metal fracture in conditions of low-cycle and high-cycle fatigue..... 60

Differences in mechanisms of damage accumulation for low-cycle and high-cycle fatigue in terms of efficiency of use of the coercive force method in diagnostics of presence of defects in metal under cyclic loading are considered.

It is pointed out that, depending on level of loading amplitude, different kinds of fracture are dominant with different probability.

In case of low loading amplitudes, the most probable mechanism comprises an intracrystalline fracture.

In case of cyclic loading with high amplitudes, there is a high probability of fracture along crystal boundaries, which causes accumulation of more coarse fracture elements and leads to greater nonuniformity of metal. Therefore energy consumption required for shifting the domain boundaries during remagnetization is increased. A substantial change in coercive force as one of the most important characteristics of the hysteretic loop, which area represents energy consumption for metal remagnetization, results from more coarse change of magnetic structure.

It is concluded that a high sensitivity of the coercive force method to development of low-cycle fatigue and far lesser sensitivity to high-cycle fatigue is connected with the said differences in metal fracture.

Keywords: low-cycle fatigue; high-cycle fatigue; intercrystalline fracture; intracrystalline fracture; submicrocracks; damage accumulation; coercive force.

References

1. Ivanova, V.S. Ustalostnoe razrushenie metallov. – M.: Gos. nauch.- tehn. izd-vo lit. po chernoi i cvetnoi metallurgii, 1963.– 272s.
2. Mil'man Yu.V. Novye metodiki mikromehanicheskikh ispytanii materialov metodom lokal'nogo nagruzheniya zhestkim indentorom / Yu.V. Mil'man. // Suchasne mater'aloznavstvo XXI stor'chchya. – Kiiv: Naukova dumka, 1998. – S.637 – 656.
3. Miheev M.N. Svyaz' magnitnyh svoistv so strukturnym sostoyaniem veshestva – fizicheskaya osnova magnitnogo strukturnogo analiza: obzor / M.N. Miheev, E.S. Gorkunov // Defektoskopiya. – 1981. – '8. – S. 5-22.
4. Fizicheskoe metallovedenie. Vyp. 1. Atomnoe stroenie metallov i splavov / pod red. R. Kana. – M.: Mir, 1967. – 334 s.
5. Bezlyud'ko G.Ya. Ekspluatacionnyi kontrol' ustalostnogo sostoyaniya i resursa metalloprodukciyi nerazrushayushim magnitnym (koercitimetricheskim) metodom / G.Ya. Bezlyud'ko // Tehnicheskaya diagnostika i nerazrushayushii kontrol'. – 2003. – '2. – S. 20–26.
6. Bezlyud'ko G.Ya., Zaval'nyuk O.P., Nesterenko V.B., Marchenko A.Yu., Solomaha R.N. Obzornaya ocenka sostoyaniya i detal'naya ekspertiza ustalosti metalla bol'sherazmernykh ob'ektor i konstrukcii nerazrushayushim magnitnym metodom / G.Ya. Bezlyud'ko // Tehnicheskaya diagnostika i nerazrushayushii kontrol'. – 2012. – '3. – S. 57–65.
7. Macevityi V. M.. Sposobnost' k peremagnichivaniyu stali 14H17N2 posle termoobrabotki, kovki i ciklicheskogo nagruzheniya / V. M. Macevityi, G. Ya. Bezlyud'ko, E. V. Belous, K. V. Vakulenko, I. B. Kazak // Problemy mashinostroeniya. – Har'kov, 2009 – T. 12, '14. – S. 79-85.
8. Lazan B. Damping, elasticity and fatigue properties of unnotched and notched N-155 alloy at room and elevated temperatures / B. Lazan, L. Demer // Proc. ASTM, 1951. – v.51. – P. 611 – 617.
9. Lazan B. Damping fatigue and dynamic stress-strain prorerties of mild steel/ B. Lazan, T.

ABSTRACTS AND REFERENCES

- Wu. // Proc. ASTM, 1951. – v.51. – P. 649 – 655.
10. Larikov L.N. Zalechivanie defektov v metallah / L.N. Larikov– K.: Naukova dumka, 1980. – 280 s.
- 11 Macevityi V.M. K fizicheskому mehanizmu razrusheniya metallov / V.M. Macevityi, I.B. Kazak, K.V. Vakulenko, E.V. Belous, S.V. Lyashok // Problemy mashinostroeniya. – Har'kov. – 2008. – T. 11, 1 5-6. – S. 87–96.
12. Vakulenko K.V. Obobshennaya koncepciya adgezii tverdyh tel / K.V. Vakulenko, I.B. Kazak, V.M. Macevityi // Vostochno-Evropeiskii zhurnal peredovyh tehnologii. – 2008. – 14. – S. 13-23.
13. Snowden K.U. Surface deformation differences between lead fatigued in air and in partial vacuum / K.U. Snowden, J.N. Greenwood // Trans. Of the Metallurgical Society of AIME. – 1958. – P. 626 – 630.

УВАЖАЕМЫЕ КОЛЛЕГИ!

Приглашаем вас принять участие в работе
научно-технической конференции

«Физико-технические проблемы энергетики и пути их решения 2014» (ФТПЭПР-2014)

Время и место проведения конференции – 25-26 июня 2014 г., Харьковский национальный университет имени В.Н. Каразина (северный корпус, актовый зал)

Тематика конференции:

- Альтернативная энергетика и возобновляемые источники энергии
- Энергосберегающие технологии и объекты нетрадиционной энергетики
- Математическое моделирование физических процессов
- Теплофизика, моделирование и идентификация нелинейных тепловых процессов
- Энергетическое машиностроение, моделирование и компьютерные технологии в энергетическом машиностроении
- Экологически чистые силовые установки для энергетики и транспорта
- Экологические аспекты энергетики
- Энергетика биофизических систем
- Охрана труда в преподавании и научных исследованиях в области физики, энергетики и экологии

Рабочие языки – украинский, русский, английский

Оригинал-макет подготовлен в редакции журнала «Проблемы машиностроения»
Компьютерная верстка *A. O. Костиков*
Редактор *H. B. Сивцова*

Подп. в печ. 06.03.14. Формат 60×84 1/8. Гарнитура «Таймс».
Бум. офс. Усл. п. л. 10,0. Тираж 300 экз.
Цена договорная. Заказ №

Издание подготовлено к печати и отпечатано
в издательско-полиграфическом центре «Контраст»
Украина, 61166, г. Харьков, пр-т Ленина, 40. комн. №231
тел./факс (0572) 19-49-13, (0572) 30-43-91
Свидетельство: ДК № 178 от 15.09.2000.