



MECHANICAL ENGINEERING TECHNOLOGY

DOI: 10.15587/2706-5448.2026.352967

DEVELOPMENT OF A PREDICTIVE THERMAL MODEL BASED ON THE EQUIVALENT SOURCE APPROACH FOR SMAW WELDING OF X70 STEEL PIPES

pages 6–14

Adel Chouiter, PhD in Mechanical Engineering, HDR, Department of Mechanical Engineering, Laboratory Applied Sciences of Mechanics, Electromechanics and Materials (ASMEM), Mentouri Brothers University Constantine1, Constantine, Algeria, ORCID: <https://orcid.org/0009-0003-1064-1805>

Lyes Bidi, PhD in Mechanical Engineering, Professor, Laboratory Applied Sciences of Mechanics, Electromechanics and Materials (ASMEM), Mentouri Brothers University Constantine1, Constantine, Algeria, ORCID: <https://orcid.org/0000-0003-0621-1274>

Hadjer Bensiali, Doctor of Technical Sciences, PhD, Department of Transport Engineering, Laboratory of Transports and Environment Engineering, Mentouri Brothers University Constantine1, Constantine, Algeria, ORCID: <https://orcid.org/0009-0000-9182-5005>

Rachid Chaib, Doctor of Technical Sciences, Professor, Department of Transport Engineering, Laboratory of Transports and Environment Engineering, Mentouri Brothers University Constantine1, Constantine, Algeria, e-mail: r3chaib@yahoo.fr, ORCID: <https://orcid.org/0000-0001-8680-1906>

Philippe Le Masson, PhD in Mechanical Engineering, Professor, C. HUYGENS Research Centre, University of Southern Brittany, Morbihan, France, ORCID: <https://orcid.org/0000-0003-2721-8504>

The object of the research is the scientific approach for modeling thermal phenomena during welding operations in SMAW welding of pipelines. This model can be used to calculate changes in temperature fields as well as stresses and deformations.

Mastering welding processes requires an understanding of the various phenomena involved. This requires numerous tests to be carried out, which are very costly for manufacturers. The ideal solution would therefore be to develop predictive numerical models that would enable the behavior of assemblies to be analyzed. The SMAW process is used to fill a chamfer between two parts. It is therefore essential to define heat input, which can be described using the equivalent heat source approach the equivalent heat source approach. The difficulty in implementing this approach lies in estimating the various parameters of the model. To this end, it was proposed to develop a simple and robust approach, which consists of using the numerical design of experiments (NDE) method.

In this research, it was decided to select four parameters from the model (r_{surf_sup} , r_{surf_inf} , r_0 and λ) and four objective functions characterizing the shape of the fusion zone (L_{sup} , L_m , L_{inf} , H). Preliminary results show good agreement between the direct model and the dimensions recorded on the macrographic sections, with the exception of the width of the median side of the fusion zone (L_m), where there is a significant deviation of 11.4% between the measurements and the model. Furthermore, the NDE shows that r_{surf_inf} is the factor that most influences L_m . Adjusting the r_{surf_inf} factor by 0.5 from its value at the central point changes the L_m value from 3.25 mm to 3.09 mm. This adjustment optimizes the digital model by improving it and reducing the discrepancy between the simulation and the experiment for the L_m function from 11.4% to 1.2%. The results of this research make it possible to increase the reliability of petroleum facilities (pipeline assemblies). The scientific novelty of this research lies in the implementation of a simple and robust scientific approach for optimizing non-physical parameters (equivalent heat source parameters) in the modeling of welding processes.

Keywords: welding simulation, numerical design, SMAW welding, equivalent heat source, adjustments parameters.

References

1. Goldak, J., Chakravarti, A., Bibby, M. (1984). A new finite element model for welding heat sources. *Metallurgical Transactions B*, 15 (2), 299–305. <https://doi.org/10.1007/bf02667333>

2. Yu, D., Yang, C., Sun, Q., Dai, L., Wang, A., Xuan, H. (2023). Impact of process parameters on temperature and residual stress distribution of X80 pipe girth welds. *International Journal of Pressure Vessels and Piping*, 203, 104939. <https://doi.org/10.1016/j.ijpvp.2023.104939>

3. Kong, F., Ma, J., Kovacevic, R. (2011). Numerical and experimental study of thermally induced residual stress in the hybrid laser–GMA welding process. *Journal of Materials Processing Technology*, 211 (6), 1102–1111. <https://doi.org/10.1016/j.jmatprotec.2011.01.012>

4. Liu, S., Sun, J., Wei, F., Lu, M. (2018). Numerical simulation and experimental research on temperature and stress fields in TIG welding for plate of RAFM steel. *Fusion Engineering and Design*, 136, 690–693. <https://doi.org/10.1016/j.fusengdes.2018.03.058>

5. Bidi, L., Mattei, S., Cicala, E., Andrzejewski, H., Le Masson, P., Schroeder, J. (2011). The use of exploratory experimental designs combined with thermal numerical modelling to obtain a predictive tool for hybrid laser/MIG welding and coating processes. *Optics & Laser Technology*, 43 (3), 537–545. <https://doi.org/10.1016/j.optlastec.2010.07.011>

6. Zubairuddin, M., Albert, S. K., Vasudevan, M., Mahadevan, S., Chaudhari, V., Suri, V. K. (2017). Numerical simulation of multi-pass GTA welding of grade 91 steel. *Journal of Manufacturing Processes*, 27, 87–97. <https://doi.org/10.1016/j.jmapro.2017.04.031>

7. Bendaoud, I., Mattei, S., Cicala, E., Tomashchuk, I., Andrzejewski, H., Sallamand, P. et al. (2014). The numerical simulation of heat transfer during a hybrid laser-MIG welding using equivalent heat source approach. *Optics & Laser Technology*, 56, 334–342. <https://doi.org/10.1016/j.optlastec.2013.09.007>

8. Obeid, O., Alfano, G., Bahai, H., Jouhara, H. (2018). Numerical simulation of thermal and residual stress fields induced by lined pipe welding. *Thermal Science and Engineering Progress*, 5, 1–14. <https://doi.org/10.1016/j.tsep.2017.10.005>

9. Goldak, J., Bibby, M., Moore, J., House, R., Patel, B. (1986). Computer modeling of heat flow in welds. *Metallurgical Transactions B*, 17 (3), 587–600. <https://doi.org/10.1007/bf02670226>

10. Li, W., Yu, R., Huang, D., Wu, J., Wang, Y., Hu, T. et al. (2019). Numerical simulation of multi-layer rotating arc narrow gap MAG welding for medium steel plate. *Journal of Manufacturing Processes*, 45, 460–471. <https://doi.org/10.1016/j.jmapro.2019.07.035>

11. Pichot, F., Danis, M., Lacoste, E., Danis, Y. (2013). Numerical definition of an equivalent GTAW heat source. *Journal of Materials Processing Technology*, 213 (7), 1241–1248. <https://doi.org/10.1016/j.jmatprotec.2013.01.009>

12. Danis, Y., Lacoste, E., Arvieu, C. (2010). Numerical modeling of inconel 738LC deposition welding: Prediction of residual stress induced cracking. *Journal of Materials Processing Technology*, 210 (14), 2053–2061. <https://doi.org/10.1016/j.jmatprotec.2010.07.027>

13. Farias, R. M., Teixeira, P. R. F., Vilarinho, L. O. (2021). An efficient computational approach for heat source optimization in numerical simulations of arc welding processes. *Journal of Constructional Steel Research*, 176, 106382. <https://doi.org/10.1016/j.jcsr.2020.106382>

14. Lei, Y., Zhu, Q., Zhang, L., Gu, K., Ju, X. (2010). Simulation on the welding of CLAM steel. *Fusion Engineering and Design*, 85 (7–9), 1503–1507. <https://doi.org/10.1016/j.fusengdes.2010.04.014>

15. Bag, S., Trivedi, A., De, A. (2009). Development of a finite element based heat transfer model for conduction mode laser spot welding process using an adaptive volumetric heat source. *International Journal of Thermal Sciences*, 48 (10), 1923–1931. <https://doi.org/10.1016/j.ijthermalsci.2009.02.010>

16. Flint, T. F., Francis, J. A., Smith, M. C., Balakrishnan, J. (2017). Extension of the double-ellipsoidal heat source model to narrow-groove and keyhole weld configurations. *Journal of Materials Processing Technology*, 246, 123–135. <https://doi.org/10.1016/j.jmatprotec.2017.02.002>

17. Chen, L., Mi, G., Zhang, X., Wang, C. (2019). Numerical and experimental investigation on microstructure and residual stress of multi-pass hybrid laser-arc welded 316L steel. *Materials & Design*, 168, 107653. <https://doi.org/10.1016/j.matdes.2019.107653>

18. Farias, R. M., Teixeira, P. R. F., Vilarinho, L. O. (2022). Variable profile heat source models for numerical simulations of arc welding processes. *International*

Journal of Thermal Sciences, 179, 107593. <https://doi.org/10.1016/j.jiththermalsci.2022.107593>

19. Mondal, A. K., Kumar, B., Bag, S., Nirsanametla, Y., Biswas, P. (2021). Development of avocado shape heat source model for finite element based heat transfer analysis of high-velocity arc welding process. *International Journal of Thermal Sciences*, 166, 107005. <https://doi.org/10.1016/j.jiththermalsci.2021.107005>
20. Belitzki, A., Marder, C., Huisel, A., Zaeh, M. F. (2016). Automated heat source calibration for the numerical simulation of laser beam welded components. *Production Engineering*, 10 (2), 129–136. <https://doi.org/10.1007/s11740-016-0664-9>
21. Gannon, L., Liu, Y., Pegg, N., Smith, M. (2010). Effect of welding sequence on residual stress and distortion in flat-bar stiffened plates. *Marine Structures*, 23 (3), 385–404. <https://doi.org/10.1016/j.marstruc.2010.05.002>
22. Azadi Moghaddam, M., Golmezergi, R., Kolahan, F. (2016). Multi-variable measurements and optimization of GMAW parameters for API-X42 steel alloy using a hybrid BPNN–PSO approach. *Measurement*, 92, 279–287. <https://doi.org/10.1016/j.measurement.2016.05.049>
23. García-García, V., Reyes-Calderón, F., Camacho-Arriaga, J. C. (2016). Optimization of experimental temperature measurement in GTAW process by means of DoE technique and computational modeling. *Measurement*, 88, 297–309. <https://doi.org/10.1016/j.measurement.2016.03.049>
24. Fu, G., Gu, J., Lourenco, M. L., Duan, M., Estefen, S. F. (2014). Parameter determination of double-ellipsoidal heat source model and its application in the multi-pass welding process. *Ships and Offshore Structures*, 10 (2), 204–217. <https://doi.org/10.1080/17445302.2014.937059>
25. Bidi, L., Le Masson, P., Cicala, E., Primault, C. (2017). Experimental design method to the weld bead geometry optimization for hybrid laser-MAG welding in a narrow chamfer configuration. *Optics & Laser Technology*, 89, 114–125. <https://doi.org/10.1016/j.optlastec.2016.09.046>
26. Wang, H., Woo, W., Kim, D.-K., Em, V., Lee, S. Y. (2018). Effect of chemical dilution and the number of weld layers on residual stresses in a multi-pass low-transformation-temperature weld. *Materials & Design*, 160, 384–394. <https://doi.org/10.1016/j.matdes.2018.09.016>
27. Forouzan, M. R., Heidari, A., Golestaneh, S. J. (2009). FE simulation of submerged arc welding of API 5L-X70 straight seam oil and gas pipes. *Journal of Computational Methods in Engineering*, 28, 93–110 Available at: https://jcme.iut.ac.ir/article_3029_3925785f0e7afbb5933eb87d589edb33.pdf
28. Bensiali, H., Bidi, L., Cicala, E., Le Masson, P., Chibani, M. E. B., Boulahlib, M. S. (2021). Effects of operating parameters on weld bead morphology with welding operations of API 5L X70 steel pipes by SMAW process. *Welding in the World*, 65 (6), 1119–1129. <https://doi.org/10.1007/s40194-021-01085-4>
29. Bidi, L., Le Masson, P., Cicala, E. (2024). Influences of laser on the energy parameters of the electric arc in the case of laser-MIG hybrid welding. *The International Journal of Advanced Manufacturing Technology*, 131 (7–8), 4055–4069. <https://doi.org/10.1007/s00170-024-13244-0>
30. Goupy, J. (2001). *Introduction aux plans d'expériences*. Paris: Dunod. Available at: <https://iadji.com/wp-content/uploads/2020/08/Introduction-aux-Plans-dExperiences.pdf>
31. Montgomery, D. C. (1991). *Design and analysis of experiments*. Singapore: John Wiley & Sons. Available at: https://www.scribd.com/document/405637459/Douglas-C-Montgomery-Design-and-analysis-of-experiments-Wiley-1991-pdf?language_settings_changed=English

DOI: 10.15587/2706-5448.2026.353043

ENHANCEMENT OF THE MEASUREMENT METHOD FOR THE RADAR CROSS SECTION OF UNMANNED AERIAL VEHICLES IN THE X-BAND UNDER ANECHOIC CHAMBER CONDITIONS

pages 15–22

Anatoliy Popov, Doctor of Technical Sciences, Associate Professor, Department of Aerospace Radioelectronic Systems, National Aerospace University "Kharkiv Aviation Institute", Kharkiv, Ukraine, ORCID: <https://orcid.org/0000-0003-0715-3870>

Iurii Vorobiov, Doctor of Technical Sciences, Professor, Department of Aircraft Manufacturing Technology, National Aerospace University "Kharkiv Aviation Institute", Kharkiv, Ukraine, e-mail: ivorobiov@khai.edu, ORCID: <https://orcid.org/0000-0001-6401-7790>

Kateryna Maiorova, PhD, Associate Professor, Department of Aircraft Manufacturing Technologies, National Aerospace University "Kharkiv Aviation Institute", Kharkiv, Ukraine, ORCID: <https://orcid.org/0000-0003-3949-0791>

Mariya Bortsova, Air Force Research Center, Ivan Kozhedub Kharkiv National Air Force University, Kharkiv, Ukraine, ORCID: <https://orcid.org/0000-0001-6644-0875>

The object of research is the process of measuring the effective scattering surface of an unmanned aerial vehicle (UAV) in the X-band of electromagnetic waves in an anechoic chamber. The problem being solved is to obtain reliable initial data for assessing the radar visibility and probability of detecting UAVs based on their backscatter diagrams. The aim of research is to improve the method of measuring the effective scattering surface (ESS) of UAV components in the X-band in an anechoic chamber and its experimental testing. As a result of the research, a technology for measuring the angular dependence of the ESS in the X-band was formed, which includes compensation of the background signal, calibration of the measuring equipment, ESS determination of the object and automation of the measurement process. The technology includes the design of the anechoic chamber, the structure of the measuring stand, the method of compensation of the background reflection, measurement of the reflected signal power, calibration of the measuring equipment, ESS calculation. The conducted field experiments allowed to obtain the characteristics of the secondary scattering of UAV components in the angle sector $\pm 45^\circ$, while the measurement error of static reference objects did not exceed ± 1 dB. Comparison of experimental results with the data of mathematical modeling based on integral equations and the physical theory of diffraction confirmed the reliability of the improved approach. The obtained results can be used to increase the accuracy of assessing the radar visibility of small-sized UAVs and improve the means of their detection.

Keywords: unmanned aerial vehicle (UAV), radar cross section (RCS), effective scattering surface, backscatter pattern measurement, anechoic chamber.

References

1. Zhuk, S., Bilorus, A., Bomberher, V., Lukovskiy, I. (2025). Use of unmanned systems in modern military operations: analysis of efficiency and risks. *Collection of Scientific Works of the National Academy of the State Border Guard Service of Ukraine. Series: Military and Technical Sciences*, 99 (2), 4–14. <https://doi.org/10.32453/3v99i2.1882>
2. Vorobiov, Yu., Maiorova, K., Popov, A., Diachenko, Yu., Bezkorovainyi, V. (2025). Development of an ontological decision support system for selection of aircraft-type unmanned aerial vehicles. *Science and technology today*, 11 (52), 1944–1961. [https://doi.org/10.52058/2786-6025-2025-11\(52\)-1944-1961](https://doi.org/10.52058/2786-6025-2025-11(52)-1944-1961)
3. Kovalov, K. (2025). UAVs in the reconnaissance and fire control system: current status and prospects. *International scientific journal "Grail of Science"*, 55, 339–345. <https://doi.org/10.36074/grail-of-science.22.08.2025.039>
4. Bezpilotni systemy ta REB: pidsumky ta dosiahnennia sichnia 2025 roku. *Zbroini Syly Ukrainy*. Available at: <https://www.zsu.gov.ua/news/bezpilotni-systemy-ta-reb-pidsumky-ta-dosyagnennya-sichnya-2025-roku>
5. Vorobiov, I., Maiorova, K., Sosunov, A. (2026). Methodology for assessing the economic efficiency of using an ontology-based decision support system for selecting aircraft-type unmanned aerial vehicles. *Aerospace Technic and Technology*, 1, 84–94. <https://doi.org/10.32620/akt.2026.1.08>
6. Jenn, D. C. (2024). Radar Cross Section. *Encyclopedia of RF and Microwave Engineering*, 1–43. <https://doi.org/10.1002/0471654507.erfme058>
7. Shevchenko, S. (2025). An improved methodology for determining unmanned aerial vehicles radar visibility characteristics in a model experiment. *Scientific Works of Kharkiv National Air Force University*, 4 (82), 72–82. <https://doi.org/10.30748/zhups.2024.82.09>

8. Knott, E. F. (1993). *Radar Cross Section Measurements*. New York: Springer. <https://doi.org/10.1007/978-1-4684-9904-9>
9. Ezuma, M., Anjinappa, C. K., Semkin, V., Guvenc, I. (2022). Comparative Analysis of Radar-Cross-Section- Based UAV Recognition Techniques. *IEEE Sensors Journal*, 22 (18), 17932–17949. <https://doi.org/10.1109/jsen.2022.3194527>
10. Sukharevsky, O., Zalevsky, G., Vasilets, V., Galkin, Y., Horielyshev, S., Sadovyi, K. (2021). Radar scattering characteristics of tactical unmanned aerial vehicle in VHF, S and X frequency bands. *Science and Technology of the Air Force of Ukraine*, 4 (45), 82–92. <https://doi.org/10.30748/nitps.2021.45.10>
11. Surhai, M. V., Zalevskyi, H. S., Vasylets, V. O., Sukharevskyi, O. I. (2017). Otsnivannia rivnia radiolokatsiinoi pomitnosti snariadu raketnoi systemy zalpovoho vohniu "Hrad" u riznykh diapazonakh dovyzhyn khvyl. *Zbirnyk naukovykh prats Kharkivskoho natsionalnoho universytetu Povitrianykh Syl*, 2 (51), 142–148. Available at: http://nbuv.gov.ua/UJRN/ZKhUPS_2017_2_30
12. Liu, J., Yinchai, W., Wei, F., Han, Q., Tao, Y., Zhao, L. et al. (2023). Secure Cloud-Aided Approximate Nearest Neighbor Search on High-Dimensional Data. *IEEE Access*, 11, 109027–109037. <https://doi.org/10.1109/access.2023.3321457>
13. Hemming, L. H. (2002). *Anechoic Chamber Design Techniques*. *Electromagnetic Anechoic Chambers*. Wiley-IEEE Press, 57–72. <https://doi.org/10.1109/9780470544501.ch5>
14. Popov, A., Kalimullin, D. (2020). Automatization of Antenna Measurements in the Anechoic Chamber. *2020 IEEE Ukrainian Microwave Week (UkrMW)*. Kharkiv: IEEE, 183–186. <https://doi.org/10.1109/ukrmw49653.2020.9252594>
15. Sukharevsky, O. I. (2018). *Electromagnetic Wave Scattering by Aerial and Ground Radar Objects*. CRC Press, 334. <https://doi.org/10.1201/9781315214511>
16. Zalevsky, G. S., Sukharevsky, O. I., Vasylets, V. A. (2021). Integral equation modelling of unmanned aerial vehicle radar scattering characteristics in VHF to S frequency bands. *IET Microwaves, Antennas & Propagation*, 15 (10), 1299–1309. <https://doi.org/10.1049/mia2.12164>
17. Ufimtsev, P. Y. (2014). *Fundamentals of the physical theory of diffraction*. Wiley-IEEE Press, 496. Available at: <https://download.e-bookshelf.de/download/0002/4020/78/L-G-0002402078-0003467319.pdf>
18. Panwar, R., Puthucheri, S., Singh, D. (2018). Experimental Demonstration of Novel Hybrid Microwave Absorbing Coatings Using Particle-Size-Controlled Hard–Soft Ferrite. *IEEE Transactions on Magnetics*, 54 (11), 1–5. <https://doi.org/10.1109/tmag.2018.2828782>
19. Zhao, H., Chen, J., Zhuang, M., Yang, X., Zhuo, J. (2024). A Novel Radar Cross-Section Calculation Method Based on the Combination of the Spectral Element Method and the Integral Method. *Symmetry*, 16 (5), 542. <https://doi.org/10.3390/sym16050542>

DOI: 10.15587/2706-5448.2026.353169

DEVELOPMENT OF AN ANALYTICAL MODEL FOR PREDICTING THE TRAJECTORY AND ENERGY DISSIPATION OF BEE BREAD GRANULES IN A ROTARY IMPACT SEPARATOR

pages 23–31

Yurii Syromiatnykov, PhD, Assistant, Department of Agroengineering, State Biotechnological University, Kharkiv, Ukraine, ORCID: <https://orcid.org/0000-0001-9502-626X>

Oleksandr Bielykh, PhD Student, Department of Agroengineering, State Biotechnological University, Kharkiv, Ukraine, e-mail: sashafincol@gmail.com, ORCID: <https://orcid.org/0009-0007-5490-4098>

Oleksandr Kharchenko, PhD Student, Department of Agroengineering, State Biotechnological University, Kharkiv, Ukraine, ORCID: <https://orcid.org/0009-0009-4955-3478>

The object of this research is the impact interaction between a bee bread granule and a hammer-type working element in a rotary separator. The practical relevance of the research arises from the need to ensure reliable release of granules while preventing their mechanical damage, since even partial destruc-

tion leads to deterioration of product quality and a decrease in its commercial value. Such an approach does not allow reliable prediction of energy transfer during impact or the subsequent trajectory of the granule. As a consequence, rotor speed and hammer mass are often selected without sufficient theoretical justification, which limits the efficiency and controllability of the separation process. To overcome these limitations, an analytical model describing granule impact and its post-impact motion in a rotating reference frame was developed. The mathematical formulation accounts for the combined action of centrifugal, Coriolis, gravitational, and friction forces, which made it possible to derive parametric relationships for velocity and displacement as functions of time. It was established that the post-impact motion follows a damped pattern, with the displacement amplitude decreasing by more than 60% within the first 0.02 s and exceeding an 80% reduction after 0.05 s. It was also found that energy transfer efficiency strongly depends on hammer mass. At a mass of 5 g, the efficiency reaches approximately 0.7–0.8%, whereas at 100 g it decreases to about 0.1%, and at 200 g it falls below 0.05%. These trends are explained by increasing dissipative losses within the rotating system. The proposed model enables prediction of granule trajectory, velocity, and energy dissipation under different operating conditions. Its practical value lies in providing a scientifically grounded basis for selecting hammer mass and rotor speed to achieve efficient and gentle separation of bee bread granules.

Keywords: bee bread, granule, rotor, mechanics, inertia, energy, trajectory, separation, dissipation, efficiency.

References

1. Ghazi Alshanti, W. (2019). Discrete Element Modeling of a Projectile Impacting and Penetrating into Granular Systems. *Ballistics*. IntechOpen. <https://doi.org/10.5772/intechopen.75550>
2. Chou, Y. F., Keh, H. J. (2024). Axisymmetric Slow Rotation of Coaxial Soft/Porous Spheres. *Molecules*, 29 (15), 3573. <https://doi.org/10.3390/molecules29153573>
3. Sanoria, M., Chelakkot, R., Nandi, A. (2021). Influence of interaction softness on phase separation of active particles. *Physical Review E*, 103 (5). <https://doi.org/10.1103/physreve.103.052605>
4. Lips, D., Cereceda-López, E., Ortiz-Ambroz, A., Tierno, P., Ryabov, A., Maass, P. (2022). Hydrodynamic interactions hinder transport of flow-driven colloidal particles. *Soft Matter*, 18 (47), 8983–8994. <https://doi.org/10.1039/d2sm01114j>
5. Zhou, L., Ren, L., Chen, Y., Niu, S., Han, Z., Ren, L. (2021). Bio-Inspired Soft Grippers Based on Impactive Gripping. *Advanced Science*, 8 (9). <https://doi.org/10.1002/advs.202002017>
6. Seifert, J., Koch, K., Hess, M., Schmidt, A. M. (2020). Magneto-mechanical coupling of single domain particles in soft matter systems. *Physical Sciences Reviews*, 7 (11), 1237–1261. <https://doi.org/10.1515/psr-2019-0092>
7. Rosas, A., Buceta, J., Lindenberg, K. (2003). Dynamics of two granules. *Physical Review E*, 68 (2). <https://doi.org/10.1103/physreve.68.021303>
8. van der Meer, D. (2017). Impact on Granular Beds. *Annual Review of Fluid Mechanics*, 49 (1), 463–484. <https://doi.org/10.1146/annurev-fluid-010816-060213>
9. Sano, T. G., Kanazawa, K., Hayakawa, H. (2016). Granular rotor as a probe for a nonequilibrium bath. *Physical Review E*, 94 (3). <https://doi.org/10.1103/physreve.94.032910>
10. Wang, X., Huang, Y., Zhang, E., Meng, Q. (2025). Influence of Rotor-Induced Airflow on Particle Fragmentation in an Impact Crusher: A Computational Fluid Dynamics–Discrete Element Method Study. *ACS Omega*, 10 (39), 46051–46064. <https://doi.org/10.1021/acsomega.5c06659>
11. Ghodki, B. M., Chhetri, K. B., Goswami, T. K. (2020). Numerical modeling of granular flow in star valve type cryogenic precooler. *Journal of Food Process Engineering*, 43 (4). <https://doi.org/10.1111/jfpe.13376>
12. Yang, J. H., Fang, H. Y., Luo, M. (2015). Load and wear experiments on the impact hammer of a vertical shaft impact crusher. *IOP Conference Series: Materials Science and Engineering*, 103. <https://doi.org/10.1088/1757-899x/103/1/012041>
13. Feng, F., Shi, J., Yang, J., Ma, J. (2020). Study on Wear form of Split Cone of Vertical Shaft Impact Crusher. *Journal of Scientific Research and Reports*, 21 (11), 13–20. <https://doi.org/10.9734/jsrr/2020/v26i1130331>

14. Xu, B., Cui, Q., Guo, L., Hao, L. (2024). Design and Parameter Optimization of a Combined Rotor and Lining Plate Crushing Organic Fertilizer Spreader. *Agronomy*, 14 (8), 1732. <https://doi.org/10.3390/agronomy14081732>
15. Paraschiv, G., Moiceanu, G., Voicu, G., Chitoiu, M., Cardei, P., Dinca, M. N., Tudor, P. (2021). Optimization Issues of a Hammer Mill Working Process Using Statistical Modelling. *Sustainability*, 13 (2), 973. <https://doi.org/10.3390/su13020973>
16. Kim, A. S., Kim, H.-J. (2017). Dissipative Dynamics of Granular Materials. *Granular Materials*. IntechOpen. <https://doi.org/10.5772/intechopen.69196>
17. Kollmer, J. E., Sack, A., Heckel, M., Pöschel, T. (2013). Relaxation of a spring with an attached granular damper. *New Journal of Physics*, 15 (9), 093023. <https://doi.org/10.1088/1367-2630/15/9/093023>
18. Păun, A., Stroescu, G., Milea, D., Olan, M., Epure, M. (2019). Concaves influence on the milling process of cereal seeds in hammer mills. *E3S Web of Conferences*, 112, 03009. <https://doi.org/10.1051/e3sconf/201911203009>
19. Ahmadian, H., Ghadiri, M. (2021). Granule attrition by coupled particle impact and shearing. *Advanced Powder Technology*, 32 (1), 204–210. <https://doi.org/10.1016/j.apt.2020.12.001>
20. Li, T., Shi, G., Zhang, Q. (2024). Research on hammering characteristics of hammer mill based on discrete element method. *Engineering Research Express*, 6 (3), 035540. <https://doi.org/10.1088/2631-8695/ad6ca4>
21. Kyzas, G., Mitropoulos, A. C. (Eds.) (2018). *Granularity in Materials Science*. IntechOpen. <https://doi.org/10.5772/intechopen.75231>
22. Syromyatnikov, Y. N., Orekhovskaya, A. A., Dzjashev, A.-M. S., Tikhonov, E. A., Kalimullin, M. N., Ivanov, A. A., Sokolova, V. A. (2021). Improving stability of movement of machine section for soil preparation and seeding. *Journal of Physics: Conference Series*, 2094 (4), 042027. <https://doi.org/10.1088/1742-6596/2094/4/042027>
23. Pashchenko, V. F., Syromyatnikov, Y. U. N. (2019). The transporting ability of the rotor of the soil-cultivating loosening and separating vehicle. *Traktory i Sel Hozmashiny*, 86 (2), 67–74. <https://doi.org/10.31992/0321-4443-2019-2-67-74>
24. Syromyatnikov, Y. N., Orekhovskaya, A. A., Dzjashev, A.-M. S., Kalimullin, M. N., Tikhonov, E. A., Luchinovich, A. A., Bielykh, A. V. (2021). Cultivator points of the rotary tillage loosening and separating machine of the stratifier. *Journal of Physics: Conference Series*, 2094 (4), 042024. <https://doi.org/10.1088/1742-6596/2094/4/042024>

DOI: 10.15587/2706-5448.2026.353156

DETERMINATION OF QUANTITATIVE RELATIONSHIPS BETWEEN THE NON-DIMENSIONAL AXIAL LENGTH OF AN ANNULAR PRE-TURBINE MIXING CHAMBER AND THE INTEGRAL CHARACTERISTICS OF TEMPERATURE FIELD UNIFORMITY

pages 32–37

Yurii Tereshchenko, Doctor of Technical Sciences, Professor, Department of Aviation Engines, National University "Kyiv Aviation Institute", Kyiv, Ukraine, ORCID: <https://orcid.org/0000-0003-4367-3232>

Illia Yudin, PhD Student, Department of Aviation Engines, National University "Kyiv Aviation Institute", Kyiv, Ukraine, e-mail: illiyudin98@gmail.com, ORCID: <https://orcid.org/0009-0001-9934-553X>

The object of the research is the annular mixing chamber of the pre-turbine duct of a three-stream aircraft turbofan engine, designed to enforce the mixing of hot and cold flows within a confined axial geometry, with particular emphasis on the gas-dynamic and thermal processes occurring within it. The research problem addressed in this research was the determination of the minimally required relative length of the mixing chamber. This length must ensure an acceptable level of temperature uniformity at the turbine inlet without increasing the overall dimensions of the propulsion system. This condition is particularly critical for compact engines, including propulsion systems for unmanned aerial vehicles. A series of three-dimensional CFD simulations was performed using ANSYS Flu-

ent with a Reynolds stress model (RSM) for turbulence. The modeling was conducted for an annular chamber with fixed geometric parameters ($D = 1107$ mm, $d = 492$ mm) within a range of relative lengths $L^* = 0.42–2.11$. The research covered four different engine operating conditions, varying in bypass ratio. The results revealed a clear nonlinear dependence of the temperature non-uniformity coefficient θ on the relative chamber length L^* . It was found that for $L^* < 1.2$, the mixing process remains incomplete, accompanied by a significant increase in temperature non-uniformity. In contrast, within the range $L^* = 1.2–1.7$, nearly complete temperature equalization is achieved ($\theta \leq 0.1$). These results can be explained by the dominance of the turbulent mixing mechanism, as confirmed by low Richardson numbers ($R_i \ll 1$) and the minor influence of operating parameters compared to geometric factors. The findings can be applied in the design of compact mixing chambers for aircraft gas turbine engines, especially under strict constraints on their axial dimensions. This is particularly relevant for propulsion systems of unmanned aerial vehicles.

Keywords: gas turbine engine, annular mixing chamber, temperature non-uniformity, turbulent mixing, CFD modeling.

References

1. Moirou, N. G. M., Sanders, D. S., Laskaridis, P. (2023). Advancements and prospects of boundary layer ingestion propulsion concepts. *Progress in Aerospace Sciences*, 138, 100897. <https://doi.org/10.1016/j.paerosci.2023.100897>
2. Advanced Air Transport Technology Project. *National Aeronautics and Space Administration*. Available at: <https://www.nasa.gov/directorates/armd/aavp/aatt/>
3. RTX Pratt & Whitney accelerates development of NGAP engine (2025). *RTX*. Available at: <https://www.rtx.com/news/news-center/2025/09/23/rtxs-pratt-whitney-accelerates-development-of-ngap-engine>
4. Tereshchenko, Iu. M., Kulik, N. S., Lastivka, I. A. (2010). *Teoriia aviatcionnykh trekhkonturnykh turboreaktivnykh dvigatelei*. K.: Izd-vo Natc. aviatc. un-ta "NAU-druk". Available at: https://scholar.google.com/citations?view_op=view_citation&hl=ru&user=A67lFQAAAAJ&citation_for_view=A67lFQAAAAJ:YFjvs_pB-GBYC
5. Lefebvre, A. H., Ballal, D. R. (2010). *Gas Turbine Combustion*. CRC Press. <https://doi.org/10.1201/9781420086058>
6. Moustapha, H., Zelesky, M. F., Baines, N. C., Japikse, D. (2003). *Axial and radial turbines*. Concepts Eti, 358.
7. Chauhan, S., Wessley, G. J. J. (2025). Simulation-driven design of UAV Micro Gas Turbines: a dual-platform validation approach. *Journal of Thermal Analysis and Calorimetry*, 150 (19), 15751–15760. <https://doi.org/10.1007/s10973-025-14894-2>
8. Abramovich, G. N.; Schindel, L. (Ed.) (2003). *The Theory of Turbulent Jets*. MIT Press. <https://doi.org/10.7551/mitpress/6781.001.0001>
9. Hinze, J. O. (1975). *Turbulence*. McGraw-Hill College, 790.
10. Pope, S. B. (2000). *Turbulent Flows*. Cambridge University Press. <https://doi.org/10.1017/cbo9780511840531>
11. Karagozian, A. R. (2010). Transverse jets and their control. *Progress in Energy and Combustion Science*, 36 (5), 531–553. <https://doi.org/10.1016/j.peecs.2010.01.001>
12. Vorobieff, P., Truman, C. R., Ragheb, A. M., Elliott, G. S., Laystrom-Woodard, J. K., King, D. M. et al. (2011). Mixing enhancement in a multi-stream injection nozzle. *Experiments in Fluids*, 51 (3), 711–722. <https://doi.org/10.1007/s00348-011-1090-6>
13. Ren, D., Fan, W., Zhang, R. (2024). Experimental and numerical study on flow mixing and combustion characteristics of a novel multibypass integrated combustor. *Physics of Fluids*, 36 (4). <https://doi.org/10.1063/5.0199051>
14. Goldsmith, E. L., Seddon, J. (1993). *Practical intake aerodynamic design*. American Institute of Aeronautics and Astronautics, 434. Available at: https://openlibrary.org/books/OL14752011M/Practical_intake_aerodynamic_design
15. Casey, M., Wintergerste, T. (Eds.). (2000). *ERCOFTAC best practice guidelines: Industrial computational fluid dynamics of single-phase flows*. ERCOFTAC. Available at: https://www.ercofac.org/publications/ercofac_best_practice_guidelines/single-phase_flows_spf2-electronic-copy/
16. Yudin, I. (2025). Comparison of numerical simulation results of the mixing chamber with physical experiment data. *Aerospace Technic and Technology*, 4, 39–44. <https://doi.org/10.32620/akt.2025.4.06>

MECHANICS

DOI: 10.15587/2706-5448.2026.353063

DEVELOPMENT OF UNIVERSAL MODEL FOR
OPTIMIZING PARKING SPACES IN COMPLEX
GEOMETRIC CONFIGURATIONS

pages 38–43

Mykola Mytko, PhD, Associate Professor, Department of Automobiles and Transport Management, Vinnytsia National Technical University, Vinnytsia, Ukraine, ORCID: <https://orcid.org/0000-0002-5484-0510>

Serhii Burlaka, PhD, Associate Professor, Department of Engineering Mechanics and Technological Processes in the Agricultural Industry, Vinnytsia National Agrarian University, Vinnytsia, Ukraine, e-mail: ipserhiy@gmail.com, ORCID: <https://orcid.org/0000-0002-4079-4867>

Oleh Antonuk, PhD, Associate Professor, Department of Automobiles and Transport Management, Vinnytsia National Technical University, Vinnytsia, Ukraine, ORCID: <https://orcid.org/0009-0006-5348-4936>

Alena Bondar, PhD, Associate Professor, Department of Construction, Urban Planning and Architecture, Vinnytsia National Technical University, Vinnytsia, Ukraine, ORCID: <https://orcid.org/0000-0002-8098-1181>

Dmytro Datsiuk, PhD, Senior Lecturer, Department of Engineering Mechanics and Technological Processes in the Agricultural Industry, Vinnytsia National Agrarian University, Vinnytsia, Ukraine, ORCID: <https://orcid.org/0000-0002-4614-2245>

The object of research is the process of designing and optimizing parking areas in complex geometric configurations in conditions of dense development.

The main problem is to solve the use of areas of complex geometric configuration for parking areas. In addition, there are currently no universal models and methods for the corresponding calculation and optimization.

The result of the work was the receipt of a universal mathematical model with which it is possible to determine the number of parking spaces based on the geometric dimensions and area of the plot. A special feature is the possibility of calculating for complex geometric configurations (polygons). For this, the Gauss formula and the JavaScript programming language are used. The initial data are geodetic measurements, and the error in such a calculation is less than 2%.

The development of JavaScript code based on the shoelace formula was practical importance. The experimental object was the residential area "Vyshenka" in Vinnytsia (Ukraine). The selected plot has an area of 1350 m² with an initial number of parking spaces before optimization – 50, after – 59. In general, the efficiency of using the area increased from 70% to 88%. In addition, a 22% reduction in accidents is noted, which indicates the significant effectiveness of the model and minimal calculation error.

A feature of the proposed solution is also that not only linear dimensions are taken into account, but also the relief, infrastructure facilities and the initial shape of the site. There is also the possibility of integration into web applications and CAD programs for simultaneous planning and construction, which allows for an increase in the number of parking spaces of up to 20% without expanding the territories.

The results of the modeling can be used by engineers and builders to improve the landscaping of residential areas where there is no possibility for expanding the territories, programmers – by integrating the model into web applications and business.

Keywords: Shoelace formula, polygon area, computational geometry, capacity increase, efficiency coefficient, urban parking.

References

- Csonka, B., Csiszár, C. (2016). Service Quality Analysis and Assessment Method for European Carsharing Systems. *Periodica Polytechnica Transportation Engineering*, 44 (2), 80–88. <https://doi.org/10.3311/pptr.8559>
- Danilov, O. (2024). *Kilkist avto na 1000 hromadian: Ukraina na ostannomu misti v Yevropi*. Mezha Media. <https://mezha.ua/2024/03/05/kilkist-avto-na-1000-hromadian/> Last accessed: 05.10.2024
- Galushchak, O., Burlaka, S., Kupchuk, I., Bondarenko, V., Gontaruk, Y. (2023). Environmental indicators of the operation of a diesel generator running on a mixture of biofuels. *Energy Policy Journal*, 26 (4), 195–208. <https://doi.org/10.33223/epj/170759>
- Goźdźeńczyk, P., Matuszak, K. (2022). Evaluation of the Parking System Efficiency Based on the Jadwizyn Settlement in Pila in the Light of Sustainable Development. *Communications – Scientific Letters of the University of Zilina*, 24 (4), A198–A215. <https://doi.org/10.26552/com.c.2022.4.a198-a215>
- Hamadneh, J., Esztergár-Kiss, D. (2021). Travel Behavior of Car Travelers with the Presence of Park-and-Ride Facilities and Autonomous Vehicles. *Periodica Polytechnica Transportation Engineering*, 50 (1), 101–110. <https://doi.org/10.3311/pptr.18020>
- Ilham, R., Shonhadji, N., Yutanto, H., Ekaningtyas, D. (2020). Analysis of the Acceptance Factor of Android-Based Parking Information Systems in Indonesia. *Communications – Scientific Letters of the University of Zilina*, 22 (2), 97–106. <https://doi.org/10.26552/com.c.2020.2.97-106>
- Katona, G., Juhasz, J. (2020). The History of the Transport System Development and Future with Sharing and Autonomous Systems. *Communications – Scientific Letters of the University of Zilina*, 22 (1), 25–34. <https://doi.org/10.26552/com.c.2020.1.25-34>
- Krivda, V., Mahdalova, I., Petru, J. (2013). Use of Video Analysis of Conflict Situations for Monitoring the Traffic on Urban Road Influenced by Parallel Parking. *Communications – Scientific Letters of the University of Zilina*, 15 (3), 118–125. <https://doi.org/10.26552/com.c.2013.3.118-125>
- Mytko, M. (2020). Determination of economic advisable distances of automobile delivery on autoservice enterprise. *Engineering, Energy, Transport AIC*, 1 (108), 58–64. <https://doi.org/10.37128/2520-6168-2020-1-7>
- Mytko, M. (2020). Methodological bases for improving the structure of production subdivisions of motor transport enterprises. *Engineering, Energy, Transport AIC*, 2 (109), 64–70. <https://doi.org/10.37128/2520-6168-2020-2-7>
- Pandey, N., Parti, R., Biswas, S. (2024). Assessing the Stream Speed of Regular Traffic under Impacts of on-Street Parking. *Communications – Scientific Letters of the University of Zilina*, 26 (4), D71–D81. <https://doi.org/10.26552/com.c.2024.046>
- Saif, M. A., Zefreh, M. M., Torok, A. (2018). Public Transport Accessibility: A Literature Review. *Periodica Polytechnica Transportation Engineering*, 47 (1), 36–43. <https://doi.org/10.3311/pptr.12072>
- Shyrokun, I. (2023). *Skilky naspravdi mashyn v Ukraini: bahato chy malo?* *Auto.24tv.ua*. https://auto.24tv.ua/skilky_naspravdi_mashyn_v_ukraini_bahato_chy_malo_n43694 Last accessed: 05.10.2024
- Szalay, Z., Nyerges, Á., Hamar, Z., Hesz, M. (2017). Technical Specification Methodology for an Automotive Proving Ground Dedicated to Connected and Automated Vehicles. *Periodica Polytechnica Transportation Engineering*, 45 (3), 168–174. <https://doi.org/10.3311/pptr.10708>
- Veselovska, N., Shargorodskiy, S., Rutkevych, V., Kupchuk, I., Burlaka, S. (2023). Development of the Mathematical Model of the Hydraulic Drive of the lift Mechanism of the Working Equipment of the Front Loader. *Przegląd Elektrotechniczny*, 99 (10), 34–38. <https://doi.org/10.15199/48.2023.10.06>

METALLURGICAL TECHNOLOGY

DOI: 10.15587/2706-5448.2026.353175

DETERMINATION OF THE INFLUENCE OF THE METHOD OF INTRODUCING C₆₀ FULLERENES AND FUNCTIONALIZED CARBON NANOTUBE ON THE FORMATION OF THE PROPERTIES OF ALUMINUM ALLOY

pages 44–49

Mykola Trenov, PhD Student, Department of Foundry, National Technical University "Kharkiv Polytechnic Institute", Kharkiv, Ukraine, ORCID: <https://orcid.org/0009-0009-8899-6044>, e-mail: djekgor4676@gmail.com

Olga Ponomarenko, Doctor of Technical Sciences, Professor, Department of Foundry, National Technical University "Kharkiv Polytechnic Institute", Kharkiv, Ukraine, ORCID: <https://orcid.org/0000-0002-3043-4497>

The object of research is the influence of carbon nanotubes and fullerene nanomaterials C₆₀ when introduced into the aluminum alloy AK12 on the formation of the eutectic microstructure.

The problem solved during the research is the insufficient effectiveness of existing modifiers such as Sr, Na, TiC and SiC to improve silicon globularization, as well as the lack of simple and effective methods for introducing carbon nanomaterials.

In the work, two methods for introducing carbon nanoparticles into the aluminum alloy were developed. Improved silicon globularization, mechanical and physical properties were achieved. The thickness of the silicon dendritic axis was reduced to almost 20–25 microns, the size of silicon inclusions was reduced from 2–10 microns, and the microhardness was increased almost twice, depending on the method. The improvement of properties is due to the fact that nanoparticles become centers of crystal nucleation and do not allow them to grow, which leads to a finer, more homogeneous structure of the alloy. Pre-treatment of nanomaterials allows them to be evenly distributed in the alloy, and the addition of magnesium improves the wetting properties.

The features and distinctive features of the obtained results are that two technologically simple methods of introducing nanoparticles into the liquid AK12 alloy have been proposed, without the use of ultrasound. A significant improvement in the mechanical and physical properties of the alloy has been achieved compared to the reference AK12 alloy. Controlled grinding of the silicon structure has been ensured. Available materials and equipment, which are available in Ukraine and suitable for scaling up in industrial volumes, have been used. The modified AK12 alloy allows it to be used for the manufacture of castings of critical importance, such as pistons, transmission mechanisms, and engine housings.

Keywords: aluminum alloy AK12, fullerene C₆₀, carbon nanotubes, nanomodification, microstructure, hardness.

References

- Singhal, V., Shelly, D., Babbar, A., Lee, S.-Y., Park, S.-J. (2024). Review of Wear and Mechanical Characteristics of Al-Si Alloy Matrix Composites Reinforced with Natural Minerals. *Lubricants*, 12 (10), 350. <https://doi.org/10.3390/lubricants12100350>
- Bin Reyaz, M. S., Singh, J., Bhati, S., Mehdi, H., Mishra, S. (2025). Examining the effect of multi-pass FSP on microstructure, texture, and mechanical properties of hybrid reinforced AA2024-T351 surface composites. *Composite Interfaces*, 33 (1), 87–110. <https://doi.org/10.1080/09276440.2025.2514871>
- Wu, Z., Yan, H., Han, Q., Chen, N., Peng, X., Wang, R., Cai, Z. (2026). Microstructure, thermo-physical and mechanical properties of heterogeneous Al/Al–70Si composites. *Journal of Materials Research and Technology*, 40, 392–403. <https://doi.org/10.1016/j.jmrt.2025.12.074>
- Nirala, A., Soren, S., Kumar, N., Khan, M. A., Islam, S., Khan, N. A. (2023). Micro-mechanical and tribological behavior of Al/SiC/B4C/CNT hybrid nanocomposite. *Scientific Reports*, 13 (1). <https://doi.org/10.1038/s41598-023-39713-2>
- Trenov, M. S., Ponomarenko, O. I., Kniaziev, S. A. (2025). Analysis of Methods for Introducing Nanoparticles into Aluminum-Based Alloys. *Metal and Casting of Ukraine*, 33 (1), 25–31. <https://doi.org/10.15407/steelcast2025.01.025>
- Lakhtakia, A. (Ed.). (2004). *The Handbook of Nanotechnology: Nanometer Structures: Theory, Modeling, and Simulation*. SPIE Press. <https://doi.org/10.1117/3.537698>
- Gleiter, H. (2000). Nanostructured materials: basic concepts and microstructure. *Acta Materialia*, 48 (1), 1–29. [https://doi.org/10.1016/s1359-6454\(99\)00285-2](https://doi.org/10.1016/s1359-6454(99)00285-2)
- Kroto, H. W., Heath, J. R., O'Brien, S. C., Curl, R. F., Smalley, R. E. (1985). C₆₀: Buckminsterfullerene. *Nature*, 318 (6042), 162–163. <https://doi.org/10.1038/318162a0>
- Manika, I., Maniks, J., Kalnacs, J. (1997). Atmosphere-Induced Effect in Microhardness, Dislocation Mobility and Plasticity of C₆₀ and Graphite Crystals. *Fullerene Science and Technology*, 5 (1), 149–166. <https://doi.org/10.1080/15363839708011979>
- Trenov, M. S., Ponomarenko, O. I. (2025). Vykorystannia nanodispersnykh materialiv dlia vdoskonalennia vlastyvoستي aliuminiyevykh splaviv u lyvarnomu vyrobnytstvi. *Lytvo. Metalurhiia*. 2025. Kharkiv; Kyiv: NTU "KhPI", 285–287. Available at: <https://repository.kpi.kharkov.ua/handle/KhPI-Press/90592>
- Sowrabh, B. S., Gurumurthy, B. M., Shivaprakash, Y. M., Sharma, S. S. (2021). Reinforcements, production techniques and property analysis of AA7075 matrix composites – a critical review. *Manufacturing Review*, 8, 31. <https://doi.org/10.1051/mfreview/2021029>
- Agarwal, S., Singh, S. (2024). Production techniques and properties of particulate reinforce metal matrix composites: a review. *Materials Physics and Mechanics*, 52 (6), 136–153.
- Trenov, M. S., Ponomarenko, O. I. (2024). Vykorystannia fulereniv u metalurhi. *Lytvo. Metalurhiia*. 2024. Kharkiv; Kyiv: NTU "KhPI", 255–256. Available at: <https://repository.kpi.kharkov.ua/items/15f6524a-20cd-4a6e-8122-3a086f904570>
- DSTU 2839-94. *Splavy aliuminiyevi lyvarni. Tekhnichni umovy* (1994). Available at: https://online.budstandart.com/ua/catalog/doc-page.html?id_doc=50317

TECHNOLOGY AND SYSTEM OF POWER SUPPLY

DOI: 10.15587/2706-5448.2026.353157

PROBABILITY-STATISTICAL APPROACH DEVELOPMENT TO THE SURVIVABILITY INCREASING OF POWER PLANT AUXILIARY GRID

pages 50–56

Volodymyr Litvinov, PhD, Head of Production-Technical Department, Branch "Dniprovsk HPP" of Private Joint-Stock Company "Ukrhydroenergo", Zaporizhzhia, Ukraine, e-mail: vv.litvinov1985@ukr.net, ORCID: <https://orcid.org/0000-0003-1974-0976>

Oleksii Stetsiura, Technician of 2-nd Category, Electro-Technical Workshop, Branch "Dniprovsk HPP" of Private Joint-Stock Company "Ukrhydroenergo", Zaporizhzhia, Ukraine, ORCID: <https://orcid.org/0009-0007-1164-2358>

Alina Yerofoieva, PhD, Associate Professor, Department of Electrical Engineering and Cyber-Physical Systems, Zaporizhzhia National University, Zaporizhzhia, Ukraine, ORCID: <https://orcid.org/0000-0002-2981-4118>

The object of research is the operating modes and ways to increase the survivability of the power plant's own needs network under the influence of external emergency disturbances.

The power system of Ukraine today operates in extremely complex conditions. This is a consequence of the fact that the existing problems associated with outdated equipment have been added by external destructive influence due to geopolitical events. These factors cause a decrease in the structural and regime reliability of electrical networks. Under such conditions, the surviv-

ability of power plants and their own needs systems becomes of particular importance. The task of increasing the survivability of the power plant's own needs network is one of the multi-criteria tasks with a large number of uncertainties. To solve it, it is advisable to apply a probabilistic-statistical approach that takes into account the available random factors and makes it possible to make effective decisions. In the course of the research, an approach to assessing the survivability of the power plant's own needs network using a random number generator was developed, and the effectiveness of measures to increase it was determined.

This approach allows for a quantitative assessment of the survivability of the power plant's own needs network under conditions of uncertainties associated with the network and surrounding power system modes. The approach also takes into account the probability of equipment failure over a time interval and the consequences of geopolitical influence on the power system of Ukraine. The risk of an emergency situation occurring in the power plant's own needs network is taken as a quantitative criterion for assessing survivability. The developed approach and its implementation algorithm allow for a comparative analysis of the effectiveness of measures to increase the survivability of the power plant's own needs network and to select the most effective ones among them. According to the results of probabilistic and statistical modeling of the HPP's own needs network, it was determined that when using survivability measures, the risk of an emergency situation is reduced by 32%.

Keywords: survivability, power plant, own needs network, technical condition, emergency situation, probabilistic and statistical approach, risk.

References

- Kosterev, N. V. (1986). *Modelirovanie i dinamika atomnykh elektrostancii pri vozmushcheniiakh v energosisteme*. Kyiv: Vishcha shkola.
- Pantelieieva, I. V., Shmatko, N. M., Horbenko, N. I. (2010). Emergency control in power systems for deep stress reduction. *Systemy ozbroiennia i viiskova tekhnika*, 1 (21), 228–231.
- Andrushko, S. L., Kulyk, V. V. (2024). Automation of Control of Distributed Generation and Load of the Distribution Network in Case of Separation from the Power System. *Visnyk of Vinnytsia Politechnical Institute*, 177 (6), 68–77. <https://doi.org/10.31649/1997-9266-2024-177-6-68-77>
- Chowdhury, S. P., Chowdhury, S., Ten, C. F., Crossley, P. A. (2009). Operation and control of DG based power island in Smart Grid environment. *20th Conference Publications*, 1051. <https://doi.org/10.1049/cp.2009.1135>
- Poroseva, S. (2010). Designing power system topologies of enhanced survivability. *51st AIAA/ASME/ASCE/AHS/ASC Structures, Structural Dynamics and Materials Conference 18th AIAA/ASME/AHS Adaptive Structures Conference 12th*, 2572. <https://doi.org/10.2514/6.2010-2572>
- Litvinov, V. V. (2020). Choose the FACTS devices and places of its installation for the decreasing the risk of accident fault in electric power system. *Hidroenerhetyka Ukrainy*, 3-4, 57–63.
- Voropai, N. (2019). Problems of Electric Power Systems Flexibility: Definitions and Measures. *VIIth International Workshop "Critical Infrastructures: Contingency Management, Intelligent, Agent-Based, Cloud Computing and Cyber Security"*, 143–145. <https://doi.org/10.2991/iwci-19.2019.25>
- Litvinov, V. V., Kosteriev, M. V. (2019). Imovirnisno-statystychnyi pidkhdid do vyznachennia zbytkiv vid vynykennia avarinoini situatsii v elektroenerhetychnii systemi. *Hidroenerhetyka Ukrainy*, 1-2, 25–30.
- Ciapessoni, E., Cirio, D., Kjolle, G., Massucco, S., Pitto, A., Sforza, M. (2016). Probabilistic Risk-Based Security Assessment of Power Systems Considering Incumbent Threats and Uncertainties. *IEEE Transactions on Smart Grid*, 7 (6), 2890–2903. <https://doi.org/10.1109/tsg.2016.2519239>
- Kazak, V. M., Dotsenko, B. I., Kuzmenko, V. M. (2013). *Nadiinist ta diahnostryka elektroobladnannia*. Kyiv: NAU, 280.
- Zickler, U., Machkin, A., Schwan, M. (2005). Asset Management in distribution systems considering new knowledge on component reliability and damage costs. *15th Power Systems Computation Conference*, 148–154.
- Matviichuk, A. V. (2011). *Shtuchnyi intelekt v ekonomitsi: neironni merezhi, nechitka lohika*. Kyiv: KNEU, 439.
- Stetsiura, O., Bashlii, S., Litvinov, V. (2025). Diesel-generator technical state estimation in fuzzy-information conditions. *Modern Engineering and Innovative Technologies*, 1 (41-1), 34–49. <https://doi.org/10.30890/2567-5273.2025-41-01-017>
- Rubanencko, O. Ye. (2011). Diahnostuvannia obladnannia v umovakh nepovnoty vykhidnykh danykh. *Naukovi pratsi Donetskoho natsionalnoho tekhnichnoho universytetu*, 11, 319–323.
- Kosteriev, M. V., Litvinov, V. V. (2021). Uzahalnenyi nechitko-intervalnyi pidkhdid do identyfikatsii parametriv obladnannia elektroenerhetychnoi systemy. *Hidroenerhetyka Ukrainy*, 1-2, 53–57.
- Seheda, M. S. (2015). *Elektrychni merezhi ta systemy*. Lviv: Lvivska politekhnika, 540.
- Alzbutas, R. (2003). Diesel generators reliability data analysis and testing interval optimization. *Energetika*, 4, 27–33.

ELECTRICAL ENGINEERING AND INDUSTRIAL ELECTRONICS

DOI: 10.15587/2706-5448.2026.353162

DETERMINATION OF ELECTRICITY QUALITY INDICATORS IN DISTRIBUTION NETWORKS OF INDUSTRIAL ENTERPRISES WHEN USING STARTING DEVICES OF POWERFUL ELECTRIC DRIVES

pages 57–64

Oleksiy Gromovyy, PhD, Associate Professor, Department of Robotics, Electric Power Engineering and Automation named after Prof. B. B. Samotokin, Zhytomyr State Polytechnic University, Zhytomyr, Ukraine, ORCID: <https://orcid.org/0000-0002-2761-0736>

Smail Arailym, Doctoral Student, Department of Automation of Manufacturing Processes, NPJSC "Abylkas Saginov Karaganda Technical University", Karaganda, The Republic of Kazakhstan, ORCID: <https://orcid.org/0009-0003-8395-3826>

Smagulova Karshiga, Doctor of Philosophy (PhD), Associate Professor, Department of Automation of Manufacturing Processes, NPJSC "Abylkas Saginov Karaganda Technical University", Karaganda, The Republic of Kazakhstan, ORCID: <https://orcid.org/0000-0001-6834-8490>

Melikuziev Mirkomil, Doctor of Philosophy (PhD), Associate Professor, Department of Electric Supply, Tashkent State Technical University named after Islam Karimov, Tashkent, Uzbekistan, ORCID: <https://orcid.org/0000-0003-3255-9741>

Mila Baranovska, PhD, Associate Professor, Department of Electromechanical, Kryvyi Rih National University, Kryvyi Rih, Ukraine, ORCID: <https://orcid.org/0000-0002-8082-1305>

Andrii Romanets, PhD Student, Department of Electrical Engineering and Cyber-Physical Systems, Zaporizhzhia National University, Zaporizhzhia, Ukraine, e-mail: ivan.van.mi@gmail.com, ORCID: <https://orcid.org/0009-0000-9893-8408>

Ihor Novitsky, Doctor of Technical Sciences, Professor, Department of Cyberphysical and Information and Measurement Systems, Dnipro University of Technology, Dnipro, Ukraine, ORCID: <https://orcid.org/0000-0002-8780-6589>

Anna Humeniuk, PhD, Associate Professor, Department of Robotics, Electric Power Engineering and Automation named after Prof. B. B. Samotokin, Zhytomyr State Polytechnic University, Zhytomyr, Ukraine, ORCID: <https://orcid.org/0009-0008-3090-4752>

Ilya Kolysnychenko, PhD, Associate Professor, Department of Cyberphysical and Information and Measurement Systems, Dnipro University of Technology, Dnipro, Ukraine, e-mail: kolysnychenko.i.yu@nmu.one, ORCID: <https://orcid.org/0000-0003-4495-0895>

Dmytro Bilukhin, PhD, Associate Professor, Department of Energy and Economic Process Management, Ukrainian State University of Science and Technologies, Dnipro, Ukraine, ORCID: <https://orcid.org/0000-0002-2791-617X>

The object of research is the processes of electromagnetic transformation in powerful asynchronous electric drives during controlled start-up and their impact on the quality of electricity in the power supply network. Distribution networks of industrial enterprises are considered, which have significant dynamic loads during the start-up of powerful machines.

The problem to which the research is aimed is to ensure proper quality of electricity in distribution networks of industrial enterprises when performing controlled start-up of powerful asynchronous electric drives from soft starters based on a thyristor voltage regulator.

Quantitative indicators of the influence of starting devices on the parameters of electricity quality were calculated using computer modeling in the MATLAB/Simulink environment. Soft start using a thyristor regulator, although it limits the starting current, has a negative impact on the quality of electricity in the distribution network. Reactive power consumption increases, which causes a voltage drop. For the case of starting an asynchronous motor with a capacity of 3500 kW in the network of a sintering factory, it was found that direct start causes a voltage drop of about 350 V. Harmonic voltage distortions with a distortion factor of up to 6% also appear. Power active filters allow to improve the quality of electricity by introducing antiphase currents, which is proven by the application of theoretical methods of electrical engineering.

The results obtained are applicable in the design of electric drive systems of powerful mechanisms during the modernization of the power supply of industrial enterprises, in the calculation of reactive power compensation means and in the development of energy quality standards. This will significantly contribute to increasing the reliability of technological equipment, reducing energy losses, and increasing the service life of electrical equipment at the enterprise.

Keywords: starting devices, power quality, controlled reactor compensator, simulation modeling of the distribution network.

References

1. *Soft Starter Market (2024–2030)*. Available at: <https://www.grandviewresearch.com/industry-analysis/soft-starter-market-report>
2. Harumwidiah, A., Kurniawan, A. (2016). Modeling and analysis of ac-ac soft starter for induction motor based on thyristor and IGBT. *ASEAN Journal of Systems Engineering*, 3 (2), 60–64. <https://doi.org/10.22146/ajsex3i2.17161>
3. Thanyaphirak, V., Kinnares, V., Kunakorn, A. (2017). Comparison of Starting Current Characteristics for Three-Phase Induction Motor Due to Phase-control Soft Starter and Asynchronous PWM AC Chopper. *Journal of Electrical Engineering and Technology*, 12 (3), 1090–1100. <https://doi.org/10.5370/jeet.2017.12.3.1090>
4. Yu, M., Tian, C., Chen, B. (2006). A Novel Induction Motor Soft Starter Based on Magnetically Controlled Reactor. 2006 1ST IEEE Conference on Industrial Electronics and Applications. Singapore 1–6. <https://doi.org/10.1109/iciea.2006.257361>
5. Wang, Y., Yin, K., Yuan, Y., Chen, J. (2019). Current-Limiting Soft Starting Method for a High-Voltage and High-Power Motor. *Energies*, 12 (16), 3068. <https://doi.org/10.3390/en12163068>
6. Zhou, J., Sun, X., Sirat, A. P., Mu, Q., Wang, Y., Zhao, T. (2024). Optimized Soft Starting of SiC MOSFET-Based Soft Starter with Constant Transient Current for Motor Control Center Applications. *IECON 2024 – 50th Annual Conference of the IEEE Industrial Electronics Society*. Chicago, 1–6. <https://doi.org/10.1109/iecon55916.2024.10905667>
7. Osita, O., Obi, P. I., Onwuka, I. K. (2017). Induction Motor Starting Analysis and Start Aided Device Comparison using ETAP. *European Journal of Engineering and Technology Research*, 2 (7), 1–7. <https://doi.org/10.24018/ejeng.2017.2.7.348>
8. Sundareswaran, K., Jos, B. M. (2005). Development and analysis of novel soft-starter/energy-saver topology for delta-connected induction motors. *IEE Proceedings – Electric Power Applications*, 152 (4), 922–932. <https://doi.org/10.1049/ip-epa:20050091>
9. Deraz, S. A., Azazi, H. Z. (2017). Current limiting soft starter for three phase induction motor drive system using PWM AC chopper. *IET Power Electronics*, 10 (11), 1298–1306. <https://doi.org/10.1049/iet-pel.2016.0762>
10. Dems, M., Majer, K., Komez, K. (2025). Optimization of Induction Motor Control to Limit the Maximum Current and Torque During Voltage Start-Up Using FEM and Analytical Simulation. *Energies*, 19 (1), 240. <https://doi.org/10.3390/en19010240>
11. *Softstarter Handbook (1SFC132060M0201)* (2010). Västerås: ABB AB, Cewe-Control. Available at: <https://library.e.abb.com/public/6b4e1a3530814df0c12579bb0030e58b/1SFC132060M0201.pdf>
12. Gudiño-Ochoa, A., Jalomo-Cuevas, J., Molinar-Solis, J. E., Ochoa-Ornelas, R. (2023). Analysis of Interharmonics Generation in Induction Motors Driven by Variable Frequency Drives and AC Choppers. *Energies*, 16 (14), 5538. <https://doi.org/10.3390/en16145538>
13. Habyarimana, M., Dorrell, D. G., Musumpuka, R. (2022). Reduction of Starting Current in Large Induction Motors. *Energies*, 15 (10), 3848. <https://doi.org/10.3390/en15103848>
14. Antonino-Daviu, J. A., Corral-Hernandez, J., Resina-Munoz, E., Clemente-Alarcon, V. (2015). A study of the harmonics introduced by soft-starters in the induction motor starting current using continuous time-frequency transforms. 2015 IEEE 13th International Conference on Industrial Informatics (INDIN), 777–781. <https://doi.org/10.1109/indin.2015.7281835>
15. Jiang, F., Tu, C., Guo, Q., Wu, Z., Li, Y. (2019). Adaptive soft starter for a three-phase induction-motor driving device using a multifunctional series compensator. *IET Electric Power Applications*, 13 (7), 977–983. <https://doi.org/10.1049/iet-epa.2018.5079>
16. Kucuk, S., Ajder, A. (2022). Analytical voltage drop calculations during direct on line motor starting: Solutions for industrial plants. *Ain Shams Engineering Journal*, 13 (4), 101671. <https://doi.org/10.1016/j.asej.2021.101671>
17. Bhuvaneshwari, G., Charles, S., Nair, M. G. (2008). Power quality studies on a Soft-start for an induction motor. 2008 IEEE/PES Transmission and Distribution Conference and Exposition. Chicago, 1–6. <https://doi.org/10.1109/tde.2008.4517215>
18. Zhuk, O., Zhuk, D., Kryvoruchko, D., D'yakonov, O. (2018). Control of Improved Hybrid Power Line Conditioner. 2018 IEEE 38th International Conference on Electronics and Nanotechnology (ELNANO). Kyiv, 605–610. <https://doi.org/10.1109/elnano.2018.8477453>
19. Tytiuk, V., Chornyi, O., Zachepa, Y., Kuznetsov, V., Tryputen, M. (2020). Control of the start of high-powered electric drives with the optimization in terms of energy efficiency. *Naukovyi Visnyk Natsionalnoho Hirnychoho Universytetu*, 5, 101–108. <https://doi.org/10.33271/nvngu/2020-5/101>
20. Tryputen, M., Kuznetsov, V., Kuznetsova, A., Tryputen, M., Kuznetsova, Y., Serdiuk, T. (2020). Improving the Reliability of Simulating the Operation of an Induction Motor in Solving the Technical and Economic Problem. *Advances in Computer Science for Engineering and Education III*, 143–152. https://doi.org/10.1007/978-3-030-55506-1_13
21. Tryputen, M., Kuznetsov, V., Kovzel, M., Kovalenko, V., Artemchuk, V., Nadtochiy, V. (2021). Minimization of the Description of Images in the Problem of Adaptive Control of Static Technological Objects. 2021 IEEE International Conference on Modern Electrical and Energy Systems (MEES), 1–4. <https://doi.org/10.1109/mees52427.2021.9598651>
22. Yevheniia, K., Vitaliy, K., Mykola, T., Alisa, K., Maksym, T., Mykola, B. (2019). Development and Verification of Dynamic Electromagnetic Model of Asynchronous Motor Operating in Terms of Poor-Quality Electric Power. 2019 IEEE International Conference on Modern Electrical and Energy Systems (MEES), 350–353. <https://doi.org/10.1109/mees.2019.8896598>

23. Kuznetsov, V. V., Nykolenko, A. V. (2015). Models of operating asynchronous engines at poor-quality electricity. *Eastern-European Journal of Enterprise Technologies*, 1 (8 (73)), 37–42. <https://doi.org/10.15587/1729-4061.2015.36755>
24. Chenchevoi, V., Kuznetsov, V., Kuznetsov, V., Chencheva, O., Zachepa, I., Chorny, O. et al. (2021). Development of mathematical models of energy conversion processes in an induction motor supplied from an autonomous induction generator with parametric non-symmetry. *Eastern-European Journal of Enterprise Technologies*, 4 (8 (112)), 67–82. <https://doi.org/10.15587/1729-4061.2021.239146>
25. Akagi, H., Kanazawa, Y., Fujita, K., Nabae, A. (1983). Generalized theory of instantaneous reactive power and its application. *Electrical Engineering in Japan*, 103 (4), 58–66. <https://doi.org/10.1002/ej.4391030409>
26. Bobrow, L. S. (1985). *Fundamentals of Electrical Engineering*. Holt, Rinehart, and Winston, 926.